belinus®

Module · Gaia
v01 · 2026-01
MODEL · belinus Gaia

BACK-CONTACT HBC MODULE · GLASS-GLASS · 490–505 WP

Gaia

Unlock the power of nature.

#495Wp #247W/m² #BackContact #HBC #GlassGlass #PerfectBlack

01 **Up to 24.7 % efficiency.** < 1 % first-year degradation, 0.35 % / yr from year 2.

02 **Perfect black appearance.** No gridlines, superior shading tolerance.

03 **Glass-glass, IP68 junction box.** Butyl rubber seals for better water resistance.

04 **Fire rating Class A.** Enhanced safety prevents localised overheating.

05 **Enhanced mechanical load.** 6000 Pa / 3600 Pa; 1500 V system voltage.

06 **Bifacial 0BB design.** Rear-side power gain up to 25 % — lower LCOE.

35 yr	35 yr	35 yr
PRODUCT WARRANTY	PERFORMANCE WARRANTY	SERVICE WARRANTY

● GLOBAL LIGHTHOUSE NETWORK · WEF AWARDED FACTORY

Copyright © 2026 Belinus Holding B.V.

www.belinus.com · info@belinus.com

belinus®

TECHNICAL SPECIFICATIONS

Gaia · Back-Contact Glass-Glass Module

MAX POWER	MAX EFFICIENCY	POWER DENSITY	BIFACIAL GAIN
505 Wp	24.7 %	247 W/m²	25 %

MODULE

Cell technology	HBC back-contact (0BB)
Construction	Glass-glass, perfect black
Appearance	No gridlines
Bifacial gain	up to 25 %
First-year degradation	< 1 %
Annual degradation	0.35 % (yr 2–30)

ELECTRICAL (STC)

Max power (Pmax)	490 – 505 Wp
Open-circuit voltage (Voc)	41.25 – 41.55 V
Short-circuit current (Isc)	15.04 – 15.37 A
Voltage at Pmax (Vmp)	34.07 – 34.37 V
Current at Pmax (Imp)	14.38 – 14.69 A
Module efficiency	24.0 – 24.7 %
Power tolerance	0 ~ +3 %

TEMPERATURE & OPERATING

Temp. coeff. Pmax	−0.240 %/°C
Temp. coeff. Voc	−0.210 %/°C
Temp. coeff. Isc	+0.050 %/°C
NOCT	45 ± 2 °C
Operational temperature	−40 °C to +85 °C
Max system voltage	DC 1500 V (IEC)
Max series fuse	30 A
Protection class	Class II

MECHANICAL

Cells	108 (6 × 18) back-contact
Dimensions	1800 × 1134 × 30 mm
Weight	23.5 kg
Frame	Black anodized aluminium
Glass	Dual glass 2.0 + 1.6 mm
Junction box	IP68
Mechanical load	6000 Pa / 3600 Pa
Fire rating	IEC Class A

WARRANTY

Product	35 yr
Performance	35 yr
Service	35 yr

CERTIFICATION

Standards	IEC 61215 · IEC 61730
Management	ISO 9001 · 14001 · 45001
Quality	IEC 62941
Factory	Global Lighthouse Network (WEF)

STRATEGIC OEM PARTNER LONGi

Notice: specifications are subject to change without notice.