

Classification	Definition for this project	When to use	Example from window case	Mitigation
Rebound effect	A response generated or enabled by the intervention that offsets part of the expected environmental benefit	Use when reparability, efficiency or life extension changes behaviour in a way that increases replacement, upgrading or use	Easier component replacement may encourage cosmetic or performance upgrading before functional failure	Repair-first hierarchy, replacement criteria and user guidance
Implementation gap	A strategy cannot function or is not used because practical conditions are missing	Use when repair is technically possible but blocked by access, parts, information, labour, installation method or responsibility gaps	Hardware is technically repairable but inaccessible because of wall finishes or poor detailing	Design for access, maintenance planning, spare-part commitment and clear actor responsibilities
Lifecycle trade-off	Improvement in one area creates additional impacts elsewhere	Use when modularity, durability or high performance adds material, complexity, cost, transport or maintenance burdens	More complex high-performance windows may require more material or mechanisms even if they improve performance	Lifecycle scenario comparison and material-minimisation strategy
Burden shifting	Environmental impact moves to another actor, stage, location or impact category	Use when repair or replacement reduces one burden but increases another, such as transport, service visits or end-of-life treatment	Full replacement may improve performance but creates removal and end-of-life burdens for the old window	Include transport, service visits and end-of-life route in assumptions
Technological lock-in	A long-lived solution restricts later environmental or technical improvement	Use when retaining a durable component makes future upgrades, glazing replacement or performance improvement difficult	Long-life frame is retained but may restrict future glazing or performance upgrades	Design for future upgrade compatibility and verify performance over time
General unintended consequence	An adverse outcome that does not necessarily offset the expected environmental benefit directly	Use when a circular strategy creates practical or social problems but the environmental offset is unclear	More complex maintenance may make clients less willing to choose repair-based strategies	Simplify maintenance and communicate repair benefits clearly