

Programming Paradigms 2025

Session 5: Recursion

Problems for solving and discussing

Hans Hüttel

7 October 2025

Problems that we will definitely talk about

1. (10 minutes)

The function `reverse` appears in the Haskell prelude. It will reverse a list such that e.g. `reverse [1,2,3]` evaluates to `[3,2,1]`.

Now it is your task to define your own version of this function, `rev`. First try to find out what the type of `rev` should be and follow the overall approach described in Section 6.6.

2. (15 minutes) A list $[a_1, a_2, \dots, a_n]$ is *descending* if $a_1 \geq a_2 \geq \dots \geq a_n$.

Write a function `descending` that will return `True` if a list is descending and `False` otherwise. As examples, `descending [6,5,5,1]` should return `True` and `descending ["plip", "pli", "ppp"]` should return `False`. What is its type?

3. (20 minutes)

The function `isolate` takes a list `l` and an element `x` and returns a pair of two new lists `(l1, l2)`. The first list `l1` is a list that contains all elements in `l` that are not equal to `x`. The second list `l2` is a list that contains all occurrences of `x` in `l`.

- `isolate [4,5,4,6,7,4] 4` evaluates to `([5,6,7],[4,4,4])`.
- `isolate ['g','a','k','a'] 'a'` evaluates to `(['g','k'], ['a','a'])`.

Define `isolate` in Haskell *without* using `fst`, `snd`, `head` or `tail`. What should the type of `isolate` be? **Major hint:** Place the recursive call in a `let`- or `where`-clause and use pattern matching to find the components in the result of that call.

4. (20 minutes) The function `wrapup` is a function that takes a list and returns a list of lists. Each list in this list contains the successive elements from the original list that are identical.

For instance, `wrapup [1,1,1,2,3,3,2]` should give us the list `[[1,1,1],[2],[3,3],[2]]` and `wrapup [True,True,False,False,False,True]` should give us the list `[[True,True],[False,False,False],[True]]`.

Define `wrapup` in Haskell using recursion¹ but *without* using `fst`, `snd`, `head` or `tail`. **Major hint:** Recall the definition of the `isolate` function from before.

5. (15 minutes)

A former minister of science and education has decided to get a university degree and is now trying to define a Haskell function `triples` that takes a list of tuples (each tuple has exactly 3 elements) and converts that list of tuples into a tuple of lists.

`triples [(1,2,3), (4, 5, 6), (7, 8, 9)]` should produce `([1,4,7], [2, 5, 8], [3, 6, 9])`.

The minister wrote the following piece of code and a type specification but ran into problems. What seems to be wrong?

```
triples :: Num a => [(a,a,a)] -> ([a],[a],[a])

triples [] = ()
triples [(a,b,c)] = ([a],[b],[c])
triples (x:xs,y:ys,z:zs) = [x,y,z] : Triples [(xs,ys,zs)]
```

¹No list comprehension – that was last week!

Can you fix these issues? How can Section 6.6 help you here?

More problems to solve at your own pace

Here, too, Section 6.6 is helpful.

- a) The function `rle` is a function that, when given a list xs produces a list of pairs of elements of xs and integers². This list of pairs has its elements appears in the order that they appeared originally and contains (x, n) if there are n successive occurrences of x in the list. For instance

```
rle ['a','a','a','g','g','b','a','a']
```

should give us the list `[('a',3),('g',2),('b',1),('a',2)]` and

```
rle [1,1,1,2,2,1,3,3]
```

should give us `[(1,3),(2,2),(1,1),(3,2)]`.

Define `rle` in Haskell. First try to find out what the type of `rle` should be and follow the overall approach described in Section 6.6.

- b) Define a function `amy` that will tell us if any elements of a list satisfy a given predicate.

For instance, if

```
odd x = ((x `mod` 2) == 1)
```

then

```
amy odd [2,5,8,3,7,4]
```

should return `True`, whereas

```
amy odd [2,8,42]
```

should return `False`.

- c) Create a function `frequencies` that, given a string s , creates a list of pairs `[(x1,f1), ..., (xk,fk)]` such that if the character `xi` occurs a total number of `fi` times throughout the list s , then the list of pairs will contain the pair `(xi, fi)`.

As an example of this,

```
frequencies "regn timer"
```

should return the list

```
[('r',2),('e',2),('g',2),('n',2),('i',1)]
```

First find out what the type of the function should be.

- d) A theorem in number theory states that every non-zero real number x can be written as a *continued fraction*. This is a potentially infinite expression of the form

$$x = a_0 + \frac{1}{a_1 + \frac{1}{a_2 + \frac{1}{a_3 + \frac{1}{a_4 + \frac{1}{\ddots + \frac{1}{a_n}}}}}} \quad (1)$$

For rational numbers, the a_i 's will eventually all be 0, so the continued fraction is finite; for irrational numbers, the continued fraction will be infinite. See e.g. [1] for more.

The goal of this problem is to write a Haskell function `cfrac` that will, given a real number r and a natural number n , finds the list of the first n numbers in the continued fraction expansion of r . What should the type of `cfrac` be?

Bibliography

- [1] Wikipedia. Continued fractions. https://en.wikipedia.org/wiki/Continued_fraction.

²This function computes what is called a run-length encoding, thus its name.