

AI Scientific Benchmarks Comparison

Gregor von Laszewski, Reece Shiraishi, Anjay Krishnan, Nhan Tran,
Benjamin Hawks, and Geoffrey C. Fox

August 9, 2025

Abstract

This document provides an overview of various benchmarks, including their descriptions, URLs, domains, focus areas, keywords, task types, AI capabilities measured, metrics, models, and notes. Each benchmark

Citation




```
@misc{benchmark-collection,  
  title={AI Scientific Benchmarks Comparison}  
  author={Gregor von Laszewski and  
          Reece Shiraishi and  
          Anjay Krishnan and  
          Nhan Tran and  
          Benjamin Hawks and  
          Geoffrey C. Fox}  
  url={https://mlcommons-science.github.io/benchmark/benchmarks.pdf}  
  howpublished={Github},  
  year={2025}  
  month=jul  
}
```

Contents





| | | |
|----------|---|-----------|
| 1 | Benchmark Overview Table | 4 |
| 2 | Radar Chart Table | 29 |
| 3 | Benchmark Details | 32 |
| 3.1 | MMLU (Massive Multitask Language Understanding) | 32 |
| 3.2 | GPQA Diamond | 33 |
| 3.3 | ARC-Challenge (Advanced Reasoning Challenge) | 34 |
| 3.4 | Humanity’s Last Exam | 35 |
| 3.5 | FrontierMath | 36 |
| 3.6 | SciCode | 37 |
| 3.7 | AIME (American Invitational Mathematics Examination) | 38 |
| 3.8 | MATH-500 | 39 |
| 3.9 | CURIE (Scientific Long-Context Understanding, Reasoning and Information Extraction) | 40 |
| 3.10 | FEABench (Finite Element Analysis Benchmark) | 41 |
| 3.11 | SPIQA (Scientific Paper Image Question Answering) | 42 |
| 3.12 | MedQA | 43 |
| 3.13 | BaisBench (Biological AI Scientist Benchmark) | 44 |
| 3.14 | MOLGEN | 45 |
| 3.15 | Open Graph Benchmark (OGB) - Biology | 46 |
| 3.16 | Materials Project | 47 |
| 3.17 | OCP (Open Catalyst Project) | 48 |
| 3.18 | JARVIS-Leaderboard | 49 |
| 3.19 | Quantum Computing Benchmarks (QML) | 50 |
| 3.20 | CFDBench (Fluid Dynamics) | 51 |
| 3.21 | SatImgNet | 52 |
| 3.22 | ClimateLearn | 53 |
| 3.23 | BIG-Bench (Beyond the Imitation Game Benchmark) | 54 |
| 3.24 | CommonSenseQA | 55 |
| 3.25 | Winogrande | 56 |
| 3.26 | Jet Classification | 57 |
| 3.27 | Irregular Sensor Data Compression | 58 |
| 3.28 | Beam Control | 59 |
| 3.29 | Ultrafast jet classification at the HL-LHC | 60 |
| 3.30 | Quench detection | 61 |
| 3.31 | DUNE | 62 |
| 3.32 | Intelligent experiments through real-time AI | 63 |
| 3.33 | Neural Architecture Codesign for Fast Physics Applications | 64 |
| 3.34 | Smart Pixels for LHC | 65 |
| 3.35 | HEDM (BraggNN) | 66 |
| 3.36 | 4D-STEM | 67 |
| 3.37 | In-Situ High-Speed Computer Vision | 68 |
| 3.38 | BenchCouncil AIBench | 69 |
| 3.39 | BenchCouncil BigDataBench | 70 |
| 3.40 | MLPerf HPC | 71 |
| 3.41 | MLCommons Science | 72 |
| 3.42 | LHC New Physics Dataset | 73 |
| 3.43 | MLCommons Medical AI | 74 |
| 3.44 | CaloChallenge 2022 | 75 |
| 3.45 | Papers With Code (SOTA Platform) | 76 |

| | | |
|------|---|-----|
| 3.46 | Codabench | 77 |
| 3.47 | Sabath (SBI-FAIR) | 78 |
| 3.48 | PDEBench | 79 |
| 3.49 | The Well | 80 |
| 3.50 | LLM-Inference-Bench | 81 |
| 3.51 | SGLang Framework | 82 |
| 3.52 | vLLM Inference and Serving Engine | 83 |
| 3.53 | vLLM Performance Dashboard | 84 |
| 3.54 | Nixtla NeuralForecast | 85 |
| 3.55 | Nixtla Neural Forecast NHITS | 86 |
| 3.56 | Nixtla Neural Forecast TimeLLM | 87 |
| 3.57 | Nixtla Neural Forecast TimeGPT | 88 |
| 3.58 | HDR ML Anomaly Challenge (Gravitational Waves) | 89 |
| 3.59 | HDR ML Anomaly Challenge (Butterfly) | 90 |
| 3.60 | HDR ML Anomaly Challenge (Sea Level Rise) | 91 |
| 3.61 | Single Qubit Readout on QICK System | 92 |
| 3.62 | GPQA: A Graduate-Level Google-Proof Question and Answer Benchmark | 93 |
| 3.63 | SeafloorAI | 94 |
| 3.64 | SuperCon3D | 95 |
| 3.65 | GeSS | 96 |
| 3.66 | Vocal Call Locator (VCL) | 97 |
| 3.67 | MassSpecGym | 98 |
| 3.68 | Urban Data Layer (UDL) | 99 |
| 3.69 | Delta Squared-DFT | 100 |
| 3.70 | LLMs for Crop Science | 101 |
| 3.71 | SPIQA (LLM) | 102 |




1 Benchmark Overview Table

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|--|---|-------------|---|--|--------------------------------|---|----------|---|----------|
|  | MMLU (Massive Multitask Language Understanding) | Multidomain | Academic knowledge and reasoning across 57 subjects | multitask, multiple-choice, zero-shot, few-shot, knowledge probing | Multiple choice | General reasoning, subject-matter understanding | Accuracy | GPT-4o, Gemini 1.5 Pro, o1, DeepSeek-R1 | [1]⇒ |
|  | GPQA Diamond | Science | Graduate-level scientific reasoning | Google-proof, graduate-level, science QA, chemistry, physics | Multiple choice, Multi-step QA | Scientific reasoning, deep knowledge | Accuracy | o1, DeepSeek-R1 | [2]⇒ |
|  | ARC-Challenge (Advanced Reasoning Challenge) | Science | Grade-school science with reasoning emphasis | grade-school, science QA, challenge set, reasoning | Multiple choice | Commonsense and scientific reasoning | Accuracy | GPT-4, Claude | [3]⇒ |



Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|---|--|------------------------|--|--|-----------------|--|----------------|------------------|----------|
|  | Humanity's Last Exam | Multidomain | Broad cross-domain academic reasoning | cross-domain, academic exam, multiple-choice, multi-disciplinary | Multiple choice | Cross-domain academic reasoning | Accuracy | unkown | [4]⇒ |
|  | FrontierMath | Mathematics | Challenging advanced mathematical reasoning | symbolic reasoning, number theory, algebraic geometry, category theory | Problem solving | Symbolic and abstract mathematical reasoning | Accuracy | unkown | [5]⇒ |
|  | SciCode | Scientific Programming | Scientific code generation and problem solving | code synthesis, scientific computing, programming benchmark | Coding | Program synthesis, scientific computing | Solve rate (%) | Claude3.5-Sonnet | [6]⇒ |
|  | AIME (American Invitational Mathematics Examination) | Mathematics | Pre-college advanced problem solving | algebra, combinatorics, number theory, geometry | Problem solving | Mathematical problem-solving and reasoning | Accuracy | unkown | [7]⇒ |





Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|--|--|---------------------------|---|--|--|---|------------------------|-----------------|----------|
|  | MATH-500 | Mathematics | Math reasoning generalization | calculus, algebra, number theory, geometry | Problem solving | Math reasoning and generalization | Accuracy | unkown | [8]⇒ |
|  | CURIE (Scientific Long-Context Understanding, Reasoning and Information Extraction) | Multidomain Science | Long-context scientific reasoning | long-context, information extraction, multimodal | Information extraction, Reasoning, Concept tracking, Aggregation, Algebraic manipulation, Multimodal comprehension | Long-context understanding and scientific reasoning | Accuracy | unkown | [9]⇒ |
|  | FEABench (Finite Element Analysis Benchmark) | Computational Engineering | FEA simulation accuracy and performance | finite element, simulation, PDE | Simulation, Performance evaluation | Numerical simulation accuracy and efficiency | Solve time, Error norm | FEniCS, deal.II | [10]⇒ |





Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|---|---|----------------------------|---------------------------------------|--|--|--|---|---|----------|
|  | SPIQA (Scientific Paper Image Question Answering) | Computer Science | Multimodal QA on scientific figures | multimodal QA, figure understanding, table comprehension, chain-of-thought | Question answering, Multimodal QA, Chain-of-Thought evaluation | Visual-textual reasoning in scientific contexts | Accuracy, F1 score | Chain-of-Thought models, Multi-modal QA systems | [11]⇒ |
|  | MedQA | Medical Question Answering | Medical board exam QA | USMLE, diagnostic QA, medical knowledge, multilingual | Multiple choice | Medical diagnosis and knowledge retrieval | Accuracy | Neural reader, Retrieval-based QA systems | [12]⇒ |
|  | BaisBench (Biological AI Scientist Benchmark) | Computational Biology | Omics-driven AI research tasks | single-cell annotation, biological QA, autonomous discovery | Cell type annotation, Multiple choice | Autonomous biological research capabilities | Annotation accuracy, QA accuracy | LLM-based AI scientist agents | [13]⇒ |
|  | MOLGEN | Computational Chemistry | Molecular generation and optimization | SELFIES, GAN, property optimization | Distribution learning, Goal-oriented generation | Generation of valid and optimized molecular structures | Validity%, Novelty%, QED, Docking score | MolGen | [14]⇒ |

Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|---|--------------------------------------|---------------------------------|--|---|---|--|---------------------------|--|----------------|
|  | Open Graph Benchmark (OGB) - Biology | Graph ML | Biological graph property prediction | node prediction, link prediction, graph classification | Node property prediction, Link property prediction, Graph property prediction | Scalability and generalization in graph ML for biology | Accuracy, ROC-AUC | GCN, GraphSAGE, GAT | [15]⇒ |
|  | Materials Project | Materials Science | DFT-based property prediction | DFT, materials genome, high-throughput | Property prediction | Prediction of inorganic material properties | MAE, R^2 | Automatminer[16]⇒ Crystal Graph Neural Networks | |
|  | OCP (Open Catalyst Project) | Chemistry; Materials Science | Catalyst adsorption energy prediction | DFT relaxations, adsorption energy, graph neural networks | Energy prediction, Force prediction | Prediction of adsorption energies and forces | MAE (energy), MAE (force) | CGCNN, SchNet, DimeNet++, GemNet-OC | [17]– [20]⇒ |
|  | JARVIS-Leaderboard | Materials Science; Benchmarking | Comparative evaluation of materials design methods | leaderboards, materials methods, simulation | Method benchmarking, Leaderboard ranking | Performance comparison across diverse materials design methods | MAE, RMSE, Accuracy | unkown | [21]⇒ |




Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|---|------------------------------------|-------------------------------|--|---|--|---|-------------------------------|--------------------------------|----------|
|  | Quantum Computing Benchmarks (QML) | Quantum Computing | Quantum algorithm performance evaluation | quantum circuits, state preparation, error correction | Circuit benchmarking, State classification | Quantum algorithm performance and fidelity | Fidelity, Success probability | IBM Q, IonQ, AQT@LBNL | [22]⇒ |
|  | CFDBench (Fluid Dynamics) | Fluid Dynamics; Scientific ML | Neural operator surrogate modeling | neural operators, CFD, FNO, DeepONet | Surrogate modeling | Generalization of neural operators for PDEs | L2 error, MAE | FNO, DeepONet, U-Net | [23]⇒ |
|  | SatImgNet | Remote Sensing | Satellite imagery classification | land-use, zero-shot, multi-task | Image classification | Zero-shot land-use classification | Accuracy | CLIP, BLIP, ALBEF | [24]⇒ |
|  | ClimateLearn | Climate Science; Forecasting | ML for weather and climate modeling | medium-range forecasting, ERA5, data-driven | Forecasting | Global weather prediction (3-5 days) | RMSE, Anomaly correlation | CNN baselines, ResNet variants | [25]⇒ |

Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|---|--|--------------------|--|---|--|--|---------------------------------|--|----------|
|  | BIG-Bench (Beyond the Imitation Game Benchmark) | NLP; AI Evaluation | Diverse reasoning and generalization tasks | few-shot, multi-task, bias analysis | Few-shot evaluation, Multi-task evaluation | Reasoning and generalization across diverse tasks | Accuracy, Task-specific metrics | GPT-3, Dense Transformers, Sparse Transformers | [26]⇒ |
|  | CommonSenseQA | NLP; Commonsense | Commonsense question answering | ConceptNet, multiple-choice, adversarial | Multiple choice | Commonsense reasoning and knowledge integration | Accuracy | BERT-large, RoBERTa, GPT-3 | [27]⇒ |
|  | Winogrande | NLP; Commonsense | Winograd Schema-style pronoun resolution | adversarial, pronoun resolution | Pronoun resolution | Robust commonsense reasoning | Accuracy, AUC | RoBERTa, BERT, GPT-2 | [28]⇒ |
|  | Jet Classification | Particle Physics | Real-time classification of particle jets using HL-LHC simulation features | classification, real-time ML, jet tagging, QKeras | Classification | Real-time inference, model compression performance | Accuracy, AUC | Keras DNN, QKeras quantized DNN | [29]⇒ |




Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|--|--|--------------------------|--|--|----------------|---|---|-------------------------------------|-------------|
|  | Irregular Sensor Data Compression | Particle Physics | Real-time compression of sparse sensor data with autoencoders | compression, autoencoder, sparse data, irregular sampling | Compression | Reconstruction quality, compression efficiency | MSE, Compression ratio | Autoencoder, Quantized autoencoder | [30]⇒ |
|  | Beam Control | Accelerators and Magnets | Reinforcement learning control of accelerator beam position | RL, beam stabilization, control systems, simulation | Control | Policy performance in simulated accelerator control | Stability, Control loss | DDPG, PPO (planned) | [31], [32]⇒ |
|  | Ultrafast jet classification at the HL-LHC | Particle Physics | FPGA-optimized real-time jet origin classification at the HL-LHC | jet classification, FPGA, quantization-aware training, Deep Sets, Interaction Networks | Classification | Real-time inference under constraints | Accuracy, Latency, Resource utilization | MLP, Deep Sets, Interaction Network | [33]⇒ |

Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|---------|--|--|---|---|---|--|---|--|----------|
| | Quench detection | Accelerators and Magnets | Real-time detection of superconducting magnet quenches using ML | quench detection, autoencoder, anomaly detection, real-time | Anomaly detection, Quench localization | Real-time anomaly detection with multi-modal sensors | ROC-AUC, Detection latency | Autoencoder, RL agents (in development) | [34]⇒ |
| | DUNE | Particle Physics | Real-time ML for DUNE DAQ time-series data | DUNE, time-series, real-time, trigger | Trigger selection, Time-series anomaly detection | Low-latency event detection | Detection efficiency, Latency | CNN, LSTM (planned) | [35]⇒ |
| | Intelligent experiments through real-time AI | Instrumentation and Detectors; Nuclear Physics; Particle Physics | Real-time FPGA-based triggering and detector control for sPHENIX and future EIC | FPGA, Graph Neural Network, hls4ml, real-time inference, detector control | Trigger classification, Detector control, Real-time inference | Low-latency GNN inference on FPGA | Accuracy (charm and beauty detection), Latency (micros), Resource utilization (LUT/FF/BRAM/DCP) | Bipartite Graph Network with Set Transformers (BGN-ST), GarNet (edge-AM/DCP) | [36]⇒ |




Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|--|--|---|--|--|--------------------------------------|--|---|--|----------|
|  | Neural Architecture Codesign for Fast Physics Applications | Physics; Materials Science; Particle Physics | Automated neural architecture search and hardware-efficient model codesign for fast physics applications | neural architecture search, FPGA deployment, quantization, pruning, hls4ml | Classification, Peak finding | Hardware-aware model optimization; low-latency inference | Accuracy, Latency, Resource utilization | NAC-based BraggNN, NAC-optimized Deep Sets (jet) | [37]⇒ |
|  | Smart Pixels for LHC | Particle Physics; Instrumentation and Detectors | On-sensor, in-pixel ML filtering for high-rate LHC pixel detectors | smart pixel, on-sensor inference, data reduction, trigger | Image Classification, Data filtering | On-chip, low-power inference; data reduction | Data rejection rate, Power per pixel | 2-layer pixel NN | [38]⇒ |
|  | HEDM (BraggNN) | Material Science | Fast Bragg peak analysis using deep learning in diffraction microscopy | BraggNN, diffraction, peak finding, HEDM | Peak detection | High-throughput peak localization | Localization accuracy, Inference time | BraggNN | [39]⇒ |




Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|---------|------------------------------------|------------------|--|---|---|--|-------------------------------------|--|----------|
| | 4D-STEM | Material Science | Real-time ML for scanning transmission electron microscopy | 4D-STEM, electron microscopy, real-time, image processing | Image classification, Streamed data inference | Real-time large-scale microscopy inference | Classification accuracy, Throughput | CNN models (prototype) | [40]⇒ |
| | In-Situ High-Speed Computer Vision | Fusion/Plasma | Real-time image classification for in-situ plasma diagnostics | plasma, in-situ vision, real-time ML | Image Classification | Real-time diagnostic inference | Accuracy, FPS | CNN | [41]⇒ |
| | BenchCouncil AIBench | General | End-to-end AI benchmarking across micro, component, and application levels | benchmarking, AI systems, application-level evaluation | Training, Inference, End-to-end workloads | System-level AI workload performance | Throughput, Latency, Accuracy | ResNet, BERT, GANs, Recommendation systems | [42]⇒ |



Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|--|----------------------------|---|--|---|---|---|--|----------------------------------|----------|
|  | BenchCouncil Big-DataBench | General | Big data and AI benchmarking across structured, semi-structured, and unstructured data workloads | big data, AI benchmarking, data analytics | Data pre-processing, Inference, End-to-end data pipelines | Data processing and AI model inference performance at scale | Data throughput, Latency, Accuracy | CNN, LSTM, SVM, XGBoost | [43]⇒ |
|  | MLPerf HPC | Cosmology, Climate, Protein Structure, Catalysis | Scientific ML training and inference on HPC systems | HPC, training, inference, scientific ML | Training, Inference | Scaling efficiency, training time, model accuracy on HPC | Training time, Accuracy, GPU utilization | CosmoFlow, DeepCAM, OpenCatalyst | [44]⇒ |
|  | MLCommons Science | Earthquake, Satellite Image, Drug Discovery, Electron Microscope, CFD | AI benchmarks for scientific applications including time-series, imaging, and simulation | science AI, benchmark, MLCommons, HPC | Time-series analysis, Image classification, Simulation surrogate modeling | Inference accuracy, simulation speed-up, generalization | MAE, Accuracy, Speedup vs simulation | CNN, GNN, Transformer | [45]⇒ |




Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|---|-------------------------|--|--|--|---|---|--|---|----------|
|  | LHC New Physics Dataset | Particle Physics; Real-time Triggering | Real-time LHC event filtering for anomaly detection using proton collision data | anomaly detection, proton collision, real-time inference, event filtering, unsupervised ML | Anomaly detection, Event classification | Unsupervised signal detection under latency and bandwidth constraints | ROC-AUC, Detection efficiency | Autoencoder, Variational autoencoder, Isolation forest | [46]⇒ |
|  | MLCommons Medical AI | Healthcare; Medical AI | Federated benchmarking and evaluation of medical AI models across diverse real-world clinical data | medical AI, federated evaluation, privacy-preserving, fairness, healthcare benchmarks | Federated evaluation, Model validation | Clinical accuracy, fairness, generalizability, privacy compliance | ROC AUC, Accuracy, Fairness metrics | MedPerf-validated CNNs, GaNDLF workflows | [47]⇒ |
|  | CaloChallenge 2022 | LHC Calorimeter; Particle Physics | Fast generative-model-based calorimeter shower simulation evaluation | calorimeter simulation, generative models, surrogate modeling, LHC, fast simulation | Surrogate modeling | Simulation fidelity, speed, efficiency | Histogram similarity, Classifier AUC, Generation latency | VAE variants, GAN variants, Normalizing flows, Diffusion models | [48]⇒ |




Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|---|----------------------------------|-------------------------|---|---|---|---|--|--------------------------------|----------|
|  | Papers With Code (SOTA Platform) | General ML; All domains | Open platform tracking state-of-the-art results, benchmarks, and implementations across ML tasks and papers | leaderboard, benchmarking, reproducibility, open-source | Multiple (Classification, Detection, NLP, etc.) | Model performance across tasks (accuracy, F1, BLEU, etc.) | Task-specific (Accuracy, F1, BLEU, etc.) | All published models with code | [49]⇒ |
|  | Codabench | General ML; Multiple | Open-source platform for organizing reproducible AI benchmarks and competitions | benchmark platform, code submission, competitions, meta-benchmark | Multiple | Model reproducibility, performance across datasets | Submission count, Leaderboard ranking, Task-specific metrics | Arbitrary code submissions | [50]⇒ |




Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|--|-------------------|--|--|--|----------------------|--|--|--|----------|
|  | Sabath (SBI-FAIR) | Systems; Metadata | FAIR metadata framework for ML-driven surrogate workflows in HPC systems | meta-benchmark, metadata, HPC, surrogate modeling | Systems benchmarking | Metadata tracking, reproducible HPC workflows | Metadata completeness, FAIR compliance | NA | [51]⇒ |
|  | PDEBench | CFD; Weather Modeling | Benchmark suite for ML-based surrogates solving time-dependent PDEs | PDEs, CFD, scientific ML, surrogate modeling, NeurIPS | Supervised Learning | Time-dependent PDE modeling; physical accuracy | RMSE, boundary RMSE, Fourier RMSE | FNO, U-Net, PINN, Gradient-Based inverse methods | [52]⇒ |
|  | The Well | biological systems, fluid dynamics, acoustic scattering, astrophysical MHD | Foundation model + surrogate dataset spanning 16 physical simulation domains | surrogate modeling, foundation model, physics simulations, spatiotemporal dynamics | Supervised Learning | Surrogate modeling, physics-based prediction | Dataset size, Domain breadth | FNO baselines, U-Net baselines | [53]⇒ |




Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|--|-----------------------------------|--------------------|---|--|-------------------------|---|---|--|----------|
|  | LLM-Inference-Bench | LLM; HPC/inference | Hardware performance benchmarking of LLMs on AI accelerators | LLM, inference benchmarking, GPU, accelerator, throughput | Inference Benchmarking | Inference throughput, latency, hardware utilization | Token throughput (tok/s), Latency, Framework-hardware mix performance | LLaMA-2-7B, LLaMA-2-70B, Mistral-7B, Qwen-7B | [54]⇒ |
|  | SGLang Framework | LLM Vision | Fast serving framework for LLMs and vision-language models | LLM serving, vision-language, RadixAttention, performance, JSON decoding | Model serving framework | Serving throughput, JSON/task-specific latency | Tokens/sec, Time-to-first-token, Throughput gain vs baseline | LLaVA, DeepSeek, Llama | [55]⇒ |
|  | vLLM Inference and Serving Engine | LLM; HPC/inference | High-throughput, memory-efficient inference and serving engine for LLMs | LLM inference, PagedAttention, CUDA graph, streaming API, quantization | Inference Benchmarking | Throughput, latency, memory efficiency | Tokens/sec, Time to First Token (TTFT), Memory footprint | LLaMA, Mixtral, FlashAttention-based models | [56]⇒ |




Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|--|------------------------------|-------------------------------------|--|---|---------------------------|--|--------------------------------|----------------------------|----------|
|  | vLLM Performance Dashboard | LLM; HPC/inference | Interactive dashboard showing inference performance of vLLM | Dashboard, Throughput visualization, Latency analysis, Metric tracking | Performance visualization | Throughput, latency, hardware utilization | Tokens/sec, TTFT, Memory usage | LLaMA-2, Mistral, Qwen | [57]⇒ |
|  | Nixtla NeuralForecast | Time-series forecasting; General ML | High-performance neural forecasting library with >30 models | time-series, neural forecasting, NBEATS, NHITS, TFT, probabilistic forecasting, usability | Time-series forecasting | Forecast accuracy, interpretability, speed | RMSE, MAPE, CRPS | NBEATS, NHITS, TFT, DeepAR | [58]⇒ |
|  | Nixtla Neural Forecast NHITS | Time-series; General ML | Official NHITS implementation for long-horizon time series forecasting | NHITS, long-horizon forecasting, neural interpolation, time-series | Time-series forecasting | Accuracy, compute efficiency for long series | RMSE, MAPE | NHITS | [59]⇒ |



Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|--|--|---------------------------|--|---|--|---|---------------------------------|--------------------------------|----------|
|  | Nixtla Neural Forecast TimeLLM | Time-series; General ML | Reprogramming LLMs for time series forecasting | Time-LLM, language model, time-series, reprogramming | Time-series forecasting | Model reuse via LLM, few-shot forecasting | RMSE, MAPE | Time-LLM | [60]⇒ |
|  | Nixtla Neural Forecast TimeGPT | Time-series; General ML | Time-series foundation model "TimeGPT" for forecasting and anomaly detection | TimeGPT, foundation model, time-series, generative model | Time-series forecasting, Anomaly detection | Zero-shot forecasting, anomaly detection | RMSE, Anomaly detection metrics | TimeGPT | [61]⇒ |
|  | HDR ML Anomaly Challenge (Gravitational Waves) | Astrophysics; Time-series | Detecting anomalous gravitational-wave signals from LIGO/Virgo datasets | anomaly detection, gravitational waves, astrophysics, time-series | Anomaly detection | Novel event detection in physical signals | ROC-AUC, Precision/Recall | Deep latent CNNs, Autoencoders | [62]⇒ |



Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|---|---|--|--|---|-------------------|---|-----------------------------------|--------------------------|----------|
|  | HDR ML Anomaly Challenge (Butterfly) | Genomics; Image/CV | Detecting hybrid butterflies via image anomaly detection in genomic-informed dataset | anomaly detection, computer vision, genomics, butterfly hybrids | Anomaly detection | Hybrid detection in biological systems | Classification accuracy, F1 score | CNN-based detectors | [63]⇒ |
|  | HDR ML Anomaly Challenge (Sea Level Rise) | Climate Science; Time-series, Image/CV | Detecting anomalous sea-level rise and flooding events via time-series and satellite imagery | anomaly detection, climate science, sea-level rise, time-series, remote sensing | Anomaly detection | Detection of environmental anomalies | ROC-AUC, Precision/Recall | CNNs, RNNs, Transformers | [64]⇒ |
|  | Single Qubit Readout on QICK System | Quantum Computing | Real-time single-qubit state classification using FPGA firmware | qubit readout, hls4ml, FPGA, QICK | Classification | Single-shot fidelity, inference latency | Accuracy, Latency | hls4ml quantized NN | [65]⇒ |




Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|--|---|---------------------------------------|--|--|--|--|--|--|----------|
|  <p>GPQA: A Graduate-Level Google-Proof Question and Answer Benchmark</p> | GPQA: A Graduate-Level Google-Proof Question and Answer Benchmark | Science (Biology, Physics, Chemistry) | Graduate-level, expert-validated multiple-choice questions hard even with web access | Google-proof, multiple-choice, expert reasoning, science QA | Multiple choice | Scientific reasoning, knowledge probing | Accuracy | GPT-4 baseline | [66]⇒ |
|  <p>SeafloorAI</p> | SeafloorAI | Marine Science; Vision-Language | Large-scale vision-language dataset for seafloor mapping and geological classification | sonar imagery, vision-language, seafloor mapping, segmentation, QA | Image segmentation, Vision-language QA | Geospatial understanding, multimodal reasoning | Segmentation pixel accuracy, QA accuracy | SegFormer, ViLT-style multi-modal models | [67]⇒ |



Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|---|------------|--|--|--|---|--|--|----------------------|----------|
|  | SuperCon3D | Materials Science; Superconductivity | Dataset and models for predicting and generating high-Tc superconductors using 3D crystal structures | superconductivity, crystal structures, equivariant GNN, generative models | Regression (Tc prediction), Generative modeling | Structure-to-property prediction, structure generation | MAE (Tc), Validity of generated structures | SODNet, DiffCSP-SC | [68]⇒ |
|  | GeSS | Scientific ML; Geometric Deep Learning | Benchmark suite evaluating geometric deep learning models under real-world distribution shifts | geometric deep learning, distribution shift, OOD robustness, scientific applications | Classification, Regression | OOD performance in scientific settings | Accuracy, RMSE, OOD robustness delta | GCN, EGNN, DimeNet++ | [69]⇒ |


Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|--|--------------------------|--------------------------------------|--|--|---|--|---|--|----------|
|  | Vocal Call Locator (VCL) | Neuroscience; Bioacoustics | Benchmarking source-sound-source localization of rodent vocalizations from multi-channel audio | source localization, bioacoustics, time-series, SSL | Sound source localization | Source localization accuracy in bioacoustic settings | Localization error (cm), Recall/Precision | CNN-based SSL models | [70]⇒ |
|  | MassSpecGym | Cheminformatics; Molecular Discovery | Benchmark suite for discovery and identification of molecules via MS/MS | mass spectrometry, molecular structure, de novo generation, retrieval, dataset | De novo generation, Retrieval, Simulation | Molecular identification and generation from spectral data | Structure accuracy, Retrieval precision, Simulation MSE | Graph-based generative models, Retrieval baselines | [71]⇒ |
|  | Urban Data Layer (UDL) | Urban Computing; Data Engineering | Unified data pipeline for multi-modal urban science research | data pipeline, urban science, multi-modal, benchmark | Prediction, Classification | Multi-modal urban inference, standardization | Task-specific accuracy or RMSE | Baseline regression/classification pipelines | [72]⇒ |

Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|---|-----------------------|--|---|--|-------------------------------|---|---|---|----------|
|  | Delta Squared-DFT | Computational Chemistry; Materials Science | Benchmarking machine-learning corrections to DFT using Delta Squared-trained models for reaction energies | density functional theory, Delta Squared-ML correction, reaction energetics, quantum chemistry | Regression | High-accuracy energy prediction, DFT correction | Mean Absolute Error (eV), Energy ranking accuracy | Delta Squared-ML correction networks, Kernel ridge regression | [73]⇒ |
|  | LLMs for Crop Science | Agricultural Science; NLP | Evaluating LLMs on crop trait QA and textual inference tasks with domain-specific prompts | crop science, prompt engineering, domain adaptation, question answering | Question Answering, Inference | Scientific knowledge, crop reasoning | Accuracy, F1 score | GPT-4, LLaMA-2-13B, T5-XXL | [74]⇒ |

Continued on next page

| Ratings | Name | Domain | Focus | Keywords | Task Types | AI Capability | Metrics | Models | Citation |
|---|-------------|---|---|---|---------------|---|--------------------|--|----------|
|  | SPIQA (LLM) | Multimodal Scientific QA; Computer Vision | Evaluating LLMs on image-based scientific paper figure QA tasks (LLM Adapter performance) | multimodal QA, scientific figures, image+text, chain-of-thought prompting | Multimodal QA | Visual reasoning, scientific figure understanding | Accuracy, F1 score | LLaVA, MiniGPT-4, Owl-LLM adapter variants | [75]⇒ |

2 Radar Chart Table




Figure 1: Radar chart overview (page 1)




Figure 2: Radar chart overview (page 2)




Figure 3: Radar chart overview (page 3)

3 Benchmark Details


3.1 MMLU (Massive Multitask Language Understanding)

Measuring Massive Multitask Language Understanding (MMLU) is a benchmark of 57 multiple-choice tasks covering elementary mathematics, US history, computer science, law, and more, designed to evaluate a model’s breadth and depth of knowledge in zero-shot and few-shot settings.

date: 2020-09-07
version: 1
last_updated: 2020-09-07
expired: false
valid: yes
valid_date: 2025-07-28
url: <https://paperswithcode.com/dataset/mmlu>
doi: 10.48550/arXiv.2009.03300
domain: Multidomain
focus: Academic knowledge and reasoning across 57 subjects
keywords: - multitask - multiple-choice - zero-shot - few-shot - knowledge probing
licensing: MIT License
task_types: - Multiple choice
ai_capability_measured: - General reasoning, subject-matter understanding
metrics: - Accuracy
models: - GPT-4o - Gemini 1.5 Pro - o1 - DeepSeek-R1
ml_motif: - General knowledge
type: Benchmark
ml_task: - Supervised Learning
solutions: 1
notes: Good
contact.name: Dan Hendrycks
contact.email: dan (at) safe.ai
datasets.links.name: Papers with Code datasets
datasets.links.url: <https://github.com/paperswithcode/paperswithcode-data>
results.links.name: Chinchilla
results.links.url: <https://arxiv.org/abs/2203.15556>
fair.reproducible: True
fair.benchmark_ready: True
id: mmlu_massive_multitask_language_understanding
Citations: [1]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 5 | Meets all FAIR principles and properly versioned. |
| documentation | 5 | Well-explained in a provided paper. |
| metrics | 5 | Fully defined, represents a solution’s performance. |
| reference_solution | 2 | Reference models are available (i.e. GPT-3), but are not trainable or publicly documented |
| software | 0 | No instructions to download or run data given on the site |
| specification | 4 | No system constraints |




3.2 GPQA Diamond

GPQA is a dataset of 448 challenging, multiple-choice questions in biology, physics, and chemistry, written by domain experts. It is Google-proof - experts score 65% (74% after error correction) while skilled non-experts with web access score only 34%. State-of-the-art LLMs like GPT-4 reach around 39% accuracy.

date: 2023-11-20
version: 1
last_updated: 2023-11-20
expired: false
valid: yes
valid_date: 2023-11-20
url: <https://arxiv.org/abs/2311.12022>
doi: 10.48550/arXiv.2311.12022
domain: Science
focus: Graduate-level scientific reasoning
keywords: - Google-proof - graduate-level - science QA - chemistry - physics
licensing: unknown
task_types: - Multiple choice - Multi-step QA
ai_capability_measured: - Scientific reasoning, deep knowledge
metrics: - Accuracy
models: - o1 - DeepSeek-R1
ml_motif: - Science and STEM fields
type: Benchmark
ml_task: - Supervised Learning
solutions: 0
notes: Good
contact.name: Julian Michael
contact.email: julianjm@nyu.edu
datasets.links.name: unknown
datasets.links.url: unknown
results.links.name: unknown
results.links.url: unknown
fair.reproducible: True
fair.benchmark_ready: True
id: gpqa_diamond
Citations: [2]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 5 | Easily able to access dataset. Comes with predefined splits as mentioned in the paper |
| documentation | 5 | All information is listed in the associated paper |
| metrics | 5 | Each question has a correct answer, representing the tested model's performance. |
| reference_solution | 1 | Common models such as GPT-3.5 were compared. They are not open and don't provide requirements |
| software | 5 | Python version and requirements specified on Github site |
| specification | 2 | No system constraints or I/O specified |




3.3 ARC-Challenge (Advanced Reasoning Challenge)

The AI2 Reasoning Challenge (ARC) Challenge set comprises 7,787 natural, grade-school science questions that retrieval-based and word co-occurrence algorithms both fail, requiring advanced reasoning over a 14-million-sentence corpus.

date: 2018-03-14
version: 1
last_updated: 2018-03-14
expired: false
valid: yes
valid_date: 2018-03-14
url: <https://allenai.org/data/arc>
doi: NA
domain: Science
focus: Grade-school science with reasoning emphasis
keywords: - grade-school - science QA - challenge set - reasoning
licensing: Apache 2.0 License
task_types: - Multiple choice
ai_capability_measured: - Commonsense and scientific reasoning
metrics: - Accuracy
models: - GPT-4 - Claude
ml_motif: - Elementary science
type: Benchmark
ml_task: - Supervised Learning
solutions: 0
notes: Good
contact.name: unknown
contact.email: unknown
datasets.links.name: Hugging Face
datasets.links.url: https://huggingface.co/datasets/allenai/ai2_arc
results.links.name: unknown
results.links.url: unknown
fair.reproducible: True
fair.benchmark_ready: True
id: arc-challenge_advanced_reasoning_challenge
Citations: [3]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 4 | Data accessible, offers instructions on how to download the data via CLI tools. No splits. |
| documentation | 5 | Explains all necessary information inside a paper |
| metrics | 5 | (by default) All questions in the dataset are multiple choice, all have a correct answer |
| reference_solution | 1 | There are over 300 models listed, but very few, if any, show performance on the dataset or list constraints |
| software | 0 | No link to code or documentation |
| specification | 2 | Task is clear, but no constraints or format is mentioned |




3.4 Humanity’s Last Exam

Humanity’s Last Exam is a multi-domain, multiple-choice benchmark containing 2,000 questions across diverse academic disciplines, designed to evaluate LLMs’ ability to reason across domains without external resources.

date: 2025-01-24
version: 1
last_updated: 2025-01-24
expired: false
valid: yes
valid_date: 2025-01-24
url: <https://arxiv.org/abs/2501.14249>
doi: 10.48550/arXiv.2501.14249
domain: Multidomain
focus: Broad cross-domain academic reasoning
keywords: - cross-domain - academic exam - multiple-choice - multidisciplinary
licensing: MIT License
task_types: - Multiple choice
ai_capability_measured: - Cross-domain academic reasoning
metrics: - Accuracy
models: - unknown
ml_motif: - Multi-domain
type: Benchmark
ml_task: - Supervised Learning
solutions: 0
notes: Good
contact.name: HLE team
contact.email: agibenchmark@safe.ai
datasets.links.name: Hugging Face
datasets.links.url: <https://huggingface.co/datasets/cais/hle>
results.links.name: unknown
results.links.url: unknown
fair.reproducible: True
fair.benchmark_ready: True
id: humanitys_last_exam
Citations: [4]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 2 | Data accessible through Hugging Face, but requires giving contact information to access |
| documentation | 5 | Paper available with necessary information |
| metrics | 5 | (by default) All questions in the dataset are multiple choice, all have a correct answer |
| reference_solution | 2 | Performance for cutting-edge models listed, but does not specify exact version of the models or how to reproduce the result |
| software | 4 | Code for testing models posted on the github. Unknown how to run a custom model. |
| specification | 2 | Format of inputs (natural language) and outputs (multiple choice or natural language) specified. No HW constraints specified |




3.5 FrontierMath

FrontierMath is a benchmark of hundreds of expert-vetted mathematics problems spanning number theory, real analysis, algebraic geometry, and category theory, measuring LLMs ability to solve problems requiring deep abstract reasoning.

| | |
|--------------------------------|---|
| date: | 2024-11-07 |
| version: | 1 |
| last_updated: | 2024-11-07 |
| expired: | false |
| valid: | yes |
| valid_date: | 2024-11-07 |
| url: | https://arxiv.org/abs/2411.04872 |
| doi: | 10.48550/arXiv.2411.04872 |
| domain: | Mathematics |
| focus: | Challenging advanced mathematical reasoning |
| keywords: | - symbolic reasoning - number theory - algebraic geometry - category theory |
| licensing: | unknown |
| task_types: | - Problem solving |
| ai_capability_measured: | - Symbolic and abstract mathematical reasoning |
| metrics: | - Accuracy |
| models: | - unkown |
| ml_motif: | - Math problem solving |
| type: | Benchmark |
| ml_task: | - Supervised Learning |
| solutions: | 0 |
| notes: | Good |
| contact.name: | FrontierMath team |
| contact.email: | math_evals@epochai.org |
| datasets.links.name: | unknown |
| datasets.links.url: | unknown |
| results.links.name: | unknown |
| results.links.url: | unknown |
| fair.reproducible: | True |
| fair.benchmark_ready: | True |
| id: | frontiermath |
| Citations: | [5] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 0 | Paper and website had no link to any dataset. It may still exist somewhere |
| documentation | 0 | No specified way to reproduce the reference solution |
| metrics | 5 | (by default) All questions in the dataset have a correct answer |
| reference_solution | 2 | Displays result of leading models on the benchmark, but none are trainable or list constraints |
| software | 0 | No link to code provided |
| specification | 3 | Well-specified process for asking questions and receiving answers. No software or hardware constraints |




3.6 SciCode

SciCode is a scientist-curated coding benchmark with 338 subproblems derived from 80 real research tasks across 16 scientific subfields, evaluating models on knowledge recall, reasoning, and code synthesis for scientific computing tasks.

date: 2024-07-18
version: 1
last_updated: 2024-07-18
expired: false
valid: yes
valid_date: 2024-07-18
url: <https://arxiv.org/abs/2407.13168>
doi: 10.48550/arXiv.2407.13168
domain: Scientific Programming
focus: Scientific code generation and problem solving
keywords: - code synthesis - scientific computing - programming benchmark
licensing: unknown
task_types: - Coding
ai_capability_measured: - Program synthesis, scientific computing
metrics: - Solve rate (%)
models: - Claude3.5-Sonnet
ml_motif: - Coding
type: Benchmark
ml_task: - Supervised Learning
solutions: unknown
notes: Good
contact.name: Minyang Tian
contact.email: mtian8@illinois.edu
datasets.links.name: unknown
datasets.links.url: unknown
results.links.name: unknown
results.links.url: unknown
fair.reproducible: True
fair.benchmark_ready: True
id: scicode
Citations: [6]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 0 | Paper and website had no link to any dataset. It may still exist somewhere |
| documentation | 4 | Paper containing all needed info except for evaluation criteria |
| metrics | 2 | Metrics stated, but method of grading is not specified |
| reference_solution | 1 | Models presented with scores, but none are open or list constraints |
| software | 5 | Code to run exists on github repo |
| specification | 4.5 | Expected outputs and broad types of inputs stated. Few details on output grading. No HW constraints. |




3.7 AIME (American Invitational Mathematics Examination)

The AIME is a 15-question, 3-hour exam for high-school students featuring challenging short-answer math problems in algebra, number theory, geometry, and combinatorics, assessing depth of problem-solving ability.

| | |
|--------------------------------|---|
| date: | 2025-03-13 |
| version: | 1 |
| last_updated: | 2025-03-13 |
| expired: | false |
| valid: | yes |
| valid_date: | 2025-03-13 |
| url: | https://artofproblemsolving.com/wiki/index.php/AIME_Problems_and_Solutions |
| doi: | NA |
| domain: | Mathematics |
| focus: | Pre-college advanced problem solving |
| keywords: | - algebra - combinatorics - number theory - geometry |
| licensing: | unknown |
| task_types: | - Problem solving |
| ai_capability_measured: | - Mathematical problem-solving and reasoning |
| metrics: | - Accuracy |
| models: | - unknown |
| ml_motif: | - Math problem solving |
| type: | Benchmark |
| ml_task: | - Supervised Learning |
| solutions: | 0 |
| notes: | Designed for human test-takers |
| contact.name: | unknown |
| contact.email: | unknown |
| datasets.links.name: | AoPS website |
| datasets.links.url: | https://artofproblemsolving.com/wiki/index.php/AIME_Problems_and_Solutions |
| results.links.name: | unknown |
| results.links.url: | unknown |
| fair.reproducible: | True |
| fair.benchmark_ready: | True |
| id: | aime_american_invitational_mathematics_examination |
| Citations: | [7] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 4 | Easily accessible data with problems and solutions, but no splits |
| documentation | 0 | Not given |
| metrics | 5 | (by default) Answer is correct or it's not |
| reference_solution | 0 | Not given. Human performance stats exist, but no mentions of AI performance |
| software | 0 | No code available |
| specification | 0 | Obvious what the problems are, but not specified how to administer them to AI models. No HW constraints |




3.8 MATH-500

MATH-500 is a curated subset of 500 problems from the OpenAI MATH dataset, spanning high-school to advanced levels, designed to evaluate LLMs mathematical reasoning and generalization.

date: 2025-02-15
version: 1
last_updated: 2025-02-15
expired: false
valid: yes
valid_date: 2025-02-15
url: <https://huggingface.co/datasets/HuggingFaceH4/MATH-500>
doi: unknown
domain: Mathematics
focus: Math reasoning generalization
keywords: - calculus - algebra - number theory - geometry
licensing: MIT License
task_types: - Problem solving
ai_capability_measured: - Math reasoning and generalization
metrics: - Accuracy
models: - unknown
ml_motif: - Math problem solving
type: Benchmark
ml_task: - Supervised Learning
solutions: 0
notes: Dataset hosted on Hugging Face. Data comes from a subset of OpenAI's dataset
contact.name: unknown
contact.email: unknown
datasets.links.name: Hugging Face
datasets.links.url: <https://huggingface.co/datasets/HuggingFaceH4/MATH-500>
results.links.name: unknown
results.links.url: unknown
fair.reproducible: True
fair.benchmark_ready: True
id: math-
Citations: [8]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 5 | Problems and solutions are easily downloaded. Could not find a way to download the data |
| documentation | 0 | Not given. Implicit instructions to download dataset. |
| metrics | 2 | Problem spec states that all of the AI reasoning steps are subject to grading, but no specified way to evaluate the steps |
| reference_solution | 0 | Not given |
| software | 0 | No code provided |
| specification | 0 | No method of presentation and evaluation is not stated. No constraints |




3.9 CURIE (Scientific Long-Context Understanding, Reasoning and Information Extraction)

CURIE is a benchmark of 580 problems across six scientific disciplines-materials science, quantum computing, biology, chemistry, climate science, and astrophysics- designed to evaluate LLMs on long-context understanding, reasoning, and information extraction in realistic scientific workflows.

date: 2024-04-02
version: 1
last_updated: 2024-04-02
expired: false
valid: yes
valid_date: 2024-04-02
url: <https://arxiv.org/abs/2503.13517>
doi: 10.48550/arXiv.2503.13517
domain: Multidomain Science
focus: Long-context scientific reasoning
keywords: - long-context - information extraction - multimodal
licensing: Apache 2.0 License
task_types: - Information extraction - Reasoning - Concept tracking - Aggregation - Algebraic manipulation
 - Multimodal comprehension
ai_capability_measured: - Long-context understanding and scientific reasoning
metrics: - Accuracy
models: - unknown
ml_motif: - Scientific problem solving
type: Benchmark
ml_task: - Supervised Learning
solutions: 0
notes: Good
contact.name: Subhashini Venugopalan
contact.email: vsubhashini@google.com
datasets.links.name: unknown
datasets.links.url: unknown
results.links.name: unknown
results.links.url: unknown
fair.reproducible: True
fair.benchmark_ready: True
id: curie_scientific_long-context_understanding_reasoning_and_information_extraction
Citations: [9]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 4 | Dataset is available via Github, but hard to find |
| documentation | 5 | Associated paper explains all criteria |
| metrics | 5 | Quantitative metrics such as ROUGE-L and F1 used. Metrics are tailored to the specific problem. |
| reference_solution | 1 | Exists, but is not open |
| software | 4 | Code is available, but not well documented |
| specification | 1 | Explains types of problems in detail, but does not state exactly how to administer them. |




3.10 FEABench (Finite Element Analysis Benchmark)

Does not exist

date: 2023-01-26
version: 1
last_updated: 2023-01-26
expired: false
valid: no
valid_date: 2023-01-26
url: <https://github.com/google/feabench>
doi: unknown
domain: Computational Engineering
focus: FEA simulation accuracy and performance
keywords: - finite element - simulation - PDE
licensing: unknown
task_types: - Simulation - Performance evaluation
ai_capability_measured: - Numerical simulation accuracy and efficiency
metrics: - Solve time - Error norm
models: - FEniCS - deal.II
ml_motif: - unknown
type: Benchmark
ml_task: - Supervised Learning
solutions: unknown
notes: OK
contact.name: unknown
contact.email: unknown
datasets.links.name: unknown
datasets.links.url: unknown
results.links.name: unknown
results.links.url: unknown
fair.reproducible: True
fair.benchmark_ready: True
id: feabench_finite_element_analysis_benchmark
Citations: [10]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 4 | Available, but not split into sets |
| documentation | 5 | In associated paper |
| metrics | 5 | Fully defined metrics |
| reference_solution | 4 | Three open-source models were used. No system constraints. |
| software | 4 | Code is available, but poorly documented |
| specification | 1.5 | Output is defined and task clarity is questionable |




3.11 SPIQA (Scientific Paper Image Question Answering)

SPIQA assesses AI models' ability to interpret and answer questions about figures and tables in scientific papers by integrating visual and textual modalities with chain-of-thought reasoning.

date: 2024-07-12
version: 1
last_updated: 2024-07-12
expired: false
valid: yes
valid_date: 2024-07-12
url: <https://arxiv.org/abs/2407.09413>
doi: 10.48550/arXiv.2407.09413
domain: Computer Science
focus: Multimodal QA on scientific figures
keywords: - multimodal QA - figure understanding - table comprehension - chain-of-thought
licensing: Apache 2.0 License
task_types: - Question answering - Multimodal QA - Chain-of-Thought evaluation
ai_capability_measured: - Visual-textual reasoning in scientific contexts
metrics: - Accuracy - F1 score
models: - Chain-of-Thought models - Multimodal QA systems
ml_motif: - Scientific paper reading
type: Benchmark
ml_task: - Supervised Learning
solutions: 0
notes: Good
contact.name: Subhashini Venugopalan
contact.email: vsubhashini@google.com
datasets.links.name: Hugging Face
datasets.links.url: <https://huggingface.co/datasets/google/spiqa>
results.links.name: unknown
results.links.url: unknown
fair.reproducible: True
fair.benchmark_ready: True
id: spiqa_scientific_paper_image_question_answering
Citations: [11]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 4.5 | Dataset is available (via paper/appendix), includes train/test/valid split. FAIR-compliant with minor gaps in versioning or access standardization. |
| documentation | 5 | All information provided in paper |
| metrics | 5 | Uses quantitative metrics (Accuracy, F1) aligned with the task |
| reference_solution | 2 | Multiple model results (e.g., GPT-4V, Gemini) reported; baselines exist, but full runnable code not confirmed for all. |
| software | 0 | Not provided |
| specification | 5 | Task administration clearly defined; prompt instructions explicitly given, no ambiguity in format or scope. |




3.12 MedQA

MedQA is a large-scale multiple-choice dataset drawn from professional medical board exams (e.g., USMLE), testing AI systems on diagnostic and medical knowledge questions in English and Chinese.

| | |
|--------------------------------|---|
| date: | 2020-09-28 |
| version: | 1 |
| last_updated: | 2020-09-28 |
| expired: | false |
| valid: | yes |
| valid_date: | 2020-09-28 |
| url: | https://arxiv.org/abs/2009.13081 |
| doi: | 10.48550/arXiv.2009.13081 |
| domain: | Medical Question Answering |
| focus: | Medical board exam QA |
| keywords: | - USMLE - diagnostic QA - medical knowledge - multilingual |
| licensing: | Under Association for the Advancement of Artificial Intelligence |
| task_types: | - Multiple choice |
| ai_capability_measured: | - Medical diagnosis and knowledge retrieval |
| metrics: | - Accuracy |
| models: | - Neural reader - Retrieval-based QA systems |
| ml_motif: | - Medical diagnosis |
| type: | Benchmark |
| ml_task: | - Supervised Learning |
| solutions: | 0 |
| notes: | Multilingual (English, Simplified and Traditional Chinese) |
| contact.name: | Di Jin |
| contact.email: | jindi15@mit.edu |
| datasets.links.name: | Github |
| datasets.links.url: | https://github.com/jind11/MedQA |
| results.links.name: | unknown |
| results.links.url: | unknown |
| fair.reproducible: | True |
| fair.benchmark_ready: | True |
| id: | medqa |
| Citations: | [12] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 4 | Dataset is publicly available (GitHub, paper, Hugging Face), well-structured. However, versioning and metadata could be more standardized to fully meet FAIR criteria. |
| documentation | 4 | Paper is available. Evaluation criteria are not mentioned. |
| metrics | 5 | Uses clear, quantitative metric (accuracy), standard for multiple-choice benchmarks; easily comparable across models. |
| reference_solution | 0 | No reference solution mentioned. |
| software | 5 | All code available on the github |
| specification | 3 | Task is clearly defined as multiple-choice QA for medical board exams; input and output formats are explicit; task scope is rigorous and structured. System constraints not specified. |




3.13 BaisBench (Biological AI Scientist Benchmark)

BaisBench evaluates AI scientists' ability to perform data-driven biological research by annotating cell types in single-cell datasets and answering MCQs derived from biological study insights, measuring autonomous scientific discovery.

date: 2025-05-13
version: 1
last_updated: 2025-05-13
expired: false
valid: yes
valid_date: 2025-05-13
url: <https://arxiv.org/abs/2505.08341>
doi: 10.48550/arXiv.2505.08341
domain: Computational Biology
focus: Omics-driven AI research tasks
keywords: - single-cell annotation - biological QA - autonomous discovery
licensing: MIT License
task_types: - Cell type annotation - Multiple choice
ai_capability_measured: - Autonomous biological research capabilities
metrics: - Annotation accuracy - QA accuracy
models: - LLM-based AI scientist agents
ml_motif: - Scientific research
type: Benchmark
ml_task: - Supervised Learning
solutions: 0
notes: Underperforms human experts; aims to advance AI-driven discovery
contact.name: Xuegong Zhang
contact.email: zhangxg@mail.tsinghua.edu.cn
datasets.links.name: Github
datasets.links.url: <https://github.com/EperLuo/BaisBench>
results.links.name: unknown
results.links.url: unknown
fair.reproducible: True
fair.benchmark_ready: True
id: baisbench_biological_ai_scientist_benchmark
Citations: [13]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 5 | Uses public scRNA-seq datasets linked in paper appendix; structured and accessible, though versioning and full metadata not formalized per FAIR standards. |
| documentation | 5 | Dataset and paper accessible; IPYNB files for setup are available on the github repo. |
| metrics | 5 | Includes precise and interpretable metrics (annotation and QA accuracy); directly aligned with task outputs and benchmarking goals. |
| reference_solution | 0 | Model evaluations and LLM agent results discussed; however, no fully packaged, runnable baseline confirmed yet. |
| software | 5 | Instructions for environment setup available |
| specification | 4 | Task clearly defined-cell type annotation and biological QA; input/output formats are well-described; system constraints are not quantified. |




3.14 MOLGEN

MolGen is a pre-trained molecular language model that generates chemically valid molecules using SELFIES and reinforcement learning, guided by chemical feedback to optimize properties such as logP, QED, and docking score.

date: 2023-01-26
version: 1
last_updated: 2023-01-26
expired: false
valid: yes
valid_date: 2023-01-26
url: <https://github.com/zjunlp/MolGen>
doi: 10.48550/arXiv.2301.11259
domain: Computational Chemistry
focus: Molecular generation and optimization
keywords: - SELFIES - GAN - property optimization
licensing: MIT License
task_types: - Distribution learning - Goal-oriented generation
ai_capability_measured: - Generation of valid and optimized molecular structures
metrics: - Validity% - Novelty% - QED - Docking score
models: - MolGen
ml_motif: - Chemical generation
type: Benchmark
ml_task: - Supervised Learning
solutions: 0
notes: This is a model, not a benchmark
contact.name: unknown
contact.email: unknown
datasets.links.name: unknown
datasets.links.url: unknown
results.links.name: unknown
results.links.url: unknown
fair.reproducible: True
fair.benchmark_ready: True
id: molgen
Citations: [14]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|-----------------------------|
| dataset | 0 | This is a pre-trained model |
| documentation | 0 | This is a pre-trained model |
| metrics | 0 | This is a pre-trained model |
| reference_solution | 0 | This is a pre-trained model |
| software | 0 | This is a pre-trained model |
| specification | 0 | This is a pre-trained model |




3.15 Open Graph Benchmark (OGB) - Biology

OGB-Biology is a suite of large-scale biological network datasets (protein-protein interaction, drug-target, etc.) with standardized splits and evaluation protocols for node, link, and graph property prediction tasks.

date: 2020-05-02
version: 1
last_updated: 2020-05-02
expired: false
valid: yes
valid_date: 2020-05-02
url: <https://ogb.stanford.edu/docs/home/>
doi: 10.48550/arXiv.2005.00687
domain: Graph ML
focus: Biological graph property prediction
keywords: - node prediction - link prediction - graph classification
licensing: MIT License
task_types: - Node property prediction - Link property prediction - Graph property prediction
ai_capability_measured: - Scalability and generalization in graph ML for biology
metrics: - Accuracy - ROC-AUC
models: - GCN - GraphSAGE - GAT
ml_motif: - Chemical biology
type: Benchmark
ml_task: - Supervised Learning
solutions: 0
notes: Community-driven updates
contact.name: OGB Team
contact.email: ogb@cs.stanford.edu
datasets.links.name: OGB Webpage
datasets.links.url: https://ogb.stanford.edu/docs/dataset_overview/
results.links.name: unknown
results.links.url: unknown
fair.reproducible: True
fair.benchmark_ready: True
id: open_graph_benchmark_ogb_-_biology
Citations: [15]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 5 | Fully FAIR- datasets are versioned, split, and accessible via a standardized API; extensive metadata and documentation are included. |
| documentation | 5 | All necessary information is included in a paper. |
| metrics | 5 | Reproducible, quantitative metrics (e.g., ROC-AUC, accuracy) that are tightly aligned with the tasks. |
| reference_solution | 3 | Multiple baselines implemented and documented (GCN, GAT, GraphSAGE). No constraints. |
| software | 5 | All necessary information is provided on the Github |
| specification | 4 | Tasks (node/link/graph property prediction) are clearly specified with input/output formats and standardized protocols; constraints (e.g., splits) are well-defined. No constraints. |




3.16 Materials Project

The Materials Project provides an open-access database of computed properties for inorganic materials via high-throughput density functional theory (DFT), accelerating materials discovery.

date: 2011-10-01
version: 1
last_updated: 2011-10-01
expired: false
valid: yes
valid_date: 2011-10-01
url: <https://materialsproject.org/>
doi: unknown
domain: Materials Science
focus: DFT-based property prediction
keywords: - DFT - materials genome - high-throughput
licensing: <https://next-gen.materialsproject.org/about/terms>
task_types: - Property prediction
ai_capability_measured: - Prediction of inorganic material properties
metrics: - MAE - R^2
models: - Automatminer - Crystal Graph Neural Networks
ml_motif: - Material properties
type: Benchmark
ml_task: - Supervised Learning
solutions: 0
notes: Core component of the Materials Genome Initiative
contact.name: unknown
contact.email: unknown
datasets.links.name: Materials Project Catalysis Explorer
datasets.links.url: <https://next-gen.materialsproject.org/catalysis>
results.links.name: unknown
results.links.url: unknown
fair.reproducible: True
fair.benchmark_ready: True
id: materials_project
Citations: [16]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 3 | API key required to access data. No predefined splits. |
| documentation | 0 | No explanations or paper provided |
| metrics | 5 | Uses numerical metrics like MAE and R^2 |
| reference_solution | 2 | Numerous models (e.g., Automatminer, CGCNN) trained on the database, but no constraints or documentation listed. |
| software | 0 | No instructions available |
| specification | 1.5 | The platform offers a wide range of material property prediction tasks, but task framing and I/O formats vary by API use and are not always standardized across use cases. |




3.17 OCP (Open Catalyst Project)

The Open Catalyst Project (OC20 and OC22) provides DFT-calculated catalyst-adsorbate relaxation datasets, challenging ML models to predict energies and forces for renewable energy applications.

date: 2020-10-20
version: 1
last_updated: 2020-10-20
expired: false
valid: yes
valid_date: 2020-10-20
url: <https://opencatalystproject.org/>
doi: unknown
domain: Chemistry; Materials Science
focus: Catalyst adsorption energy prediction
keywords: - DFT relaxations - adsorption energy - graph neural networks
licensing: OCP Terms of Use
task_types: - Energy prediction - Force prediction
ai_capability_measured: - Prediction of adsorption energies and forces
metrics: - MAE (energy) - MAE (force)
models: - CGCNN - SchNet - DimeNet++ - GemNet-OC
ml_motif: - Chemistry
type: Benchmark
ml_task: - Supervised Learning
solutions: 0
notes: Public leaderboards; active community development
contact.name: unknown
contact.email: unknown
datasets.links.name: OCP Dataset
datasets.links.url: <https://fair-chem.github.io/catalysts/datasets/summary>
results.links.name: OCP Pretrained Models
results.links.url: <https://fair-chem.github.io/catalysts/models.html>
fair.reproducible: True
fair.benchmark_ready: True
id: ocp_open_catalyst_project
Citations: [17], [18], [19], [20]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 5 | Fully FAIR- OC20, per-adsorbate trajectories, and OC22 are versioned; datasets come with standardized splits, metadata, and are downloadable. |
| documentation | 1 | Paper exists, but content is behind a paywall. |
| metrics | 5 | MAE (energy and force) are standard and reproducible. |
| reference_solution | 4 | Multiple baselines (GemNet-OC, DimeNet++, etc.) implemented and evaluated. No hardware listed. |
| software | 5 | Data provided in Github links |
| specification | 5 | Tasks (energy and force prediction) are clearly defined with explicit I/O specifications, constraints, and physical relevance for renewable energy. |




3.18 JARVIS-Leaderboard

JARVIS-Leaderboard is a community-driven platform benchmarking AI, electronic structure, force-fields, quantum computing, and experimental methods across hundreds of materials science tasks.

date: 2023-06-20
version: 1
last_updated: 2023-06-20
expired: false
valid: yes
valid_date: 2023-06-20
url: <https://arxiv.org/abs/2306.11688>
doi: 10.48550/arXiv.2306.11688
domain: Materials Science; Benchmarking
focus: Comparative evaluation of materials design methods
keywords: - leaderboards - materials methods - simulation
licensing: NIST
task_types: - Method benchmarking - Leaderboard ranking
ai_capability_measured: - Performance comparison across diverse materials design methods
metrics: - MAE - RMSE - Accuracy
models: - unknown
ml_motif: - Material science
type: Benchmark
ml_task: - Supervised Learning
solutions: 0
notes: 1281 contributions across 274 benchmarks
contact.name: Kamal Choudhary
contact.email: kamal.choudhary@nist.gov
datasets.links.name: AI model specific benchmarks
datasets.links.url: https://pages.nist.gov/jarvis_leaderboard/AI/
results.links.name: unknown
results.links.url: unknown
fair.reproducible: True
fair.benchmark_ready: True
id: jarvis-leaderboard
Citations: [21]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 4 | Data is public and adheres to FAIR principles across the NIST-hosted infrastructure; however, metadata completeness varies slightly across benchmarks. No splits. |
| documentation | 1 | Only the task is specified. |
| metrics | 5 | Metrics stated for each benchmark. |
| reference_solution | 4 | Many baselines across tasks (CGCNN, ALIGNN, M3GNet, etc.); no constraints specified. |
| software | 1 | Setup script provided, but no code provided |
| specification | 1 | Only dataset format is defined. |




3.19 Quantum Computing Benchmarks (QML)

A suite of benchmarks evaluating quantum hardware and algorithms on tasks such as state preparation, circuit optimization, and error correction across multiple platforms.

date: 2022-02-22
version: 1
last_updated: 2022-02-22
expired: false
valid: yes
valid_date: 2022-02-22
url: <https://github.com/XanaduAI/qml-benchmarks>
doi: 10.48550/arXiv.2307.03901
domain: Quantum Computing
focus: Quantum algorithm performance evaluation
keywords: - quantum circuits - state preparation - error correction
licensing: Apache-2.0
task_types: - Circuit benchmarking - State classification
ai_capability_measured: - Quantum algorithm performance and fidelity
metrics: - Fidelity - Success probability
models: - IBM Q - IonQ - AQT@LBNL
ml_motif: - Performance Evaluation
type: Benchmark
ml_task: - Supervised Learning
solutions: Varies per benchmark
notes: Hardware-agnostic, application-level metrics. The citation may not be correct.
contact.name: Xanadu AI
contact.email: support@xanadu.ai
datasets.links.name: PennyLane QML Benchmarks Datasets
datasets.links.url: <https://pennylane.ai/datasets/collection/qml-benchmarks>
results.links.name: QML Benchmarks GitHub Repository (Results section)
results.links.url: <https://github.com/XanaduAI/qml-benchmarks#results-and-leaderboards>
fair.reproducible: True
fair.benchmark_ready: True
id: quantum_computing_benchmarks_qml
Citations: [22]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 4 | Datasets are accessible, but not split. |
| documentation | 1 | Only the task is defined. |
| metrics | 3 | Partially defined, somewhat inferable metrics. Unknown whether a system's performance is captured. |
| reference_solution | 0 | Not provided |
| software | 4 | Run instructions exist, but are not easy to follow |
| specification | 3 | No system constraints. Task clarity and dataset format are not clearly specified. |




3.20 CFDBench (Fluid Dynamics)

CFDBench provides large-scale CFD data for four canonical fluid flow problems, assessing neural operators’ ability to generalize to unseen PDE parameters and domains.

date: 2024-10-01
version: 1
last_updated: 2024-10-01
expired: false
valid: yes
valid_date: 2024-10-01
url: <https://arxiv.org/abs/2310.05963>
doi: 10.48550/arXiv.2310.05963
domain: Fluid Dynamics; Scientific ML
focus: Neural operator surrogate modeling
keywords: - neural operators - CFD - FNO - DeepONet
licensing: CC-BY-4.0
task_types: - Surrogate modeling
ai_capability_measured: - Generalization of neural operators for PDEs
metrics: - L2 error - MAE
models: - FNO - DeepONet - U-Net
ml_motif: - Generalization
type: Benchmark
ml_task: - Supervised Learning
solutions: Numerous, as it’s a benchmark for ML models
notes: 302K frames across 739 cases
contact.name: Yining Luo
contact.email: yining.luo@mail.utoronto.ca
datasets.links.name: unknown
datasets.links.url: unknown
results.links.name: unknown
results.links.url: unknown
fair.reproducible: True
fair.benchmark_ready: True
id: cfdbench_fluid_dynamics
Citations: [23]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 0 | Not given |
| documentation | 5 | Associated paper gives all necessary information. |
| metrics | 5 | Quantitative metrics (L2 error, MAE, relative error) are clearly defined and align with regression task objectives. |
| reference_solution | 5 | Baseline models like FNO and DeepONet are implemented, hardware specified. |
| software | 5 | The benchmark provides Python scripts for data loading, preprocessing, and model training/evaluation |
| specification | 0 | Not listed |




3.21 SatImgNet

SATIN (sometimes referred to as SatImgNet) is a multi-task metadataset of 27 satellite imagery classification datasets evaluating zero-shot transfer of vision-language models across diverse remote sensing tasks.

date: 2023-04-23
version: 1
last_updated: 2023-04-23
expired: false
valid: yes
valid_date: 2023-04-23
url: <https://huggingface.co/datasets/saral-ai/satimagnet>
doi: 10.48550/arXiv.2304.11619
domain: Remote Sensing
focus: Satellite imagery classification
keywords: - land-use - zero-shot - multi-task
licensing: CC-BY-4.0
task_types: - Image classification
ai_capability_measured: - Zero-shot land-use classification
metrics: - Accuracy
models: - CLIP - BLIP - ALBEF
ml_motif: - Transfer Learning
type: Benchmark
ml_task: - Supervised Learning
solutions: Numerous, evaluated via leaderboard
notes: Public leaderboard available
contact.name: Jonathan Roberts
contact.email: j.roberts@cs.ox.ac.uk
datasets.links.name: SatImgNet on Hugging Face
datasets.links.url: <https://huggingface.co/datasets/saral-ai/satimagnet>
results.links.name: SatImgNet Leaderboard
results.links.url: <https://huggingface.co/spaces/saral-ai/satin-leaderboard>
fair.reproducible: True
fair.benchmark_ready: True
id: satimgnet
Citations: [24]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 5 | Hosted on Hugging Face, versioned, FAIR-compliant with rich metadata; covers many well-known remote sensing datasets unified under one metadataset, though documentation depth varies slightly across tasks. |
| documentation | 5 | Paper provides all required information |
| metrics | 5 | Accuracy of classification is an appropriate metric |
| reference_solution | 4 | Baselines like CLIP, BLIP, ALBEF evaluated in the paper; no constraints specified |
| software | 0 | No scripts or environment information provided |
| specification | 4 | Tasks (image classification across 27 satellite datasets) are clearly defined with multi-task and zero-shot framing; input/output structure is mostly standard but some task-specific nuances require interpretation. |




3.22 ClimateLearn

ClimateLearn provides standardized datasets and evaluation protocols for machine learning models in medium-range weather and climate forecasting using ERA5 reanalysis.

date: 2023-07-19
version: 1
last_updated: 2023-07-19
expired: false
valid: yes
valid_date: 2023-07-19
url: <https://arxiv.org/abs/2307.01909>
doi: 10.48550/arXiv.2307.01909
domain: Climate Science; Forecasting
focus: ML for weather and climate modeling
keywords: - medium-range forecasting - ERA5 - data-driven
licensing: CC-BY-4.0
task_types: - Forecasting
ai_capability_measured: - Global weather prediction (3-5 days)
metrics: - RMSE - Anomaly correlation
models: - CNN baselines - ResNet variants
ml_motif: - Forecasting - Benchmarking
type: Benchmark
ml_task: - Supervised Learning
solutions: Multiple baseline models provided
notes: Includes physical and ML baselines.
contact.name: Jason Jewik
contact.email: jason.jewik@ucla.edu
datasets.links.name: ClimateLearn GitHub Repository (data loaders and processing)
datasets.links.url: <https://github.com/aditya-grover/climate-learn>
results.links.name: ClimateLearn Paper (results section)
results.links.url: <https://arxiv.org/abs/2307.01909>
fair.reproducible: True
fair.benchmark_ready: True
id: climatelearn
Citations: [25]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 5 | Provides standardized access to ERA5 and other reanalysis datasets, with ML-ready splits, metadata, and Xarray-compatible formats; versioned and fully FAIR-compliant. |
| documentation | 5 | Explained in the benchmark's paper. |
| metrics | 5 | ACC and RMSE are standard, quantitative, and appropriate for climate forecasting; well-integrated into the benchmark, though interpretation across domains may vary. |
| reference_solution | 0 | The benchmark is geared for CNN architectures, but no specific model was mentioned. |
| software | 5 | Quickstart notebook makes for easy usage |
| specification | 5 | Task framing (medium-range climate forecasting), input/output formats, and evaluation windows are clearly defined; benchmark supports both physical and learned models with detailed constraints. |




3.23 BIG-Bench (Beyond the Imitation Game Benchmark)

BIG-Bench is a collaborative suite of 204 tasks designed to probe LLMs’ reasoning, knowledge, and bias across diverse domains and difficulty levels beyond simple imitation.

date: 2022-06-09
version: 1
last_updated: 2022-06-09
expired: false
valid: yes
valid_date: 2022-06-09
url: <https://github.com/google/BIG-bench>
doi: 10.48550/arXiv.2206.04615
domain: NLP; AI Evaluation
focus: Diverse reasoning and generalization tasks
keywords: - few-shot - multi-task - bias analysis
licensing: Apache-2.0
task_types: - Few-shot evaluation - Multi-task evaluation
ai_capability_measured: - Reasoning and generalization across diverse tasks
metrics: - Accuracy - Task-specific metrics
models: - GPT-3 - Dense Transformers - Sparse Transformers
ml_motif: - LLM evaluation
type: Benchmark
ml_task: - Supervised Learning
solutions: Multiple, including human baselines
notes: Human baselines included
contact.name: Aarohi Srivastava et al.
contact.email: bigbench@googlegroups.com
datasets.links.name: BIG-Bench GitHub Repository (contains tasks and data)
datasets.links.url: https://github.com/google/BIG-bench/tree/main/bigbench/benchmark_tasks
results.links.name: BIG-Bench GitHub Repository (results in papers and code)
results.links.url: <https://github.com/google/BIG-bench>
fair.reproducible: True
fair.benchmark_ready: True
id: big-bench_beyond_the_imitation_game_benchmark
Citations: [26]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 5 | Public, versioned, and well-documented; FAIR overall |
| documentation | 5 | Explained in the associated paper. |
| metrics | 5 | Many tasks use standard quantitative metrics (accuracy, BLEU, F1). Others involve subjective ratings (e.g., Likert), which reduces cross-task comparability. |
| reference_solution | 2 | Human baselines and LLM performance results are included; however, runnable reference solutions are limited and setup is not fully turnkey. |
| software | 4.5 | Quick start notebook provided, but instructions on how to run it are lacking. |
| specification | 4.5 | Tasks are diverse and clearly described; input/output formats are usually defined but vary widely, and system constraints are not standardized. |




3.24 CommonSenseQA

CommonsenseQA is a challenging multiple-choice QA dataset built from ConceptNet, requiring models to apply commonsense knowledge to select the correct answer among five choices.

| | |
|--------------------------------|---|
| date: | 2019-11-20 |
| version: | 1 |
| last_updated: | 2019-11-20 |
| expired: | false |
| valid: | yes |
| valid_date: | 2019-11-20 |
| url: | https://paperswithcode.com/paper/commonsenseqa-a-question-answering-challenge |
| doi: | 10.48550/arXiv.1811.00937 |
| domain: | NLP; Commonsense |
| focus: | Commonsense question answering |
| keywords: | - ConceptNet - multiple-choice - adversarial |
| licensing: | MIT |
| task_types: | - Multiple choice |
| ai_capability_measured: | - Commonsense reasoning and knowledge integration |
| metrics: | - Accuracy |
| models: | - BERT-large - RoBERTa - GPT-3 |
| ml_motif: | - Commonsense question answering |
| type: | Benchmark |
| ml_task: | - Supervised Learning |
| solutions: | 2 |
| notes: | Baseline 56%, human 89% |
| contact.name: | Alon Talmor, Jonathan Herzig, Nicholas Lourie, Jonathan Berant |
| contact.email: | Unknown |
| datasets.links.name: | CommonsenseQA Dataset (Hugging Face) |
| datasets.links.url: | https://huggingface.co/datasets/commonsense_qa |
| results.links.name: | Papers With Code Leaderboard for CommonsenseQA |
| results.links.url: | https://paperswithcode.com/dataset/commonsenseqa |
| fair.reproducible: | True |
| fair.benchmark_ready: | True |
| id: | commonsenseqa |
| Citations: | [27] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 5 | Public, versioned, and FAIR-compliant; includes metadata, splits, and licensing; well-integrated with HuggingFace and other ML libraries. |
| documentation | 5 | Given in paper. |
| metrics | 5 | Accuracy is a simple, reproducible metric aligned with task goals; no ambiguity in evaluation. |
| reference_solution | 4 | Several baseline models (e.g., BERT, RoBERTa) are reported with scores; implementations exist in public repos, but not run with hardware constraints |
| software | 5 | All code given on Github site |
| specification | 4 | Task and format (multiple-choice QA with 5 options) are clearly defined; grounded in ConceptNet with consistent structure, though no hardware/system constraints are specified. |




3.25 Winogrande

WinoGrande is a large-scale adversarial dataset of 44,000 Winograd Schema-style questions with reduced bias using AFLite, serving as both a benchmark and transfer learning resource.

| | |
|--------------------------------|---|
| date: | 2019-07-24 |
| version: | 1 |
| last_updated: | 2019-07-24 |
| expired: | false |
| valid: | yes |
| valid_date: | 2019-07-24 |
| url: | https://leaderboard.allenai.org/winogrande/submissions/public |
| doi: | 10.48550/arXiv.1907.10641 |
| domain: | NLP; Commonsense |
| focus: | Winograd Schema-style pronoun resolution |
| keywords: | - adversarial - pronoun resolution |
| licensing: | CC-BY |
| task_types: | - Pronoun resolution |
| ai_capability_measured: | - Robust commonsense reasoning |
| metrics: | - Accuracy - AUC |
| models: | - RoBERTa - BERT - GPT-2 |
| ml_motif: | - Commonsense reasoning |
| type: | Benchmark |
| ml_task: | - Supervised Learning |
| solutions: | 2 |
| notes: | Human ~94% |
| contact.name: | Keisuke Sakaguchi |
| contact.email: | keisukes@allenai.org |
| datasets.links.name: | Hugging Face / AllenAI |
| datasets.links.url: | https://huggingface.co/datasets/allenai/winogrande |
| results.links.name: | Papers With Code leaderboard |
| results.links.url: | https://paperswithcode.com/dataset/winogrande |
| fair.reproducible: | True |
| fair.benchmark_ready: | True |
| id: | winogrande |
| Citations: | [28] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 5 | Public, versioned, and FAIR-compliant with AFLite-generated splits to reduce annotation artifacts; hosted by AllenAI with good metadata. |
| documentation | 5 | Dataset page and paper provide sufficient detail |
| metrics | 5 | Accuracy and AUC are quantitative and well-aligned with disambiguation goals; standardized across evaluations. |
| reference_solution | 4 | Baseline results available, requiring users to submit their methods along with their submissions. Constraints are not required in submissions. |
| software | 0 | No template code provided |
| specification | 5 | Task (pronoun/coreference resolution) is clearly defined in Winograd Schema style, with consistent input/output format; no system constraints included. |




3.26 Jet Classification

This benchmark evaluates ML models for real-time classification of particle jets using high-level features derived from simulated LHC data. It includes both full-precision and quantized models optimized for FPGA deployment.

date: 2024-05-01
version: v0.2.0
last_updated: 2024-05
expired: unknown
valid: yes
valid_date: 2024-05-01
url: <https://github.com/fastmachinelearning/fastml-science/tree/main/jet-classify>
doi: 10.48550/arXiv.2207.07958
domain: Particle Physics
focus: Real-time classification of particle jets using HL-LHC simulation features
keywords: - classification - real-time ML - jet tagging - QKeras
licensing: Apache License 2.0
task_types: - Classification
ai_capability_measured: - Real-time inference - model compression performance
metrics: - Accuracy - AUC
models: - Keras DNN - QKeras quantized DNN
ml_motif: - Real-time
type: Benchmark
ml_task: - Supervised Learning
solutions: Solution details are described in the referenced paper or repository.
notes: Includes both float and quantized models using QKeras
contact.name: Jules Muhizi
contact.email: unknown
datasets.links.name: JetClass
datasets.links.url: <https://zenodo.org/record/6619768>
results.links.name: ChatGPT LLM
results.links.url: https://docs.google.com/document/d/1runrcij-eoH3_lgGZ8wm2z1YbL1Qf5cSNbVbHyWFDs4
fair.reproducible: True
fair.benchmark_ready: True
id: jet_classification
Citations: [29]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 5 | None |
| documentation | 4 | Full reproducibility requires manual setup |
| metrics | 5 | None |
| reference_solution | 4 | HW/SW requirements missing; Reference not bundled as official starter kit |
| software | 3 | Not containerized; Setup automation/documentation could be improved |
| specification | 4 | System constraints missing |




3.27 Irregular Sensor Data Compression

This benchmark addresses lossy compression of irregularly sampled sensor data from particle detectors using real-time autoencoder architectures, targeting latency-critical applications in physics experiments.

| | |
|--------------------------------|---|
| date: | 2024-05-01 |
| version: | v0.2.0 |
| last_updated: | 2024-05 |
| expired: | unknown |
| valid: | yes |
| valid_date: | 2024-05-01 |
| url: | https://github.com/fastmachinelearning/fastml-science/tree/main/sensor-data-compression |
| doi: | 10.48550/arXiv.2207.07958 |
| domain: | Particle Physics |
| focus: | Real-time compression of sparse sensor data with autoencoders |
| keywords: | - compression - autoencoder - sparse data - irregular sampling |
| licensing: | Apache License 2.0 |
| task_types: | - Compression |
| ai_capability_measured: | - Reconstruction quality - compression efficiency |
| metrics: | - MSE - Compression ratio |
| models: | - Autoencoder - Quantized autoencoder |
| ml_motif: | - Real-time, Image/CV |
| type: | Benchmark |
| ml_task: | - Unsupervised Learning |
| solutions: | Solution details are described in the referenced paper or repository. |
| notes: | Based on synthetic but realistic physics sensor data |
| contact.name: | Ben Hawks, Nhan Tran |
| contact.email: | unknown |
| datasets.links.name: | Custom synthetic irregular sensor dataset |
| datasets.links.url: | https://github.com/fastmachinelearning/fastml-science/tree/main/sensor-data-compression |
| results.links.name: | ChatGPT LLM |
| fair.reproducible: | True |
| fair.benchmark_ready: | True |
| id: | irregular_sensor_data_compression |
| Citations: | [30] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 5 | All criteria met |
| documentation | 4 | Setup for deployment (e.g., FPGA pipeline) requires familiarity with tooling |
| metrics | 5 | All criteria met |
| reference_solution | 4 | Not fully documented or automated for reproducibility |
| software | 3 | Not containerized; Full automation and documentation could be improved |
| specification | 4 | Exact latency or resource constraints not numerically specified |




3.28 Beam Control

Beam Control explores real-time reinforcement learning strategies for maintaining stable beam trajectories in particle accelerators. The benchmark is based on the BOOSTR environment for accelerator simulation.

| | |
|--------------------------------|---|
| date: | 2024-05-01 |
| version: | v0.2.0 |
| last_updated: | 2024-05 |
| expired: | unknown |
| valid: | yes |
| valid_date: | 2024-05-01 |
| url: | https://github.com/fastmachinelearning/fastml-science/tree/main/beam-control |
| doi: | 10.48550/arXiv.2207.07958 |
| domain: | Accelerators and Magnets |
| focus: | Reinforcement learning control of accelerator beam position |
| keywords: | - RL - beam stabilization - control systems - simulation |
| licensing: | Apache License 2.0 |
| task_types: | - Control |
| ai_capability_measured: | - Policy performance in simulated accelerator control |
| metrics: | - Stability - Control loss |
| models: | - DDPG - PPO (planned) |
| ml_motif: | - Real-time, RL |
| type: | Benchmark |
| ml_task: | - Reinforcement Learning |
| solutions: | Solution details are described in the referenced paper or repository. |
| notes: | Environment defined, baseline RL implementation is in progress |
| contact.name: | Ben Hawks, Nhan Tran |
| contact.email: | unknown |
| results.links.name: | ChatGPT LLM |
| fair.reproducible: | in progress |
| fair.benchmark_ready: | in progress |
| id: | beam_control |
| Citations: | [31], [32] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 3 | Not findable (no DOI/indexing); Not interoperable (format/schema unspecified) |
| documentation | 3 | Setup instructions and pretrained model details are missing |
| metrics | 5 | All criteria met |
| reference_solution | 2 | HW/SW requirements missing; Metrics not evaluated with reference; Baseline not trainable/open |
| software | 1 | Code not documented; Incomplete setup and not containerized |
| specification | 4 | Latency/resource constraints not fully quantified |




3.29 Ultrafast jet classification at the HL-LHC

Demonstrates three ML models (MLP, Deep Sets, Interaction Networks) optimized for FPGA deployment with O(100 ns) inference using quantized models and hls4ml, targeting real-time jet tagging in the L1 trigger environment at the high-luminosity LHC. Data is available on Zenodo DOI:10.5281/zenodo.3602260.

date: 2024-07-08
version: v1.0
last_updated: 2024-07
expired: unknown
valid: yes
valid_date: 2024-07-08
url: <https://arxiv.org/pdf/2402.01876>
doi: 10.48550/arXiv.2402.01876
domain: Particle Physics
focus: FPGA-optimized real-time jet origin classification at the HL-LHC
keywords: - jet classification - FPGA - quantization-aware training - Deep Sets - Interaction Networks
licensing: CC-BY
task_types: - Classification
ai_capability_measured: - Real-time inference under FPGA constraints
metrics: - Accuracy - Latency - Resource utilization
models: - MLP - Deep Sets - Interaction Network
ml_motif: - Real-time
type: Model
ml_task: - Supervised Learning
solutions: Solution details are described in the referenced paper or repository.
notes: Uses quantization-aware training; hardware synthesis evaluated via hls4ml
contact.name: Patrick Odagiu
contact.email: podagiu@ethz.ch
datasets.links.name: Zenodo dataset
datasets.links.url: <https://zenodo.org/records/3602260>
results.links.name: ChatGPT LLM
results.links.url: https://docs.google.com/document/d/1gDf1CIYtfmfZ9urv1jCRZMYz_3WwEETkugUC65OZBdw
fair.reproducible: True
fair.benchmark_ready: False
id: ultrafast_jet_classification_at_the_hl-lhc
Citations: [33]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 4 | FAIR metadata limited; no clear mention of dataset format or splits |
| documentation | 3 | No linked GitHub repo or setup instructions; paper provides partial guidance only |
| metrics | 3 | Metrics exist (accuracy, latency, utilization), but formal definitions and evaluation guidance are limited |
| reference_solution | 2 | Reference implementations not fully reproducible; no evaluation pipeline or training setup provided |
| software | 3 | Not containerized; Setup and automation incomplete |
| specification | 4 | Hardware constraints are referenced but not fully detailed or standardized |




3.30 Quench detection

Exploration of real-time quench detection using unsupervised and RL approaches, combining multi-modal sensor data (BPM, power supply, acoustic), operating on kHz-MHz streams with anomaly detection and frequency-domain features.

date: 2024-10-15
version: v1.0
last_updated: 2024-10
expired: no
valid: yes
valid_date: 2024-10-15
url: https://indico.cern.ch/event/1387540/contributions/6153618/attachments/2948441/5182077/fast_ml_magnets_
doi: NA
domain: Accelerators and Magnets
focus: Real-time detection of superconducting magnet quenches using ML
keywords: - quench detection - autoencoder - anomaly detection - real-time
licensing: Via Fermilab
task_types: - Anomaly detection - Quench localization
ai_capability_measured: - Real-time anomaly detection with multi-modal sensors
metrics: - ROC-AUC - Detection latency
models: - Autoencoder - RL agents (in development)
ml_motif: - Real-time, RL
type: Benchmark
ml_task: - Reinforcement + Unsupervised Learning
solutions: 0
notes: Precursor detection in progress; multi-modal and dynamic weighting methods
contact.name: Maira Khan
contact.email: unknown
datasets.links.name: BPM and power supply data from BNL
results.links.name: ChatGPT LLM
fair.reproducible: in progress
fair.benchmark_ready: False
id: quench_detection
Citations: [34]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 2 | Dataset URL is missing; FAIR principles largely unmet |
| documentation | 2 | Only a conference slide deck is available; lacks detailed instructions or repository for reproduction |
| metrics | 3 | ROC-AUC and latency are mentioned, but metric definitions and formal evaluation setup are missing |
| reference_solution | 1 | No baseline or reproducible model implementation available |
| software | 1 | Code not provided; no evidence of documentation or containerization |
| specification | 4 | Real-time detection task is clearly described, but exact constraints, inputs/outputs, and evaluation protocol are only partially specified |




3.31 DUNE

Applying real-time ML methods to time-series data from DUNE detectors, exploring trigger-level anomaly detection and event selection with low latency constraints.

date: 2024-10-15
version: v1.0
last_updated: 2024-10
expired: unknown
valid: yes
valid_date: 2024-10-15
url: https://indico.fnal.gov/event/66520/contributions/301423/attachments/182439/250508/fast_ml_dunedaq_sonic
doi: 10.48550/arXiv.2103.13910
domain: Particle Physics
focus: Real-time ML for DUNE DAQ time-series data
keywords: - DUNE - time-series - real-time - trigger
licensing: Via Fermilab
task_types: - Trigger selection - Time-series anomaly detection
ai_capability_measured: - Low-latency event detection
metrics: - Detection efficiency - Latency
models: - CNN - LSTM (planned)
ml_motif: - Real-time, Time-series
type: Benchmark (in progress)
ml_task: - Supervised Learning
solutions: Solution details are described in the referenced paper or repository.
notes: Prototype models demonstrated on SONIC platform
contact.name: Andrew J. Morgan
contact.email: unknown
datasets.links.name: DUNE SONIC data
results.links.name: ChatGPT LLM
fair.reproducible: in progress
fair.benchmark_ready: False
id: dune
Citations: [35]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 3 | Dataset lacks a public URL; FAIR metadata and versioning are missing |
| documentation | 3 | Documentation exists only in slides/GDocs; no implementation guide or structured release |
| metrics | 4 | Metrics are relevant but no benchmark baseline or detailed evaluation guidance is provided |
| reference_solution | 2 | Autoencoder prototype exists but is not reproducible; RL model still in development |
| software | 1 | Code not available; no containerization or setup provided |
| specification | 4 | Constraints like latency thresholds are described qualitatively but not numerically defined |




3.32 Intelligent experiments through real-time AI

Research and Development demonstrator for real-time processing of high-rate tracking data from the sPHENIX detector (RHIC) and future EIC systems. Uses GNNs with hls4ml for FPGA-based trigger generation to identify rare events (heavy flavor, DIS electrons) within 10 micros latency. Demonstrated improved accuracy and latency on Alveo/FELIX platforms.

date: 2025-01-08
version: v1.0
last_updated: 2025-01
expired: unknown
valid: yes
valid_date: 2025-01-08
url: <https://arxiv.org/pdf/2501.04845>
doi: 10.48550/arXiv.2501.04845
domain: Instrumentation and Detectors; Nuclear Physics; Particle Physics
focus: Real-time FPGA-based triggering and detector control for sPHENIX and future EIC
keywords: - FPGA - Graph Neural Network - hls4ml - real-time inference - detector control
licensing: CC BY-NC-ND 4.0
task_types: - Trigger classification - Detector control - Real-time inference
ai_capability_measured: - Low-latency GNN inference on FPGA
metrics: - Accuracy (charm and beauty detection) - Latency (micros) - Resource utilization (LUT/FF/BRAM/DSP)
models: - Bipartite Graph Network with Set Transformers (BGN-ST) - GarNet (edge-classifier)
ml_motif: - Real-time
type: Model
ml_task: - Supervised Learning
solutions: Solution details are described in the referenced paper or repository.
notes: Achieved ~97.4% accuracy for beauty decay triggers; sub-10 micros latency on Alveo U280; hit-based FPGA design via hls4ml and FlowGNN.
contact.name: Jakub Kvapil
contact.email: Jakub.Kvapil@lanl.gov
datasets.links.name: Internal simulated tracking data (sPHENIX and EIC DIS-electron tagger)
results.links.name: ChatGPT LLM
fair.reproducible: True
fair.benchmark_ready: False
id: intelligent_experiments_through_real-time_ai
Citations: [36]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 2 | Dataset is internal and not publicly available or FAIR-compliant |
| documentation | 3 | No public GitHub or complete pipeline documentation |
| metrics | 3 | Metrics relevant but not supported by evaluation scripts or baselines |
| reference_solution | 3 | No public or reproducible implementation released |
| software | 3 | No containerized or open-source setup provided |
| specification | 4 | Architectural/system specifications are incomplete |




3.33 Neural Architecture Codesign for Fast Physics Applications

Introduces a two-stage neural architecture codesign (NAC) pipeline combining global and local search, quantization-aware training, and pruning to design efficient models for fast Bragg peak finding and jet classification, synthesized for FPGA deployment with hls4ml. Achieves $>30\times$ reduction in BOPs and sub-100 ns inference latency on FPGA.

date: 2025-01-09
version: v1.0
last_updated: 2025-01
expired: unknown
valid: yes
valid_date: 2025-01-09
url: <https://arxiv.org/abs/2501.05515>
doi: 10.48550/arXiv.2501.05515
domain: Physics; Materials Science; Particle Physics
focus: Automated neural architecture search and hardware-efficient model codesign for fast physics applications
keywords: - neural architecture search - FPGA deployment - quantization - pruning - hls4ml
licensing: Via Fermilab
task_types: - Classification - Peak finding
ai_capability_measured: - Hardware-aware model optimization; low-latency inference
metrics: - Accuracy - Latency - Resource utilization
models: - NAC-based BraggNN - NAC-optimized Deep Sets (jet)
ml_motif: - Real-time, Image/CV
type: Framework
ml_task: - Supervised Learning
solutions: Solution details are described in the referenced paper or repository.
notes: Demonstrated two case studies (materials science, HEP); pipeline and code open-sourced.
contact.name: Jason Weitz (UCSD), Nhan Tran (FNAL)
contact.email: unknown
results.links.name: ChatGPT LLM
fair.reproducible: Yes (nac-opt, hls4ml)
fair.benchmark_ready: False
id: neural_architecture_codesign_for_fast_physics_applications
Citations: [37]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 2 | Simulated datasets referenced but not publicly available or FAIR-compliant |
| documentation | 4 | Detailed paper and tools described; open repo planned but not yet complete |
| metrics | 5 | Clear, quantitative metrics aligned with task goals and hardware evaluation |
| reference_solution | 4 | Models tested on hardware with source code references; full training pipeline not yet released |
| software | 3 | Toolchain (hls4ml, nac-opt) described but not yet containerized or fully packaged |
| specification | 5 | Fully specified task with constraints and target deployment; includes hardware context |




3.34 Smart Pixels for LHC

Presents a 256x256-pixel ROIC in 28 nm CMOS with embedded 2-layer NN for cluster filtering at 25 ns, achieving 54-75% data reduction while maintaining noise and latency constraints. Prototype consumes ~300 microW/pixel and operates in combinatorial digital logic.

date: 2024-06-24
version: v1.0
last_updated: 2024-06
expired: unknown
valid: yes
valid_date: 2024-06-24
url: <https://arxiv.org/abs/2406.14860>
doi: 10.48550/arXiv.2406.14860
domain: Particle Physics; Instrumentation and Detectors
focus: On-sensor, in-pixel ML filtering for high-rate LHC pixel detectors
keywords: - smart pixel - on-sensor inference - data reduction - trigger
licensing: Via Fermilab
task_types: - Image Classification - Data filtering
ai_capability_measured: - On-chip - low-power inference; data reduction
metrics: - Data rejection rate - Power per pixel
models: - 2-layer pixel NN
ml_motif: - Real-time, Image/CV
type: Benchmark
ml_task: - Image Classification
solutions: Solution details are described in the referenced paper or repository.
notes: Prototype in CMOS 28 nm; proof-of-concept for Phase III pixel upgrades.
contact.name: Lindsey Gray; Jennet Dickinson
contact.email: unknown
results.links.name: ChatGPT LLM
fair.reproducible: True
fair.benchmark_ready: Yes (Zenodo:7331128)
id: smart_pixels_for_lhc
Citations: [38]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 2 | No dataset links; not publicly hosted or FAIR-compliant |
| documentation | 3 | Paper contains detailed descriptions, but no repo or external guide for reproducing results |
| metrics | 5 | None |
| reference_solution | 3 | In-pixel 2-layer NN described and evaluated, but reproducibility and source files are not released |
| software | 2 | No packaged code or setup scripts available; replication depends on hardware description and paper |
| specification | 5 | None |




3.35 HEDM (BraggNN)

Uses BraggNN, a deep neural network, for rapid Bragg peak localization in high-energy diffraction microscopy, achieving about 13x speedup compared to Voigt-based methods while maintaining sub-pixel accuracy.

date: 2023-10-03
version: v1.0
last_updated: 2023-10
expired: unknown
valid: yes
valid_date: 2023-10-03
url: <https://arxiv.org/abs/2008.08198>
doi: 10.48550/arXiv.2008.08198
domain: Material Science
focus: Fast Bragg peak analysis using deep learning in diffraction microscopy
keywords: - BraggNN - diffraction - peak finding - HEDM
licensing: DOE Public Access Plan
task_types: - Peak detection
ai_capability_measured: - High-throughput peak localization
metrics: - Localization accuracy - Inference time
models: - BraggNN
ml_motif: - Real-time, Image/CV
type: Framework
ml_task: - Peak finding
solutions: Solution details are described in the referenced paper or repository.
notes: Enables real-time HEDM workflows; basis for NAC case study.
contact.name: Jason Weitz (UCSD)
contact.email: unknown
results.links.name: ChatGPT LLM
fair.reproducible: True
fair.benchmark_ready: True
id: hedm_braggmn
Citations: [39]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 2 | No dataset links or FAIR metadata; unclear public access |
| documentation | 3 | Paper is clear, but lacks a GitHub repo or full reproducibility pipeline |
| metrics | 4 | Only localization accuracy and inference time mentioned; not formally benchmarked with scripts |
| reference_solution | 3 | BraggNN model is described and evaluated, but no direct implementation or inference scripts available |
| software | 2 | No standalone code repository or setup instructions provided |
| specification | 5 | None |




3.36 4D-STEM

Proposes ML methods for real-time analysis of 4D scanning transmission electron microscopy datasets; framework details in progress.

date: 2023-12-03
version: v1.0
last_updated: 2023-12
expired: unknown
valid: yes
valid_date: 2023-12-03
url: <https://openreview.net/pdf?id=7yt3N0o0W9>
doi: unknown
domain: Material Science
focus: Real-time ML for scanning transmission electron microscopy
keywords: - 4D-STEM - electron microscopy - real-time - image processing
licensing: unknown
task_types: - Image Classification - Streamed data inference
ai_capability_measured: - Real-time large-scale microscopy inference
metrics: - Classification accuracy - Throughput
models: - CNN models (prototype)
ml_motif: - Real-time, Image/CV
type: Model
ml_task: - Image Classification
solutions: 0
notes: In-progress; model design under development.
contact.name: Shuyu Qin
contact.email: shq219@lehigh.edu
results.links.name: ChatGPT LLM
fair.reproducible: in progress
fair.benchmark_ready: False
id: d-stem
Citations: [40]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 2 | No dataset links or FAIR metadata; unclear public access |
| documentation | 3 | Paper is clear, but lacks a GitHub repo or full reproducibility pipeline |
| metrics | 4 | Only localization accuracy and inference time mentioned; not formally benchmarked with scripts |
| reference_solution | 3 | BraggNN model is described and evaluated, but no direct implementation or inference scripts available |
| software | 2 | No standalone code repository or setup instructions provided |
| specification | 5 | None |




3.37 In-Situ High-Speed Computer Vision

Applies low-latency CNN models for image classification of plasma diagnostics streams; supports deployment on embedded platforms.

date: 2023-12-05
version: v1.0
last_updated: 2023-12
expired: unknown
valid: yes
valid_date: 2023-12-05
url: <https://arxiv.org/abs/2312.00128>
doi: 10.48550/arXiv.2312.00128
domain: Fusion/Plasma
focus: Real-time image classification for in-situ plasma diagnostics
keywords: - plasma - in-situ vision - real-time ML
licensing: Via Fermilab
task_types: - Image Classification
ai_capability_measured: - Real-time diagnostic inference
metrics: - Accuracy - FPS
models: - CNN
ml_motif: - Real-time, Image/CV
type: Model
ml_task: - Image Classification
solutions: Solution details are described in the referenced paper or repository.
notes: Embedded/deployment details in progress.
contact.name: unknown
contact.email: unknown
results.links.name: ChatGPT LLM
results.links.url: https://docs.google.com/document/d/1EqkRHuQs1yQqMvZs_L6p9JAY2vKX5OC'TubztFBuRoQ/edit?usp=sha
fair.reproducible: in progress
fair.benchmark_ready: False
id: in-situ_high-speed_computer_vision
Citations: [41]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 0 | Dataset not provided or described in any formal way |
| documentation | 2 | Some insight via papers, but no working repo, setup, or replication path |
| metrics | 2 | Throughput and accuracy mentioned, but not defined or benchmarked |
| reference_solution | 1 | Prototype CNNs described; no code, baseline, or training details available |
| software | 1 | No public implementation or containerized setup released |
| specification | 3 | No standardized I/O, latency constraint, or complete framing |




3.38 BenchCouncil AIBench

AIBench is a comprehensive benchmark suite that evaluates AI workloads at different levels (micro, component, application) across hardware systems-covering image generation, object detection, translation, recommendation, video prediction, etc.

date: 2020-01-01
version: v1.0
last_updated: 2020-01
expired: unknown
valid: yes
valid_date: 2020-01-01
url: <https://www.benchcouncil.org/AIBench/>
doi: 10.48550/arXiv.1908.08998
domain: General
focus: End-to-end AI benchmarking across micro, component, and application levels
keywords: - benchmarking - AI systems - application-level evaluation
licensing: Apache License 2.0
task_types: - Training - Inference - End-to-end AI workloads
ai_capability_measured: - System-level AI workload performance
metrics: - Throughput - Latency - Accuracy
models: - ResNet - BERT - GANs - Recommendation systems
ml_motif: - General
type: Benchmark
ml_task: - NA
solutions: Solution details are described in the referenced paper or repository.
notes: Covers scenario-distilling, micro, component, and end-to-end benchmarks.
contact.name: Wanling Gao (BenchCouncil)
contact.email: unknown
results.links.name: ChatGPT LLM
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: benchcouncil_aibench
Citations: [42]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 3 | Multiple datasets are mentioned, but not consistently FAIR-documented, versioned, or linked |
| documentation | 3 | Paper is comprehensive, but minimal user-facing documentation or structured reproduction guide |
| metrics | 4 | Metrics are appropriate, but standardization and reproducibility across tasks vary |
| reference_solution | 3 | Reference models (e.g., ResNet, BERT) described; no turnkey implementation or results repository for all levels |
| software | 3 | No containerized or automated implementation provided for full benchmark suite |
| specification | 4 | Task coverage is broad and well-scoped, but system constraints and expected outputs are not uniformly defined |



3.39 BenchCouncil BigDataBench


BigDataBench provides benchmarks for evaluating big data and AI workloads with realistic datasets (13 sources) and pipelines across analytics, graph, warehouse, NoSQL, streaming, and AI.

date: 2020-01-01
version: v1.0
last_updated: 2020-01
expired: unknown
valid: yes
valid_date: 2020-01-01
url: <https://www.benchcouncil.org/BigDataBench/>
doi: 10.48550/arXiv.1802.08254
domain: General
focus: Big data and AI benchmarking across structured, semi-structured, and unstructured data workloads

keywords: - big data - AI benchmarking - data analytics
licensing: Apache License 2.0
task_types: - Data preprocessing - Inference - End-to-end data pipelines
ai_capability_measured: - Data processing and AI model inference performance at scale
metrics: - Data throughput - Latency - Accuracy
models: - CNN - LSTM - SVM - XGBoost
ml_motif: - General
type: Benchmark
ml_task: - NA
solutions: Solution details are described in the referenced paper or repository.
notes: Built on eight data motifs; provides Hadoop, Spark, Flink, MPI implementations.
contact.name: Jianfeng Zhan (BenchCouncil)
contact.email: unknown
results.links.name: ChatGPT LLM
results.links.url: <https://docs.google.com/document/d/1VFRxhR2G5A83S8PqKBrP99LLVgcCGvX2WW4vTtwxmQ4/edit?usp=s>
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: benchcouncil_bigdatabench
Citations: [43]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 4 | Some datasets lack consistent versioning or rich metadata annotations. |
| documentation | 4 | Setup requires manual steps; some task-specific instructions lack clarity. |
| metrics | 5 | None |
| reference_solution | 4 | Not all benchmark components have fully reproducible baselines; deployment across platforms is fragmented. |
| software | 3 | No automated setup across all tasks; some components require manual integration. |
| specification | 4 | Specific I/O formats and hardware constraints are not uniformly detailed across all tasks. |




3.40 MLPerf HPC

MLPerf HPC introduces scientific model benchmarks (e.g., CosmoFlow, DeepCAM) aimed at large-scale HPC evaluation with >10x performance scaling through system-level optimizations.

date: 2021-10-20
version: v1.0
last_updated: 2021-10
expired: unknown
valid: yes
valid_date: 2021-10-20
url: <https://github.com/mlcommons/hpc>
doi: 10.48550/arXiv.2110.11466
domain: Cosmology, Climate, Protein Structure, Catalysis
focus: Scientific ML training and inference on HPC systems
keywords: - HPC - training - inference - scientific ML
licensing: Apache License 2.0
task_types: - Training - Inference
ai_capability_measured: - Scaling efficiency - training time - model accuracy on HPC
metrics: - Training time - Accuracy - GPU utilization
models: - CosmoFlow - DeepCAM - OpenCatalyst
ml_motif: - HPC/inference, HPC/training
type: Framework
ml_task: - NA
solutions: Solution details are described in the referenced paper or repository.
notes: Shared framework with MLCommons Science; reference implementations included.
contact.name: Steven Farrell (MLCommons)
contact.email: unknown
results.links.name: ChatGPT LLM
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: mlperf_hpc
Citations: [44]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 5 | Not all data is independently versioned or comes with standardized FAIR metadata. |
| documentation | 4 | Central guidance is available but requires domain-specific effort to replicate results across systems. |
| metrics | 5 | None |
| reference_solution | 4 | Reproducibility and environment tuning depend on system configuration; baseline models not uniformly bundled. |
| software | 3 | Reference implementations exist but containerization and environment setup require manual effort across HPC systems. |
| specification | 4 | Hardware constraints and I/O formats are not fully defined for all scenarios. |




3.41 MLCommons Science

MLCommons Science assembles benchmark tasks with datasets, targets, and implementations across earthquake forecasting, satellite imagery, drug screening, electron microscopy, and CFD to drive scientific ML reproducibility.

date: 2023-06-01
version: v1.0
last_updated: 2023-06
expired: unknown
valid: yes
valid_date: 2023-06-01
url: <https://github.com/mlcommons/science>
doi: unknown
domain: Earthquake, Satellite Image, Drug Discovery, Electron Microscope, CFD
focus: AI benchmarks for scientific applications including time-series, imaging, and simulation
keywords: - science AI - benchmark - MLCommons - HPC
licensing: Apache License 2.0
task_types: - Time-series analysis - Image classification - Simulation surrogate modeling
ai_capability_measured: - Inference accuracy - simulation speed-up - generalization
metrics: - MAE - Accuracy - Speedup vs simulation
models: - CNN - GNN - Transformer
ml_motif: - Time-series, Image/CV, HPC/inference
type: Framework
ml_task: - NA
solutions: 0
notes: Joint national-lab effort under Apache-2.0 license.
contact.name: MLCommons Science Working Group
contact.email: unknown
results.links.name: ChatGPT LLM
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: mlcommons_science
Citations: [45]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 5 | Public scientific datasets are used with defined splits. At least 4 FAIR principles are followed. |
| documentation | 5 | Thorough documentation exists covering the task, background, motivation, evaluation criteria, and includes a supporting paper. |
| metrics | 5 | Clearly defined metrics such as accuracy, training time, and GPU utilization are used. These metrics are explained and effectively capture solution performance. |
| reference_solution | 5 | A reference implementation is available, well-documented, trainable/open, and includes full metric evaluation and software/hardware details. |
| software | 5 | Actively maintained GitHub repository available at https://github.com/mlcommons/science with implementations, scripts, and reproducibility support. |
| specification | 5 | All five specification aspects are covered: system constraints, task, dataset format, benchmark inputs, and outputs. |




3.42 LHC New Physics Dataset

A dataset of proton-proton collision events emulating a 40 MHz real-time data stream from LHC detectors, pre-filtered on electron or muon presence. Designed for unsupervised new-physics detection algorithms under latency/bandwidth constraints.

| | |
|--------------------------------|--|
| date: | 2021-07-05 |
| version: | v1.0 |
| last_updated: | 2021-07 |
| expired: | unknown |
| valid: | yes |
| valid_date: | 2021-07-05 |
| url: | https://arxiv.org/pdf/2107.02157 |
| doi: | unknown |
| domain: | Particle Physics; Real-time Triggering |
| focus: | Real-time LHC event filtering for anomaly detection using proton collision data |
| keywords: | - anomaly detection - proton collision - real-time inference - event filtering - unsupervised ML |
| licensing: | unknown |
| task_types: | - Anomaly detection - Event classification |
| ai_capability_measured: | - Unsupervised signal detection under latency and bandwidth constraints |
| metrics: | - ROC-AUC - Detection efficiency |
| models: | - Autoencoder - Variational autoencoder - Isolation forest |
| ml_motif: | - Multiple |
| type: | Framework |
| ml_task: | - NA |
| solutions: | 0 |
| notes: | Includes electron/muon-filtered background and black-box signal benchmarks; 1M events per black box. |
| contact.name: | Ema Puljak (ema.puljak@cern.ch) |
| contact.email: | unknown |
| datasets.links.name: | Zenodo stores, background + 3 black-box signal sets. 1M events each |
| results.links.name: | ChatGPT LLM |
| fair.reproducible: | Yes |
| fair.benchmark_ready: | Yes |
| id: | lhc_new_physics_dataset |
| Citations: | [46] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 5 | Large-scale dataset hosted on Zenodo, publicly available, well-documented, with defined train/test structure. Appears to follow at least 4 FAIR principles. |
| documentation | 3 | Some description in papers and dataset metadata exists, but lacks a unified guide, README, or training setup in a central location. |
| metrics | 4 | Uses reasonable metrics (ROC-AUC, detection efficiency) that capture performance but lacks full explanation and standard evaluation tools. |
| reference_solution | 2 | Baselines are described across multiple papers but lack centralized, reproducible implementations and hardware/software setup details. |
| software | 3 | While not formally evaluated in the previous version, Zenodo and paper links suggest available code for baseline models (e.g., autoencoders, GANs), though they are scattered and not unified in a single repository. |
| specification | 3 | The task and context are clearly described, but system constraints and formal inputs/outputs are not fully specified. |




3.43 MLCommons Medical AI

The MLCommons Medical AI working group develops benchmarks, best practices, and platforms (MedPerf, GaNDLF, COFE) to accelerate robust, privacy-preserving AI development for healthcare. MedPerf enables federated testing of clinical models on diverse datasets, improving generalizability and equity while keeping data onsite .

| | |
|--------------------------------|--|
| date: | 2023-07-17 |
| version: | v1.0 |
| last_updated: | 2023-07 |
| expired: | unknown |
| valid: | yes |
| valid_date: | 2023-07-17 |
| url: | https://github.com/mlcommons/medical |
| doi: | unknown |
| domain: | Healthcare; Medical AI |
| focus: | Federated benchmarking and evaluation of medical AI models across diverse real-world clinical data |
| keywords: | - medical AI - federated evaluation - privacy-preserving - fairness - healthcare benchmarks |
| licensing: | Apache License 2.0 |
| task_types: | - Federated evaluation - Model validation |
| ai_capability_measured: | - Clinical accuracy - fairness - generalizability - privacy compliance |
| metrics: | - ROC AUC - Accuracy - Fairness metrics |
| models: | - MedPerf-validated CNNs - GaNDLF workflows |
| ml_motif: | - Multiple |
| type: | Platform |
| ml_task: | - NA |
| solutions: | 0 |
| notes: | Open-source platform under Apache-2.0; used across 20+ institutions and hospitals . |
| contact.name: | Alex Karargyris (MLCommons Medical AI) |
| contact.email: | unknown |
| datasets.links.name: | Multi-institutional clinical datasets, radiology |
| results.links.name: | ChatGPT LLM |
| fair.reproducible: | Yes |
| fair.benchmark_ready: | Yes |
| id: | mlcommons_medical_ai |
| Citations: | [47] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 4 | Multi-institutional datasets used in federated settings; real-world data is handled privately onsite, but some FAIR aspects (e.g., accessibility and metadata) are implicit. |
| documentation | 5 | Extensive documentation, papers, and community support exist. Clear examples and usage instructions are provided in GitHub and publications. |
| metrics | 5 | Metrics such as ROC AUC, accuracy, and fairness are clearly specified and directly support goals like generalizability and equity. |
| reference_solution | 3 | GaNDLF workflows and MedPerf-validated CNNs are referenced, but not all baseline models are centrally documented or easily reproducible. |
| software | 5 | GitHub repository (https://github.com/mlcommons/medical) provides actively maintained open-source tools like MedPerf and GaNDLF for federated medical AI evaluation. |
| specification | 4 | The platform defines federated tasks and model evaluation scenarios. Some clinical and system-level constraints are implied but not uniformly formalized across all use cases. |




3.44 CaloChallenge 2022

The Fast Calorimeter Simulation Challenge 2022 assessed 31 generative-model submissions (VAEs, GANs, Flows, Diffusion) on four calorimeter shower datasets; benchmarking shower quality, generation speed, and model complexity .

date: 2024-10-28
version: v1.0
last_updated: 2024-10
expired: unknown
valid: yes
valid_date: 2024-10-28
url: <http://arxiv.org/abs/2410.21611>
doi: 10.48550/arXiv.2410.21611
domain: LHC Calorimeter; Particle Physics
focus: Fast generative-model-based calorimeter shower simulation evaluation
keywords: - calorimeter simulation - generative models - surrogate modeling - LHC - fast simulation
licensing: Via Fermilab
task_types: - Surrogate modeling
ai_capability_measured: - Simulation fidelity - speed - efficiency
metrics: - Histogram similarity - Classifier AUC - Generation latency
models: - VAE variants - GAN variants - Normalizing flows - Diffusion models
ml_motif: - Surrogate
type: Dataset
ml_task: - Surrogate Modeling
solutions: Solution details are described in the referenced paper or repository.
notes: The most comprehensive survey to date on ML-based calorimeter simulation; 31 submissions over different dataset sizes.
contact.name: Claudius Krause (CaloChallenge Lead)
contact.email: unknown
datasets.links.name: Four LHC calorimeter shower datasets
datasets.links.url: various voxel resolutions
results.links.name: ChatGPT LLM
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: calochallenge_
Citations: [48]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 5 | Four well-structured calorimeter datasets are provided, with different voxel resolutions, open access, signal/background separation, and metadata. FAIR principles are well covered. |
| documentation | 4 | Accompanied by a detailed paper and dataset description. Reproduction of pipelines may require additional setup or familiarity with the model submissions. |
| metrics | 5 | Metrics like histogram similarity, classifier AUC, and generation latency are well defined and relevant for simulation quality, fidelity, and performance. |
| reference_solution | 4 | Several baselines (GANs, VAEs, flows, diffusion models) are documented and evaluated. Some are available via community repos, though not all are fully standardized or bundled. |
| software | 4 | Community GitHub repos and model implementations are available for the 31 submissions. While not fully unified in one place, the software is accessible and reproducible. |
| specification | 5 | The task—evaluating fast generative calorimeter simulations—is clearly defined with benchmarking protocols, constraints like latency and model complexity, and structured evaluation criteria. |




3.45 Papers With Code (SOTA Platform)

Papers With Code (PWC) aggregates benchmark suites, tasks, and code across ML research: 12,423 benchmarks, 5,358 unique tasks, and 154,766 papers with code links. It tracks SOTA metrics and fosters reproducibility.

date: ongoing
version: v1.0
last_updated: 2025-06
expired: unknown
valid: yes
valid_date: ongoing
url: <https://paperswithcode.com/sota>
doi: unknown
domain: General ML; All domains
focus: Open platform tracking state-of-the-art results, benchmarks, and implementations across ML tasks and papers
keywords: - leaderboard - benchmarking - reproducibility - open-source
licensing: Apache License 2.0
task_types: - Multiple (Classification, Detection, NLP, etc.)
ai_capability_measured: - Model performance across tasks (accuracy - F1 - BLEU - etc.)
metrics: - Task-specific (Accuracy, F1, BLEU, etc.)
models: - All published models with code
ml_motif: - Multiple
type: Platform
ml_task: - Multiple
solutions: 0
notes: Community-driven open platform; automatic data extraction and versioning.
contact.name: Papers With Code Team
contact.email: unknown
results.links.name: ChatGPT LLM
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: papers_with_code_sota_platform
Citations: [49]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 3 | Relies on external datasets submitted by the community. While links are available, FAIR compliance is not guaranteed or systematically enforced across all benchmarks. |
| documentation | 4 | Strong front-end documentation and metadata on benchmarks, tasks, and models; however, some benchmark-specific instructions are sparse or dependent on external paper links. |
| metrics | 5 | Tracks state-of-the-art using task-specific metrics like Accuracy, F1, BLEU, etc., with consistent aggregation and historical SOTA tracking. |
| reference_solution | 3 | Provides links to implementations of many SOTA models, but no single unified reference baseline is required or maintained per benchmark. |
| software | 5 | Actively maintained open-source platform (https://paperswithcode.com) under Apache 2.0 license; includes automatic integration with GitHub, datasets, and models for reproducibility. |
| specification | 4 | Task and benchmark structures are well organized and standardized, but due to its broad coverage, input/output formats vary significantly between tasks and are not always tightly controlled. |




3.46 Codabench

Codabench (successor to CodaLab) is a flexible, easy-to-use, reproducible API platform for hosting AI benchmarks and code-submission challenges. It supports custom scoring, inverted benchmarks, and scalable public or private queues .

| | |
|--------------------------------|---|
| date: | 2022-01-01 |
| version: | v1.0 |
| last_updated: | 2025-03 |
| expired: | unknown |
| valid: | yes |
| valid_date: | 2022-01-01 |
| url: | https://www.codabench.org/ |
| doi: | https://doi.org/10.1016/j.patter.2022.100543 |
| domain: | General ML; Multiple |
| focus: | Open-source platform for organizing reproducible AI benchmarks and competitions |
| keywords: | - benchmark platform - code submission - competitions - meta-benchmark |
| licensing: | https://github.com/codalab/codalab-competitions/wiki/Privacy |
| task_types: | - Multiple |
| ai_capability_measured: | - Model reproducibility - performance across datasets |
| metrics: | - Submission count - Leaderboard ranking - Task-specific metrics |
| models: | - Arbitrary code submissions |
| ml_motif: | - Multiple |
| type: | Platform |
| ml_task: | - Multiple |
| solutions: | Several |
| notes: | Hosts 51 public competitions, ~26 k users, 177 k submissions |
| contact.name: | Isabelle Guyon (Université Paris-Saclay) |
| contact.email: | unknown |
| results.links.name: | ChatGPT LLM |
| fair.reproducible: | Yes |
| fair.benchmark_ready: | Yes |
| id: | codabench |
| Citations: | [50] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 1 | This is a platform for posting benchmarks, not a benchmark in itself. |
| documentation | 1 | This is a platform for posting benchmarks, not a benchmark in itself. |
| metrics | 1 | This is a platform for posting benchmarks, not a benchmark in itself. |
| reference_solution | 1 | This is a platform for posting benchmarks, not a benchmark in itself. |
| software | 1 | This is a platform for posting benchmarks, not a benchmark in itself. |
| specification | 1 | This is a platform for posting benchmarks, not a benchmark in itself. |




3.47 Sabath (SBI-FAIR)

Sabath is a metadata framework from the SBI-FAIR group (UTK, Argonne, Virginia) facilitating FAIR-compliant benchmarking and surrogate execution logging across HPC systems .

date: 2021-09-27
version: v1.0
last_updated: 2023-07
expired: unknown
valid: yes
valid_date: 2021-09-27
url: <https://sbi-fair.github.io/docs/software/sabath/>
doi: unknown
domain: Systems; Metadata
focus: FAIR metadata framework for ML-driven surrogate workflows in HPC systems
keywords: - meta-benchmark - metadata - HPC - surrogate modeling
licensing: BSD 3-Clause License
task_types: - Systems benchmarking
ai_capability_measured: - Metadata tracking - reproducible HPC workflows
metrics: - Metadata completeness - FAIR compliance
models: - NA
ml_motif: - Systems
type: Platform
ml_task: - NA
solutions: 0
notes: Developed by PI Piotr Luszczek at UTK; integrates with MiniWeatherML, AutoPhaseNN, Cosmoflow, etc.
contact.name: Piotr Luszczek
contact.email: luszczek@utk.edu
results.links.name: ChatGPT LLM
fair.reproducible: Yes
fair.benchmark_ready: N/A
id: sabath_sbi-fair
Citations: [51]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 4 | Datasets used in surrogate benchmarks are publicly available, well-structured, and FAIR-aligned, but not independently hosted by Sabath itself. |
| documentation | 3 | Basic instructions and code are provided on GitHub, but more detailed walkthroughs, use-case examples, or tutorials are limited. |
| metrics | 4 | Emphasizes metadata completeness and FAIR compliance. Metrics are clear and well-matched to its metadata-focused benchmarking context. |
| reference_solution | 3 | Includes integration with multiple surrogate benchmarks and models, though not all are fully documented or packaged as standardized reference solutions. |
| software | 4 | Actively maintained GitHub repository (https://github.com/icl-utk-edu/slip/tree/sabath) with BSD-licensed tooling for FAIR metadata capture; integrates with existing surrogate modeling benchmarks. |
| specification | 4 | FAIR metadata structure and logging goals are clearly described. Input/output definitions are implied through integrations (e.g., MiniWeatherML), though not always formalized. |




3.48 PDEBench

PDEBench offers forward/inverse PDE tasks with large ready-to-use datasets and baselines (FNO, U-Net, PINN), packaged via a unified API. It won the SimTech Best Paper Award 2023 .

| | |
|--------------------------------|---|
| date: | 2022-10-13 |
| version: | v0.1.0 |
| last_updated: | 2025-05 |
| expired: | unknown |
| valid: | yes |
| valid_date: | 2022-10-13 |
| url: | https://github.com/pdebench/PDEBench |
| doi: | 10.48550/arXiv.2210.07182 |
| domain: | CFD; Weather Modeling |
| focus: | Benchmark suite for ML-based surrogates solving time-dependent PDEs |
| keywords: | - PDEs - CFD - scientific ML - surrogate modeling - NeurIPS |
| licensing: | Other |
| task_types: | - Supervised Learning |
| ai_capability_measured: | - Time-dependent PDE modeling; physical accuracy |
| metrics: | - RMSE - boundary RMSE - Fourier RMSE |
| models: | - FNO - U-Net - PINN - Gradient-Based inverse methods |
| ml_motif: | - Multiple |
| type: | Framework |
| ml_task: | - Supervised Learning |
| solutions: | Solution details are described in the referenced paper or repository. |
| notes: | Datasets hosted on DaRUS (DOI:10.18419/darus-2986); contact maintainers by email |
| contact.name: | Makoto Takamoto (makoto.takamoto@neclab.eu) |
| contact.email: | unknown |
| results.links.name: | ChatGPT LLM |
| fair.reproducible: | Yes |
| fair.benchmark_ready: | Yes |
| id: | pdebench |
| Citations: | [52] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 5 | Diverse PDE datasets (synthetic and real-world) hosted on DaRUS with DOIs. Datasets are well-documented, structured, and follow FAIR practices. |
| documentation | 4 | Strong documentation on GitHub including examples, configs, and usage instructions. Some model-specific details and tutorials could be further expanded. |
| metrics | 4 | Includes RMSE, boundary RMSE, and Fourier-domain RMSE. These are well-suited to PDE problems, though rationale behind metric choices could be expanded in some cases. |
| reference_solution | 4 | Baselines (FNO, U-Net, PINN, etc.) are available and documented, but not every model includes full training and evaluation reproducibility out-of-the-box. |
| software | 5 | GitHub repository (https://github.com/pdebench/PDEBench) is actively maintained and includes training pipelines, data loaders, and evaluation scripts. Installation and usage are well-documented. |
| specification | 5 | Clearly defined tasks for forward and inverse PDE problems, with structured input/output formats, system constraints, and task specifications. |




3.49 The Well

A 15 TB collection of ML-ready physics simulation datasets (HDF5), covering 16 domains-from biology to astrophysical magnetohydrodynamic simulations-with unified API and metadata. Ideal for training surrogate and foundation models on scientific data.

| | |
|--------------------------------|---|
| date: | 2024-12-03 |
| version: | v1.0 |
| last_updated: | 2025-06 |
| expired: | unknown |
| valid: | yes |
| valid_date: | 2024-12-03 |
| url: | https://polymathic-ai.org/the_well/ |
| doi: | unknown |
| domain: | biological systems, fluid dynamics, acoustic scattering, astrophysical MHD |
| focus: | Foundation model + surrogate dataset spanning 16 physical simulation domains |
| keywords: | - surrogate modeling - foundation model - physics simulations - spatiotemporal dynamics |
| licensing: | BSD 3-Clause License |
| task_types: | - Supervised Learning |
| ai_capability_measured: | - Surrogate modeling - physics-based prediction |
| metrics: | - Dataset size - Domain breadth |
| models: | - FNO baselines - U-Net baselines |
| ml_motif: | - Foundation model, Surrogate |
| type: | Dataset |
| ml_task: | - Supervised Learning |
| solutions: | 1 |
| notes: | Includes unified API and dataset metadata; see 2025 NeurIPS paper for full benchmark details. Size: 15 TB. |
| contact.name: | Ruben Ohana |
| contact.email: | rohana@flatironinstitute.org |
| datasets.links.name: | 16 simulation datasets |
| datasets.links.url: | HDF5) via PyPI/GitHub |
| results.links.name: | ChatGPT LLM |
| fair.reproducible: | Yes |
| fair.benchmark_ready: | Yes |
| id: | the_well |
| Citations: | [53] |
| Ratings: | |

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 5 | 15 TB of ML-ready HDF5 datasets across 16 physics domains. Public, well-structured, richly annotated, and designed with FAIR principles in mind. |
| documentation | 4 | The GitHub repo and NeurIPS paper provide detailed guidance on dataset use, structure, and training setup. Tutorials and walkthroughs could be expanded further. |
| metrics | 3 | Domain breadth and dataset size are emphasized. Standardized quantitative metrics for model evaluation (e.g., RMSE, accuracy) are not uniformly applied across all domains. |
| reference_solution | 3 | Includes FNO and U-Net baselines, but does not yet provide fully trained, reproducible models or scripts across all datasets. |
| software | 5 | BSD-licensed software and unified API are available via GitHub and PyPI. Supports loading and manipulating large HDF5 datasets across 16 domains. |
| specification | 4 | The benchmark includes clearly defined surrogate modeling tasks, data structure, and metadata. However, constraints and formal task specs vary slightly across domains. |




3.50 LLM-Inference-Bench

A suite evaluating inference performance of LLMs (LLaMA, Mistral, Qwen) across diverse accelerators (NVIDIA, AMD, Intel, SambaNova) and frameworks (vLLM, DeepSpeed-MII, etc.), with an interactive dashboard and per-platform metrics.

date: 2024-10-31
version: v1.0
last_updated: 2024-11
expired: unknown
valid: yes
valid_date: 2024-10-31
url: <https://github.com/argonne-lcf/LLM-Inference-Bench>
doi: unknown
domain: LLM; HPC/inference
focus: Hardware performance benchmarking of LLMs on AI accelerators
keywords: - LLM - inference benchmarking - GPU - accelerator - throughput
licensing: BSD 3-Clause "New" or "Revised" License
task_types: - Inference Benchmarking
ai_capability_measured: - Inference throughput - latency - hardware utilization
metrics: - Token throughput (tok/s) - Latency - Framework-hardware mix performance
models: - LLaMA-2-7B - LLaMA-2-70B - Mistral-7B - Qwen-7B
ml_motif: - HPC/inference
type: Dataset
ml_task: - Inference Benchmarking
solutions: 0
notes: Licensed under BSD-3, maintained by Argonne; supports GPUs and accelerators.
contact.name: Krishna Teja Chitty-Venkata (Argonne LCF)
contact.email: unknown
results.links.name: ChatGPT LLM
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: llm-inference-bench
Citations: [54]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 2 | No novel dataset is introduced; benchmark relies on pre-trained LLMs and synthetic inference inputs. Dataset structure and FAIR considerations are minimal. |
| documentation | 4 | GitHub repo provides clear usage instructions, setup guides, and interactive dashboard tooling. Some areas like benchmarking extensions or advanced tuning are less detailed. |
| metrics | 5 | Hardware-specific metrics (token throughput, latency, utilization) are well-defined, consistently measured, and aggregated in dashboards. |
| reference_solution | 3 | Inference configurations and baseline performance results are provided, but there are no full reference training pipelines or model implementations. |
| software | 5 | Public GitHub repository (https://github.com/argonne-lcf/LLM-Inference-Bench) under BSD-3 license. Includes scripts, configurations, and dashboards for running and visualizing LLM inference benchmarks across multiple accelerator platforms. |
| specification | 5 | Benchmark scope, models, accelerator targets, and supported frameworks are clearly specified. Input configurations and output metrics are standardized across hardware types. |




3.51 SGLang Framework

A high-performance open-source serving framework combining efficient backend runtime (RadixAttention, batching, quantization) and expressive frontend language, boosting LLM/VLM inference throughput up to $\sim 3\times$ over alternatives.

| | |
|--------------------------------|---|
| date: | 2023-12-12 |
| version: | v0.4.9 |
| last_updated: | 2025-06 |
| expired: | unknown |
| valid: | yes |
| valid_date: | 2023-12-12 |
| url: | https://github.com/sgl-project/sglang/tree/main/benchmark |
| doi: | 10.48550/arXiv.2312.07104 |
| domain: | LLM Vision |
| focus: | Fast serving framework for LLMs and vision-language models |
| keywords: | - LLM serving - vision-language - RadixAttention - performance - JSON decoding |
| licensing: | Apache License 2.0 |
| task_types: | - Model serving framework |
| ai_capability_measured: | - Serving throughput - JSON/task-specific latency |
| metrics: | - Tokens/sec - Time-to-first-token - Throughput gain vs baseline |
| models: | - LLaVA - DeepSeek - Llama |
| ml_motif: | - LLM Vision |
| type: | Framework |
| ml_task: | - Model serving |
| solutions: | Solution details are described in the referenced paper or repository. |
| notes: | Deployed in production (xAI, NVIDIA, Google Cloud); v0.4.8 release June 2025. |
| contact.name: | SGLang Team |
| contact.email: | unknown |
| datasets.links.name: | Benchmark configs |
| results.links.name: | ChatGPT LLM |
| fair.reproducible: | Yes |
| fair.benchmark_ready: | Yes |
| id: | sglang_framework |
| Citations: | [55] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 2 | Does not introduce new datasets; instead, it evaluates performance using existing model benchmarks. Only configuration files are included. |
| documentation | 4 | Strong GitHub documentation, install guides, and benchmarks. Some advanced topics (e.g., scaling, hardware tuning) could use deeper walkthroughs. |
| metrics | 5 | Serving-related metrics such as tokens/sec, time-to-first-token, and throughput gain vs. baselines are well-defined and consistently applied. |
| reference_solution | 3 | Provides benchmark configs and example integrations (e.g., with LLaVA, DeepSeek), but not all models or scripts are runnable out-of-the-box. |
| software | 5 | Actively maintained and production-deployed (e.g., xAI, NVIDIA); source code available under Apache 2.0. Includes efficient backends (RadixAttention, quantization, batching) and full serving infrastructure. |
| specification | 4 | The framework clearly defines performance targets, serving logic, and model integration. Input/output expectations are consistent, but not all benchmarks are standardized. |




3.52 vLLM Inference and Serving Engine

vLLM is a fast, high-throughput, memory-efficient inference and serving engine for large language models, featuring PagedAttention, continuous batching, and support for quantized and pipelined model execution. Benchmarks compare it to TensorRT-LLM, SGLang, and others.

| | |
|--------------------------------|---|
| date: | 2023-09-12 |
| version: | v0.10.0 |
| last_updated: | 2025-06 |
| expired: | unknown |
| valid: | yes |
| valid_date: | 2023-09-12 |
| url: | https://github.com/vllm-project/vllm/tree/main/benchmarks |
| doi: | unknown |
| domain: | LLM; HPC/inference |
| focus: | High-throughput, memory-efficient inference and serving engine for LLMs |
| keywords: | - LLM inference - PagedAttention - CUDA graph - streaming API - quantization |
| licensing: | Apache License 2.0 |
| task_types: | - Inference Benchmarking |
| ai_capability_measured: | - Throughput - latency - memory efficiency |
| metrics: | - Tokens/sec - Time to First Token (TTFT) - Memory footprint |
| models: | - LLaMA - Mixtral - FlashAttention-based models |
| ml_motif: | - HPC/inference |
| type: | Framework |
| ml_task: | - Inference |
| solutions: | 0 |
| notes: | Incubated by LF AI and Data; achieves up to 24x throughput over HuggingFace Transformers |
| contact.name: | Woosuk Kwon (vLLM Team) |
| contact.email: | unknown |
| results.links.name: | ChatGPT LLM |
| fair.reproducible: | Yes |
| fair.benchmark_ready: | Yes |
| id: | vllm_inference_and_serving_engine |
| Citations: | [56] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 3 | No traditional dataset is included. Instead, it uses structured configs and logs suitable for inference benchmarking. FAIR principles are only partially applicable. |
| documentation | 4 | Well-structured GitHub documentation with setup instructions, config examples, benchmarking comparisons, and performance tuning guides. |
| metrics | 5 | Comprehensive performance metrics like tokens/sec, time-to-first-token (TTFT), and memory footprint are consistently applied and benchmarked across frameworks. |
| reference_solution | 4 | Provides runnable scripts and configs for several models (LLaMA, Mixtral, etc.) across platforms. Baselines are reproducible, though not all models are fully wrapped or hosted. |
| software | 5 | Actively maintained open-source project under Apache 2.0. GitHub repo includes full serving engine, benchmarking scripts, CUDA integration, and deployment examples. |
| specification | 5 | Inference benchmarks are well-defined with clear input/output formats and platform-specific constraints. Covers multiple models, hardware backends, and batching configurations. |




3.53 vLLM Performance Dashboard

A live visual dashboard for vLLM showcasing throughput, latency, and other inference metrics across models and hardware configurations.

| | |
|--------------------------------|---|
| date: | 2022-06-22 |
| version: | v1.0 |
| last_updated: | 2025-01 |
| expired: | unknown |
| valid: | yes |
| valid_date: | 2022-06-22 |
| url: | https://simon-mo-workspace.observablehq.cloud/vllm-dashboard-v0/ |
| doi: | unknown |
| domain: | LLM; HPC/inference |
| focus: | Interactive dashboard showing inference performance of vLLM |
| keywords: | - Dashboard - Throughput visualization - Latency analysis - Metric tracking |
| licensing: | unknown |
| task_types: | - Performance visualization |
| ai_capability_measured: | - Throughput - latency - hardware utilization |
| metrics: | - Tokens/sec - TTFT - Memory usage |
| models: | - LLaMA-2 - Mistral - Qwen |
| ml_motif: | - HPC/inference |
| type: | Framework |
| ml_task: | - Visualization |
| solutions: | 0 |
| notes: | Built using ObservableHQ; integrates live data from vLLM benchmarks. The URL requires a login to access the content. |
| contact.name: | Simon Mo |
| contact.email: | unknown |
| results.links.name: | ChatGPT LLM |
| fair.reproducible: | Yes |
| fair.benchmark_ready: | Yes |
| id: | vllm_performance_dashboard |
| Citations: | [57] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 2 | No datasets are bundled; the dashboard visualizes metrics derived from model inference logs or external endpoints, not a formal dataset. |
| documentation | 4 | Public dashboard with instructions and tooltips; documentation is clear, though access is restricted (login required) and backend setup is opaque to users. |
| metrics | 4 | Tracks tokens/sec, TTFT, memory usage, and platform comparisons. Metrics are clear but focused on visualization rather than statistical robustness. |
| reference_solution | 3 | Dashboards include reproducible views of benchmarked models, but do not ship with runnable model code. Relies on external serving infrastructure. |
| software | 4 | Interactive dashboard built with ObservableHQ and linked to vLLM benchmarks. Source code is not fully open, but backend integration with vLLM is well-maintained. |
| specification | 4 | While primarily a visualization tool, it includes benchmark configurations, metric definitions, and supports comparison across models and hardware. |




3.54 Nixtla NeuralForecast

NeuralForecast offers scalable, user-friendly implementations of over 30 neural forecasting models (NBEATS, NHITS, TFT, DeepAR, etc.), emphasizing quality, usability, interpretability, and performance.

| | |
|--------------------------------|--|
| date: | 2022-04-01 |
| version: | v3.0.2 |
| last_updated: | 2025-06 |
| expired: | unknown |
| valid: | yes |
| valid_date: | 2022-04-01 |
| url: | https://github.com/Nixtla/neuralforecast |
| doi: | unknown |
| domain: | Time-series forecasting; General ML |
| focus: | High-performance neural forecasting library with >30 models |
| keywords: | - time-series - neural forecasting - NBEATS, NHITS, TFT - probabilistic forecasting - usability |
| licensing: | Apache License 2.0 |
| task_types: | - Time-series forecasting |
| ai_capability_measured: | - Forecast accuracy - interpretability - speed |
| metrics: | - RMSE - MAPE - CRPS |
| models: | - NBEATS - NHITS - TFT - DeepAR |
| ml_motif: | - Time-series |
| type: | Platform |
| ml_task: | - Forecasting |
| solutions: | 0 |
| notes: | AutoModel supports hyperparameter tuning and distributed execution via Ray and Optuna. First official NHITS implementation. contentReference oaicite:4 ndex=4 |
| contact.name: | Kin G. Olivares (Nixtla) |
| contact.email: | unknown |
| results.links.name: | ChatGPT LLM |
| fair.reproducible: | Yes |
| fair.benchmark_ready: | Yes |
| id: | nixtla_neuralforecast |
| Citations: | [58] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 3 | NeuralForecast does not include its own datasets but supports standard datasets (e.g., M4, M5, ETT). FAIR compliance depends on user-supplied data. |
| documentation | 5 | Rich documentation with examples, API references, tutorials, notebooks, and CLI support. PyPI, GitHub, and official blog posts offer clear guidance for usage and extension. |
| metrics | 5 | RMSE, MAPE, CRPS, and other domain-relevant metrics are well supported and integrated into the evaluation loop. |
| reference_solution | 4 | Includes runnable model baselines and training scripts for all supported models. Some models have pretrained weights, but not all are fully benchmarked out-of-the-box. |
| software | 5 | Actively maintained open-source library under Apache 2.0. Offers a clean API, extensive model zoo (>30 models), integration with Ray, Optuna, and supports scalable training and inference workflows. |
| specification | 5 | Forecasting task is well-defined with clear input/output structures. Framework supports probabilistic and deterministic forecasting, with unified interfaces and support for batch evaluation. |




3.55 Nixtla Neural Forecast NHITS

NHITS (Neural Hierarchical Interpolation for Time Series) is a state-of-the-art model that improved accuracy by ~25% and reduced compute by 50x compared to Transformer baselines, using hierarchical interpolation and multi-rate sampling .

date: 2023-06-01
version: v3.0.2
last_updated: 2025-06
expired: unknown
valid: yes
valid_date: 2023-06-01
url: <https://github.com/Nixtla/neuralforecast>
doi: unknown
domain: Time-series; General ML
focus: Official NHITS implementation for long-horizon time series forecasting
keywords: - NHITS - long-horizon forecasting - neural interpolation - time-series
licensing: Apache License 2.0
task_types: - Time-series forecasting
ai_capability_measured: - Accuracy - compute efficiency for long series
metrics: - RMSE - MAPE
models: - NHITS
ml_motif: - Time-series
type: Platform
ml_task: - Forecasting
solutions: 0
notes: Official implementation in NeuralForecast, included since its AAAI 2023 release.
contact.name: Kin G. Olivares (Nixtla)
contact.email: unknown
datasets.links.name: Standard forecast datasets, M4
results.links.name: ChatGPT LLM
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: nixtla_neural_forecast_nhits
Citations: [59]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 3 | Uses standard benchmark datasets like M4, but does not bundle them directly. FAIR compliance depends on external dataset sources and user setup. |
| documentation | 4 | Well-documented on GitHub and in AAAI paper, with code examples, training guidance, and usage tutorials. More model-specific docs could improve clarity further. |
| metrics | 5 | Evaluated using RMSE, MAPE, and other standard forecasting metrics, integrated into training and evaluation APIs. |
| reference_solution | 4 | Official NHITS implementation is fully reproducible with training/eval configs, though pretrained weights are not always provided. |
| software | 5 | Implemented within the open-source NeuralForecast library under Apache 2.0. Includes training, evaluation, and hyperparameter tuning pipelines. Actively maintained. |
| specification | 5 | The NHITS forecasting task is clearly defined with structured input/output formats. Model design targets long-horizon accuracy and compute efficiency. |




3.56 Nixtla Neural Forecast TimeLLM

Time-LLM uses reprogramming layers to adapt frozen LLMs for time series forecasting, treating forecasting as a language task .

date: 2023-10-03
version: v3.0.2
last_updated: 2025-06
expired: unknown
valid: yes
valid_date: 2023-10-03
url: <https://github.com/Nixtla/neuralforecast>
doi: 10.48550/arXiv.2310.01728
domain: Time-series; General ML
focus: Reprogramming LLMs for time series forecasting
keywords: - Time-LLM - language model - time-series - reprogramming
licensing: Apache License 2.0
task_types: - Time-series forecasting
ai_capability_measured: - Model reuse via LLM - few-shot forecasting
metrics: - RMSE - MAPE
models: - Time-LLM
ml_motif: - Time-series
type: Platform
ml_task: - Forecasting
solutions: Solution details are described in the referenced paper or repository.
notes: Fully open-source; transforms forecasting using LLM text reconstruction.
contact.name: Ming Jin (Nixtla)
contact.email: unknown
datasets.links.name: Standard forecast datasets, M4
results.links.name: ChatGPT LLM
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: nixtla_neural_forecast_timellm
Citations: [60]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 3 | Evaluated on standard datasets like M4 and ETT, but dataset splits and versioning are not bundled or explicitly FAIR-compliant. |
| documentation | 3 | GitHub README provides installation and quick usage examples, but lacks detailed API docs, training walkthroughs, or extended tutorials. |
| metrics | 4 | Standard forecasting metrics such as RMSE, MAPE, and SMAPE are reported. Evaluation is consistent, though deeper metric justification is limited. |
| reference_solution | 3 | Time-LLM implementation is open and reproducible, but limited baselines or comparative implementations are included directly. |
| software | 4 | Fully open-source under Apache 2.0, integrated into the NeuralForecast library. Includes Time-LLM implementation with example usage and training scripts. |
| specification | 3 | High-level framing of forecasting as language modeling is clear, but detailed input/output specifications, constraints, and task formalization are minimal. |




3.57 Nixtla Neural Forecast TimeGPT

TimeGPT is a transformer-based generative pretrained model on 100B+ time series data for zero-shot forecasting and anomaly detection via API .

| | |
|--------------------------------|---|
| date: | 2023-10-05 |
| version: | v3.0.2 |
| last_updated: | 2025-06 |
| expired: | unknown |
| valid: | yes |
| valid_date: | 2023-10-05 |
| url: | https://github.com/Nixtla/neuralforecast |
| doi: | 10.48550/arXiv.2310.03589 |
| domain: | Time-series; General ML |
| focus: | Time-series foundation model "TimeGPT" for forecasting and anomaly detection |
| keywords: | - TimeGPT - foundation model - time-series - generative model |
| licensing: | Apache License 2.0 |
| task_types: | - Time-series forecasting - Anomaly detection |
| ai_capability_measured: | - Zero-shot forecasting - anomaly detection |
| metrics: | - RMSE - Anomaly detection metrics |
| models: | - TimeGPT |
| ml_motif: | - Time-series |
| type: | Platform |
| ml_task: | - Forecasting |
| solutions: | Solution details are described in the referenced paper or repository. |
| notes: | Offered via Nixtla API and Azure Studio; enterprise-grade support available. |
| contact.name: | Azul Garza (Nixtla) |
| contact.email: | unknown |
| results.links.name: | ChatGPT LLM |
| fair.reproducible: | Yes |
| fair.benchmark_ready: | Yes |
| id: | nixtla_neural_forecast_timegpt |
| Citations: | [61] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 3 | Evaluated on existing open datasets, but consolidated data release, splits, and FAIR metadata are not provided. |
| documentation | 3 | Basic README with installation and usage examples; more detailed API docs and tutorials would improve usability. |
| metrics | 4 | Uses standard forecasting metrics such as RMSE, MASE, SMAPE, and anomaly detection metrics consistently across evaluations. |
| reference_solution | 3 | TimeGPT implementation is available, but baseline comparisons and additional reference models are limited. |
| software | 4 | Fully open-source Apache 2.0 implementation integrated in NeuralForecast, supporting training and evaluation via API. Production-grade deployment available via Nixtla API and Azure. |
| specification | 3 | Concept and forecasting goals are described, but formal input/output definitions and task constraints are not rigorously specified. |




3.58 HDR ML Anomaly Challenge (Gravitational Waves)

A benchmark for detecting anomalous transient gravitational-wave signals, including "unknown-unknowns," using preprocessed LIGO time-series at 4096 Hz. Competitors submit inference models on Codabench for continuous 50 ms segments from dual interferometers.

| | |
|--------------------------------|---|
| date: | 2025-03-03 |
| version: | v1.0 |
| last_updated: | 2025-03 |
| expired: | unknown |
| valid: | yes |
| valid_date: | 2025-03-03 |
| url: | https://www.codabench.org/competitions/2626/ |
| doi: | 10.48550/arXiv.2503.02112 |
| domain: | Astrophysics; Time-series |
| focus: | Detecting anomalous gravitational-wave signals from LIGO/Virgo datasets |
| keywords: | - anomaly detection - gravitational waves - astrophysics - time-series |
| licensing: | NA |
| task_types: | - Anomaly detection |
| ai_capability_measured: | - Novel event detection in physical signals |
| metrics: | - ROC-AUC - Precision/Recall |
| models: | - Deep latent CNNs - Autoencoders |
| ml_motif: | - Time-series |
| type: | Dataset |
| ml_task: | - Anomaly detection |
| solutions: | Solution details are described in the referenced paper or repository. |
| notes: | NSF HDR A3D3 sponsored; prize pool and starter kit provided on Codabench. |
| contact.name: | HDR A3D3 Team |
| contact.email: | unknown |
| results.links.name: | ChatGPT LLM |
| fair.reproducible: | Yes |
| fair.benchmark_ready: | Yes |
| id: | hdr_ml_anomaly_challenge_gravitational_waves |
| Citations: | [62] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 5 | Uses preprocessed LIGO/Virgo time series data at 4096 Hz, publicly available and standard in astrophysics. |
| documentation | 4 | Documentation includes challenge instructions, starter kit details, and baseline descriptions, but could benefit from more thorough tutorials and code walkthroughs. |
| metrics | 4 | ROC-AUC, precision, and recall metrics are clearly specified and appropriate for anomaly detection. |
| reference_solution | 4 | Baseline deep latent CNNs and autoencoders are provided and reproducible, but not extensively documented. |
| software | 4 | Benchmark platform provided on Codabench with starter kits and submission infrastructure. Code and baseline models are publicly accessible but not extensively maintained beyond the challenge. |
| specification | 4 | Well-defined anomaly detection task on gravitational-wave time series with clear input/output expectations and challenge constraints. |




3.59 HDR ML Anomaly Challenge (Butterfly)

Image-based challenge for detecting butterfly hybrids in microscopy-driven species data. Participants evaluate models on Codabench using image segmentation/classification.

date: 2025-03-03
version: v1.0
last_updated: 2025-03
expired: unknown
valid: yes
valid_date: 2025-03-03
url: <https://www.codabench.org/competitions/3764/>
doi: 10.48550/arXiv.2503.02112
domain: Genomics; Image/CV
focus: Detecting hybrid butterflies via image anomaly detection in genomic-informed dataset
keywords: - anomaly detection - computer vision - genomics - butterfly hybrids
licensing: NA
task_types: - Anomaly detection
ai_capability_measured: - Hybrid detection in biological systems
metrics: - Classification accuracy - F1 score
models: - CNN-based detectors
ml_motif: - Image/CV
type: Dataset
ml_task: - Anomaly detection
solutions: Solution details are described in the referenced paper or repository.
notes: Hybrid detection benchmarks hosted on Codabench
contact.name: Imageomics/HDR Team
contact.email: unknown
results.links.name: ChatGPT LLM
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: hdr_ml_anomaly_challenge_butterfly
Citations: [63]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 3 | Dataset consists of real detector data with synthetic anomaly injections; access is restricted and requires NDA, limiting openness and FAIR compliance. |
| documentation | 3 | Challenge website provides basic descriptions and evaluation metrics but lacks comprehensive tutorials or example workflows. |
| metrics | 3 | Standard metrics (ROC, F1, precision) are used; evaluation protocols are clear but not deeply elaborated. |
| reference_solution | 2 | Baselines are partially described but lack public code or reproducible execution scripts. |
| software | 3 | Codabench platform provides submission infrastructure but no fully maintained code repository or reproducible baseline implementations. |
| specification | 4 | Task is clearly described with domain-specific anomaly detection objectives and relevant physics motivation. |




3.60 HDR ML Anomaly Challenge (Sea Level Rise)

A challenge combining North Atlantic sea-level time-series and satellite imagery to detect flooding anomalies. Models submitted via Codabench.

| | |
|--------------------------------|---|
| date: | 2025-03-03 |
| version: | v1.0 |
| last_updated: | 2025-03 |
| expired: | unknown |
| valid: | yes |
| valid_date: | 2025-03-03 |
| url: | https://www.codabench.org/competitions/3223/ |
| doi: | 10.48550/arXiv.2503.02112 |
| domain: | Climate Science; Time-series, Image/CV |
| focus: | Detecting anomalous sea-level rise and flooding events via time-series and satellite imagery |
| keywords: | - anomaly detection - climate science - sea-level rise - time-series - remote sensing |
| licensing: | NA |
| task_types: | - Anomaly detection |
| ai_capability_measured: | - Detection of environmental anomalies |
| metrics: | - ROC-AUC - Precision/Recall |
| models: | - CNNs, RNNs, Transformers |
| ml_motif: | - Time-series, Image/CV |
| type: | Dataset |
| ml_task: | - Anomaly detection |
| solutions: | Solution details are described in the referenced paper or repository. |
| notes: | Sponsored by NSF HDR; integrates sensor and satellite data. |
| contact.name: | HDR A3D3 Team |
| contact.email: | unknown |
| results.links.name: | ChatGPT LLM |
| fair.reproducible: | Yes |
| fair.benchmark_ready: | Yes |
| id: | hdr_ml_anomaly_challenge_sea_level_rise |
| Citations: | [64] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 5 | Uses preprocessed, public, and well-structured sensor and satellite data for the North Atlantic sea-level rise region. |
| documentation | 5 | Challenge page, starter kits, and related papers offer strong guidance for participants. |
| metrics | 5 | Standard metrics such as ROC-AUC, precision, and recall are specified and suitable for the anomaly detection tasks. |
| reference_solution | 1 | No starter models or baseline implementations linked or provided publicly. |
| software | 2 | Benchmark platform exists on Codabench, but no baseline code or maintained repository for reference solutions provided yet. |
| specification | 5 | Well-defined anomaly detection task combining satellite imagery and time-series data, with clear physical and domain-specific framing. |




3.61 Single Qubit Readout on QICK System

Implements real-time ML models for single-qubit readout on the Quantum Instrumentation Control Kit (QICK), using hls4ml to deploy quantized neural networks on RFSoc FPGAs. Offers high-fidelity, low-latency quantum state discrimination. :contentReference[oaicite:0]{index=0}

date: 2025-01-24
version: v1.0
last_updated: 2025-02
expired: unknown
valid: yes
valid_date: 2025-01-24
url: <https://github.com/fastmachinelearning/ml-quantum-readout>
doi: 10.48550/arXiv.2501.14663
domain: Quantum Computing
focus: Real-time single-qubit state classification using FPGA firmware
keywords: - qubit readout - hls4ml - FPGA - QICK
licensing: NA
task_types: - Classification
ai_capability_measured: - Single-shot fidelity - inference latency
metrics: - Accuracy - Latency
models: - hls4ml quantized NN
ml_motif: - Real-time
type: Benchmark
ml_task: - Supervised Learning
solutions: Solution details are described in the referenced paper or repository.
notes: Achieves ~96% fidelity with ~32 ns latency and low FPGA resource utilization.
contact.name: Javier Campos, Giuseppe Di Guglielmo
contact.email: unknown
datasets.links.name: Zenodo: ml-quantum-readout dataset
datasets.links.url: zenodo.org/records/14427490
results.links.name: ChatGPT LLM
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: single_qubit_readout_on_qick_system
Citations: [65]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 4 | Dataset hosted on Zenodo with structured data; however, detailed documentation on image acquisition and labeling pipeline is limited. |
| documentation | 4 | Codabench task page and GitHub repo provide descriptions and usage instructions, but detailed API or deployment tutorials are limited. |
| metrics | 5 | Standard classification metrics (accuracy, latency) are used and directly relevant to the quantum readout task. |
| reference_solution | 1 | No baseline or starter models with runnable code are linked publicly. |
| software | 3 | Code and FPGA firmware available on GitHub; integration with hls4ml demonstrated. Some deployment details and examples are provided but overall software maturity is moderate. |
| specification | 4 | Task clearly defined: real-time single-qubit state classification with latency and fidelity constraints. Labeling and ground truth definitions could be more explicit. |




3.62 GPQA: A Graduate-Level Google-Proof Question and Answer Benchmark

Contains 448 challenging questions written by domain experts, with expert accuracy at 65% (74% discounting clear errors) and non-experts reaching just 34%. GPT-4 baseline scores ~39%-designed for scalable oversight evaluation.

date: 2023-11-20
version: v1.0
last_updated: 2023-11
expired: unknown
valid: yes
valid_date: 2023-11-20
url: <https://arxiv.org/abs/2311.12022>
doi: 10.48550/arXiv.2311.12022
domain: Science (Biology, Physics, Chemistry)
focus: Graduate-level, expert-validated multiple-choice questions hard even with web access
keywords: - Google-proof - multiple-choice - expert reasoning - science QA
licensing: NA
task_types: - Multiple choice
ai_capability_measured: - Scientific reasoning - knowledge probing
metrics: - Accuracy
models: - GPT-4 baseline
ml_motif: - Multiple choice
type: Benchmark
ml_task: - Multiple choice
solutions: Solution details are described in the referenced paper or repository.
notes: Google-proof, supports oversight research.
contact.name: David Rein (NYU)
contact.email: unknown
datasets.links.name: GPQA dataset
datasets.links.url: [zip/HuggingFace](https://huggingface.co/datasets/epicure/GPQA)
results.links.name: ChatGPT LLM
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: gpqa_a_graduate-level_google-proof_question_and_answer_benchmark
Citations: [66]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 5 | The GPQA dataset is publicly released, well curated, with metadata and clearly documented splits. |
| documentation | 3 | Documentation includes dataset description and benchmark instructions, but lacks detailed usage tutorials or pipelines. |
| metrics | 5 | Accuracy is the primary metric and is clearly defined and appropriate for multiple-choice QA. |
| reference_solution | 1 | No baseline implementations or starter code are linked or provided for reproduction. |
| software | 3 | Dataset and benchmark materials are publicly available via HuggingFace and GitHub, but no integrated runnable code or software framework is provided. |
| specification | 5 | Task is clearly defined as a multiple-choice benchmark requiring expert-level scientific reasoning. Input/output formats and evaluation criteria are well described. |




3.63 SeafloorAI

A first-of-its-kind dataset covering 17,300 sq.km of seafloor with 696K sonar images, 827K segmentation masks, and 696K natural-language descriptions plus ~7M QA pairs-designed for both vision and language-based ML models in marine science

date: 2024-12-13
version: v1.0
last_updated: 2024-12
expired: unknown
valid: yes
valid_date: 2024-12-13
url: <https://neurips.cc/virtual/2024/poster/97432>
doi: 10.48550/arXiv.2411.00172
domain: Marine Science; Vision-Language
focus: Large-scale vision-language dataset for seafloor mapping and geological classification
keywords: - sonar imagery - vision-language - seafloor mapping - segmentation - QA
licensing: unknown
task_types: - Image segmentation - Vision-language QA
ai_capability_measured: - Geospatial understanding - multimodal reasoning
metrics: - Segmentation pixel accuracy - QA accuracy
models: - SegFormer - ViLT-style multimodal models
ml_motif: - Vision-Language
type: Dataset
ml_task: - Segmentation, QA
solutions: Solution details are described in the referenced paper or repository.
notes: Data processing code publicly available, covering five geological layers; curated with marine scientists
contact.name: Kien X. Nguyen
contact.email: unknown
datasets.links.name: Sonar imagery + annotations
datasets.links.url: unknown
results.links.name: ChatGPT LLM
results.links.url: unknown
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: seafloorai
Citations: [67]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 5 | Large-scale, well-annotated sonar imagery dataset with segmentation masks and natural language descriptions; curated with domain experts. |
| documentation | 4 | Dataset description and data processing instructions are provided, but tutorials and benchmark usage guides are limited. |
| metrics | 5 | Standard segmentation pixel accuracy and QA accuracy metrics are clearly specified and appropriate for the tasks. |
| reference_solution | 4 | Some baseline models (e.g., SegFormer, ViLT-style) are mentioned, but reproducible code or pretrained weights are not fully available yet. |
| software | 3 | Data processing code is publicly available, but no full benchmark framework or runnable model implementations are provided yet. |
| specification | 5 | Tasks (image segmentation and vision-language QA) are clearly defined with geospatial and multimodal objectives well specified. |




3.64 SuperCon3D

SuperCon3D introduces 3D crystal structures with associated critical temperatures (Tc) and two deep-learning models: SODNet (equivariant graph model) and DiffCSP-SC (diffusion generator) designed to screen and synthesize high-Tc candidates .

| | |
|-------------------------|---|
| date: | 2024-12-13 |
| version: | v1.0 |
| last_updated: | 2024-12 |
| expired: | unknown |
| valid: | yes |
| valid_date: | 2024-12-13 |
| url: | https://neurips.cc/virtual/2024/poster/97553 |
| doi: | unknown |
| domain: | Materials Science; Superconductivity |
| focus: | Dataset and models for predicting and generating high-Tc superconductors using 3D crystal structures |
| keywords: | - superconductivity - crystal structures - equivariant GNN - generative models |
| licensing: | unknown |
| task_types: | - Regression (Tc prediction) - Generative modeling |
| ai_capability_measured: | - Structure-to-property prediction - structure generation |
| metrics: | - MAE (Tc) - Validity of generated structures |
| models: | - SODNet - DiffCSP-SC |
| ml_motif: | - Materials Modeling |
| type: | Dataset + Models |
| ml_task: | - Regression, Generation |
| solutions: | 0 |
| notes: | Demonstrates advantage of combining ordered and disordered structural data in model design |
| contact.name: | Zhong Zuo |
| contact.email: | unknown |
| results.links.name: | ChatGPT LLM |
| fair.reproducible: | Yes |
| fair.benchmark_ready: | Yes |
| id: | supercond |
| Citations: | [68] |

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 5 | Dataset contains 3D crystal structures and associated properties; well-curated but not fully released publicly at this time. |
| documentation | 4 | Paper and GitHub provide good metadata and data processing descriptions; tutorials and user guides could be expanded. |
| metrics | 4 | Metrics such as MAE for Tc prediction and validity checks for generated structures are appropriate and clearly described. |
| reference_solution | 4 | Paper provides model architecture details and some training insights, but no complete open-source reference implementations yet. |
| software | 3 | Baseline models (SODNet, DiffCSP-SC) are described in the paper; however, fully reproducible code and pretrained models are not publicly available yet. |
| specification | 5 | Tasks for regression (Tc prediction) and generative modeling with clear input/output structures and domain constraints are well defined. |




3.65 GeSS

GeSS provides 30 benchmark scenarios across particle physics, materials science, and biochemistry, evaluating 3 GDL backbones and 11 algorithms under covariate, concept, and conditional shifts, with varied OOD access .

date: 2024-12-13
version: v1.0
last_updated: 2024-12
expired: unknown
valid: yes
valid_date: 2024-12-13
url: <https://neurips.cc/virtual/2024/poster/97816>
doi: unknown
domain: Scientific ML; Geometric Deep Learning
focus: Benchmark suite evaluating geometric deep learning models under real-world distribution shifts
keywords: - geometric deep learning - distribution shift - OOD robustness - scientific applications
licensing: unknown
task_types: - Classification - Regression
ai_capability_measured: - OOD performance in scientific settings
metrics: - Accuracy - RMSE - OOD robustness delta
models: - GCN - EGNN - DimeNet++
ml_motif: - Geometric DL
type: Benchmark
ml_task: - Classification, Regression
solutions: 0
notes: Includes no-OOD, unlabeled-OOD, and few-label scenarios .
contact.name: Deyu Zou
contact.email: unknown
results.links.name: ChatGPT LLM
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: gess
Citations: [69]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 5 | Curated datasets of 3D crystal structures and material properties are included and publicly available for reproducible research. |
| documentation | 4 | Paper and poster provide solid explanation of benchmarks and scientific motivation; more extensive user documentation forthcoming. |
| metrics | 5 | Uses well-established metrics such as MAE and structural validity for materials modeling, plus accuracy and OOD robustness deltas. |
| reference_solution | 4 | Two reference models (SODNet, DiffCSP-SC) are reported with results, code expected to be released soon. |
| software | 3 | Reference code expected post-conference; current public software availability limited. Benchmark infrastructure partially described but not fully released yet. |
| specification | 5 | Benchmark clearly defines OOD robustness scenarios with classification and regression tasks in scientific domains, though no explicit hardware constraints are given. |




3.66 Vocal Call Locator (VCL)

The first large-scale benchmark (767K sounds across 9 conditions) for localizing rodent vocal calls using synchronized audio and video in standard lab environments, enabling systematic evaluation of sound-source localization algorithms in bioacoustics .

date: 2024-12-13
version: v1.0
last_updated: 2024-12
expired: unknown
valid: yes
valid_date: 2024-12-13
url: <https://neurips.cc/virtual/2024/poster/97470>
doi: unknown
domain: Neuroscience; Bioacoustics
focus: Benchmarking sound-source localization of rodent vocalizations from multi-channel audio
keywords: - source localization - bioacoustics - time-series - SSL
licensing: unknown
task_types: - Sound source localization
ai_capability_measured: - Source localization accuracy in bioacoustic settings
metrics: - Localization error (cm) - Recall/Precision
models: - CNN-based SSL models
ml_motif: - Real-time
type: Dataset
ml_task: - Anomaly detection / localization
solutions: 0
notes: Dataset spans real, simulated, and mixed audio; supports benchmarking across data types .
contact.name: Ralph Peterson
contact.email: unknown
results.links.name: ChatGPT LLM
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: vocal_call_locator_vcl
Citations: [70]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 4 | Large-scale audio dataset covering real and simulated data with standardized splits, though exact data formats are not fully detailed. |
| documentation | 1 | Methodology and paper are thorough, but setup instructions and runnable code are not publicly provided, limiting user onboarding. |
| metrics | 5 | Includes localization error, precision, recall, and other relevant metrics for robust evaluation. |
| reference_solution | 5 | Multiple baselines evaluated over diverse models and architectures, supporting reproducibility of benchmark comparisons. |
| software | 3 | Some baseline CNN models for sound source localization are reported, but no publicly available or fully integrated runnable codebase yet. |
| specification | 5 | Well-defined localization tasks with multiple scenarios and real-world environment conditions; input/output formats clearly described. |




3.67 MassSpecGym

MassSpecGym curates the largest public MS/MS dataset with three standardized tasks-de novo structure generation, molecule retrieval, and spectrum simulation-using challenging generalization splits to propel ML-driven molecule discovery .

| | |
|--------------------------------|---|
| date: | 2024-12-13 |
| version: | v1.0 |
| last_updated: | 2024-12 |
| expired: | unknown |
| valid: | yes |
| valid_date: | 2024-12-13 |
| url: | https://neurips.cc/virtual/2024/poster/97823 |
| doi: | unknown |
| domain: | Cheminformatics; Molecular Discovery |
| focus: | Benchmark suite for discovery and identification of molecules via MS/MS |
| keywords: | - mass spectrometry - molecular structure - de novo generation - retrieval - dataset |
| licensing: | unknown |
| task_types: | - De novo generation - Retrieval - Simulation |
| ai_capability_measured: | - Molecular identification and generation from spectral data |
| metrics: | - Structure accuracy - Retrieval precision - Simulation MSE |
| models: | - Graph-based generative models - Retrieval baselines |
| ml_motif: | - Benchmark |
| type: | Dataset + Benchmark |
| ml_task: | - Generation, retrieval, simulation |
| solutions: | 0 |
| notes: | Dataset~>1M spectra; open-source GitHub repo; widely cited as a go-to benchmark for MS/MS tasks . |
| contact.name: | Roman Bushuiev |
| contact.email: | unknown |
| results.links.name: | ChatGPT LLM |
| fair.reproducible: | Yes |
| fair.benchmark_ready: | Yes |
| id: | massspecgym |
| Citations: | [71] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 5 | Largest public MS/MS dataset with extensive annotations; minor point deducted for lack of explicit train/validation/test splits. |
| documentation | 1 | Paper and poster describe benchmark goals and design, but documentation and user guides are minimal and repo status uncertain. |
| metrics | 5 | Well-defined metrics such as structure accuracy, retrieval precision, and simulation MSE used consistently. |
| reference_solution | 3.5 | CNN-based baselines are referenced, but pretrained weights and comprehensive training pipelines are not fully documented. |
| software | 3 | Open-source GitHub repository available; baseline models and training code partially provided but overall framework maturity is moderate. |
| specification | 5 | Clearly defined tasks including molecule generation, retrieval, and spectrum simulation, scoped for MS/MS molecular identification. |




3.68 Urban Data Layer (UDL)

UrbanDataLayer standardizes heterogeneous urban data formats and provides pipelines for tasks like air quality prediction and land-use classification, enabling the rapid creation of multi-modal urban benchmarks .

date: 2024-12-13
version: v1.0
last_updated: 2024-12
expired: unknown
valid: yes
valid_date: 2024-12-13
url: <https://neurips.cc/virtual/2024/poster/97837>
doi: unknown
domain: Urban Computing; Data Engineering
focus: Unified data pipeline for multi-modal urban science research
keywords: - data pipeline - urban science - multi-modal - benchmark
licensing: unknown
task_types: - Prediction - Classification
ai_capability_measured: - Multi-modal urban inference - standardization
metrics: - Task-specific accuracy or RMSE
models: - Baseline regression/classification pipelines
ml_motif: - Data engineering
type: Framework
ml_task: - Prediction, classification
solutions: 0
notes: Source code available on GitHub (SJTU-CILAB/udl); promotes reusable urban-science foundation models .
contact.name: Yiheng Wang
contact.email: unknown
results.links.name: ChatGPT LLM
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: urban_data_layer_udl
Citations: [72]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|--|
| dataset | 5 | Large, multi-modal urban datasets are open-source, well-documented, and support reproducible research. |
| documentation | 5 | GitHub repository and conference poster provide comprehensive code and reproducibility instructions. |
| metrics | 5 | Uses task-specific accuracy and RMSE metrics appropriate for prediction and classification. |
| reference_solution | 4 | Baseline models available but not exhaustive; community adoption and extensions expected. |
| software | 3 | Source code is publicly available on GitHub; baseline regression and classification pipelines are included but framework maturity is moderate. |
| specification | 5 | Multiple urban science tasks like prediction and classification are well specified with clear input/output and evaluation criteria. |




3.69 Delta Squared-DFT

Introduces the Delta Squared-ML paradigm-using ML corrections to DFT to predict reaction energies with accuracy comparable to CCSD(T), while training on small CC datasets. Evaluated across 10 reaction datasets covering organic and organometallic transformations.

| | |
|--------------------------------|---|
| date: | 2024-12-13 |
| version: | v1.0 |
| last_updated: | 2024-12 |
| expired: | unknown |
| valid: | yes |
| valid_date: | 2024-12-13 |
| url: | https://neurips.cc/virtual/2024/poster/97788 |
| doi: | 10.48550/arXiv.2406.14347 |
| domain: | Computational Chemistry; Materials Science |
| focus: | Benchmarking machine-learning corrections to DFT using Delta Squared-trained models for reaction energies |
| keywords: | - density functional theory - Delta Squared-ML correction - reaction energetics - quantum chemistry |
| licensing: | unknown |
| task_types: | - Regression |
| ai_capability_measured: | - High-accuracy energy prediction - DFT correction |
| metrics: | - Mean Absolute Error (eV) - Energy ranking accuracy |
| models: | - Delta Squared-ML correction networks - Kernel ridge regression |
| ml_motif: | - Scientific ML |
| type: | Dataset + Benchmark |
| ml_task: | - Regression |
| solutions: | Solution details are described in the referenced paper or repository. |
| notes: | Demonstrates CC-level accuracy with ~1% of high-level data. Benchmarks publicly included for reproducibility. |
| contact.name: | Wei Liu |
| contact.email: | unknown |
| results.links.name: | ChatGPT LLM |
| fair.reproducible: | Yes |
| fair.benchmark_ready: | Yes |
| id: | delta_squared-dft |
| Citations: | [73] |

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 4.5 | Multi-modal quantum chemistry datasets are standardized and accessible; repository available. |
| documentation | 4 | Source code supports pipeline reuse, but formal evaluation splits may vary. |
| metrics | 4 | Uses standard regression metrics like MAE and energy ranking accuracy; appropriate for task. |
| reference_solution | 3.5 | Includes baseline regression and kernel ridge models; implementations are reproducible. |
| software | 3 | Source code and baseline models available for ML correction to DFT; framework maturity is moderate. |
| specification | 4 | Benchmark focuses on reaction energy prediction with clear goals, though some task specifics could be formalized further. |




3.70 LLMs for Crop Science

Establishes a benchmark of 3,500 expert-annotated prompts and QA pairs covering crop traits, growth stages, and environmental interactions. Tests GPT-style LLMs on accuracy and domain reasoning using in-context, chain-of-thought, and retrieval-augmented prompts.

date: 2024-12-13
version: v1.0
last_updated: 2024-12
expired: unknown
valid: yes
valid_date: 2024-12-13
url: <https://neurips.cc/virtual/2024/poster/97570>
doi: 10.48550/arXiv.2406.03085
domain: Agricultural Science; NLP
focus: Evaluating LLMs on crop trait QA and textual inference tasks with domain-specific prompts
keywords: - crop science - prompt engineering - domain adaptation - question answering
licensing: unknown
task_types: - Question Answering - Inference
ai_capability_measured: - Scientific knowledge - crop reasoning
metrics: - Accuracy - F1 score
models: - GPT-4 - LLaMA-2-13B - T5-XXL
ml_motif: - NLP
type: Dataset
ml_task: - QA, inference
solutions: Solution details are described in the referenced paper or repository.
notes: Includes examples with retrieval-augmented and chain-of-thought prompt templates; supports few-shot adaptation.
contact.name: Deepak Patel
contact.email: unknown
results.links.name: ChatGPT LLM
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: llms_for_crop_science
Citations: [74]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|-----------------------------------|
| dataset | 0 | This is a model, not a benchmark. |
| documentation | 0 | This is a model, not a benchmark. |
| metrics | 0 | This is a model, not a benchmark. |
| reference_solution | 0 | This is a model, not a benchmark. |
| software | 0 | This is a model, not a benchmark. |
| specification | 0 | This is a model, not a benchmark. |




3.71 SPIQA (LLM)

A workshop version of SPIQA comparing 10 LLM adapter methods on the SPIQA benchmark with scientific diagram/questions. Highlights performance differences between chain-of-thought and end-to-end adapter models.

date: 2024-12-13
version: v1.0
last_updated: 2024-12
expired: unknown
valid: yes
valid_date: 2024-12-13
url: <https://neurips.cc/virtual/2024/poster/97575>
doi: 10.48550/arXiv.2407.09413
domain: Multimodal Scientific QA; Computer Vision
focus: Evaluating LLMs on image-based scientific paper figure QA tasks (LLM Adapter performance)
keywords: - multimodal QA - scientific figures - image+text - chain-of-thought prompting
licensing: unknown
task_types: - Multimodal QA
ai_capability_measured: - Visual reasoning - scientific figure understanding
metrics: - Accuracy - F1 score
models: - LLaVA - MiniGPT-4 - Owl-LLM adapter variants
ml_motif: - Multimodal QA
type: Benchmark
ml_task: - Multimodal QA
solutions: Solution details are described in the referenced paper or repository.
notes: Companion to SPIQA main benchmark; compares adapter strategies using same images and QA pairs.
contact.name: Xiaoyan Zhong
contact.email: unknown
results.links.name: ChatGPT LLM
fair.reproducible: Yes
fair.benchmark_ready: Yes
id: spiqqa_llm
Citations: [75]

Ratings:

| Rating | Value | Reason |
|--------------------|-------|---|
| dataset | 5 | Full dataset available on Hugging Face with train/test/valid splits. |
| documentation | 5 | Full paper available |
| metrics | 4 | Reports accuracy and F1; fair but no visual reasoning-specific metric. |
| reference_solution | 4 | 10 LLM adapter baselines; results included without constraints. |
| software | 5 | Well-documented codebase available on Github |
| specification | 3.5 | Task of QA over scientific figures is sufficient but not fully formalized in input/output terms. No hardware constraints. |



References

- [1] D. Hendrycks, C. Burns, and S. Kadavath, *Measuring massive multitask language understanding*, 2021. [Online]. Available: <https://arxiv.org/abs/2009.03300>.
- [2] D. Rein, B. L. Hou, and A. C. Stickland, *Gpqa: A graduate-level google-proof q and a benchmark*, 2023. [Online]. Available: <https://arxiv.org/abs/2311.12022>.
- [3] P. Clark, I. Cowhey, and O. Etzioni, “Think you have solved question answering? try arc, the ai2 reasoning challenge,” in *EMNLP 2018*, 2018, pp. 237–248. [Online]. Available: <https://allenai.org/data/arc>.
- [4] L. Phan, A. Gatti, Z. Han, *et al.*, *Humanity’s last exam*, 2025. arXiv: 2501.14249 [cs.LG]. [Online]. Available: <https://arxiv.org/abs/2501.14249>.
- [5] E. Glazer, E. Erdil, T. Besiroglu, *et al.*, *Frontiermath: A benchmark for evaluating advanced mathematical reasoning in ai*, 2024. arXiv: 2411.04872 [cs.AI]. [Online]. Available: <https://arxiv.org/abs/2411.04872>.
- [6] M. Tian, L. Gao, S. D. Zhang, *et al.*, *Scicode: A research coding benchmark curated by scientists*, 2024. arXiv: 2407.13168 [cs.AI]. [Online]. Available: <https://arxiv.org/abs/2407.13168>.
- [7] TBD, *Aime*, [Online accessed 2025-06-24], Mar. 2025. [Online]. Available: <https://www.vals.ai/benchmarks/aime-2025-03-13>.
- [8] HuggingFaceH4, *Math-500*, 2025. [Online]. Available: <https://huggingface.co/datasets/HuggingFaceH4/MATH-500>.
- [9] H. Cui, Z. Shamsi, G. Cheon, *et al.*, *Curie: Evaluating llms on multitask scientific long context understanding and reasoning*, 2025. arXiv: 2503.13517 [cs.CL]. [Online]. Available: <https://arxiv.org/abs/2503.13517>.
- [10] N. Mudur, H. Cui, S. Venugopalan, P. Raccuglia, M. P. Brenner, and P. Norgaard, *Feabench: Evaluating language models on multiphysics reasoning ability*, 2025. arXiv: 2504.06260 [cs.AI]. [Online]. Available: <https://arxiv.org/abs/2504.06260>.
- [11] X. Zhong, Y. Gao, and S. Gururangan, *Spiga: Scientific paper image question answering*, 2024. [Online]. Available: <https://arxiv.org/abs/2407.09413>.
- [12] D. Jin, E. Pan, N. Oufattole, W.-H. Weng, H. Fang, and P. Szolovits, *What disease does this patient have? a large-scale open domain question answering dataset from medical exams*, 2020. arXiv: 2009.13081 [cs.CL]. [Online]. Available: <https://arxiv.org/abs/2009.13081>.
- [13] E. Luo, J. Jia, Y. Xiong, *et al.*, *Benchmarking ai scientists in omics data-driven biological research*, 2025. arXiv: 2505.08341 [cs.AI]. [Online]. Available: <https://arxiv.org/abs/2505.08341>.
- [14] Y. Fang, N. Zhang, Z. Chen, L. Guo, X. Fan, and H. Chen, *Domain-agnostic molecular generation with chemical feedback*, 2024. arXiv: 2301.11259 [cs.LG]. [Online]. Available: <https://arxiv.org/abs/2301.11259>.
- [15] W. Hu, M. Fey, M. Zitnik, *et al.*, *Open graph benchmark: Datasets for machine learning on graphs*, 2021. arXiv: 2005.00687 [cs.LG]. [Online]. Available: <https://arxiv.org/abs/2005.00687>.
- [16] A. Jain, S. P. Ong, G. Hautier, *et al.*, “The materials project: A materials genome approach,” *APL Materials*, vol. 1, no. 1, 2013. DOI: 10.1063/1.4812323. [Online]. Available: <https://materialsproject.org/>.
- [17] L. Chanussot, A. Das, S. Goyal, *et al.*, “The open catalyst 2020 (oc20) dataset and community challenges,” *ACS Catalysis*, vol. 11, no. 10, pp. 6059–6072, 2021. DOI: 10.1021/acscatal.0c04525. [Online]. Available: <https://pubs.acs.org/doi/10.1021/acscatal.0c04525>.
- [18] R. Tran, J. Lan, M. Shuaibi, *et al.*, “The open catalyst 2022 (oc22) dataset and challenges for oxide electrocatalysts,” *ACS Catalysis*, vol. 13, no. 5, pp. 3066–3084, 2023. DOI: 10.1021/acscatal.2c05426. [Online]. Available: <https://pubs.acs.org/doi/10.1021/acscatal.2c05426>.

- [19] L. Chanussot, A. Das, S. Goyal, *et al.*, “Open catalyst 2020 (oc20) dataset and community challenges,” *ACS Catalysis*, vol. 11, no. 10, pp. 6059–6072, 2021. DOI: 10.1021/acscatal.0c04525. eprint: <https://doi.org/10.1021/acscatal.0c04525>. [Online]. Available: <https://doi.org/10.1021/acscatal.0c04525>.
- [20] R. Tran, J. Lan, M. Shuaibi, *et al.*, “The open catalyst 2022 (oc22) dataset and challenges for oxide electrocatalysts,” *ACS Catalysis*, vol. 13, no. 5, pp. 3066–3084, Feb. 2023, ISSN: 2155-5435. DOI: 10.1021/acscatal.2c05426. [Online]. Available: <http://dx.doi.org/10.1021/acscatal.2c05426>.
- [21] K. Choudhary, D. Wines, K. Li, *et al.*, “JARVIS-Leaderboard: A large scale benchmark of materials design methods,” *npj Computational Materials*, vol. 10, no. 1, p. 93, 2024. DOI: 10.1038/s41524-024-01259-w. [Online]. Available: <https://doi.org/10.1038/s41524-024-01259-w>.
- [22] F. J. Kiwit, M. Marso, P. Ross, C. A. Riofrío, J. Klepsch, and A. Luckow, “Application-oriented benchmarking of quantum generative learning using quark,” in *2023 IEEE International Conference on Quantum Computing and Engineering (QCE)*, IEEE, Sep. 2023, pp. 475–484. DOI: 10.1109/qce57702.2023.00061. [Online]. Available: <http://dx.doi.org/10.1109/QCE57702.2023.00061>.
- [23] Y. Luo, Y. Chen, and Z. Zhang, *Cfdbench: A large-scale benchmark for machine learning methods in fluid dynamics*, 2024. [Online]. Available: <https://arxiv.org/abs/2310.05963>.
- [24] J. Roberts, K. Han, and S. Albanie, *Satin: A multi-task metadataset for classifying satellite imagery using vision-language models*, 2023. [Online]. Available: <https://huggingface.co/datasets/saral-ai/satimagnet>.
- [25] T. Nguyen, J. Jewik, H. Bansal, P. Sharma, and A. Grover, *Climatelearn: Benchmarking machine learning for weather and climate modeling*, 2023. arXiv: 2307.01909 [cs.LG]. [Online]. Available: <https://arxiv.org/abs/2307.01909>.
- [26] A. Srivastava, A. Rastogi, A. Rao, *et al.*, *Beyond the imitation game: Quantifying and extrapolating the capabilities of language models*, 2023. arXiv: 2206.04615 [cs.CL]. [Online]. Available: <https://arxiv.org/abs/2206.04615>.
- [27] A. Talmor, J. Herzig, N. Lourie, and J. Berant, *Commonsenseqa: A question answering challenge targeting commonsense knowledge*, 2019. arXiv: 1811.00937 [cs.CL]. [Online]. Available: <https://arxiv.org/abs/1811.00937>.
- [28] K. Sakaguchi, R. L. Bras, C. Bhagavatula, and Y. Choi, *Winogrande: An adversarial winograd schema challenge at scale*, 2019. arXiv: 1907.10641 [cs.CL]. [Online]. Available: <https://arxiv.org/abs/1907.10641>.
- [29] J. Duarte, N. Tran, B. Hawks, *et al.*, *Fastml science benchmarks: Accelerating real-time scientific edge machine learning*, 2022. arXiv: 2207.07958 [cs.LG]. [Online]. Available: <https://arxiv.org/abs/2207.07958>.
- [30] J. Duarte, N. Tran, B. Hawks, *et al.*, *Fastml science benchmarks: Accelerating real-time scientific edge machine learning*, 2022. arXiv: 2207.07958 [cs.LG]. [Online]. Available: <https://arxiv.org/abs/2207.07958>.
- [31] J. Duarte, N. Tran, B. Hawks, *et al.*, *Fastml science benchmarks: Accelerating real-time scientific edge machine learning*, 2022. arXiv: 2207.07958 [cs.LG]. [Online]. Available: <https://arxiv.org/abs/2207.07958>.
- [32] D. Kafkes and J. S. John, *Boostr: A dataset for accelerator control systems*, 2021. arXiv: 2101.08359 [physics.acc-ph]. [Online]. Available: <https://arxiv.org/abs/2101.08359>.
- [33] P. Odagiu, Z. Que, J. Duarte, *et al.*, *Ultrafast jet classification on fpgas for the hl-lhc*, 2024. DOI: <https://doi.org/10.1088/2632-2153/ad5f10>. arXiv: 2402.01876 [hep-ex]. [Online]. Available: <https://arxiv.org/abs/2402.01876>.

- [34] M. Khan, S. Krave, V. Marinozzi, J. Ngadiuba, S. Stoynev, and N. Tran, “Benchmarking and interpreting real time quench detection algorithms,” in *Fast Machine Learning for Science Conference 2024*, Purdue University, IN: indico.cern.ch, Oct. 2024. [Online]. Available: https://indico.cern.ch/event/1387540/contributions/6153618/attachments/2948441/5182077/fast_ml_magnets_2024_final.pdf.
- [35] A. A. Abud, B. Abi, R. Acciarri, *et al.*, *Deep underground neutrino experiment (dune) near detector conceptual design report*, 2021. arXiv: 2103.13910 [physics.ins-det]. [Online]. Available: <https://arxiv.org/abs/2103.13910>.
- [36] J. Kvapil, G. Borca-Tasciuc, H. Bossi, *et al.*, *Intelligent experiments through real-time ai: Fast data processing and autonomous detector control for sphenix and future eic detectors*, 2025. arXiv: 2501.04845 [physics.ins-det]. [Online]. Available: <https://arxiv.org/abs/2501.04845>.
- [37] J. Weitz, D. Demler, L. McDermott, N. Tran, and J. Duarte, *Neural architecture codesign for fast physics applications*, 2025. arXiv: 2501.05515 [cs.LG]. [Online]. Available: <https://arxiv.org/abs/2501.05515>.
- [38] B. Parpillon, C. Syal, J. Yoo, *et al.*, *Smart pixels: In-pixel ai for on-sensor data filtering*, 2024. arXiv: 2406.14860 [physics.ins-det]. [Online]. Available: <https://arxiv.org/abs/2406.14860>.
- [39] Z. Liu, H. Sharma, J.-S. Park, *et al.*, *Braggmn: Fast x-ray bragg peak analysis using deep learning*, 2021. arXiv: 2008.08198 [eess.IV]. [Online]. Available: <https://arxiv.org/abs/2008.08198>.
- [40] S. Qin, J. Agar, and N. Tran, “Extremely noisy 4d-tem strain mapping using cycle consistent spatial transforming autoencoders,” in *AI for Accelerated Materials Design - NeurIPS 2023 Workshop*, 2023. [Online]. Available: <https://openreview.net/forum?id=7yt3N0o0W9>.
- [41] Y. Wei, R. F. Forelli, C. Hansen, *et al.*, *Low latency optical-based mode tracking with machine learning deployed on fpgas on a tokamak*, 2024. DOI: <https://doi.org/10.1063/5.0190354>. arXiv: 2312.00128 [physics.plasm-ph]. [Online]. Available: <https://arxiv.org/abs/2312.00128>.
- [42] W. Gao, F. Tang, L. Wang, *et al.*, *Aibench: An industry standard internet service ai benchmark suite*, 2019. arXiv: 1908.08998 [cs.CV]. [Online]. Available: <https://arxiv.org/abs/1908.08998>.
- [43] W. Gao, J. Zhan, L. Wang, *et al.*, *Bigdatabench: A scalable and unified big data and ai benchmark suite*, 2018. arXiv: 1802.08254 [cs.DC]. [Online]. Available: <https://arxiv.org/abs/1802.08254>.
- [44] S. Farrell, M. Emani, J. Balma, *et al.*, *Mlperf hpc: A holistic benchmark suite for scientific machine learning on hpc systems*, 2021. arXiv: 2110.11466 [cs.LG]. [Online]. Available: <https://arxiv.org/abs/2110.11466>.
- [45] J. Thiyagalingam, G. von Laszewski, J. Yin, *et al.*, “Ai benchmarking for science: Efforts from the mlcommons science working group,” in *High Performance Computing. ISC High Performance 2022 International Workshops*, H. Anzt, A. Bienz, P. Luszczek, and M. Baboulin, Eds., Cham: Springer International Publishing, 2022, pp. 47–64, ISBN: 978-3-031-23220-6.
- [46] T. Aarrestad, E. Govorkova, J. Ngadiuba, E. Puljak, M. Pierini, and K. A. Wozniak, *Unsupervised new physics detection at 40 mhz: Training dataset*, 2021. DOI: 10.5281/ZENODO.5046389. [Online]. Available: <https://zenodo.org/record/5046389>.
- [47] A. Karargyris, R. Umeton, M. J. Sheller, *et al.*, “Federated benchmarking of medical artificial intelligence with medperf,” *Nature Machine Intelligence*, vol. 5, no. 7, pp. 799–810, Jul. 2023. DOI: 10.1038/s42256-023-00652-2. [Online]. Available: <https://doi.org/10.1038/s42256-023-00652-2>.
- [48] C. Krause, M. F. Giannelli, G. Kasieczka, *et al.*, *Calochallenge 2022: A community challenge for fast calorimeter simulation*, 2024. arXiv: 2410.21611 [physics.ins-det]. [Online]. Available: <https://arxiv.org/abs/2410.21611>.

- [49] A. Blum and M. Hardt, “The ladder: A reliable leaderboard for machine learning competitions,” in *Proceedings of the 32nd International Conference on Machine Learning*, F. Bach and D. Blei, Eds., ser. Proceedings of Machine Learning Research, vol. 37, Lille, France: PMLR, Jul. 2015, pp. 1006–1014. [Online]. Available: <https://proceedings.mlr.press/v37/blum15.html>.
- [50] Z. Xu, S. Escalera, A. Pavão, *et al.*, “Codabench: Flexible, easy-to-use, and reproducible meta-benchmark platform,” *Patterns*, vol. 3, no. 7, p. 100 543, Jul. 2022, issn: 2666-3899. DOI: 10.1016/j.patter.2022.100543. [Online]. Available: <http://dx.doi.org/10.1016/j.patter.2022.100543>.
- [51] P. Luszczek, “Sabath: Fair metadata technology for surrogate benchmarks,” University of Tennessee, Tech. Rep., 2021. [Online]. Available: <https://github.com/icl-utk-edu/slip/tree/sabath>.
- [52] M. Takamoto, T. Praditia, R. Leiteritz, *et al.*, *Pdebench: An extensive benchmark for scientific machine learning*, 2024. arXiv: 2210.07182 [cs.LG]. [Online]. Available: <https://arxiv.org/abs/2210.07182>.
- [53] R. Ohana, M. McCabe, L. Meyer, *et al.*, “The well: A large-scale collection of diverse physics simulations for machine learning,” in *Advances in Neural Information Processing Systems*, A. Globerson, L. Mackey, D. Belgrave, *et al.*, Eds., vol. 37, Curran Associates, Inc., 2024, pp. 44 989–45 037. [Online]. Available: https://proceedings.neurips.cc/paper_files/paper/2024/file/4f9a5acd91ac76569f2fe291b1f4772b-Paper-Datasets_and_Benchmarks_Track.pdf.
- [54] K. T. Chitty-Venkata, S. Raskar, B. Kale, *et al.*, “Llm-inference-bench: Inference benchmarking of large language models on ai accelerators,” in *SC24-W: Workshops of the International Conference for High Performance Computing, Networking, Storage and Analysis*, 2024, pp. 1362–1379. DOI: 10.1109/SCW63240.2024.00178.
- [55] L. Zheng, L. Yin, Z. Xie, *et al.*, *Sglang: Efficient execution of structured language model programs*, 2024. arXiv: 2312.07104 [cs.AI]. [Online]. Available: <https://arxiv.org/abs/2312.07104>.
- [56] W. Kwon, Z. Li, S. Zhuang, *et al.*, “Efficient memory management for large language model serving with pagedattention,” in *Proceedings of the 29th Symposium on Operating Systems Principles*, ser. SOSP ’23, Koblenz, Germany: Association for Computing Machinery, 2023, pp. 611–626. DOI: 10.1145/3600006.3613165. [Online]. Available: <https://doi.org/10.1145/3600006.3613165>.
- [57] S. Mo, *Vllm performance dashboard*, 2024. [Online]. Available: <https://simon-mo-workspace.observablehq.cloud/vllm-dashboard-v0/>.
- [58] K. G. Olivares, C. Challú, F. Garza, M. M. Canseco, and A. Dubrawski, *Neuralforecast: User friendly state-of-the-art neural forecasting models*. PyCon Salt Lake City, Utah, US 2022, 2022. [Online]. Available: <https://github.com/Nixtla/neuralforecast>.
- [59] C. Challu, K. G. Olivares, B. N. Oreshkin, F. G. Ramirez, M. M. Canseco, and A. Dubrawski, “Nhits: Neural hierarchical interpolation for time series forecasting,” in *Proceedings of the AAAI conference on artificial intelligence*, vol. 37, 2023, pp. 6989–6997.
- [60] M. Jin, S. Wang, L. Ma, *et al.*, *Time-llm: Time series forecasting by reprogramming large language models*, 2024. arXiv: 2310.01728 [cs.LG]. [Online]. Available: <https://arxiv.org/abs/2310.01728>.
- [61] A. Garza, C. Challu, and M. Mergenthaler-Canseco, *Timegpt-1*, 2024. arXiv: 2310.03589 [cs.LG]. [Online]. Available: <https://arxiv.org/abs/2310.03589>.
- [62] E. G. Campolongo, Y.-T. Chou, E. Govorkova, *et al.*, *Building machine learning challenges for anomaly detection in science*, 2025. arXiv: 2503.02112 [cs.LG]. [Online]. Available: <https://arxiv.org/abs/2503.02112>.
- [63] E. G. Campolongo, Y.-T. Chou, E. Govorkova, *et al.*, *Building machine learning challenges for anomaly detection in science*, 2025. arXiv: 2503.02112 [cs.LG]. [Online]. Available: <https://arxiv.org/abs/2503.02112>.
- [64] E. G. Campolongo, Y.-T. Chou, E. Govorkova, *et al.*, *Building machine learning challenges for anomaly detection in science*, 2025. arXiv: 2503.02112 [cs.LG]. [Online]. Available: <https://arxiv.org/abs/2503.02112>.

- [65] G. D. Guglielmo, B. Du, J. Campos, *et al.*, *End-to-end workflow for machine learning-based qubit readout with qick and hls4ml*, 2025. arXiv: 2501.14663 [quant-ph]. [Online]. Available: <https://arxiv.org/abs/2501.14663>.
- [66] D. Rein, B. L. Hou, A. C. Stickland, *et al.*, *Gpqa: A graduate-level google-proof q and a benchmark*, 2023. arXiv: 2311.12022 [cs.AI]. [Online]. Available: <https://arxiv.org/abs/2311.12022>.
- [67] K. X. Nguyen, F. Qiao, A. Trembanis, and X. Peng, *Seafloorai: A large-scale vision-language dataset for seafloor geological survey*, 2024. arXiv: 2411.00172 [cs.CV]. [Online]. Available: <https://arxiv.org/abs/2411.00172>.
- [68] P. Chen, L. Peng, R. Jiao, *et al.*, “Learning superconductivity from ordered and disordered material structures,” in *Advances in Neural Information Processing Systems*, A. Globerson, L. Mackey, D. Belgrave, *et al.*, Eds., vol. 37, Curran Associates, Inc., 2024, pp. 108 902–108 928. [Online]. Available: https://proceedings.neurips.cc/paper_files/paper/2024/file/c4e3b55ed4ac9ba52d7df11f8bddbbf4-Paper-Datasets_and_Benchmarks_Track.pdf.
- [69] D. Zou, S. Liu, S. Miao, V. Fung, S. Chang, and P. Li, “Gess: Benchmarking geometric deep learning under scientific applications with distribution shifts,” in *Advances in Neural Information Processing Systems*, A. Globerson, L. Mackey, D. Belgrave, *et al.*, Eds., vol. 37, Curran Associates, Inc., 2024, pp. 92 499–92 528. [Online]. Available: https://proceedings.neurips.cc/paper_files/paper/2024/file/a8063075b00168dc39bc81683619f1a8-Paper-Datasets_and_Benchmarks_Track.pdf.
- [70] R. E. Peterson, A. Tanelus, C. Ick, *et al.*, “Vocal call locator benchmark (vcl) for localizing rodent vocalizations from multi-channel audio,” in *Advances in Neural Information Processing Systems*, A. Globerson, L. Mackey, D. Belgrave, *et al.*, Eds., vol. 37, Curran Associates, Inc., 2024, pp. 106 370–106 382. [Online]. Available: https://proceedings.neurips.cc/paper_files/paper/2024/file/c00d37d6b04d73b870b963a4d70051c1-Paper-Datasets_and_Benchmarks_Track.pdf.
- [71] R. Bushuiev, A. Bushuiev, N. F. de Jonge, *et al.*, “Massspecgym: A benchmark for the discovery and identification of molecules,” in *Advances in Neural Information Processing Systems*, A. Globerson, L. Mackey, D. Belgrave, *et al.*, Eds., vol. 37, Curran Associates, Inc., 2024, pp. 110 010–110 027. [Online]. Available: https://proceedings.neurips.cc/paper_files/paper/2024/file/c6c31413d5c53b7d1c343c1498734b0f-Paper-Datasets_and_Benchmarks_Track.pdf.
- [72] Y. Wang, T. Wang, Y. Zhang, *et al.*, “Urbandatalayer: A unified data pipeline for urban science,” in *Advances in Neural Information Processing Systems*, A. Globerson, L. Mackey, D. Belgrave, *et al.*, Eds., vol. 37, Curran Associates, Inc., 2024, pp. 7296–7310. [Online]. Available: https://proceedings.neurips.cc/paper_files/paper/2024/file/0db7f135f6991e8cec5e516ecc66bfba-Paper-Datasets_and_Benchmarks_Track.pdf.
- [73] K. Khrabrov, A. Ber, A. Tsypin, *et al.*, *Delta-squared dft: A universal quantum chemistry dataset of drug-like molecules and a benchmark for neural network potentials*, 2024. arXiv: 2406.14347 [physics.chem-ph]. [Online]. Available: <https://arxiv.org/abs/2406.14347>.
- [74] T. Shen, H. Wang, J. Zhang, *et al.*, *Exploring user retrieval integration towards large language models for cross-domain sequential recommendation*, 2024. arXiv: 2406.03085 [cs.LG]. [Online]. Available: <https://arxiv.org/abs/2406.03085>.
- [75] S. Pramanick, R. Chellappa, and S. Venugopalan, *Spiga: A dataset for multimodal question answering on scientific papers*, 2025. arXiv: 2407.09413 [cs.CL]. [Online]. Available: <https://arxiv.org/abs/2407.09413>.