

Hetnet connectivity search provides rapid insights into how two biomedical entities are related

This manuscript ([permalink](#)) was automatically generated from [greenelab/connectivity-search-manuscript@ec2d568](#) on May 26, 2020.

Authors

Manuscript in preparation

The authorship information below is incomplete and preliminary. This notice will be updated once all contributors meeting [authorship criteria](#) have added themselves to [metadata.yaml](#).

- **Daniel S. Himmelstein**

 [0000-0002-3012-7446](#) ·  [dhimmel](#) ·  [dhimmel](#)

Department of Systems Pharmacology and Translational Therapeutics, University of Pennsylvania, Philadelphia, Pennsylvania, United States of America · Funded by GBMF4552

Abstract

Hetnets, short for “heterogeneous networks”, contain multiple node and relationship types and offer a way to encode biomedical knowledge. For example, Hetionet connects 11 types of nodes — including genes, diseases, drugs, pathways, and anatomical structures — with over 2 million edges of 24 types. Previously, we trained a classifier to repurpose drugs using features extracted from Hetionet. The model identified types of paths between a drug and disease that occurred more frequently between known treatments.

For many applications however, a training set of known relationships does not exist; Yet researchers would still like to know how two nodes are meaningfully connected. For example, users may want to know not only how metformin is related to breast cancer, but also how the GJA1 gene might be involved in insomnia. Therefore, we developed hetnet connectivity search to propose the most important paths between any two nodes.

The algorithm behind connectivity search identifies types of paths that occur more frequently than would be expected by chance (based on node degree alone). We implemented the method on Hetionet and provide an online interface at <https://het.io/search>. Several optimizations were required to precompute significant instances of node connectivity at scale. We provide an open source implementation of these methods in our new Python package named [hetmatpy](#).

To validate the method, we show that it identifies much of the same evidence for specific instances of drug repurposing as the previous supervised approach, but without requiring a training set.

Introduction

Hetionet

Rephetio

Unsupervised connectivity search

Results

Hetmatpy Package

DWPC null distribution

Enriched metapaths

Enriched paths

Comparison to Rephetio

Detecting Mechanisms of Action for Indications

Assess ability to predict paths in <https://github.com/SuLab/DrugMechDB>

Connectivity Search Webapp

Use cases

Discussion

Methods

Computing DWPCs with matrix multiplication

Permuted hetnets

Degree-grouping of node pairs

Gamma-hurdle distribution

Prioritizing metapaths for database storage

Rest API & backend

Webapp & Frontend

Realtime open science

Software & data availability

References
