

# (12) United States Patent

Calderon Oliveras et al.

### (54) DRUG DELIVERY DEVICE WITH **ELECTRONICS**

(71) Applicant: Norton (Waterford) Limited, Waterford (IE)

(72) Inventors: Enrique Calderon Oliveras, Waterford (IE); Carl L. Lewis, Cambridgeshire (GB); Symon D'Oyly Cotton, Cambridge (GB); Steven D. Gardner, Peterborough (GB); Robert O. Kivlin,

Cambridge (GB)

Assignee: Norton (Waterford) Limited,

Waterford (IE)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 919 days.

Appl. No.: 16/240,983

Jan. 7, 2019 (22)Filed:

(65)**Prior Publication Data** 

> US 2019/0134321 A1 May 9, 2019

### Related U.S. Application Data

(63) Continuation of application No. 16/148,046, filed on Oct. 1, 2018, which is a continuation of application No. 15/815,758, filed on Nov. 17, 2017.

(Continued)

(51) Int. Cl.

A61M 15/00 (2006.01)G16H 20/13 (2018.01)

(Continued)

(52) U.S. Cl.

CPC ..... A61M 15/008 (2014.02); A61M 15/0001 (2014.02); A61M 15/009 (2013.01);

(Continued)

### (10) Patent No.: US 11,439,777 B2

Sep. 13, 2022 (45) **Date of Patent:** 

### (58) Field of Classification Search

CPC ...... A61M 15/008; A61M 15/0065; A61M 15/0091; A61M 15/0026; A61M 15/0071; (Continued)

#### (56)References Cited

## U.S. PATENT DOCUMENTS

4,495,944 A 1/1985 Brisson et al. 4,984,158 A 1/1991 Hillsman (Continued)

### FOREIGN PATENT DOCUMENTS

EP 667168 A1 8/1995 EP 0933092 A1 8/1999 (Continued)

Primary Examiner — Tu A Vo

(74) Attorney, Agent, or Firm — Flaster Greenberg, P.C.

#### **ABSTRACT** (57)

A device for delivering medication to a user may include a main body, an electronics module, and a slider. The main body may include a mouthpiece, a medication reservoir, and a mouthpiece cover, where the mouthpiece cover may be hinged to the main body. The electronics module may include a communication circuit, a pressure sensor, and a switch. The slider may be configured to engage the switch when the mouthpiece cover moves from a closed position to an open position. The switch may be configured to switch the electronics module from an off state or a sleep state to an active state. The electronics module may be configured to never return to the off state after the mouthpiece cover is moved to expose the mouthpiece for the first time by the user.

### 20 Claims, 12 Drawing Sheets

