LQ05041QCS6

5 V, 4 A, Ultra Low Consumption Load Switch With Slew Rate Control

Description

The LQ05041QCS6 is an ultimated efficient, 4 A rated integrated load switch with slew rate control. This remarkable device incorporates cutting-edge technology that achieves industry-leading performance in terms of the lowest R_{ON}, quiescent current (I_Q), and shutdown current (I_{SD}). A reduced R_{ON} minimizes conduction losses, and the low I_Q and I_{SD} solutions empower designers to curtail parasitic leakage current, enhance system efficiency, and extend battery lifespan.

The integration of slew rate control within the LQ05041QCS6 serves as a critical enhancement to system reliability, effectively mitigating voltage swings on the bus during switching events. In situations where uncontrolled switches might otherwise generate substantial inrush currents, leading to voltage droop and potential bus reset events, the slew rate control functions to confine inrush current during activation, thereby minimizing the voltage droop.

The LQ05041QCS6 load switch device is designed in a chip scale package of 0.97 mm x 1.47 mm x 0.55 mm with 6 bumps and 0.5 mm pitch and support an extensive input voltage range, enhancing both the operational lifespan and the resilience of the system. Additionally, this single device can serve in various voltage rail applications, streamlining inventory management and lowering operational expenses.

Pinout Designation



0.97 mm x 1.47 mm x 0.55 mm WLCSP

Pin Description

Pin #	Pin Name	Description
A1,B1	V_{OUT}	Switch output
A2,B2	V_{IN}	Switch Input. Supply voltage for IC
C1	GND	Ground
C2	EN	Enable to control the switch

Features and Benefits

- Low R_{ON}: 15 mΩ Typ @ 5.5 V_{IN}
- Ultra-low I_Q: 3 nA Typ @ 5.5 V_{IN}
- Ultra-low I_{SD}: 50 nA Typ @ 5.5 V_{IN}
- I_{OUT} max: 4 A
- Wide input range: 1.1 V to 5.5 V, 6 Vabs max
- Controlled rise time: 400 µs at 3.3 V_{IN}
- Internal EN pull-down resistor
- Integrated output discharge switch
- Wide operating temperature range: -40 °C ~ 85 °C
- HBM: 6 kV, CDM: 2 kV
- Ultra-small: 6 bumps in a 0.97 mm x 1.47 mm x 0.55 mm WLCSP

Applications

- Mobile devices
- Data storage, SSD
- IoT devices
- Wearables
- Low power subsystems

Revised: FW.10/12/23

LQ05041QCS6

5 V, 4 A, Ultra Low Consumption Load Switch With Slew Rate Control

Functional Block Diagram



Typical Applications



Absolute Maximum Rating

Symbol	Parameter		Min	Max	Unit
V_{IN}, V_{OUT}, V_{EN}	Each Pin Voltage Range to GND		-0.3	6	V
I_{OUT}	Maximum Continuous Switch Current			4	A
P_D	Power Dissipation at T_A = 25 °C			1.2	W
T_{STG}	Storage Junction Temperature		-65	150	°C
T_J	Maximum Junction Temperature			150	°C
θ_{JA}	Thermal Resistance, Junction to Ambient (Measured using 2S2P JEDEC std. PCB.)			85	°C/W
ESD	Electrostatic Discharge Capability	Human Body Model, JESD22-A114	6		kV
		Charged Device Model, JESD22-C101	2		kV

Note: Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions; extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Recommend Operating Conditions

Symbol	Parameter	Min	Max	Unit
V_{IN}	Supply Voltage	1.5	5.5	V
T_A	Ambient Operating Temperature	-40	85	°C

Note: The device is not guaranteed to function outside of the recommended operating conditions.

Revised: FW.10/12/23

LQ05041QCS6

5 V, 4 A, Ultra Low Consumption Load Switch With Slew Rate Control

Electrical Characteristics (V_{IN} = 1.1 V to 5.5 V, typical values are at V_{IN} = 3.3 V and T_A = 25 °C. Unless otherwise noted)

Symbol	Parameter	Test Conditions		Min	Typ	Max	Unit
Basic Operation							
V_{IN}	Supply Voltage			1.1		5.5	V
I_Q	Quiescent Current	EN = Enable, I_{OUT} = 0 mA, V_{IN} = V_{EN} = 5.5 V			540		nA
		EN = Enable, I_{OUT} = 0 mA, V_{IN} = V_{EN} = 5.5 V[1]			3		nA
		EN = Enable, I_{OUT} = 0 mA, V_{IN} = VEN = 5.5 V, T_A = 85 °C[1,5]			10		nA
I_{SD}	Shutdown Current	EN = Disable, I_{OUT} = 0 mA, V_{IN} = 1.1 V			9		nA
		EN = Disable, I_{OUT} = 0 mA, V_{IN} = 1.8 V			11		nA
		EN = Disable, I_{OUT} = 0 mA, V_{IN} = 3.3 V			16		nA
		EN = Disable, I_{OUT} = 0 mA, V_{IN} = 4.5 V			20		nA
		EN = Disable, I_{OUT} = 0 mA, V_{IN} = 5.5 V			50	100	nA
		EN = Disable, I_{OUT} = 0 mA, V_{IN} = 5.5 V, T_A = 55 °C[5]			250		nA
		EN = Disable, I_{OUT} = 0 mA, V_{IN} = 5.5 V, T_A = 85 °C[5]			1.7		µA
R_{ON}	On-Resistance	V_{IN} = 5.5 V, I_{OUT} = 500 mA	T_A = 25 °C		15	17	mΩ
			T_A = 85 °C[5]		17		mΩ
		VI_{IN} = 3.3 V, I_{OUT} = 500 mA	T_A = 25 °C		18	21	mΩ
			T_A = 85 °C[5]		21		mΩ
		V_{IN} = 1.8 V, I_{OUT} = 300 mA	T_A = 25 °C		28		mΩ
		V_{IN} = 1.1 V, I_{OUT} = 100 mA	T_A = 25 °C		55		mΩ
R_{DSC}	Output Discharge Resistance	E_N=Low , I_{FORCE} = 10 mA			80	100	Ω
V_{IH}	EN Input Logic High Voltage	V_{IN} = 1.1 - 1.8 V		0.9			V
		V_{IN} = 1.8 - 5.5 V		1.2			V
V_{IL}	EN Input Logic Low Voltage	V_{IN} = 1.1 - 1.8 V				0.3	V
		V_{IN} = 1.8 - 5.5 V				0.4	V
R_{EN}	EN pull down resistance	E_N = 5.5 V		7	10.1	13	MΩ
I_{EN}	EN Current	E_N = 5.5 V				0.8	µA
Switching Characteristics							
t_{dON}	Turn-On Delay[2]	R_{OUT} = 150 Ω, C_{OUT} = 0.1 µF			250		µs
t_R	V_{OUT} Rise Time[2]				400		µs
t_{dON}	Turn-On Delay[2,5]	R_{OUT} = 500 Ω, C_{OUT} = 0.1 µF			240		µs
t_R	V_{OUT} Rise Time[3,4,5]				390		µs
t_{dOFF}	Turn-Off Delay[3,4,5]	R_{OUT} = 10 Ω, C_{OUT} = 0.1 µF			0.4		µs
t_F	V_{OUT} Fall Time[3,4,5]				1.5		µs
t_{dOFF}	Turn-Off Delay[3,4,5]	R_{OUT} = 500 Ω, C_{OUT} = 0.1 µF			1.3		µs
t_F	V_{OUT} Fall Time[3,4,5]				16		µs

Notes:

1. I_Q does not include enable pull down current through the pull-down resistor RPD.
2. t_{ON} = td_{ON} + t_R
3. t_{OFF} = td_{OFF} + t_F
4. Output discharge path is enabled during off.
5. By design; characterized, not production tested.

Revised: FW.10/12/23

LQ05041QCS6

5 V, 4 A, Ultra Low Consumption Load Switch With Slew Rate Control

Timing Waveforms



Typical Performance Characteristics

Figure 1 - On-Resistance vs. Supply Voltage



Figure 2 - On-Resistance vs. Temperature



Figure 3 - Quiescent Current vs. Supply Voltage



Figure 4 - Quiescent Current vs. Temperature



Figure 5 - Shutdown Current vs. Supply Voltage



Figure 6 - Shutdown Current vs. Temperature



Figure 7 - EN Input Logic High Threshold



Figure 8 - EN Input Logic High Threshold Vs. Temperature



Figure 9 - EN Input Logic Low Threshold



Figure 10 - EN Input Logic Low Threshold Vs. Temperature



Revised: FW.10/12/23

Figure 11 - V_{OUT} Rise Time vs. Temperature



Figure 12 - Turn-On Delay Time vs. Temperature



Figure 13 - V_{OUT} Discharge Resistance vs. Temperature



Figure 14 - Enable Pulldown Current vs. Temperature



Figure 15 - Turn-On Response
V_{IN} = 3.3 V, C_{IN} = 1.0 µF, C_{OUT} = 0.1 µF, R_L = 10 Ω



Figure 16 - Turn-On Response
V_{IN}=3.3 V, C_{IN}=1.0 µF, C_{OUT} = 0.1 µF, R_L = 500 Ω



LQ05041QCS6

5 V, 4 A, Ultra Low Consumption Load Switch With Slew Rate Control

Application Information

The LQ05041QCS6 is a highly efficient integrated load switch with a 4 A capacity. It allows a fixed slew rate control to limit inrush current when activated. This device works with a wide input voltage range, from 1.1 V to 5.5 V, and has minimal on-resistance to reduce power loss. When it is off, it has very low leakage current, saving power resources. It is in a chip scale size package at 0.97 mm x 1.47 mm x 0.55 mm with 6 bumps at a 0.5 mm pitch make it ideal for efficient manufacturing in the space-saving required applications.

Input Capacitor

Although this is not required to have an input capacitor. Suggest to use a 0.1 µF capacitor positioned near the VIN pin to address voltage fluctuations on the input power rail that may occur as a result of transient inrush current during startup. To reduce the extent of the input voltage drop, suggest to use a higher input capacitor value.

Output Capacitor

An output capacitor is not mandatory for the LQ05041QCS6. Nevertheless, it is advisable to employ an output capacitor to minimize voltage undershoot on the output pin during switch-off.

Voltage undershoot may arise due to parasitic inductance from board traces or deliberate load inductances. In the presence of load inductances, utilizing an output capacitor can enhance output voltage stability and overall system reliability. Position the C_{OUT} capacitor in close proximity to the V_{OUT} and GND pins.

EN pin

The LQ05041QCS6 can be turned on by setting the EN pin to a high level. Be aware that there is an internal pull-down resistor in EN pin which can pull the primary switch to “off state” as long as no EN signal from an external controller is applied.

Output Discharge Function

The device incorporates an internal discharge N-channel FET switch located at the VOUT pin. When the EN signal switches the primary power FET to an off state, the N-channel switch activates to rapidly discharge the output capacitor.

Board Layout

To minimize the impact of parasitic inductance, it is advisable to keep all traces as short as possible. Using wider traces for V_{IN}, V_{OUT}, and GND is recommended to mitigate parasitic effects during dynamic operations and enhance thermal efficiency under high load currents.

Dimensions



Dimension	Millimeters		
	Min	Nom	Max
A	0.500	0.550	0.600
A1	0.225	0.250	0.275
A2	0.250	0.275	0.300
A3	0.020	0.025	0.030
D	1.460	1.470	1.485
E	0.960	0.970	0.985
D1	0.950	1.000	1.050
E1	0.450	0.500	0.550
b	0.260	0.310	0.360
e	0.500 BSC		
SD	0.000 BSC		
SE	0.250 BSC		
Tol. of Form & Position			
aaa	0.100		
bbb	0.100		
ccc	0.050		
ddd	0.050		

Revised: FW.10/12/23

LQ05041QCS6

5 V, 4 A, Ultra Low Consumption Load Switch With Slew Rate Control

Part Numbering



Part Marking

BB = Device Code
XX = Wafer Lot Run Code
xx = Assembly Lot Run Code
C = Assembly Code

Carrier Tape & Reel Specification







Quandrant assignments pin 1 orientation
Dimensions are in millimeters

Device	Package	Pins	SPQ	Reel Diameter	Reel Width W1	A0	B0	K0	P	W	Pin1
LQ05041QCS6	6 Bumps WLCSP	6	3000	180	9	1.18	1.68	0.83	4	8	Q1