



AERO4600 Automatic Flight Control Systems

Assignment 3 — 2024

Ben Miller^c Jabez Mehanathan^c Kaitlyn Ashcroft^c

^a *Student of Aerospace Systems Engineering,
The University of Newcastle, Callaghan, NSW 2308, AUSTRALIA
Student Number: c3328484
E-mail: c3328484@uon.edu.au*

^b *Student of Aerospace Systems Engineering,
The University of Newcastle, Callaghan, NSW 2308, AUSTRALIA
Student Number: c3355997
E-mail: c3355997@uon.edu.au*

^c *Student of Aerospace Systems Engineering,
The University of Newcastle, Callaghan, NSW 2308, AUSTRALIA
Student Number: c3350754
E-mail: c3350754@uon.edu.au*

Abstract

This Report examines the lateral dynamics and gust response of an aircraft and builds on prior work ?, focusing on utilizing Matlab System Identification Toolbox as well as simulating aircraft response to gust inputs. The primary lateral modes analysed in this report are the side-slip (β) and bank angle (ϕ) of the aircraft, and are evaluated through the influence of aileron/rudder control inputs and gust disturbances. This report also evaluates the impact of sensor noise on the the system identification model and methods of improving the robustness of the system identification process. Additionally, the gust/turbulence was modelled using the Dryden Spectra method to aid in simulating the gust responses, in order to compute the maximum side-slip and bank angle perturbations. These finding contribute to modelling and understanding the aircraft's dynamics and control in the lateral motion.

Contents

1. Introduction	4
2. Q1 – Vertical Speed Transfer Function	4
3. Q2 – Pitch Rate Autopilot	4
4. Q3 – Vertical Speed Guidance Loop	5
4.1. Loop Topology	5
4.2. Aircraft Response to Vertical Speed Command	5
4.3. Pitch Rate Response	5
4.4. Elevator Activity	6
5. Q4 – Design Auto-Throttle Control System	7
5.1. MIMO Loop Topology	7
5.2. Guidance Loop Topology Specifications	7
5.3. Primary Control Effects	7
5.4. Cross-coupling Control Effects	7
5.5. Elevator and Throttle Response	7
5.6. Auto-Throttle Effectiveness	7
6. Final Design	7
6.1. Q5 – Implementation of the control and guidance laws	7
6.2. Q6 – Gust Effectiveness	7
6.3. Q7 – Commanded Large Vertical Speed	7
7. Conclusion	7
A. Example of a Table	8

1. Introduction

test here

2. Q1 – Vertical Speed Transfer Function

3. Q2 – Pitch Rate Autopilot

4. Q3 – Vertical Speed Guidance Loop

The vertical speed guidance loop is designed to control the aircraft's ascent and descent rates by incorporating a pitch rate controller as an inner loop. This loop includes a compensator in the forward leg, which processes the vertical speed error to generate a pitch rate command. The pitch rate command then feeds into the inner loop to modulate the elevator input, allowing the system to adjust vertical speed in response to deviations from the desired reference.

4.1. Loop Topology

The complete loop topology of the vertical speed guidance loop is shown in Figure 1. The compensator transforms the vertical speed error ($vs_{ref} - vs$) into a pitch rate command. This command is then processed within the inner loop section ($de2q$), where the transfer functions G_1 and G_2 are used in the pitch rate controller to compute the required elevator deflection (δ_e) to achieve the target pitch rate.




Figure 1: Vertical Speed Guidance Loop Topology

4.2. Aircraft Response to Vertical Speed Command

For a 500 ft/min vertical speed command step input, the vertical speed response is analyzed to verify that it meets the performance criteria.

4.3. Pitch Rate Response

The pitch rate response, following the vertical speed command, is evaluated to confirm that the inner pitch rate control loop accurately tracks the generated pitch rate command.




Figure 2: Vertical Speed Response




Figure 3: Pitch Rate Response

4.4. Elevator Activity

The elevator control activity is analyzed to ensure that control actions remain within acceptable operational limits.




Figure 4: Elevator Control Activity

5. Q4 – Design Auto-Throttle Control System

5.1. MIMO Loop Topology

5.2. Guidance Loop Topology Specifications

5.3. Primary Control Effects

5.4. Cross-coupling Control Effects

5.5. Elevator and Throttle Response

5.6. Auto-Throttle Effectiveness

6. Final Design

6.1. Q5 – Implementation of the control and guidance laws

6.2. Q6 – Gust Effectiveness

6.3. Q7 – Commanded Large Vertical Speed

7. Conclusion

References

A. Example of a Table