Step 1:

user.h | user.cpp

Users > benjaminding > Desktop > CSCI_62_HW > user.cpp > ...

```cpp
#include "user.h"

User :: User () {} // implement default constructor

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
Screenshot 2025-09-24 at 11.17.18 AM.png        Screenshot 2025-09-29 at 10.04.42 PM.png        Screenshot 2025-11-05 at 11.25.00 AM.png
benjaminding@NotAnotherMacbook Desktop % cd CSCI_62_HW
benjaminding@NotAnotherMacbook CSCI_62_HW % ls
benjaminding@NotAnotherMacbook CSCI_62_HW % pwd
/Users/benjaminding/Desktop/CSCI_62_HW
benjaminding@NotAnotherMacbook CSCI_62_HW % ls
user.cpp        user.h
benjaminding@NotAnotherMacbook CSCI_62_HW % s
zsh: command not found: s
benjaminding@NotAnotherMacbook CSCI_62_HW % g++ user.cpp
Undefined symbols for architecture arm64:
  "_main", referenced from:
      <initial-undefines>
ld: symbol(s) not found for architecture arm64
clang++: error: linker command failed with exit code 1 (use -v to see invocation)
benjaminding@NotAnotherMacbook CSCI_62_HW %
```

Ln 3, Col 52 Spaces: 4 UTF-8 LF {} C++

Step 2

user.h | user.cpp

Users > benjaminding > Desktop > CSCI_62_HW > user.cpp > ...

```cpp
#include "user.h"

User :: User () {} // implement default constructor

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
benjaminding@NotAnotherMacbook CSCI_62_HW % ls
benjaminding@NotAnotherMacbook CSCI_62_HW % pwd
/Users/benjaminding/Desktop/CSCI_62_HW
benjaminding@NotAnotherMacbook CSCI_62_HW % ls
user.cpp        user.h
benjaminding@NotAnotherMacbook CSCI_62_HW % s
zsh: command not found: s
benjaminding@NotAnotherMacbook CSCI_62_HW % g++ user.cpp
Undefined symbols for architecture arm64:
  "_main", referenced from:
      <initial-undefines>
ld: symbol(s) not found for architecture arm64
clang++: error: linker command failed with exit code 1 (use -v to see invocation)
benjaminding@NotAnotherMacbook CSCI_62_HW % g++ test_user_1.cpp user.cpp
benjaminding@NotAnotherMacbook CSCI_62_HW % ./a.out
benjaminding@NotAnotherMacbook CSCI_62_HW %
```

Visual Studio Code

Ln 3, Col 52 Spaces: 4 UTF-8 LF {} C++

Step 3:

user.h | user.cpp | test_user_header_guard.cpp

Users > benjaminding > Desktop > CSCI_62_HW > user.cpp > ...

```cpp
#include "user.h"

User :: User () {} // implement default constructor

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
    7 | #include "user.h" // check no compile error on double include
      |          ^
./user.h:1:7: note: unguarded header; consider using #ifdef guards or #pragma once
    1 | class User {
      |       ^
1 error generated.
benjaminding@NotAnotherMacbook CSCI_62_HW % g++ test_user_header_guard.cpp user.h
clang++: warning: treating 'c-header' input as 'c++-header' when in C++ mode, this behavior is deprecated [-Wdeprecated]
Undefined symbols for architecture arm64:
  "User::User()", referenced from:
      _main in test_user_header_guard-bb751c.o
ld: symbol(s) not found for architecture arm64
clang++: error: linker command failed with exit code 1 (use -v to see invocation)
benjaminding@NotAnotherMacbook CSCI_62_HW % g++ test_user_header_guard.cpp user.cpp
benjaminding@NotAnotherMacbook CSCI_62_HW % ./a.out
benjaminding@NotAnotherMacbook CSCI_62_HW %
```

Ln 4, Col 1 Spaces: 4 UTF-8 LF {} C++