

SECTION 1: IDENTIFICATION

Product name: Acme Solvent X

Product code: AC-4471

Recommended use: Industrial degreasing agent. Uses advised against: Not for consumer use.

Manufacturer: Acme Chemical Company, 123 Industrial Way, Springfield, IL 62701

Telephone: (217) 555-0100

Emergency telephone number: (800) 555-9111 (CHEMTREC, 24 hour)

SECTION 2: HAZARDS IDENTIFICATION

GHS Classification: Flammable liquid, Category 2; Skin irritation, Category 2; Eye irritation, Category 2A

Signal word: DANGER

Hazard statements: H225 Highly flammable liquid and vapor. H315 Causes skin irritation. H319 Causes serious eye irritation.

Precautionary statements: P210 Keep away from heat, sparks, open flames. P280 Wear protective gloves/eye protection.

Pictograms: Flame, Exclamation mark

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture. The following components are hazardous within the meaning of the applicable regulations:

Chemical Name	CAS No.	EC No.	Concentration (%)
Toluene	108-88-3	203-625-9	60-80
Xylene	1330-20-7	215-535-7	10-20
Ethylbenzene	100-41-4	202-849-4	1-5

SECTION 4: FIRST-AID MEASURES

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen.

Skin contact: Wash with soap and water. Remove contaminated clothing.

Eye contact: Rinse cautiously with water for several minutes. Remove contact lenses if present.

Ingestion: Rinse mouth. Do NOT induce vomiting. Call a physician.

Most important symptoms and effects: Irritation, dizziness, headache.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable extinguishing media: Dry chemical, CO2, foam, water spray.

Unsuitable extinguishing media: Do not use a direct water jet.

Specific hazards arising from the chemical: Vapors may form explosive mixtures with air.

Special protective equipment for fire-fighters: Wear self-contained breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions: Remove ignition sources. Ventilate area.

Environmental precautions: Prevent entry into waterways, drains and soil.

Methods for containment and cleaning up: Absorb with inert material and place in closed containers.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling: Use only in well-ventilated areas. Avoid contact with skin and eyes.

Conditions for safe storage: Store in a cool, dry, well-ventilated area away from ignition sources.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits:

Component	TWA	STEL	Source
Toluene	20 ppm	-	OSHA
Xylene	100 ppm	150 ppm	OSHA

Engineering controls: Use local exhaust ventilation.

Eye/face protection: Chemical splash goggles.

Hand protection: Wear chemical-resistant gloves (nitrile).

Skin protection: Wear protective clothing (lab coat or coveralls) to prevent skin contact.

Respiratory protection: Use NIOSH-approved organic vapor respirator if ventilation inadequate.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, colorless liquid

Odor: Aromatic, solvent-like

pH: Not applicable

Melting point: -95 C

Boiling point: 110-144 C

Flash point: 4 C (closed cup)

Vapor pressure: 29 mmHg at 20 C

Relative density: 0.87

Solubility: Insoluble in water; miscible with most organic solvents

Autoignition temperature: 480 C

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions of use.

Chemical stability: Stable under recommended storage conditions.

Possibility of hazardous reactions: Hazardous polymerization does not occur.

Conditions to avoid: Heat, sparks, open flame.

Hazardous decomposition products: Carbon monoxide, carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute toxicity: Oral LD50 (rat) 5580 mg/kg (toluene).

Skin corrosion/irritation: Causes skin irritation.

Eye damage/irritation: Causes serious eye irritation.

Carcinogenicity: Not classified as a carcinogen by IARC, OSHA, or NTP.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: Toxic to aquatic life.

Persistence and degradability: Expected to biodegrade.

Bioaccumulative potential: Low potential for bioaccumulation.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal methods: Dispose of in accordance with local, state, and federal regulations. Do not discharge to sewer.

SECTION 14: TRANSPORT INFORMATION

UN number: UN1993

UN proper shipping name: Flammable liquid, n.o.s. (Toluene, Xylene)

Transport hazard class: 3

Packing group: II

SECTION 15: REGULATORY INFORMATION

TSCA: All components listed on the TSCA inventory. SARA 313: Toluene and Xylene are subject to reporting requirements.

SECTION 16: OTHER INFORMATION

Revision date: 2026-03-15

Version number: 4.2

Disclaimer: This information is believed to be accurate but is not exhaustive and is provided without warranty.