

SECTION 1: IDENTIFICATION

Product name: DuraSeal Construction Adhesive

Manufacturer: BuildFast Materials Inc, Columbus, OH

Emergency telephone: (800) 555-7890

SECTION 2: HAZARDS IDENTIFICATION

Signal word: DANGER

Hazard statements: H225 Highly flammable liquid and vapor. H336 May cause drowsiness or dizziness.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Toluene, CAS 108-88-3, 10-20%. Heptane, CAS 142-82-5, 5-10%.

SECTION 4: FIRST-AID MEASURES

Inhalation: Remove to fresh air immediately.

Skin contact: Remove contaminated clothing and wash skin.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable extinguishing media: Foam, dry chemical, CO2.

SECTION 8: EXPOSURE

CONTROLS/PERSONAL PROTECTION

Respiratory protection: Use in well-ventilated area; NIOSH-approved respirator if needed.

Hand protection: Nitrile gloves recommended.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Amber paste Flash point: -4 C

SECTION 16: OTHER INFORMATION

Revision date: 2026-01-20