

SECTION 1: IDENTIFICATION

Substance name: Aluminium Powder

CAS No.: 7429-90-5

Manufacturer: Metal Powders Europe Ltd, Sheffield, UK

Emergency telephone number: +44 114 555 0123

SECTION 2: HAZARDS IDENTIFICATION

Hazard pictogram: GHS02

Signal word: Danger

Hazard statements: H228 Flammable solid.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Aluminium, CAS No. 7429-90-5, >96%.

SECTION 4: FIRST AID MEASURES

General information: No special measures required.

Inhalation: Fresh air.

Skin contact: Wash with soap and water.

Eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

Ingestion: Rinse the mouth. Call doctor.

Most important symptoms and effects, both acute and delayed: High amounts of aluminium dust can cause coughing and irritation.

Indication of any immediate medical attention and special treatment needed: No special measures required.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable extinguishing agents: Extinguish with dry sand and/or mineral wool, or special powder for metal fires.

Unsuitable extinguishing agents: Do NOT use water, foam or carbon dioxide.

Special hazards arising from the substance or mixture: Prevent formation of dust. Contact with water liberates extremely flammable gas (hydrogen).

Advice for firefighters: No special measures required.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Prevent formation of dust and keep away from ignition sources. Wear protective equipment.

Environmental precautions: Do not allow product to reach sewage system or water resources.

Methods and material for containment and cleaning up: Sweep up and put in a dry receptacle. Dispose of waste material in accordance with local, state or federal regulations. Do not use a vacuum cleaner. Do not flush with water or aqueous cleaning agents.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling: Prevent formation of dust. Dust in combination with air can form an explosive mixture. Any deposit of dust which cannot be avoided must be removed regularly. Prevent sparks arising from static electricity. No smoking, fire, sparks or welding. Use explosion proof electric equipment. Water for eye flushing to be available. Contact with water liberates extremely flammable gases. Wash hands during breaks and at the end of the work. Keep away from foodstuffs, beverages and feed. Do not eat, drink, smoke or sniff while working.

Conditions for safe storage, including any incompatibilities: Keep container tightly closed, cool and dry and protected from direct sunlight. Protect from humidity and keep away from water. Keep away from sources of ignition - No smoking. Do not store together with alkalis, oxidizing and acidic materials.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits: 4 mg/m³ (respirable aerosol), 10 mg/m³ (inhalable aerosol).

Respiratory protection: Use suitable breathing protection if workplace concentration requires, filter P1. The European standards EN 136, EN 140, EN 143, EN 149 and EN 405 (Respiratory protective devices) inform about requirements, testing, marking.

Hand protection: Use anti-static and fire resistant protective gloves.

Eye protection: Use protective goggles if necessary.

Skin protection: Use anti-static and fire resistant protective clothing, EN 531, EN 533, EN 1149-1. Use anti-static shoes.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Melting point: 660 C

Boiling point: 2467 C

Appearance: Grey powder

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Flammable solid.

Incompatible materials: Reacts with alkalis, acids, water and oxidizing agents. Contact with water may release flammable gases (hydrogen). Reacts with acids and alkalis releasing hydrogen.

SECTION 11: TOXICOLOGICAL INFORMATION

Carcinogenicity: Aluminum powder is not carcinogenic, mutagenic or toxic to reproduction.

Germ cell mutagenicity: Aluminum powder is not carcinogenic, mutagenic or toxic to reproduction.

Reproductive toxicity: Aluminum powder is not carcinogenic, mutagenic or toxic to reproduction.

Sensitization: Not stated in SDS.

Other information on hazards: Dust explosion risk. High amounts of aluminium dust can cause coughing and irritation. Prevent formation of dust. Dust in combination with air can form an explosive mixture. Any deposit of dust which cannot be avoided must be removed regularly. May form explosive dust/air mixtures. Avoid dust clouds, they may form explosible dust-air-mixture. Risk of dust explosion if enriched with fine dust in presence of air. Avoid inhalation of dust / fume / mist.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal methods: Dispose of in accordance with local regulations.

SECTION 14: TRANSPORT INFORMATION

UN number: UN1309

SECTION 15: REGULATORY INFORMATION

REACH: Registered.

SECTION 16: OTHER INFORMATION

Revision date: 03/06/2019

Version number: 12