

8. Intro. to Quantifier Logic

1. Intro. to Quantifier Logic

1.1 The goals of QL

1.2 Beginning symbolization in QL

1.3 The existential quantifier

1.4 The universal quantifier

1.5 'No', 'only', 'a', 'some', and 'any'

1.6 Mixed domains

1.7 Captain Morgan's (tele)scope!

8. Intro. to Quantifier Logic

a. The goals of QL

Limits of symbolization in SL

- ▶ Consider the argument:

Greta is a hero.

\therefore There is a hero.

- ▶ It's clearly valid: in any case in which Greta is a hero, someone (or something, at least) is a hero, so there must be a hero.
- ▶ But its symbolization in SL is invalid in SL:

G

$\therefore H$

The problem

- ▶ Symbolization in SL allows us to break down sentences containing “and,” “or,” “if-then” and determine validity in virtue of these **connectives**.
- ▶ Anything that can't be further broken down must be symbolized by sentence letters.
- ▶ That includes basic sentences like “Greta is a hero,” but also:
 - Everyone is a hero.
 - No one is a hero.
 - All heroes wear capes.

The goals of **Quantifier Logic** (QL)

- ▶ Finer-grained symbolization
- ▶ Augments SL (all of SL and *more!*)
- ▶ Allows for precise semantics (like truth tables for SL)
- ▶ Works with natural deduction (add new rules!)
- ▶ Be simple & expressive (only a few new symbols!)

The goals of QL

- ▶ Consider the valid argument:
Greta is a hero.
Greta does not wear a cape.
 \therefore Not all heroes wear capes.
- ▶ We'll need to connect the occurrences of the name "Greta" in the premises
- ▶ We'll need to connect "hero" in the premise and conclusion
- ▶ We want to retain using the symbol ' \sim ' for "not"
- ▶ Ultimately, we'll want our argument-symbolization to have a proof

8. Intro. to Quantifier Logic

b. Beginning symbolization in QL

First steps: names (a.k.a. ‘constants’)

- ▶ Purpose of a **proper name**: to pick out a single, specific thing.
- ▶ (Contrast with common nouns like “hero” or “rock” which pick out collections of things)
- ▶ For simplicity, we’ll only consider names that pick out a **specific object** (often within a hypothetical case we’re considering)
- ▶ Later on, we’ll be able to deal with other expressions that play a similar role to names, e.g., “the president of the USA”
- ▶ In QL, names are symbolized by lowercase letters $a-v$ (allowing natural number sub-scripts, e.g. m_1 , t_{2022})

First steps: predicates (including properties and relations)

- ▶ Remove a name from a sentence. What's left over is a **predicate**:
Greta is a hero
 \Rightarrow ______x is a hero. (i.e. property of being a hero)
Greta admires Autumn
 \Rightarrow ______x admires ______y. (i.e. relation of x admiring y)
- ▶ In QL, predicates are symbolized using uppercase letters A-Z plus a number of argument slots (marked with variables), e.g., *Hx* or *Axy*.
- ▶ Argument slots correspond to blanks.

Symbolization keys

- ▶ **Names/constants**: lowercase letters for proper names
- ▶ **Predicates**: uppercase letters with variables marking blanks
 - a : Autumn
 - g : Greta
 - Hx : _____ x is a hero
 - Vx : _____ x is a villain
 - Ix : _____ x inspires
 - Cx : _____ x wears a cape
 - Wxy : _____ x welcomed _____ y
 - Axy : _____ x admires _____ y
 - Yxy : _____ x is younger than _____ y
- ▶ **Domain**: the non-predicate objects we're talking about in a context—also called grandly the '**Universe of Discourse**' (UD)
e.g., people alive in 2022

Symbolization of Sentences without Quantifiers

- ▶ Basic sentences: predicates with names replacing variables.
 - Greta is a hero: Hg
 - Greta admires Autumn: Aga
- ▶ Combinations using connectives:
 - Greta and Autumn are heroes: $Hg \& Ha$
 - If Autumn admires Greta, then Autumn is a hero: $Aag \supset Ha$

Symbolization of Pronouns

► Replacing pronouns by antecedents:

- If Autumn is a hero, Greta admires **her**: $Ha \supset Aga$
- Greta doesn't admire **herself**: $\sim Agg$ (but she should!)
- Greta and Autumn welcomed **each other**: $Wga \& Wag$

► Modifiers:

- Autumn is an **inspiring hero**:
i.e. Autumn inspires, and she is a hero: $Ia \& Ha$
- Greta is a **hero who doesn't wear a cape**:
Greta is a hero, and it's not the case that Greta wears a cape:
 $Hg \& \sim Cg$

Mind the Modifiers!

- ▶ ‘Greta is an international hero’:
 - Can’t be paraphrased as
“Greta is international and a hero.”
 - So “_____ is an international hero” needs its own predicate
- ▶ ‘The **Piltdown Man** is a fake fossil’
 - Can’t be paraphrased as
“The Piltdown Man is fake and a fossil.”
 - Since “fake” and other privative adjectives (“pretend,” “fictitious”) deny the property that they modify! (‘fake news’ isn’t news!)

Examples

- ▶ Autumn and Greta are inspiring heroes.

$(Ia \ \& \ Ha) \ \& \ (Ig \ \& \ Hg)$

- ▶ Greta admires Autumn but not herself.

$Aga \ \& \ \sim Agg$

- ▶ Greta inspires only if Autumn does.

$Ig \supset Ia$

- ▶ Greta and Autumn welcomed each other.

$Wga \ \& \ Wag$

- ▶ Greta is older than Autumn.

Yag (i.e. Autumn is *younger than* Greta)

- ▶ One of Greta and Autumn welcomed the other.

At least one:

$Wga \ \vee \ Wag$

Exactly one:

$(Wga \ \vee \ Wag) \ \& \ \sim (Wga \ \& \ Wag)$

8. Intro. to Quantifier Logic

c. The existential quantifier

Existential quantifier (something or other)

- ▶ In English: “something,” “someone,” “there is ...”
- ▶ For instance:
 - **Someone** wears a cape.
 - **There is** a hero.
 - **Something** inspires.
- ▶ Note: often goes where names and pronouns are placed
- ▶ But works differently from names (“something” doesn’t pick out a unique, specific object).

How (not) to symbolize “something”

- ▶ Idea(?): introduce a special term ‘*sg*’ for ‘a something’?
- ▶ Problem: now we can’t distinguish between
 - Someone is a hero and wears a cape.
 - Someone is a hero and someone wears a cape.as both would be symbolized by ‘ $H(sg) \& C(sg)$ ’.
- ▶ Better idea: symbolize (complex) **properties** and introduce a notation for expressing that properties are **instantiated**

Expressing properties (and relations)

- ▶ One-place predicates **express** properties, e.g.,
 - Hx expresses property “being a hero”
 - Ix expresses “is inspiring” (‘x’ is a variable)
- ▶ Combinations of predicates (with connectives, names) can express **derived** properties, e.g.,
 - Axg expresses “admires Greta”
 - Wax expresses “is welcomed by Autumn”
 - $Hx \ \& \ Cx$ expresses “is a hero who wears a cape”
- ▶ Note: all contain a **single** variable x

The existential quantifier \exists

- ▶ Symbol for “there is”: \exists
- ▶ Combine ‘ \exists ’ with an expression for a property (e.g., $(Hx \ \& \ Cx)$) to say “something (or someone) has that property”
- ▶ Put the variable that serves as a marker for the gap after \exists . E.g.,

$$(\exists x) (Hx \ \& \ Cx)$$

says “Someone is a hero and wears a cape”

- ▶ **MUST** always wrap a quantifier and the variable it ‘binds’ within **parentheses**: $(\exists y)$; *Carnap* will require this!!!

Quantifiers and variables

Compare: $(\exists x) (Hx \& Cx)$ to
 $(\exists x) Hx \& (\exists x) Cx$

- ▶ In first case, *the same person* must be a hero and wear a cape.
- ▶ In second case, one person can be the hero and another (possibly different) person wears a cape.
- ▶ Instances of ' $(\exists x)$ ' separated by other connectives are independent, even if they bind the same variable x .
e.g. there's no difference in meaning between the following:

$(\exists x) Hx \& (\exists x) Cx$ **vs.**
 $(\exists x) Hx \& (\exists y) Cy$

- ▶ But we'll **never write** ' $(\exists x)(\exists x)(Hx \& Cx)$ '

The domain (UD) and quantifiers

- ▶ Symbolization key gives a domain of objects being talked about.
- ▶ Quantifier **ranges over** this ‘universe of discourse’ (UD).
- ▶ That means: $(\exists x) \dots x \dots$ is true iff some object **in the domain** has the property expressed by $\dots x \dots$.
- ▶ Domain makes a difference: Consider $(\exists x) Wxg$.
 - True if someone welcomed Greta (say, Autumn did).
 - Now take the domain to include only Greta.
 - Relative to that domain, $(\exists x) Wxg$ is true iff Greta welcomed herself (e.g. to the left-over chocolate fondue!)

Quantifier restriction in English

- ▶ “something” and “someone” work grammatically like singular terms (they can go where names can also go).
- ▶ “some” (on its own) does not: it is a **determiner** and needs a **complement**, e.g.,
 - a common noun (“some hero”), or
 - a noun phrase (“some admirer of Greta”).
- ▶ “some” + complement works grammatically like “someone”, e.g.,
“**Some hero** wears a cape”
- ▶ General form: “Some F is G .”

Quantifier restriction in QL

- ▶ “Some F is G ” **restricts** the “something” quantifier to F s.
- ▶ We could (and linguists often do) mark restrictions in the quantifier, e.g., $((\exists x): Fx)Gx$
- ▶ We won’t because we can do without this additional notation
- ▶ “Some F is G ” is true iff there is something which is both F and also G , so:
- ▶ “Some F is G ” can be symbolized as

$$(\exists x)(Fx \& Gx)$$

- ▶ We’ll also symbolize the plural form this way (“Some F s are G s”).
- ▶ And more generally (most) sentences of the form: “ G (some F)” or “ G (something that F s)”.

Examples

- ▶ Some hero wears a cape.

Some heroes wear capes.

$$(\exists x)(Hx \& Cx)$$

- ▶ Someone who wears a cape welcomed Greta.

$$(\exists x)(Cx \& Wxg)$$

- ▶ Greta admires some hero who wears a cape.

$$(\exists x)((Hx \& Cx) \& Agx)$$

- ▶ Autumn welcomed someone who welcomed Greta.

$$(\exists x)(Wxg \& Wax)$$

8. Intro. to Quantifier Logic

d. The universal quantifier

Universal quantifier

- ▶ “**Something** is F ” is true iff **at least one** element of domain is F .
- ▶ “**Everything** is F ” is true iff **every element** of the domain is F .
- ▶ In QL: $(\forall x) Fx$.
- ▶ E.g.:
 - “Everyone wears a cape”: $(\forall x) Cx$
 - “Everyone welcomed Greta or Autumn”: $(\forall x)(Wxg \vee Wxa)$

Universal determiners: all, every, any

- ▶ Determiners with universal meaning: **all, every, any**.
- ▶ Take complements (just like “some” does), e.g.,
 - **Every hero** inspires.
 - **All heroes** inspire.
 - **Any hero** inspires.
- ▶ These are true in the same cases (i.e. they are synonymous).
- ▶ “Every F is G ” is true iff everything **which is an F** is G .
- ▶ Watch out for “any”: not always universal.

Restricted \forall in QL

- ▶ Suppose we can symbolize two properties ' F ' and ' G '.
- ▶ How do we symbolize “Every F is G ”?
- ▶ Initial Ideas (only one of which is correct):
 - $(\forall x)(Fx \ \& \ Gx)$
If true, everything must be F .
So can be false when “Every F is G ” is true.
 - $(\forall x)(Fx \vee Gx)$
True if everything is F (without being G).
So can be true when “Every F is G ” is false.
 - $(\forall x)(Fx \supset Gx)$
If x is F , x must also be G .
(If x is not F , doesn't matter if it's G or not.)

Symbolizing “all F s are G s” (memorize this!)

Symbolize the following as

$$(\forall x)(Fx \supset Gx)$$

- ▶ All F s are G s.
- ▶ Every F is G .
- ▶ Any F is G .

Examples

- ▶ **Every hero** wears a cape.

All heroes wear capes.

$$(\forall x)(Hx \supset Cx)$$

- ▶ **Every hero who wears a cape** welcomed Greta.

$$(\forall x)((Hx \& Cx) \supset Wxg)$$

- ▶ Greta and Autumn admire **anyone who wears a cape**.

$$(\forall x)(Cx \supset (Agx \& Aax))$$

- ▶ Autumn welcomed **everyone who welcomed Greta**.

$$(\forall x)(Wxg \supset Wax)$$

- ▶ All heroes and villains welcomed Greta (a tricky one!).

$$(\forall x)((Hx \vee Vx) \supset Wxg)$$

equivalent to $(\forall x)((Hx \supset Wxg) \& (Vx \supset Wxg))$

8. Intro. to Quantifier Logic

e. 'No', 'only', 'a', 'some', and 'any'

No F is G

- ▶ “No F s are G s” can be paraphrased as
 - “Every F is not- G ,” or as
 - “Not: some F is G .”
- ▶ So symbolize it using:
 - $(\forall x)(Fx \supset \sim Gx)$ or
 - $\sim(\exists x)(Fx \& Gx)$ (i.e. ‘it is not the case that there is something that is both an F and a G ’)

Examples

- ▶ **No hero** wears a cape.

No heroes wear capes.

$$(\forall x)(Hx \supset \sim Cx)$$

- ▶ **No hero who wears a cape** welcomed Greta.

$$(\forall x)((Hx \& Cx) \supset \sim Wxg)$$

- ▶ Greta admires **no one who wears a cape**.

$$\sim(\exists x)(Cx \& Agx)$$

- ▶ Autumn welcomed **no one who welcomed Greta**.

$$\sim(\exists x)(Wxg \& Wax)$$

Only F s are G

- ▶ When is “Only F s are G s” false?
- ▶ When there is a **non**- F that is a G .
- ▶ So symbolize it as

$$\sim(\exists x)(\sim Fx \ \& \ Gx)$$

- ▶ Or, paraphrase it as: “Any x is G **only if** it is F ”
- ▶ So another symbolization is:

$$(\forall x)(Gx \supset Fx)$$

i.e. being an F is a necessary condition for being a G :
if it's not an F , then it can't be a G

Examples

- ▶ Only heroes wear capes:

$(\forall x)(Cx \supset Hx)$ (being a hero is necessary for cape-wearing)

- ▶ Only heroes who wear capes welcomed Greta.

$(\forall x)(Wxg \supset (Hx \& Cx))$

- ▶ Greta admires only people who wear capes.

$\sim(\exists x)(\sim Cx \& Agx)$

- ▶ Autumn welcomed only heroes and villains.

$\sim(\exists x)(\sim(Hx \vee Vx) \& Wax)$

$(\forall x)(Wax \supset (Hx \vee Vx))$

The indefinite article

- ▶ We use “is a” to indicate predication, e.g., “Greta is a hero.”
- ▶ Often “a” is used to claim existence, e.g.,

Greta admires a hero.

$(\exists x)(Hx \ \& \ Agx)$

- ▶ But a **generic** indefinite is closer to a universal quantifier:

A hero is someone who inspires.

$(\forall x)(Hx \supset Ix)$

- ▶ Be careful if the indefinite article is in the antecedent of a conditional:

If **a hero** wears a cape, **they** inspire.

That means: all heroes who wear capes inspire.

$(\forall x)((Hx \ \& \ Cx) \supset Ix)$

Universal “some”; existential “any”

- ▶ “Someone,” “something” can require a **universal** quantifier: if it’s in the antecedent of a conditional, with a pronoun in the consequent referring back to it, e.g.,
If **someone** is a hero, Autum admires **them**.
Roughly: Autumn admires all heroes.
 $(\forall x)(Hx \supset Aax)$
- ▶ “Any” in antecedents but **without** pronouns referring back to them are **existential**:
If **anyone** is a hero, Greta is.
Roughly: if there are heroes (at all), Greta is a hero.
 $(\exists x) Hx \supset Hg$

8. Intro. to Quantifier Logic

f. Mixed domains

Mixed domains

- ▶ Sometimes you want to talk about more than one kind of thing.
- ▶ The domain can include any mix of things (e.g., people, animals, items of clothing, feelings)
- ▶ Proper symbolization then needs predicates for these kinds, e.g.:

Domain: people alive in 2022 and items of clothing

Px : ______x is a person

Lx : ______x is an item of clothing.

Ex : ______x is a cape (recall: 'Cx' is 'wears a cape')

Rxy : ______x wears ______y

Quantification in mixed domains

► Not everyone is wearing a cape.

- In domain of people only:

$$\sim(\forall x) Cx$$

- In mixed domain:

$$\sim(\forall x) (Px \supset Cx)$$

► Some people inspire.

- In domain of people only:

$$(\exists x) Ix$$

- In mixed domain:

$$(\exists x)(Px \ \& \ Ix)$$

► Greta wears something.

$$(\exists x)(Lx \ \& \ Rgx)$$

8. Intro. to Quantifier Logic

g. Captain Morgan's (tele)scope!

(Spiced) de Morgan's for Quantifiers

- ▶ We can push negations through quantified expressions, flipping the quantifiers and negating what lies in their scope:
 - ▶ $\sim(\forall x)\Phi(x)$: “it’s not the case that for everything, Phi”
is equivalent to
 $(\exists x)\sim\Phi(x)$: “there exists something such that not-Phi”
 - ▶ $\sim(\exists x)\Phi(x)$: “it’s not the case that for something, Phi”
is equivalent to
 $(\forall x)\sim\Phi(x)$: “for everything, not-Phi”, i.e. Phi for-nothing!
- A concrete example:
- ▶ *It's not the case that some hero wears a cape:*
 $\sim(\exists x)(Hx \ \& \ Cx)$
 $(\forall x)\sim(Hx \ \& \ Cx)$ (now apply regular de Morgan's!)
 $(\forall x)(\sim Hx \vee \sim Cx)$

Quantifier Scope

- ▶ **Scope of a Quantifier**: the **sub**formula for which the quantifier is the main logical operator

in $(\exists x)(Lx \ \& \ Rgx)$, the scope of the existential is $(Lx \ \& \ Rgx)$

in $(\exists x)Lx \ \& \ (\forall y)Rgy$, the scope of the existential is Lx

- ▶ A variable is **bound** if it lies within the scope of a quantifier
- ▶ By the recursive definition that follows, each variable is bound by at most one quantifier!

Recall our Recursive definition of SL wffs

1. Every atomic formula is a wff.
2. If Φ is a wff, then $\sim\Phi$ is a wff.
3. If Φ and Ψ are wffs, then $(\Phi \& \Psi)$ is a wff.
4. If Φ and Ψ are wffs, $(\Phi \vee \Psi)$ is a wff.
5. If Φ and Ψ are wffs, then $(\Phi \supset \Psi)$ is a wff.
6. If Φ and Ψ are wffs, then $(\Phi \equiv \Psi)$ is a wff.

Nothing else is a wff of SL! (But some new things are wffs of QL!)

Extending our Recursive definition to QL wffs

- 1.* **Atomic formula of QL**: an n -place predicate followed by n terms (i.e. constants or variables), where $n \in \mathbb{N}$

This includes the SL atomic wff, which are 0 -place predicates

7. If Φ is a wff, χ is a variable, and Φ contains no χ -quantifiers, then $(\forall \chi)\Phi$ is a wff.
8. If Φ is a wff, χ is a variable, and Φ contains no χ -quantifiers, then $(\exists \chi)\Phi$ is a wff.
9. All and only wffs of QL come from the prior 8 rules.

QL Sentences: proper subset of QL wffs

- ▶ Recall: the wffs of SL *just are* the sentences of SL, i.e. the statements that are true or false under a truth-value assignment to atomic sentences
- ▶ Not all wffs of QL are sentences! Watch out!
- ▶ Let L be a two-place predicate. Then Lxx is an atomic wff of QL, but NOT a sentence (' Lxx ' is neither true nor false)
- ▶ the x 's in ' Lxx ' are **free variables**, i.e. unbound variables
- ▶ **Sentence of QL**: a wff that has no free variables: i.e. any variable that occurs is bound by a quantifier