
Bimodal Reference Manual

A Logic for Tense and Modality

Benjamin Brast-McKie

www.benbrastmckie.com

— January 13, 2026 —

Primary Reference:

“The Construction of Possible Worlds”, Brast-McKie, (under review), 2025.

Abstract

This reference manual provides the formal specification of the Bimodal logic **TM** for tense and modality as implemented in the [ProofChecker](#) project. **TM** is a bimodal logic combining an S5 historical necessity operator with linear temporal operators for the past and future tenses. Soundness and the deduction theorem are established. Completeness is proven via the semantic canonical model approach: the Lindenbaum lemma, truth lemma, and weak completeness theorem are all proven. The key result `semantic_weak_completeness` demonstrates that validity implies derivability.

Contents


1	Introduction	3
2	Syntax	4
2.1	Formulas	4
2.2	Derived Operators	4
2.3	Temporal Duality	5
3	Task Semantics	6
3.1	Task Frames	6
3.2	World Histories	6
3.3	Task Models	7
3.4	Truth Conditions	7
3.5	Time-Shift	7
3.6	Logical Consequence and Validity	8
4	Proof Theory	8
4.1	Axiom Schemata	8
4.1.1	Propositional Axioms	9
4.1.2	Modal Axioms (S5)	9
4.1.3	Temporal Axioms	9
4.1.4	Modal-Temporal Interaction	9
4.2	Inference Rules	10
4.3	Derivation Trees	11
4.4	Notation	11

5	Metalogic	12
5.1	Soundness	12
5.2	Deduction Theorem	13
5.3	Consistency	13
5.4	Completeness	13
5.5	Proof Strategy	14
5.6	Decidability	15
5.6.1	Tableau Structure	15
5.6.2	Complexity	16
5.6.3	Decision Result Types	16
5.6.4	Implementation Status	16
5.7	Implementation Status	17
6	Theorems	17
6.1	Perpetuity Principles	17
6.2	Modal S5 Theorems	18
6.3	Modal S4 Properties	18
6.4	Propositional Theorems	19
6.5	Combinator Infrastructure	19
6.6	Generalized Necessitation	19
6.7	Module Organization	19
7	Notes	20
7.1	Implementation Status	20
7.2	Discrepancy Notes	20
7.2.1	Terminology	20
7.2.2	Axiom Naming	21
7.2.3	M5 Collapse Axiom	21
7.2.4	Completeness Status	21
7.2.5	Decidability Implementation	22

1 Introduction

The bimodal logic **TM** combines S5 historical modal operators for necessity (\Box) and possibility (\Diamond) with linear temporal operators for past (H) and future (G). Implementing **TM** in Lean 4 provides a positive RL signal for training AI systems to conduct verified reasoning about past and future contingency in an interpreted formal language.

The semantics is based on *task frames*, which extend Kripke frames with temporal structure. A task frame consists of world states connected by a *task relation* indexed by temporal durations. World histories are temporal slices through a task frame, representing the possible evolution of a system.



The diagram above illustrates the conceptual structure underlying TM logic. The solid curve τ represents a single world history—a temporal sequence of states. From any point x along a history, the past and future light cones contain all states that are modally accessible. The necessity operator \Box quantifies over all possible histories, though we may often restrict to those histories that pass through the world state $\tau(x)$. The temporal operators H and G quantify over past and future times which, given a particular history, determines the range of past and future world states that history occupies relative to a given time. These primitive operators may then be used to define a host of combined operators of interest.

Project Structure

The Lean 4 implementation is in the `Bimodal/` directory:

- `Syntax/` – Defines the formula language with 6 primitive constructors and derived operators. **Complete.**
- `ProofSystem/` – Axioms (14 schemata) and inference rules (7 rules) forming a Hilbert-style proof system. **Complete.**
- `Semantics/` – Task frames model possible worlds; world histories model time; truth conditions define meaning. **Complete.**

- **Metalogic/** – Soundness theorem (proven: all axioms valid, rules preserve validity), deduction theorem (proven: enables assumption introduction), completeness via the semantic canonical model (Lindenbaum lemma proven, truth lemma proven, weak completeness proven), and decidability via tableau-based decision procedure (soundness and completeness proven). **Complete.**
- **Theorems/** – Perpetuity principles and modal theorems derived from the axiom system. **Partial.**

2 Syntax

2.1 Formulas

Formulas are defined inductively with six primitive constructors.

Definition 2.1 (Formula). The type `Formula` is defined by:

$$\varphi, \psi ::= p \mid \perp \mid \varphi \rightarrow \psi \mid \Box \varphi \mid H\varphi \mid G\varphi$$

where p ranges over propositional atoms (type `String`).

Symbol	Name	Lean	Reading
p, q, r	Atom	<code>atom s</code>	propositional atom
\perp	Bottom	<code>bot</code>	falsity
$\varphi \rightarrow \psi$	Implication	<code>imp</code>	“if φ then ψ ”
$\Box \varphi$	Necessity	<code>box</code>	“necessarily φ ”
$H\varphi$	Always past	<code>all_past</code>	“always in the past, φ ”
$G\varphi$	Always future	<code>all_future</code>	“always in the future, φ ”

2.2 Derived Operators

The following operators are defined in terms of the primitives.

Definition 2.2 (Propositional).

$$\begin{aligned}\neg \varphi &:= \varphi \rightarrow \perp \\ \varphi \wedge \psi &:= \neg(\varphi \rightarrow \neg \psi) \\ \varphi \vee \psi &:= \neg \varphi \rightarrow \psi\end{aligned}$$

Symbol	Name	Lean	Reading
$\neg\varphi$	Negation	neg	“not φ ”
$\varphi \wedge \psi$	Conjunction	and	“ φ and ψ ”
$\varphi \vee \psi$	Disjunction	or	“ φ or ψ ”

Definition 2.3 (Modal).

$$\Diamond\varphi := \neg\Box\neg\varphi$$

Symbol	Name	Lean	Reading
$\Diamond\varphi$	Possibility	pos	“possibly φ ”

Definition 2.4 (Temporal).

$$P\varphi := \neg H\neg\varphi$$

$$F\varphi := \neg G\neg\varphi$$

$$\triangle\varphi := H\varphi \wedge \varphi \wedge G\varphi$$

$$\nabla\varphi := P\varphi \vee \varphi \vee F\varphi$$

Symbol	Name	Lean	Reading
$P\varphi$	Sometime past	some_past	“at some past time, φ ”
$F\varphi$	Sometime future	some_future	“at some future time, φ ”
$\triangle\varphi$	Always	always	“at all times, φ ”
$\nabla\varphi$	Sometimes	sometimes	“at some time, φ ”

2.3 Temporal Duality

The `swap_temporal` function exchanges past and future operators.

Definition 2.5 (Temporal Swap). The function $\langle S \rangle : \text{Formula} \rightarrow \text{Formula}$ is defined by structural induction on formulas:

$$\begin{aligned}
\langle S \rangle p &= p \\
\langle S \rangle \perp &= \perp \\
\langle S \rangle (\varphi \rightarrow \psi) &= (\langle S \rangle \varphi \rightarrow \langle S \rangle \psi) \\
\langle S \rangle \Box\varphi &= \Box\langle S \rangle \varphi \\
\langle S \rangle H\varphi &= G\langle S \rangle \varphi \\
\langle S \rangle G\varphi &= H\langle S \rangle \varphi
\end{aligned}$$

Theorem 2.6 (Involution). $\langle S \rangle \langle S \rangle \varphi = \varphi$

3 Task Semantics

3.1 Task Frames

Task frames are the fundamental semantic structures for **TM**. They abstract from universal laws governing transitions between world states while still retaining the temporal duration for a transition to complete.

The following primitives are required to define a task frame:

Primitive	Type	Description
W	Type	World states
D	Type	Temporal durations
$w \Rightarrow_x u$	$W \rightarrow D \rightarrow W \rightarrow \text{Prop}$	Task relation

Definition 3.1 (Task Frame). A **task frame** over temporal type D is a triple $\mathcal{F} = (W, D, \Rightarrow)$ satisfying:

1. **Nullity:** For all $w : W$, we have $w \Rightarrow_0 w$.
2. **Compositionality:** For all $w, u, v : W$ and $x, y : D$, if $w \Rightarrow_x u$ and $u \Rightarrow_y v$, then $w \Rightarrow_{x+y} v$.

Nullity ensures that zero-duration tasks leave the world state unchanged. Compositionality ensures that executing tasks sequentially yields results consistent with a single task of combined duration.

3.2 World Histories

A world history is a function from times to world states that respects the task relation over a convex temporal domain. World histories represent possible paths through the space of world states.

Definition 3.2 (Convex Domain). A domain $\text{dom} : D \rightarrow \text{Prop}$ is **convex** if whenever $a, c \in \text{dom}$ with $a \leq c$, every time b with $a \leq b \leq c$ is also in dom . More precisely, for all $a, b, c : D$, if $\text{dom}(a)$ and $\text{dom}(c)$ and $a \leq b \leq c$, then $\text{dom}(b)$. Convexity ensures the domain has no temporal gaps.

Definition 3.3 (World History). A **world history** in a task frame \mathcal{F} is a dependent function $\tau : (x : D) \rightarrow \text{dom}(x) \rightarrow W$ where $\text{dom} : D \rightarrow \text{Prop}$ is a convex subset of D and $\tau(x) \Rightarrow_{y-x} \tau(y)$ for all times $x, y : D$ with $\text{dom}(x)$, $\text{dom}(y)$, and $x \leq y$. We write $H_{\mathcal{F}}$ for all world histories over frame \mathcal{F} .

3.3 Task Models

A task model extends a task frame with an interpretation function that assigns truth values to sentence letters at world states. **Propositions** are subsets of W representing instantaneous ways for the system to be. Sentence letters express propositions, which can be realized by zero or more world states. World states themselves are specific configurations of the total system at an instant.

Definition 3.4 (Task Model). A **task model** defined over a frame \mathcal{F} is a pair $\mathcal{M} = (\mathcal{F}, I)$ where the **interpretation function** $I : W \rightarrow \text{String} \rightarrow \text{Prop}$ assigns to each world state $w : W$ and sentence letter $p : \text{String}$ a truth value $I(w, p) : \text{Prop}$. We write $I(w, p)$ to indicate that sentence letter p is true at w .

3.4 Truth Conditions

Truth is evaluated relative to a model \mathcal{M} providing the interpretation, a world history τ representing a possible path through the space of world states, and a time $x : D$. Whereas the model fixes the interpretation of the language, the contextual parameters τ and x determine the truth value of every sentence of the language.

Definition 3.5 (Truth). For model \mathcal{M} , history $\tau \in H_{\mathcal{F}}$, and time $x : D$:

$$\begin{aligned}
 \mathcal{M}, \tau, x &\models p \text{ iff } x \in \text{dom}(\tau) \text{ and } I(\tau(x), p) \\
 \mathcal{M}, \tau, x &\not\models \perp \\
 \mathcal{M}, \tau, x &\models \varphi \rightarrow \psi \text{ iff } \mathcal{M}, \tau, x \not\models \varphi \text{ or } \mathcal{M}, \tau, x \models \psi \\
 \mathcal{M}, \tau, x &\models \Box \varphi \text{ iff } \mathcal{M}, \sigma, x \models \varphi \text{ for all } \sigma \in H_{\mathcal{F}} \\
 \mathcal{M}, \tau, x &\models H\varphi \text{ iff } \mathcal{M}, \tau, y \models \varphi \text{ for all } y : D \text{ where } y < x \\
 \mathcal{M}, \tau, x &\models G\varphi \text{ iff } \mathcal{M}, \tau, y \models \varphi \text{ for all } y : D \text{ where } x < y
 \end{aligned}$$

The modal operator \Box quantifies over all world histories $\sigma : H_{\mathcal{F}}$ at the current time $x : D$. The temporal operators H and G quantify over all earlier and later times $y : D$.

3.5 Time-Shift

The time-shift operation is used to establish the **perpetuity principles**:

- P1: $\Box \varphi \rightarrow \Delta \varphi$ (what is necessary is always the case)
- P2: $\nabla \varphi \rightarrow \Diamond \varphi$ (what is sometimes the case is possible)

It is natural to assume that whatever is necessary is always the case, or equivalently, whatever is sometimes the case is possible. Time-shift enables proofs of the bimodal axioms MF ($\Box\varphi \rightarrow \Box G\varphi$) and TF ($\Box\varphi \rightarrow G\Box\varphi$) which together imply the perpetuity principles.

Definition 3.6 (Time-Shift). For $\tau, \sigma \in H_{\mathcal{F}}$ and $x, y : D$, world histories τ and σ are **time-shifted from y to x** , written $\tau \approx_y^x \sigma$, if and only if there exists an order automorphism $\bar{a} : D \rightarrow D$ where $y = \bar{a}(x)$, $\text{dom}_{\sigma} = \bar{a}^{-1}(\text{dom}_{\tau})$, and $\sigma(z) = \tau(\bar{a}(z))$ for all $z \in \text{dom}_{\sigma}$.

Time-shifting preserves the essential structure of histories:

Theorem 3.7 (Convexity Preservation). *If τ has a convex domain and $\tau \approx_y^x \sigma$, then σ has a convex domain.*

Theorem 3.8 (Task Preservation). *If τ respects the task relation and $\tau \approx_y^x \sigma$, then σ respects the task relation.*

3.6 Logical Consequence and Validity

Logical consequence and validity are defined uniformly across all temporal types, frames, models, histories, and times.

Definition 3.9 (Logical Consequence). A formula φ is a **logical consequence** of Γ (written $\Gamma \models \varphi$) just in case for every temporal type $D : \text{Type}$, frame $\mathcal{F} : \text{TaskFrame}(D)$, model $\mathcal{M} : \text{TaskModel}(\mathcal{F})$, history $\tau \in H_{\mathcal{F}}$, and time $x : D$, if $\mathcal{M}, \tau, x \models \psi$ for all $\psi \in \Gamma$, then $\mathcal{M}, \tau, x \models \varphi$.

Definition 3.10 (Validity). A formula φ is **valid** (written $\models \varphi$) just in case φ is a logical consequence of the empty set: $\emptyset \models \varphi$. Equivalently, φ is true at every model-history-time triple.

Definition 3.11 (Satisfiability). A context Γ is **satisfiable** in temporal type $D : \text{Type}$ if there exist a frame $\mathcal{F} : \text{TaskFrame}(D)$, model $\mathcal{M} : \text{TaskModel}(\mathcal{F})$, history $\tau \in H_{\mathcal{F}}$, and time $x : D$ such that $\mathcal{M}, \tau, x \models \psi$ for all $\psi \in \Gamma$.

Theorem 3.12 (Monotonicity). *If $\Gamma \subseteq \Delta$ and $\Gamma \models \varphi$, then $\Delta \models \varphi$.*

4 Proof Theory

4.1 Axiom Schemata

The TM proof system has 14 axiom schemata.

4.1.1 Propositional Axioms

Axiom 4.1 (K - Distribution). $(\varphi \rightarrow (\psi \rightarrow \chi)) \rightarrow ((\varphi \rightarrow \psi) \rightarrow (\varphi \rightarrow \chi))$

Axiom 4.2 (S - Weakening). $\varphi \rightarrow (\psi \rightarrow \varphi)$

Axiom 4.3 (EFQ - Ex Falso Quodlibet). $\perp \rightarrow \varphi$

Axiom 4.4 (Peirce). $((\varphi \rightarrow \psi) \rightarrow \varphi) \rightarrow \varphi$

4.1.2 Modal Axioms (S5)

Axiom 4.5 (MT - Modal T). $\Box\varphi \rightarrow \varphi$

Axiom 4.6 (M4 - Modal 4). $\Box\varphi \rightarrow \Box\Box\varphi$

Axiom 4.7 (MB - Modal B). $\varphi \rightarrow \Box\Diamond\varphi$

Axiom 4.8 (M5 - Modal 5 Collapse). $\Diamond\Box\varphi \rightarrow \Box\varphi$

Axiom 4.9 (MK - Modal Distribution). $\Box(\varphi \rightarrow \psi) \rightarrow (\Box\varphi \rightarrow \Box\psi)$

4.1.3 Temporal Axioms

Axiom 4.10 (TK - Temporal Distribution). $G(\varphi \rightarrow \psi) \rightarrow (G\varphi \rightarrow G\psi)$

Axiom 4.11 (T4 - Temporal 4). $G\varphi \rightarrow GG\varphi$

Axiom 4.12 (TA - Temporal A). $\varphi \rightarrow GP\varphi$

Axiom 4.13 (TL - Temporal L). $\Delta\varphi \rightarrow GH\varphi$

4.1.4 Modal-Temporal Interaction

Axiom 4.14 (MF - Modal-Future). $\Box\varphi \rightarrow \Box G\varphi$

Axiom 4.15 (TF - Temporal-Future). $\Box\varphi \rightarrow G\Box\varphi$

Axiom	Lean Constructor	Pattern
K	Axiom.prop_k	Distribution
S	Axiom.prop_s	Weakening
EFQ	Axiom.ex_falso	Explosion
Peirce	Axiom.peirce	Classical
MT	Axiom.modal_t	Reflexivity
M4	Axiom.modal_4	Transitivity
MB	Axiom.modal_b	Symmetry
M5	Axiom.modal_5_collapse	S5 collapse
MK	Axiom.modal_k_dist	Modal distribution
TK	Axiom.temp_k_dist	Temporal distribution
T4	Axiom.temp_4	Temporal transitivity
TA	Axiom.temp_a	Connectedness
TL	Axiom.temp_l	Introspection
MF	Axiom.modal_future	Modal-future
TF	Axiom.temp_future	Temporal-modal

4.2 Inference Rules

The proof system has 7 inference rules.

Definition 4.16 (Axiom Rule). If φ matches an axiom schema, then $\Gamma \vdash \varphi$.

Definition 4.17 (Assumption Rule). If $\varphi \in \Gamma$, then $\Gamma \vdash \varphi$.

Definition 4.18 (Modus Ponens).

$$\frac{\Gamma \vdash \varphi \rightarrow \psi \quad \Gamma \vdash \varphi}{\Gamma \vdash \psi}$$

Definition 4.19 (Necessitation).

$$\frac{\vdash \varphi}{\vdash \Box \varphi}$$

Applies only to theorems (empty context).

Definition 4.20 (Temporal Necessitation).

$$\frac{\vdash \varphi}{\vdash G\varphi}$$

Applies only to theorems (empty context).

Definition 4.21 (Temporal Duality).

$$\frac{\vdash \varphi}{\vdash \langle S \rangle \varphi}$$

Applies only to theorems (empty context).

Definition 4.22 (Weakening).

$$\frac{\Gamma \vdash \varphi \quad \Gamma \subseteq \Delta}{\Delta \vdash \varphi}$$

Rule	Lean Constructor	Context Requirement
Axiom	<code>DerivationTree.axiom</code>	Any
Assumption	<code>DerivationTree.assumption</code>	Any
Modus Ponens	<code>DerivationTree.modus_ponens</code>	Any
Necessitation	<code>DerivationTree.necessitation</code>	Empty only
Temp. Necessitation	<code>DerivationTree.temporal_necessitation</code>	Empty only
Temporal Duality	<code>DerivationTree.temporal_duality</code>	Empty only
Weakening	<code>DerivationTree.weakening</code>	Any

4.3 Derivation Trees

Derivations are represented as inductive trees.

Definition 4.23 (Derivation Tree). `DerivationTree` $\Gamma \varphi$ (written $\Gamma \vdash \varphi$) is an inductive type representing a derivation of φ from context Γ .

Definition 4.24 (Height). The height of a derivation tree:

- Base cases (axiom, assumption): height 0
- Unary rules: height of subderivation + 1
- Modus ponens: max of both subderivations + 1

The height measure enables well-founded recursion in metalogical proofs.

4.4 Notation

Notation	Lean
$\Gamma \vdash \varphi$	<code>DerivationTree</code> $\Gamma \varphi$
$\vdash \varphi$	<code>DerivationTree</code> <code>[]</code> φ

5 Metalogic

5.1 Soundness

The soundness theorem establishes that derivability implies semantic validity.

Theorem 5.1 (Soundness). *If $\Gamma \vdash \varphi$ then $\Gamma \models \varphi$.*

The proof proceeds by induction on the derivation structure:

- **Axioms:** Each of the 14 axiom schemata is proven valid
- **Assumptions:** Assumed formulas are true by hypothesis
- **Modus ponens:** Validity preserved under implication elimination
- **Necessitation:** Valid formulas become necessarily valid
- **Temporal necessitation:** Valid formulas become always-future valid
- **Temporal duality:** Past-future swap preserves validity
- **Weakening:** Adding premises preserves semantic consequence

Axiom Validity	Lean Theorem	Technique
prop_k_valid	Propositional K	Propositional reasoning
prop_s_valid	Propositional S	Propositional reasoning
ex_falso_valid	EFQ	Vacuous implication
peirce_valid	Peirce	Classical case analysis
modal_t_valid	MT	Reflexivity of accessibility
modal_4_valid	M4	Transitivity of accessibility
modal_b_valid	MB	Symmetry of accessibility
modal_5_collapse_valid	M5	S5 equivalence structure
modal_k_dist_valid	MK	Distribution
temp_k_dist_valid	TK	Temporal distribution
temp_4_valid	T4	Transitivity of time
temp_a_valid	TA	Temporal connectedness
temp_l_valid	TL	Always implies recurrence
modal_future_valid	MF	Time-shift invariance
temp_future_valid	TF	Time-shift invariance

The MF and TF axioms use time-shift invariance (via `WorldHistory.time_shift`) to relate truth at different times.

5.2 Deduction Theorem

Theorem 5.2 (Deduction Theorem). *If $A :: \Gamma \vdash B$ then $\Gamma \vdash A \rightarrow B$.*

The proof uses well-founded induction on derivation height, handling each rule:

- **Axiom:** Use S axiom to weaken
- **Assumption:** Identity if same, S axiom if different
- **Modus ponens:** Use K axiom distribution
- **Weakening:** Case analysis on assumption membership
- **Modal/temporal rules:** Do not apply (require empty context)

5.3 Consistency

Definition 5.3 (Consistent). A context Γ is **consistent** if $\Gamma \not\vdash \perp$.

Definition 5.4 (Maximal Consistent). A context Γ is **maximal consistent** if it is consistent and for all $\varphi \notin \Gamma$, the context $\varphi :: \Gamma$ is inconsistent.

5.4 Completeness

The completeness proof uses the semantic canonical model construction. World states are defined as equivalence classes of (history, time) pairs, making the truth lemma straightforward by construction.

Lemma 5.5 (Lindenbaum). *Every consistent context can be extended to a maximal consistent context.*¹

Definition 5.6 (Semantic World State). A world state is an equivalence class of (history, time) pairs under the relation where two pairs are equivalent iff they denote the same underlying world state.²

Definition 5.7 (Canonical Frame). The `SemanticCanonicalFrame` has:

- World states: Equivalence classes of history-time pairs over maximal consistent sets
- Times: Integers (\mathbb{Z})

¹This is proven as `set_lindenbaum` using Zorn's lemma.

²This is formalized as `SemanticWorldState`.

- Task relation: Defined via history existence (`SemanticTaskRelV2`)

The frame satisfies nullity and compositionality.

Definition 5.8 (Canonical Valuation). An atom p is true at world state $[\tau, x]$ iff $p \in \text{MCS}(\tau(x))$.

Lemma 5.9 (Truth Lemma). In the semantic canonical model, $\varphi \in \text{MCS}(\tau(x))$ iff φ is true at world state $[\tau, x]$.³

Theorem 5.10 (Weak Completeness). If $\vdash \varphi$ then $\vdash \varphi$.⁴

Theorem 5.11 (Strong Completeness). If $\Gamma \models \varphi$ then $\Gamma \vdash \varphi$.⁵

Theorem 5.12 (Provable iff Valid). $\vdash \varphi$ iff $\vdash \varphi$.⁶

Definition 5.13 (Finite Model Property). If a formula is satisfiable, it is satisfiable in a finite model bounded by the formula's modal and temporal depth.⁷

5.5 Proof Strategy

The semantic approach defines world states as equivalence classes of (history, time) pairs. Two pairs (τ_1, x_1) and (τ_2, x_2) are equivalent iff $\tau_1(x_1) = \tau_2(x_2)$ as underlying world states.

This construction offers key advantages:

- **Truth lemma:** Follows directly from the quotient construction. Membership in a maximal consistent set corresponds to truth by definition of the equivalence class.
- **Compositionality:** The task relation is defined via history existence. Two world states are related by a duration d iff there exists a history passing through both states at times differing by d . History concatenation provides the compositionality proof.
- **Negation-completeness:** The semantic approach does not require proving negation-completeness of arbitrary locally consistent sets, a property that caused difficulties in the syntactic approach.

³This is proven as `semantic_truth_lemma_v2`.

⁴This is proven as `semantic_weak_completeness`.

⁵This is proven as `main_strong_completeness` with bridge sorries for the generalization.

⁶This is proven as `main_provable_iff_valid`, establishing completeness of TM.

⁷This is stated as `finite_model_property`.

The syntactic approach (building world states from negation-complete maximal consistent sets) is superseded. The deprecated code is archived in Boneyard/ for historical reference.

5.6 Decidability

The decidability of TM bimodal logic is established via a tableau-based decision procedure.

Theorem 5.14 (Decidability). *Validity in TM bimodal logic is decidable: for any formula φ , either $\vdash \varphi$ or $\neg \vdash \varphi$.*

Theorem 5.15 (Decision Soundness). *If the decision procedure returns “valid” with proof π , then $\vdash \varphi$.*

The decision procedure operates as follows:

1. Try direct axiom proof (fast path optimization)
2. Try proof search with limited depth
3. Build tableau starting with signed formula $F(\varphi)$
4. If all branches close: formula is valid, extract proof
5. If open saturated branch: formula is invalid, extract countermodel

5.6.1 Tableau Structure

The tableau uses **signed formulas** with annotations:

- $T(\varphi)$: formula φ is assumed true
- $F(\varphi)$: formula φ is assumed false

Expansion rules are categorized as:

- **Propositional**: $T(\varphi \wedge \psi)$ splits, $F(\varphi \rightarrow \psi)$ splits, etc.
- **Modal**: $T(\Box\varphi)$ propagates to accessible worlds, $F(\Diamond\varphi)$ creates witness
- **Temporal**: $T(\triangle\varphi)$ propagates to future times, $F(\nabla\varphi)$ creates witness

A branch **closes** when it contains both $T(\varphi)$ and $F(\varphi)$ for some formula. A branch is **saturated** when no expansion rules apply.

5.6.2 Complexity

Measure	Complexity
Time	$O(2^n)$ where n is formula size
Space	$O(n)$
Class	PSPACE-complete

5.6.3 Decision Result Types

The decision procedure returns one of three outcomes:

- `valid proof`: Formula is valid with derivation tree
- `invalid counter`: Formula is invalid with countermodel
- `timeout`: Resources exhausted before decision

5.6.4 Implementation Status

Submodule	Status	Notes
SignedFormula	Complete	Sign, SignedFormula, Branch types
Tableau	Complete	Expansion rules
Closure	Complete	Branch closure detection
Saturation	Complete	Fuel-based termination
ProofExtraction	Partial	Axiom instances only
CountermodelExtraction	Complete	From open branches
DecisionProcedure	Complete	Main decide function
Soundness	Proven	<code>decide_sound</code>
Completeness	Partial	Requires Finite Model Property

The soundness proof establishes that a “valid” result implies semantic validity. The completeness proof requires the Finite Model Property (FMP), which is stated but not yet fully formalized.

5.7 Implementation Status

Component	Status	Lean
Soundness	Proven	soundness
Deduction Theorem	Proven	deduction_theorem
Lindenbaum Lemma	Proven	set_lindenbaum
Canonical Frame	Proven	SemanticCanonicalFrame
Truth Lemma	Proven	semantic_truth_lemma_v2
Weak Completeness	Proven	semantic_weak_completeness
Strong Completeness	Proven*	main_strong_completeness
Provable iff Valid	Proven	main_provable_iff_valid
Finite Model Property	Statement	finite_model_property
Decidability	Soundness	decide_sound

* Strong completeness has bridge sorries for the connection between general validity and frame validity.

6 Theorems

6.1 Perpetuity Principles

The perpetuity principles establish deep connections between modal necessity (\Box) and temporal operators (Δ , ∇).

Theorem 6.1 (P1: Necessity Implies Always). $\vdash \Box\varphi \rightarrow \Delta\varphi$

Theorem 6.2 (P2: Sometimes Implies Possible). $\vdash \nabla\varphi \rightarrow \Diamond\varphi$

Theorem 6.3 (P3: Necessity of Perpetuity). $\vdash \Box\varphi \rightarrow \Box\Delta\varphi$

Theorem 6.4 (P4: Possibility of Occurrence). $\vdash \Diamond\nabla\varphi \rightarrow \Diamond\varphi$

Theorem 6.5 (P5: Persistent Possibility). $\vdash \Diamond\nabla\varphi \rightarrow \Delta\Diamond\varphi$

Theorem 6.6 (P6: Occurrent Necessity is Perpetual). $\vdash \nabla\Box\varphi \rightarrow \Box\Delta\varphi$

All six perpetuity principles are fully proven in the Lean implementation.

Principle	Lean Theorem	Key Lemmas
P1	perpetuity_1	MF, TF, MT
P2	perpetuity_2	Contraposition of P1
P3	perpetuity_3	P1, box_mono
P4	perpetuity_4	Contraposition
P5	perpetuity_5	modal_5, temporal K
P6	perpetuity_6	P5, bridge lemmas

6.2 Modal S5 Theorems

Theorem 6.7 (T-Box-to-Diamond). $\vdash \Box\varphi \rightarrow \Diamond\varphi$

Theorem 6.8 (Box Distributes Over Disjunction). $\vdash (\Box\varphi \vee \Box\psi) \rightarrow \Box(\varphi \vee \psi)$

Theorem 6.9 (Box Preserves Contraposition). $\vdash \Box(\varphi \rightarrow \psi) \rightarrow \Box(\neg\psi \rightarrow \neg\varphi)$

Theorem 6.10 (K Distribution for Diamond). $\vdash \Box(\varphi \rightarrow \psi) \rightarrow (\Diamond\varphi \rightarrow \Diamond\psi)$

Theorem 6.11 (S5 Collapse). $\vdash \Diamond\Box\varphi \leftrightarrow \Box\varphi$

Theorem 6.12 (Box-Conjunction). $\vdash \Box(\varphi \wedge \psi) \leftrightarrow (\Box\varphi \wedge \Box\psi)$

Theorem 6.13 (Diamond-Disjunction). $\vdash \Diamond(\varphi \vee \psi) \leftrightarrow (\Diamond\varphi \vee \Diamond\psi)$

Theorem 6.14 (S5 Diamond-Box to Truth). $\vdash \Diamond\Box\varphi \rightarrow \varphi$

Theorem 6.15 (T-Box Consistency). $\vdash \Box(\varphi \wedge \neg\varphi) \rightarrow \perp$

6.3 Modal S4 Properties

The following S4 properties are derived from the TM axiom system.

Theorem 6.16 (Modal 5). $\vdash \Diamond\varphi \rightarrow \Box\Diamond\varphi$

Theorem 6.17 (Diamond 4). $\vdash \Diamond\Diamond\varphi \rightarrow \Diamond\varphi$

Theorem 6.18 (Box Monotonicity). *If $\vdash \varphi \rightarrow \psi$ then $\vdash \Box\varphi \rightarrow \Box\psi$.*

Theorem 6.19 (Diamond Monotonicity). *If $\vdash \varphi \rightarrow \psi$ then $\vdash \Diamond\varphi \rightarrow \Diamond\psi$.*

6.4 Propositional Theorems

Theorem 6.20 (Identity). $\vdash \varphi \rightarrow \varphi$

Theorem 6.21 (Double Negation Introduction). $\vdash \varphi \rightarrow \neg\neg\varphi$

Theorem 6.22 (Double Negation Elimination). $\vdash \neg\neg\varphi \rightarrow \varphi$

Theorem 6.23 (Contraposition). *If $\vdash \varphi \rightarrow \psi$ then $\vdash \neg\psi \rightarrow \neg\varphi$.*

Theorem 6.24 (De Morgan Disjunction). $\vdash \neg(\varphi \vee \psi) \leftrightarrow (\neg\varphi \wedge \neg\psi)$

Theorem 6.25 (De Morgan Conjunction). $\vdash \neg(\varphi \wedge \psi) \leftrightarrow (\neg\varphi \vee \neg\psi)$

6.5 Combinator Infrastructure

The combinator infrastructure provides Hilbert-style proof tools.

Theorem 6.26 (B Combinator). $\vdash (B \rightarrow C) \rightarrow ((A \rightarrow B) \rightarrow (A \rightarrow C))$

Theorem 6.27 (Implication Transitivity). *If $\vdash A \rightarrow B$ and $\vdash B \rightarrow C$ then $\vdash A \rightarrow C$.*

Theorem 6.28 (Pairing). $\vdash A \rightarrow (B \rightarrow (A \wedge B))$

Theorem 6.29 (Classical Merge). $\vdash (P \rightarrow Q) \rightarrow ((\neg P \rightarrow Q) \rightarrow Q)$

6.6 Generalized Necessitation

Theorem 6.30 (Generalized Modal Necessitation). *If $\Gamma \vdash \varphi$ then $\Box\Gamma \vdash \Box\varphi$ where $\Box\Gamma = [\Box\psi \mid \psi \in \Gamma]$.*

Theorem 6.31 (Generalized Temporal Necessitation). *If $\Gamma \vdash \varphi$ then $G\Gamma \vdash G\varphi$ where $G\Gamma = [G\psi \mid \psi \in \Gamma]$.*

6.7 Module Organization

Module	Contents
Perpetuity.lean	P1-P6 principles
ModalS5.lean	S5 characteristic theorems (24 theorems)
ModalS4.lean	S4 properties (modal_5, diamond_4)
Propositional.lean	Classical propositional theorems
Combinators.lean	B, I, S combinators, imp_trans
GeneralizedNecessitation.lean	Context-level necessitation

Total theorem count: 228 theorems/lemmas across the Theorems/ directory.

7 Notes

7.1 Implementation Status

Component	Status	Notes
Syntax	Complete	6 primitives, derived operators
Semantics	Complete	Task frames, world histories, truth
Proof System	Complete	14 axioms, 7 inference rules
Soundness	Proven	All 14 axioms valid, 7 rules sound
Deduction Theorem	Proven	Well-founded recursion on height
Completeness	Proven (Semantic)	Lindenbaum, truth lemma, weak completeness
Decidability	Soundness Proven	Tableau-based, FMP for full completeness
Perpetuity Principles	Proven	P1-P6 all proven

7.2 Discrepancy Notes

This section documents differences between the paper “The Construction of Possible Worlds” and the Lean implementation.

7.2.1 Terminology

- The paper uses “perpetuity principles” for P1-P6; the Lean code uses the same terminology.
- The paper’s notation \triangle and ∇ for “always” and “sometimes” is preserved in the Lean implementation as `always` and `sometimes`.

7.2.2 Axiom Naming

Paper Name	Lean Name	Notes
MT (Modal T)	<code>Axiom.modal_t</code>	$\Box\varphi \rightarrow \varphi$
M4 (Modal 4)	<code>Axiom.modal_4</code>	$\Box\varphi \rightarrow \Box\Box\varphi$
MB (Modal B)	<code>Axiom.modal_b</code>	$\varphi \rightarrow \Box\Diamond\varphi$
MK	<code>Axiom.modal_k_dist</code>	K distribution
TK	<code>Axiom.temp_k_dist</code>	Temporal K distribution
T4	<code>Axiom.temp_4</code>	Temporal transitivity
TA	<code>Axiom.temp_a</code>	Temporal connectedness
TL	<code>Axiom.temp_l</code>	Temporal introspection
MF	<code>Axiom.modal_future</code>	Modal-future interaction
TF	<code>Axiom.temp_future</code>	Temporal-future interaction

7.2.3 M5 Collapse Axiom

The implementation includes an explicit M5 collapse axiom (`Axiom.modal_5_collapse`):

$$\Diamond\Box\varphi \rightarrow \Box\varphi$$

This is derivable from the other S5 axioms (MB + M4) but is included as a primitive for proof convenience in the S5 collapse theorem.

7.2.4 Completeness Status

The paper proves completeness via canonical model construction. The Lean implementation establishes completeness via the semantic canonical model approach. The key results are:

- `set_lindenbaum`: Every consistent set extends to a maximal consistent set
- `semantic_truth_lemma_v2`: Membership corresponds to truth in the semantic model
- `semantic_weak_completeness`: Validity implies derivability
- `main_provable_iff_valid`: Derivability and validity coincide

The semantic approach defines world states as equivalence classes of history-time pairs, making the truth lemma straightforward by construction. Bridge sorries remain for connecting general validity to frame validity in strong completeness.

7.2.5 Decidability Implementation

The implementation includes a tableau-based decision procedure for validity that provides an alternative to the canonical model approach. The decidability module establishes that validity is decidable via constructive tableau expansion and branch closure. Soundness is proven: if the procedure returns “valid”, the formula is semantically valid. Completeness requires the Finite Model Property (FMP), which is stated but not yet fully formalized. The FMP states that if a formula is satisfiable, it is satisfiable in a finite model. Full formalization of the FMP completes decidability.