

# MAA-200 Product Specification

Model MAA-200 | Rev C | Engineering

SPEC-MAA-200

*Prototype sample document for the clickable demo. Not an official publication.*

| Rev | Date | Description |
|---|---|---|
| A | 2016-01 | Initial release. |
| B | 2019-05 | Updated capacity and refrigerant data. |
| C | 2023-05 | Three-wire control connection required. |

> For professional use only. Service work must be performed by qualified personnel.

# Contents


| Section | Page |
|---|---|
| Scope and Ratings | 3 |
| Control Wiring Requirements | 4 |
| Electrical Characteristics | 5 |
| Performance | 6 |
| Revision History | 6 |


> Page numbers refer to the printed page footer.

# Control Wiring Requirements

## Section 7.2: Control Wiring

**Three-wire control connection required (rev C).**

The control circuit requires a three-wire connection to the indoor unit. Terminals R, C, and G must be wired.

This supersedes the two-wire arrangement documented in earlier revisions.

| Terminal | Wire | Function |
|---|---|---|
| R | RED | 24VAC supply |
| C | WHT | Common return |
| G | GRN | Fan / 3-wire enable |

> Engineering source of truth. Supersedes the two-wire arrangement in rev A and rev B.

# Electrical Characteristics

## Section 4: Electrical Characteristics

Component and connector locations are shown in the reference drawings. Confirm each pin against the drawing before probing or reconnecting any harness.

## Procedure notes

- Use only factory-approved parts.
- Match the full part number and revision.
- Transfer configuration settings where fitted.
- Confirm routing against the reference drawings.
- Run a full startup sequence after assembly.

| Terminal | Wire | Function |
|---|---|---|
| R | RED | 24VAC supply |
| C | WHT | Common return |
| W | BLU | Call for heat |
| G | GRN | Call for fan |

> Always confirm 0VAC and 0VDC before making resistance measurements.

# Performance

## Section 9: Performance

Nominal capacity is rated at 24,000 BTU/h in cooling. Values are at standard rating conditions.

| Property | Value |
|---|---|
| Nominal capacity | 24,000 BTU/h |
| Refrigerant | R-410A |
| Operating range | -10 to 46 deg C |
| Sound pressure | 56 dB(A) |

# Revision History

| Rev | Date | Description |
|---|---|---|
| A | 2016-01 | Initial release. |
| B | 2019-05 | Updated capacity and refrigerant data. |
| C | 2023-05 | Three-wire control connection required. |