

- Configurazione di 2 client in modo tale da ricevere IP dal server DHCP

The screenshot shows the configuration window for a device named 'Laptop0'. The window has a title bar with the name 'Laptop0' and standard window controls. Below the title bar is a tabbed interface with four tabs: 'Physical', 'Config' (which is selected), 'Desktop', and 'Attributes'. On the left side of the 'Config' tab is a sidebar menu with two main sections: 'GLOBAL' and 'INTERFACE'. Under 'GLOBAL', there are 'Settings' and 'Algorithm Settings'. Under 'INTERFACE', there are 'FastEthernet0' and 'Bluetooth'. The main area of the 'Config' tab is titled 'Global Settings'. It contains the following fields and options:

- Display Name:** A text field containing 'Laptop0'.
- Interfaces:** A dropdown menu showing 'FastEthernet0'.
- Gateway/DNS IPv4:**
 - Radio buttons for 'DHCP' (selected) and 'Static'.
 - Default Gateway:** A text field containing '0.0.0.0'.
 - DNS Server:** A text field containing '192.168.1.2'.
- Gateway/DNS IPv6:**
 - Radio buttons for 'Automatic' and 'Static' (selected).
 - Default Gateway:** An empty text field.
 - DNS Server:** An empty text field.