

Ardrand: The feasibility of the Arduino as a random number generator

Benedikt Kristinsson
Advisor: Ýmir Vigfússon

December 19, 2011

Randomness

- Hard on CPU

Randomness

- Hard on CPU
- External sources needed

Randomness

- Hard on CPU
- External sources needed
 - Hard drives

Randomness

- Hard on CPU
- External sources needed
 - Hard drives
 - Radioactive decay

Randomness

- Hard on CPU
- External sources needed
 - Hard drives
 - Radioactive decay
 - Atmospheric noise (RANDOM.ORG)

Randomness

- Hard on CPU
- External sources needed
 - Hard drives
 - Radioactive decay
 - Atmospheric noise (RANDOM.ORG)
 - Intel RNG

Randomness

- Hard on CPU
- External sources needed
 - Hard drives
 - Radioactive decay
 - Atmospheric noise (RANDOM.ORG)
 - Intel RNG
- But why?

Randomness

- Hard on CPU
- External sources needed
 - Hard drives
 - Radioactive decay
 - Atmospheric noise (RANDOM.ORG)
 - Intel RNG
- But why?

Pseudo-Random Number Generator

- Auðkennislykilinn/RSA SecureID

Pseudo-Random Number Generator

- Auðkennislykilinn/RSA SecureID



Pseudo-Random Number Generator

- Auðkennislykilinn/RSA SecureID



- Deterministic

Pseudo-Random Number Generator

- Auðkennislykilinn/RSA SecureID



- Deterministic
- Only as secure as its seed

Pseudo-Random Number Generator

- Auðkennislykilinn/RSA SecureID



- Deterministic
- Only as secure as its seed
- Unpredictable sequences

Pseudo-Random Number Generator

- Auðkennislykilinn/RSA SecureID



- Deterministic
- Only as secure as its seed
- Unpredictable sequences

Cryptography

- Bad seeding methods have resulted in breaking of cryptosystems

Cryptography

- Bad seeding methods have resulted in breaking of cryptosystems
 - Netscape browser

Cryptography

- Bad seeding methods have resulted in breaking of cryptosystems
 - Netscape browser
 - Enigma

Cryptography

- Bad seeding methods have resulted in breaking of cryptosystems
 - Netscape browser
 - Enigma
- Single-purpose devices

Cryptography

- Bad seeding methods have resulted in breaking of cryptosystems
 - Netscape browser
 - Enigma
- Single-purpose devices

Possible ways

- External hardware

Possible ways

- External hardware
- Obtain keys from outside

Possible ways

- External hardware
- Obtain keys from outside
- Need

Possible ways

- External hardware
- Obtain keys from outside
- Need
 - Available hardware

Possible ways

- External hardware
- Obtain keys from outside
- Need
 - Available hardware
 - Cheap

Possible ways

- External hardware
- Obtain keys from outside
- Need
 - Available hardware
 - Cheap
 - Statistically sound

Possible ways

- External hardware
- Obtain keys from outside
- Need
 - Available hardware
 - Cheap
 - Statistically sound
 - Fast


Possible ways

- External hardware
- Obtain keys from outside
- Need
 - Available hardware
 - Cheap
 - Statistically sound
 - Fast

Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results

Arduino
Hypothesis

Today: Arduino



Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results

Arduino
Hypothesis

Arduino

- Available

Arduino

- Available
- Cheap (\$30)

Arduino

- Available
- Cheap (\$30)
- Analog noise from `analogRead`

Arduino

- Available
- Cheap (\$30)
- Analog noise from `analogRead`
- Does it work ?

Arduino

- Available
- Cheap (\$30)
- Analog noise from `analogRead`
- Does it work ?
- Is it fast enough?

Arduino

- Available
- Cheap (\$30)
- Analog noise from `analogRead`
- Does it work ?
- Is it fast enough?
- Has it been tried before?

Arduino

- Available
- Cheap (\$30)
- Analog noise from `analogRead`
- Does it work ?
- Is it fast enough?
- Has it been tried before?

If it is important for a sequence of [random] values generated to differ [...] initialize the random number generator with a fairly random input, such as `analogRead()` on an unconnected pin.

Hypothesis

Hypothesis: Values returned from `analogRead` are random

Hypothesis

Hypothesis: Values returned from `analogRead` are random

- Need stats!

Hypothesis

Hypothesis: Values returned from `analogRead` are random

- Need stats!
- Need an controlled environment (Iceland vs. Azerbaijan)

Hypothesis

Hypothesis: Values returned from `analogRead` are random

- Need stats!
- Need an controlled environment (Iceland vs. Azerbaijan)

Analysis

1 Obtain sequences

Analysis

- 1 Obtain sequences
- 2 Algorithms used

Analysis

- 1 Obtain sequences
- 2 Algorithms used
- 3 Statistical tests

Analysis

- 1 Obtain sequences
- 2 Algorithms used
- 3 Statistical tests

Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results

Obtained numbers

Questions

Does the environment matter?

Temperature is important

Odd locations

Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results


Obtained numbers

Questions

Does the environment matter?

Temperature is important

Odd locations



Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results


Obtained numbers

Questions

Does the environment matter?

Temperature is important

Odd locations



Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results


Obtained numbers

Questions

Does the environment matter?

Temperature is important

Odd locations



Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results


Obtained numbers

Questions

Does the environment matter?

Temperature is important

Odd locations



Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results

Obtained numbers

Questions

Does the environment matter?
Temperature is important

Questions

- Q: Does the environment matter?

Questions

- Q: Does the environment matter?
- Q: How can we use the bits?

Questions

- Q: Does the environment matter?
- Q: How can we use the bits?
- Q: How can we can for randomness?

Questions

- Q: Does the environment matter?
- Q: How can we use the bits?
- Q: How can we can for randomness?

Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results

Obtained numbers
Questions
Does the environment matter?
Temperature is important

Does the environment matter?


Q: Does the environment matter?

Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results

Obtained numbers
Questions
Does the environment matter?
Temperature is important

Does the environment matter?

Q: Does the environment matter?



Yes!

Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results


Obtained numbers
Questions
Does the environment matter?
Temperature is important

Temperature is important

Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results

Obtained numbers
Questions
Does the environment matter?
Temperature is important



Temperature is important



Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results

Obtained numbers
Questions
Does the environment matter?
Temperature is important

Temperature is important



Benedikt Kristinsson Advisor: Ýmir Vigfússon

Ardrand: The feasibility of the Arduino as a random number generator

The von Neumann box

Used to remove bias from a generator

The von Neumann box

Used to remove bias from a generator

Idea

Input two bits and discard them if they are the same. A 1,0-pair becomes a 1-bit and 0,1 pair becomes a 0-bit.

The von Neumann box

Used to remove bias from a generator

Idea

Input two bits and discard them if they are the same. A 1,0-pair becomes a 1-bit and 0,1 pair becomes a 0-bit.

Math

Let p be the probability that the generator yields a 1-bit and q that it yields a 0-bit. This relies on the fact that 01 and 10 are equiprobable since $p \cdot q = q \cdot p$.

The von Neumann box

Used to remove bias from a generator

Idea

Input two bits and discard them if they are the same. A 1,0-pair becomes a 1-bit and 0,1 pair becomes a 0-bit.

Math

Let p be the probability that the generator yields a 1-bit and q that it yields a 0-bit. This relies on the fact that 01 and 10 are equiprobable since $p \cdot q = q \cdot p$.

Applied in all our algorithms.

Meanrand

Idea

Keep track of the mean of the values read, generate a 0 if below and a 1 otherwise.

- Observed bitrate: 25-85 bps

Meanrand

Idea

Keep track of the mean of the values read, generate a 0 if below and a 1 otherwise.

- Observed bitrate: 25-85 bps
- Slow and not very random

Meanrand

Idea

Keep track of the mean of the values read, generate a 0 if below and a 1 otherwise.

- Observed bitrate: 25-85 bps
- Slow and not very random

Updownrand

Idea

Read one value. Generate a 1 bit if the next value is higher and a 0 bit otherwise.

Updownrand

Idea

Read one value. Generate a 1 bit if the next value is higher and a 0 bit otherwise.

- Observed bitrate: 4 bps

Updownrand

Idea

Read one value. Generate a 1 bit if the next value is higher and a 0 bit otherwise.

- Observed bitrate: 4 bps
- Rejected: too slow

Updownrand

Idea

Read one value. Generate a 1 bit if the next value is higher and a 0 bit otherwise.

- Observed bitrate: 4 bps
- Rejected: too slow
- Not very random

Mixmeanupdownrand

Idea

See what happens if we mix Mean-RAND and Updown-RAND.
Generate one bit from either and XOR them together.

Mixmeanupdownrand

Idea

See what happens if we mix Mean-RAND and Updown-RAND.
Generate one bit from either and XOR them together.

- Observed bitrate: 2 bps

Mixmeanupdownrand

Idea

See what happens if we mix Mean-RAND and Updown-RAND.
Generate one bit from either and XOR them together.

- Observed bitrate: 2 bps
- Rejected: too slow

Mixmeanupdownrand

Idea

See what happens if we mix Mean-RAND and Updown-RAND.
Generate one bit from either and XOR them together.

- Observed bitrate: 2 bps
- Rejected: too slow
- Not very random either

Leastsignrand

Idea

Return the least significant (rightmost) bit for each value from `analogRead`

Leastsigrand

Idea

Return the least significant (rightmost) bit for each value from `analogRead`

Math

Let $b = b_9, \dots, b_1, b_0$ be a 10-bit integer generated by `analogRead`. Return b_0 .

Leastsigrand

Idea

Return the least significant (rightmost) bit for each value from `analogRead`

Math

Let $b = b_9, \dots, b_1, b_0$ be a 10-bit integer generated by `analogRead`. Return b_0 .

- Observed bitrate: 290 bps

Leastsigrand

Idea

Return the least significant (rightmost) bit for each value from `analogRead`

Math

Let $b = b_9, \dots, b_1, b_0$ be a 10-bit integer generated by `analogRead`. Return b_0 .

- Observed bitrate: 290 bps
- Fastest

Leastsigrand

Idea

Return the least significant (rightmost) bit for each value from `analogRead`

Math

Let $b = b_9, \dots, b_1, b_0$ be a 10-bit integer generated by `analogRead`. Return b_0 .

- Observed bitrate: 290 bps
- Fastest
- Passes most tests in some settings

Twoleastsignrand

Idea

Return the XOR of the two least significant (rightmost) bits for each value from `analogRead`

Twoleastsignrand

Idea

Return the XOR of the two least significant (rightmost) bits for each value from `analogRead`

Math

Let $b = b_9, \dots, b_1, b_0$ be a 10-bit integer generated by `analogRead`. Return $b_0 \oplus b_1$.

Twoleastsignrand

Idea

Return the XOR of the two least significant (rightmost) bits for each value from `analogRead`

Math

Let $b = b_9, \dots, b_1, b_0$ be a 10-bit integer generated by `analogRead`. Return $b_0 \oplus b_1$.

- Observed bitrate: ≈ 170 bps

Twoleastsignrand

Idea

Return the XOR of the two least significant (rightmost) bits for each value from `analogRead`

Math

Let $b = b_9, \dots, b_1, b_0$ be a 10-bit integer generated by `analogRead`. Return $b_0 \oplus b_1$.

- Observed bitrate: ≈ 170 bps
- Second fastest, but not fast enough

Twoleastsignrand

Idea

Return the XOR of the two least significant (rightmost) bits for each value from `analogRead`

Math

Let $b = b_9, \dots, b_1, b_0$ be a 10-bit integer generated by `analogRead`. Return $b_0 \oplus b_1$.

- Observed bitrate: ≈ 170 bps
- Second fastest, but not fast enough
- Passes all tests in some settings

Statistical testing

- Impossible to prove that a generator is random [AJM, PO, SA, 1996]

Statistical testing

- Impossible to prove that a generator is random [AJM, PO, SA, 1996]
- Not rejected rather than accepted as random

Statistical testing

- Impossible to prove that a generator is random [AJM, PO, SA, 1996]
- Not rejected rather than accepted as random
- FIPS boundaries

Statistical testing

- Impossible to prove that a generator is random [AJM, PO, SA, 1996]
- Not rejected rather than accepted as random
- FIPS boundaries
- 20,000 bits

Monobit

Idea

A random sequences should contain roughly the same number of 1's and 0's. This gives a statistic on this ratio.

Monobit

Idea

A random sequences should contain roughly the same number of 1's and 0's. This gives a statistic on this ratio.

Math

Let n_0 denote the number of 0's and n_1 the number of 1's. We then find

$$X_1 = \frac{(n_0 - n_1)^2}{2}$$

Results

Results

Passed • Mean-RAND on all our computers

Results

Results

Passed

- Mean-RAND on all our computers
- Leastsign-RAND on all our computers

Results

Results

Passed

- Mean-RAND on all our computers
- Leastsign-RAND on all our computers
- Twoleastsign-RAND on all our computers

Results

Results

Passed

- Mean-RAND on all our computers
- Leastsign-RAND on all our computers
- Twoleastsign-RAND on all our computers

Rejected

- Updown

Results

Results

Passed

- Mean-RAND on all our computers
- Leastsign-RAND on all our computers
- Twoleastsign-RAND on all our computers

Rejected

- Updown
- MixMeanUpdown (inconsistently)

Results

Results

Passed

- Mean-RAND on all our computers
- Leastsign-RAND on all our computers
- Twoleastsign-RAND on all our computers

Rejected

- Updown
- MixMeanUpdown (inconsistently)

Poker test

Idea

Based on the idea of five-card hands in poker. In a random sequence we would expect each hand to show up about the same amount of time.

Poker test

Idea

Based on the idea of five-card hands in poker. In a random sequence we would expect each hand to show up about the same amount of time.

Math

Let m be the size of the poker hand and $k = \lfloor \frac{n}{m} \rfloor$, where n is the length of the sequence. Find

$$X_3 = \frac{2^m}{k} \left(\sum_{i=1}^{2^m} n_i^2 \right) - k$$

Results

Results

Passed • Leastsign-RAND on our laptops

Results

Results

Passed

- Leastsign-RAND on our laptops
- Twoleastsign-RAND on our laptops

Results

Results

Passed

- Leastsign-RAND on our laptops
- Twoleastsign-RAND on our laptops

Rejected

- Updown-RAND

Results

Results

Passed

- Leastsign-RAND on our laptops
- Twoleastsign-RAND on our laptops

Rejected

- Updown-RAND
- Mean-RAND

Results

Results

Passed

- Leastsign-RAND on our laptops
- Twoleastsign-RAND on our laptops

Rejected

- Updown-RAND
- Mean-RAND
- MixMeanUpdown-RAND

Results

Results

Passed

- Leastsign-RAND on our laptops
- Twoleastsign-RAND on our laptops

Rejected

- Updown-RAND
- Mean-RAND
- MixMeanUpdown-RAND
- All algorithms on desktop computer

Runs

Runs examples

100011

Runs

Runs examples

100011

- Has one run (gap) of length 3 (three zeroes)

Runs

Runs examples

100011

- Has one run (gap) of length 3 (three zeroes)
- One run (block) of length 2

Runs

Runs examples

100011

- Has one run (gap) of length 3 (three zeroes)
- One run (block) of length 2
- One run of length 1

Runs

Runs examples

100011

- Has one run (gap) of length 3 (three zeroes)
- One run (block) of length 2
- One run of length 1

Runs

Runs examples

100011

- Has one run (gap) of length 3 (three zeroes)
- One run (block) of length 2
- One run of length 1

Idea

Find the number of runs of each length. The longer the run, the unlikelier it is. The FIPS publication has a nice table listing how many sequences of each length should appear.

Runs

Runs examples

100011

- Has one run (gap) of length 3 (three zeroes)
- One run (block) of length 2
- One run of length 1

Idea

Find the number of runs of each length. The longer the run, the unlikelier it is. The FIPS publication has a nice table listing how many sequences of each length should appear.

Math

Let G_i and B_i be the number of gaps and blocks of length i and e_i denote the expected number of blocks of length i . Find

$$X_4 = \sum_{i=1}^k \frac{(B_i - e_i)^2}{e_i} + \sum_{i=1}^k \frac{(G_i - e_i)^2}{e_i}$$

Results

Results

Passed

- Leastsign-RAND sometimes on laptops
- Twoleastsign-RAND always on one laptop
- Twoleastsign-RAND sometimes on another laptop

Rejected

- Updown-RAND
- Mean-RAND
- MixMeanUpdown-RAND
- All algorithms on desktop computer

Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results

What does this mean?
Future work

Results

Algorithm	Monobit	Poker	Runs	Long runs	Bandwidth
Leastsign	ACC	ACC	(REJ)	ACC	290.55 bps

Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results

What does this mean?
Future work

Results

Algorithm	Monobit	Poker	Runs	Long runs	Bandwidth
Leastsign	ACC	ACC	(REJ)	ACC	290.55 bps
Twoleastsign	ACC	ACC	ACC	ACC	172.0 bps

Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results

What does this mean?
Future work

Results

Algorithm	Monobit	Poker	Runs	Long runs	Bandwidth
Leastsign	ACC	ACC	(REJ)	ACC	290.55 bps
Twoleastsign	ACC	ACC	ACC	ACC	172.0 bps
Mean	ACC	REJ	REJ	REJ	25.32 bps

Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results

What does this mean?
Future work

Results

Algorithm	Monobit	Poker	Runs	Long runs	Bandwidth
Leastsign	ACC	ACC	(REJ)	ACC	290.55 bps
Twoleastsign	ACC	ACC	ACC	ACC	172.0 bps
Mean	ACC	REJ	REJ	REJ	25.32 bps
Updown-RAND	REJ	REJ	REJ	REJ	4 bps

Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results

What does this mean?
Future work

Results

Algorithm	Monobit	Poker	Runs	Long runs	Bandwidth
Leastsign	ACC	ACC	(REJ)	ACC	290.55 bps
Twoleastsign	ACC	ACC	ACC	ACC	172.0 bps
Mean	ACC	REJ	REJ	REJ	25.32 bps
Updown-RAND	REJ	REJ	REJ	REJ	4 bps
MixMeanUpdown	ACC	REJ	REJ	REJ	2 bps

Randomness
 How do we get entropy?
 Today: Arduino
 Analysis
 Obtaining numbers
 Algorithms
 The statistical tests
 Results

What does this mean?
 Future work

Results

Algorithm	Monobit	Poker	Runs	Long runs	Bandwidth
Leastsign	ACC	ACC	(REJ)	ACC	290.55 bps
Twoleastsign	ACC	ACC	ACC	ACC	172.0 bps
Mean	ACC	REJ	REJ	REJ	25.32 bps
Updown-RAND	REJ	REJ	REJ	REJ	4 bps
MixMeanUpdown	ACC	REJ	REJ	REJ	2 bps

Results

Algorithm	Monobit	Poker	Runs	Long runs	Bandwidth
Leastsign	ACC	ACC	(REJ)	ACC	290.55 bps
Twoleastsign	ACC	ACC	ACC	ACC	172.0 bps
Mean	ACC	REJ	REJ	REJ	25.32 bps
Updown-RAND	REJ	REJ	REJ	REJ	4 bps
MixMeanUpdown	ACC	REJ	REJ	REJ	2 bps

- Twoleastsign passes NIST tests as well when it passes our tests

Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results

What does this mean?
Future work

What does this mean?

- Arduino not a feasible target using our methods

What does this mean?

- Arduino not a feasible target using our methods
- We created a seed discovery program

What does this mean?

- Arduino not a feasible target using our methods
- We created a seed discovery program
 - Runs quickly (Mean: 1.6 seconds)

What does this mean?

- Arduino not a feasible target using our methods
- We created a seed discovery program
 - Runs quickly (Mean: 1.6 seconds)
 - Always finds seed in our experiments (5000 sequences)

What does this mean?

- Arduino not a feasible target using our methods
- We created a seed discovery program
 - Runs quickly (Mean: 1.6 seconds)
 - Always finds seed in our experiments (5000 sequences)
 - Almost always finds the seed

What does this mean?

- Arduino not a feasible target using our methods
- We created a seed discovery program
 - Runs quickly (Mean: 1.6 seconds)
 - Always finds seed in our experiments (5000 sequences)
 - Almost always finds the seed

Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results

What does this mean?
Future work

Future work

- Find out what factors cause it to pass tests

Future work

- Find out what factors cause it to pass tests
 - Stabilize if possible

Future work

- Find out what factors cause it to pass tests
 - Stabilize if possible
- Implement more algorithms to look for entropy

Future work

- Find out what factors cause it to pass tests
 - Stabilize if possible
- Implement more algorithms to look for entropy
- Cheap and simple modifications of Arduino

Future work

- Find out what factors cause it to pass tests
 - Stabilize if possible
- Implement more algorithms to look for entropy
- Cheap and simple modifications of Arduino
- Workshop

Future work

- Find out what factors cause it to pass tests
 - Stabilize if possible
- Implement more algorithms to look for entropy
- Cheap and simple modifications of Arduino
- Workshop

Randomness
How do we get entropy?
Today: Arduino
Analysis
Obtaining numbers
Algorithms
The statistical tests
Results

What does this mean?
Future work

Thank you

Thank you. Questions?