



ADDING ORDER HISTORY TO YOUR EXPERIENCE

Table of Contents

Introduction.....	2
Key Terms	3
Step 1: List a Member’s Orders	3
Step 2: List Order Details for a Member or Guest.....	7
Understanding Order Status	10
API Quick Reference	20
Best Practices.....	20
Troubleshooting	22
Terms of Service.....	22
Common Questions	24
Contacting the Team.....	32
Document Change Log	33
Next Steps.....	33

[➔](/doc/commerce/order/use-order.pdf) DOWNLOAD

ADDING ORDER HISTORY TO YOUR EXPERIENCE

Last Updated: 04/02/2021

Retrieve a complete order history for your consumers.

TIP: Before using this guide you should have already completed [Adding Checkout to Your Experience \(https://developer.niketech.com/nde-docs/doc/commerce/checkout/use-checkout.html \)](https://developer.niketech.com/nde-docs/doc/commerce/checkout/use-checkout.html).

Introduction

Adding order history to your app is a two-step process:

1. Your application makes an [Order Summary API \(https://developer.niketech.com/docs/projects/User%20order%20summary?tab=api \)](https://developer.niketech.com/docs/projects/User%20order%20summary?tab=api) request to retrieve all, or a filtered [list of a member's orders](#).
2. Using an order ID from the Order Summary response, your application makes an Order Details API request to [list order details for a member or guest](#).

What is an Order?

An order consists of all data related to:

- Consumers' purchased items/services
- Consumers' payment method(s) and billing address(es)
- Consumers' shipping method(s) and shipping address(es)
- Pricing
- Taxes
- Promotions
- Status

An order is created in the last step of [Checkout \(https://developer.niketech.com/nde-docs/](https://developer.niketech.com/nde-docs/)

[doc/commerce/checkout/use-checkout.html](#)) when the consumer has provided all the necessary checkout information and submits it for fulfillment. After an order is created, it is stamped with a unique order number, the date and time the order was submitted, and a status of CREATED. The order is assigned different statuses as it progresses through the order lifecycle. See [Understanding Order Status](#) for more detail.

Key Terms

Listed below are key terms for the Order History APIs.

Table 1: Key Terms for Order History APIs

Term	Definition
Employee	An employee that is logged in with a Swoosh account
Guest	An anonymous consumer, i.e. not logged-in with a Nike account
Member	A logged-in consumer with a Nike account
Order	A set of data for a checkout submitted by a consumer. Often contains products/services, payment methods, shipping methods, taxes, and promotions
Order Details	Use the Order Details API (https://developer.niketech.com/docs/projects/User%20order%20details?tab=api) to get full details of an order for a member or guest
Order Line	A line item with an order, representing a product, payment, etc.
Order Number	The unique identifier for the order
Order Status	The status of an order, as represented for individual lines and payments, or as a combined <code>status</code> . See Understanding Order Status for more
Order Summary	Use the Order Summary API (https://developer.niketech.com/docs/projects/User%20order%20summary?tab=api) to get a list of orders for a Nike member
DOMS	Nike's Digital Order Management System

Step 1: List a Member's Orders

Use the [Order Summary API \(https://developer.niketech.com/docs/projects/](https://developer.niketech.com/docs/projects/)

[User%20order%20summary?tab=api](#)) to get all, or a filtered list of orders for a Nike member. By making their past orders available to members as a self-service in your app, they can view their product and payment history without having to contact Consumer Services.

TIPS

- Order Summary returns limited information about each order. For order pricing, tax, shipping, and detailed product information, or if you want to list the details of a guest's order, see [List Order Details for a Member or Guest](#).
- For the required request headers, see [Required Request Headers](#).

Customizing Your Results

You control what is returned in your result set, and how it is sorted, through URL parameters.

Filtering

The table below lists the fields by which you can filter your Order Summary results. If no filter is applied, all of a member's orders are returned. While some filters only allow one value, you can send multiple filters in the same request. For instance, even though only one `orderSubmitDateAfter` filter value is allowed, you can request a Order Summary filtered by `orderSubmitDateAfter` and status. Note that filter parameter names and values are case-sensitive.

Table 2: Available Filters for Order Summary

Order Field Name	Description	Sample Value
<code>orderType</code>	List orders of this type. You can only filter by one orderType at a time.	SALES_ORDER
<code>storeId</code>	List orders placed in this store. You can only filter by one storeId at a time.	28382
<code>status</code>	List orders with this status.	Cancelled
<code>orderSubmitDateAfter</code>	List orders placed after this date. You can only filter by one date at a time.	Format is yyyy-MM-dd'T'HH:mm:ssZ
<code>orderLines.parentSalesOrderNumber</code>	Allows search of return orders based on sales order number	O7280930876
<code>orderLines.parentSalesOrderLineKey</code>	Allows search of return orders based on sales	20170822053845753136865

ADDING ORDER HISTORY TO YOUR EXPERIENCE

Order Field Name	Description	Sample Value
	order line key	
<code>email</code>	Filter by customer email address. Only works in combination with <code>orderLines.parentSalesOrderNumber</code> or <code>orderLines.parentSalesOrderLineKey</code> and it must match email in parent order	sample@gmail.com
<code>phoneNumber</code>	Filter by customer phone number. Only number 0-9 are valid. Only works in combination with <code>orderLines.parentSalesOrderNumber</code> or <code>orderLines.parentSalesOrderLineKey</code> and it must match phone number in parent order	7134567890

Sorting

You can sort a member's orders in several ways using the `sort` query parameter. You can sort by one or more order fields, separated by a comma. If the field name you want to sort by is nested, refer to it with dot notation. For sort parameter syntax, see the [Query Parameters \(https://developer.niketech.com/nde-docs/doc/getting-started/using-nike-apis.html#query-parameters \)](https://developer.niketech.com/nde-docs/doc/getting-started/using-nike-apis.html#query-parameters) section of [Using Nike APIs \(https://developer.niketech.com/nde-docs/doc/getting-started/using-nike-apis.html \)](https://developer.niketech.com/nde-docs/doc/getting-started/using-nike-apis.html).

TIP: It is recommended that your app pass the `sort` query parameter in the request to ensure that the results are sorted appropriately for your experience.

Other Query Parameters

The Order Summary API also supports the `fields`, `count` and `anchor` query parameters to restrict the results to certain fields, restrict the number of results, and control pagination. For more information on syntax, see the [Query Parameters \(https://developer.niketech.com/nde-docs/doc/getting-started/using-nike-apis.html#query-parameters \)](https://developer.niketech.com/nde-docs/doc/getting-started/using-nike-apis.html#query-parameters) section of [Using Nike APIs \(https://developer.niketech.com/nde-docs/doc/getting-started/using-nike-apis.html \)](https://developer.niketech.com/nde-docs/doc/getting-started/using-nike-apis.html).

Order Summary Scenarios

Table 3: Scenarios for Order Summary

I want to list for a member	Sample Query
Order types of RESERVE_ORDER, submitted after 2018-01-24, purchased at store 12345	<code>https://api.nike.com/order_mgmt/user_order_summary/v2?filter=storeId(12345)&filter=orderSubmitDateAfter(2018-01-24)&filter=orderType(RESERVE_ORDER)</code>
Orders with a status of Shipped or Delivered	<code>https://api.nike.com/order_mgmt/user_order_summary/v2?filter=status(Shipped,Delivered)</code>
All orders sorted in ascending modificationDate	<code>https://api.nike.com/order_mgmt/user_order_summary/v2?sort=modificationDateAsc</code>
Just order ID, status and submitted date fields of all orders	<code>https://api.nike.com/order_mgmt/user_order_summary/v2?fields=id,status,orderSubmitDate</code>
Two most-recently-submitted orders	<code>https://api.nike.com/order_mgmt/user_order_summary/v2?count=2</code>

Executing the Request

Sample CURL for Order Summary for a Member/Employee:

```
curl -X GET \
  https://api.nike.com/order_mgmt/user_order_summary/v2 \
  -H 'Authorization: Bearer
eyJhbGciOiJSUzI1NiIsImtpZCI6IjcyYWI1NTlkLWwzMtNGVhYi05MTljLTJkYjA3YjFjN2
NmMHNpZyJ9.eyJpYXQiOiJlMzQxOTMyOTcsImV4cCI6MTUzNDE5Njg5NywiaXNzIjoib2FldGg
yYWNjIiwianRpIjojY2IyOGE4OGItYWU4ZC00NWw1LWE2NjMtNDRkMmY0NWQwZDZjIiwibGF0I
joXNTM0MTkzMjk3LCJhdWQiOiJjb20ubmlrZS5kaWdpdGFsIiwic3ViIjojY29tLm5pa2UuY29
```

```
tbWVyY2UubmlrZWRvdGNvbS53ZWlLCJzYnQiOiJuaWtlOmFwcCI6WyJuaWtlLmRpZ
2l0YWwiXSwicHJlIjoimTYxODI2OTIwMTIiLCJwcnQiOiJuaWtlOnN3b29zaCJ9.Nt-
Irlborb2gmz6e-CwUmvPlm80m5lEMHR18AEftE5qqVmlm-
HbFHNPPA6AWj8gscQRs02ft_CQTKvHza7EivQ64RajD-
sj0FTTaPBMXUsWqL1Jt1fFv61cYmbrErOsEBcV_NWbgOVQ_NNF3aL9FCLi12OgrVilpa7ManTL
lOP_nmI_SaMN3USawECzKbYlOW58DaHBQjezkpeejyv4AQXm99HL1qWYb5fARnpubrwlcN7Gy
UepOwImfNf8xZZrcJKTx4HBXmYVFg8gMskoqzSEjJijfxYNxSy507Y4fUyRq2glISPMnrQnAF5
NAw19SCQm8wZxKxPaxc590EhMLA'
```

Parsing the Response

The Order Summary JSON response contains several fields relating to status. See [Understanding Order Status](#) for more detail about how status is determined, and the suggested order statuses to display in your experience. See the [Order Summary API \(https://developer.nike.com/docs/projects/User%20order%20summary?tab=api \)](https://developer.nike.com/docs/projects/User%20order%20summary?tab=api) for a full list of fields returned in the response.

Step 2: List Order Details for a Member or Guest

Use the [Order Details API \(https://developer.nike.com/docs/projects/User%20order%20details?tab=api \)](https://developer.nike.com/docs/projects/User%20order%20details?tab=api) to get order details for a member or guest. This API returns a complete picture of an order including product detail, tax information and line item details. If you are looking for higher level order information, or you want information on more than one order for either a member or employee, see [List a Member's Orders](#).

TIP: The Order Details API does not return image URLs, but you can call the [Merchandised Product API \(https://developer.nike.com/nde-docs/doc/commerce/product/use-merch-product.html#product-image-set-by-style-color \)](https://developer.nike.com/nde-docs/doc/commerce/product/use-merch-product.html#product-image-set-by-style-color) using the style-color returned from the Order Details API to get a list of images for a styleColor and country.

The Order Details API requires that you pass certain headers in the request depending upon whether the consumer is a member, guest, or employee. For more information, see [Required Request Headers](#).

Required Request Parameters

For members and employees, the `orderNumber` path parameter is required. For validation

purposes for guest consumers, the `orderNumber` path parameter and email address filter parameter are required.

TIPS:

- To avoid a 404 response, the authentication header for a member request must match the member who created the order.
- For guests, the email address must match the shipTo email address on the order.

Customizing Your Results

You control what is returned in your result set through URL parameters. The Order Details API supports the `fields` query parameter to restrict the fields returned in the response. Since the Order Details API only returns one consumer order, the `anchor`, `sort`, and `count` query parameters are not supported. For more information on the `fields` query parameter syntax, see the [Query Parameters \(https://developer.niketech.com/nde-docs/doc/getting-started/using-nike-apis.html#query-parameters \)](https://developer.niketech.com/nde-docs/doc/getting-started/using-nike-apis.html#query-parameters) section of [Using Nike APIs \(https://developer.niketech.com/nde-docs/doc/getting-started/using-nike-apis.html \)](https://developer.niketech.com/nde-docs/doc/getting-started/using-nike-apis.html).

Filtering

The table below lists the fields by which you can filter your Order Detail results.

Table 4: Available Filters for Order Summary

Order Field Name	Description	Sample Value
<code>email</code>	Filter by customer email address	sample@gmail.com
<code>phoneNumber</code>	Filter by customer phone number. Only numbers 0-9 allowed	7134567890

Let's take a look at some [Order Details \(https://developer.niketech.com/docs/projects/User%20order%20details?tab=api \)](https://developer.niketech.com/docs/projects/User%20order%20details?tab=api) scenarios.

Table 5: Scenarios for Order Details

I want to	Sample Query
List the details for order ID C00011554850	<code>https://api.nike.com/order_mgmt/user_order_detail/v2/C00011554850</code>

I want to	Sample Query
for a member	
List the ID, status and shipping method fields for orderNumber C00011554850 for a guest	<code>https://api.nike.com/order_mgmt/user_order_details/v2/C00011554850?filter=email(my.email@address.com)&fields=id,status,orderLines.shippingMethod</code>

Executing the Request

Sample CURL for Order Details C00011554850 for a member/employee:

```
curl -X GET \
  https://api.nike.com/order_mgmt/user_order_detail/v2/C00011554850 \
  -H 'Authorization: Bearer eyJhbGciOiJSUzI1NiIsImtpZCI6IjcyYWI1NTlkLWwzMtNGVhYi05MTljLTJkYjA3YjFjN2NhMHNPZyJ9.eyJpYXQiOiJlMzQxOTMyOTcsImV4cCI6MTUzNDE5Njg5NywiaXNzIjoib2F1dGgyYWNjIiwianRpIjoiyY2IyOGE4OGItYWU4ZC00NWw1LWE2NjMtNDRkMmY0NWQwZDZjIiwibGF0IjoxNTM0MTkzMjk3LCJhdWQiOiJjb20ubmlrZS5kaWdpdGFsIiwic3ViIjoiyY29tLm5pa2UuY29tbWVYy2UubmlrZWRvdGNvbS53ZWl1LCJzYnQiOiJuaWtlOmFwcCI6WyJuaWtlLmRpZ2l0YWwiXSwicHJuaWtlMTYxODI2OTIwMTIiLCJwcnQiOiJuaWtlOnN3b29zaCJ9.Nt-Irlborb2gmz6e-CwUmvPlm80m5lEMHR18AEftE5qqVmlm-HbFHNPPA6AWj8gscQRs02ft_CQTKvHZa7EIVQ64RajD-sj0FTTaPBmXUsWqL1JtlfFv61cYmbrErOsEBcV_NWbgOVQ_NNF3aL9FCLiL2OgrVilpa7ManTL1OP_nmI_SaMN3USawECzKbYlOW58DaHBQjezkpeejyv4AQXm99HL1qWYb5fARnpubrwlcN7GyUepOwImfNf8xZZrcJKTx4HBXmYVFg8gMskoqzSEjJijfxYNxSy507Y4fUyRq2glISPMnrQnAF5NAw19SCQm8wZxKxPaxc590EhMLA'
```

Sample CURL for Order Details C00011554850 for a guest:

```
curl -X GET \
  'https://api.nike.com/order_mgmt/user_order_details/v2/C00011554850?filter=email%28my.email@address.com%29' \
  -H 'X-Nike-Visitorid: 2c83877b-10fa-44da-a92d-2451efef8671' \
  -H 'appid: com.nike.sport.running.ios' \
```

```
-H 'x-nike-visitid: 2'
```

Parsing the Response

The **Order Details** (<https://developer.nike.com/docs/projects/User%20order%20details?tab=api>) JSON response contains several fields relating to status. See **Understanding Order Status** for more detail about how status is determined, and the suggested order statuses to display in your experience. See the **Order Details API** (<https://developer.nike.com/docs/projects/User%20order%20details?tab=api>) for a full list of fields returned in the response.

Understanding Order Status

An order contains three types of statuses:

- order
- order line
- payment

An order line is a Nike service or product associated with a quantity, e.g. Nike Air VaporMax, quantity 1. Orders have at least one order line and may have several. Each order line has one or more statuses that map(s) to a numeric status code. Behind the scenes, the status of the order is calculated by evaluating which order line has a `rolledUpStatus` with the highest status code.

The table below describes each status associated with an order.

Table 6: Fields Relating to Order Status for Order Details/Summary

Status Field Name	Description	API
<code>status</code>	Status of the order. Matches the <code>orderLines.rolledUpStatus</code> with the highest status code on the order.	Order Summary Order Details
<code>orderLines.rolledUpStatus</code>	Status of an order line. Computed by “Partially” + <code>orderLines.maxOrderLineStatus</code> . e.g. “Partially Shipped”.	Order Summary Order Details
<code>orderLines.maxOrderLineStatus</code>	Status of the highest status code on this order line e.g	Order

ADDING ORDER HISTORY TO YOUR EXPERIENCE

Status Field Name	Description	API
	“Shipped”. Matches orderLines.rolledUpStatus. This status is included in orderLines.statuses.	Details
orderLines.minOrderLineStatus	Status of the lowest status code on this order line e.g. “Factory Delayed”. This status is included in orderLines.statuses.	Order Details
orderLines.statuses	An array of statuses for each status code on this order line. The description with the highest status code matches orderLines.maxOrderLineStatus. The description with the lowest status code matches orderLines.minOrderLineStatus.	Order Details
paymentStatus	Status of payment.	Order Summary

In the scenario illustrated by the Order Details response below, a consumer has purchased two order lines. One order line has shipped and has a `rolledUpStatus` of “Shipped”, and the other has been delayed at the factory and has a `rolledUpStatus` of “Factory Delayed”. Because the “Shipped” status has a higher status code than the “Factory Delayed” status code, the order status is “Partially Shipped”, calculated by “Partially” + the order line with the highest `rolledUpStatus` on the order.

```
{
  "status": "Partially Shipped",
  ...
  "orderLines": [
    {
      ...

      "statuses": [
        {
          "description": "Shipped",
          "quantity": 1,
          "date": "2018-01-30T12:16:51Z"
        }
      ],
      "rolledUpStatus": "Shipped",
    }
  ]
}
```

ADDING ORDER HISTORY TO YOUR EXPERIENCE

```
...
    "maxOrderLineStatus": "Shipped",
    ...
    "minOrderLineStatus": "Shipped",
    ...
},
{
    ...

    "statuses": [
        {
            "description": "Factory Delayed",
            "quantity": 1,
            "date": "2018-01-30T12:16:51Z"
        }
    ],
    "rolledUpStatus": "Factory Delayed",
    ...
    "maxOrderLineStatus": "Factory Delayed",
    ...
    "minOrderLineStatus": "Factory Delayed",
    ...
}
]
}
```

Let's look at a slightly more complex example. As illustrated by the Order Details response below, a consumer purchased three identical shorts. One short was delivered and has a status of "Delivered", another short was delivered and returned and has a status of "Return Processed", and one short was shipped and has a status of "Shipped". Because the "Delivered" status has the highest status code of the order line, the `rolledUpStatus` of the order line is "Delivered". The highest `rolledUpStatus` of the order is "Delivered", so the order status is "Partially Delivered".

```
{
  "status": "Partially Delivered",
  ...
  "orderLines": [
```

ADDING ORDER HISTORY TO YOUR EXPERIENCE

```
{
  ...

  "statuses": [
    {
      "description": "Delivered",
      "quantity": 1,
      "date": "2018-01-30T12:16:51Z"
    },
    {
      "description": "Shipped",
      "quantity": 1,
      "date": "2018-01-30T12:16:51Z"
    },
    {
      "description": "Return Processed",
      "quantity": 1,
      "date": "2018-01-30T12:16:51Z"
    }
  ],
  "rolledUpStatus": "Partially Delivered",
  ...
  "maxOrderLineStatus": "Partially Delivered",
  ...
  "minOrderLineStatus": "Shipped",
  ...
}
]
```

Listed below are the order line statuses, status codes, and simple status:

- **STATUS:** The order line status is returned by both the Order Summary and Order Details APIs.
- **STATUS CODE:** Behind the scenes, status code is used by both APIs to calculate status ranking. However, the status code is not returned by either the Order Summary or Order Details API.
- **SIMPLE STATUS:** The simple status is not returned by either the Order Summary or Order

ADDING ORDER HISTORY TO YOUR EXPERIENCE

Details API but is provided as a sample, consumer-friendly status. Your experience could perform a similar status-to-simple-status mapping to display status to the consumer.

Table 7: Matrix of Order Line Statuses, Status Codes, and Simple Statuses

STATUS	STATUS CODE * not returned by either API	SIMPLE STATUS * not returned by either API
Draft Order Created	1000	CREATED
Draft Order Reserved Awaiting Acceptance	1040	CREATED
Draft Order Reserved	1050	CREATED
Created or CREATED	1100	CREATED
Authorized	1100.01	CREATED
Not Authorized	1100.02	CREATED
Pending Completion	1100.03	CREATED
Origin Scan	1100.050	CREATED
In Transit	1100.100	CREATED
Acknowledged	1100.110	IN PROCESS
Work Order Cancelled	1100.1600	IN PROCESS
Factory Processing	1100.600	IN PROCESS
Factory Completed	1100.700	IN PROCESS
Factory Delayed	1100.800	IN PROCESS
Reserved Awaiting Acceptance	1140	IN PROCESS
Reserved	1200	IN PROCESS
Being Negotiated	1230	IN PROCESS
Accepted	1260	IN PROCESS
Rescheduling	1300	IN PROCESS
BOReview	1300	IN PROCESS
Unscheduled	1310	IN PROCESS
Scheduled	1500	IN PROCESS

ADDING ORDER HISTORY TO YOUR EXPERIENCE

STATUS	STATUS CODE * not returned by either API	SIMPLE STATUS * not returned by either API
Awaiting Chained Order Creation	1600	IN PROCESS
Awaiting Procurement Purchase Order Creation	2030	IN PROCESS
Awaiting Procurement Transfer Order Creation	2060	IN PROCESS
Chained Order Created	2100	IN PROCESS
PO Released	2100.100	IN PROCESS
Released For SO Create	2100.1000	IN PROCESS
DSV Acknowledged	2100.1100	IN PROCESS
Released To Third Party	2100.1200	IN PROCESS
Received By Partner	2100.1210	IN PROCESS
Confirmed By Partner	2100.1220	IN PROCESS
Order Processing	2100.1230	IN PROCESS
Order Delayed	2100.1250	IN PROCESS
PO Acknowledged	2100.200	IN PROCESS
Released To FC	2100.30	IN PROCESS
PO Sent To Warehouse	2100.300	IN PROCESS
PO Warehouse Acknowledged	2100.350	IN PROCESS
PO Scheduled For Pick	2100.40	IN PROCESS
Order Received	2100.400	IN PROCESS
PO Awaiting Shipment	2100.50	IN PROCESS
Order Processed	2100.500	IN PROCESS
DSV Acknowledged	2100.550	IN PROCESS
Factory Processing	2100.600	IN PROCESS
Sent For SO Create	2100.620	IN PROCESS

ADDING ORDER HISTORY TO YOUR EXPERIENCE

STATUS	STATUS CODE * not returned by either API	SIMPLE STATUS * not returned by either API
DSV Acknowledged	2100.650	IN PROCESS
Factory Completed	2100.700	IN PROCESS
Factory Delayed	2100.800	IN PROCESS
Procurement Purchase Order Created	2130	IN PROCESS
Procurement Purchase Order Shipped	2130.01	IN PROCESS
Work Order Created	2140	IN PROCESS
Work Order Completed	2141	IN PROCESS
Procurement Transfer Order Created	2160	IN PROCESS
Procurement Transfer Order Shipped	2160.01	IN PROCESS
Released	3200	IN PROCESS
Awaiting Shipment Consolidation	3200.01	IN PROCESS
Awaiting WMS Interface	3200.02	IN PROCESS
Published To WMS	3200.03	IN PROCESS
Acknowledged	3200.100	IN PROCESS
Sent To Warehouse	3200.1000	IN PROCESS
Released To Third Party	3200.1200	IN PROCESS
Received By Partner	3200.1210	IN PROCESS
Confirmed By Partner	3200.1220	IN PROCESS
Order Processing	3200.1230	IN PROCESS
Pending Release To SAP	3200.150	IN PROCESS
Scheduled For Pick	3200.200	IN PROCESS
Awaiting Shipment	3200.300	IN PROCESS
Order Received	3200.400	IN PROCESS
Order Processed	3200.500	IN PROCESS

ADDING ORDER HISTORY TO YOUR EXPERIENCE

STATUS	STATUS CODE * not returned by either API	SIMPLE STATUS * not returned by either API
Factory Processing	3200.600	IN PROCESS
Factory Completed	3200.700	IN PROCESS
DSV Acknowledged	3200.900	IN PROCESS
Sent To Node	3300	IN PROCESS
Included In Shipment	3350	IN PROCESS
Awaiting Invoice	3700.0101	IN PROCESS
Invoiced	3700.999	IN PROCESS
Held	8000	IN PROCESS
Carried	1100.7777	COMPLETE
Order Completed	2100.1240	COMPLETED
Order Completed	3200.1240	COMPLETED
Completed	3700.12	COMPLETED
Order Completed	3700.777710	COMPLETED
Order Completed	3700.7777.10	COMPLETED
Backordered From Node	1400	BACKORDER
Order Delayed	3200.1250	DELAYED
Factory Delayed	3200.800	DELAYED
Shipped	3700	SHIPPED
Origin Scan	3700.10	SHIPPED
Customs Cleared	3700.100	SHIPPED
Manifest Scan	3700.200	SHIPPED
In Transit	3700.30	SHIPPED
Delivered To Store	3700.105	DELIVERED
Notionally Delivered	3700.69	DELIVERED

ADDING ORDER HISTORY TO YOUR EXPERIENCE

STATUS	STATUS CODE * not returned by either API	SIMPLE STATUS * not returned by either API
Delivered	3700.70	DELIVERED
Order Delivered	3700.7777	DELIVERED
Ready For Pickup	3700.110	READY FOR PICKUP
Consumer Picked Up	3700.120	PICKED UP
Picked Up	3700.20	PICKED UP
Shipment Delayed	3700.130	SHIPMENT DELAYED
Shipment Delayed	8500	SHIPMENT DELAYED
Abandoned	3700.210	ABANDONED
Delivery Attempt 1	3700.40	DELIVERY ATTEMPT 1
Delivery Attempt 2	3700.50	DELIVERY ATTEMPT 2
Delivery Attempt 3	3700.60	DELIVERY ATTEMPT 3
Unable To Deliver	3700.80	UNABLE TO DELIVER
Refused Shipment	3700.90	REFUSED SHIPMENT
Pending Cancel	1300.9000	CANCEL IN PROCESS
Pending Cancel	3200.9000	CANCEL IN PROCESS
Cancelled	9000	CANCELLED
Void	9000.100	CANCELLED
Post Voided	9000.200	POST VOIDED
Delivered to Return Center	1100.200	RETURN CREATED
Early Refund	1100.300	RETURN CREATED
Return Created	3700.01	RETURN CREATED
Return Request Created	3700.011	RETURN CREATED
Return Received	3700.02	RETURN CREATED
Returned At Store	1100.400	RETURN COMPLETED

ADDING ORDER HISTORY TO YOUR EXPERIENCE

STATUS	STATUS CODE * not returned by either API	SIMPLE STATUS * not returned by either API
Returned At Store	3700.04	RETURN COMPLETED
Returned to DC	3700.85	RETURN COMPLETED
Returned To Carrier	3700.95	RETURN COMPLETED
Delivered to Return Center	1100.200100	RETURN IN PROCESS
Inspection Escalate	1100.500	RETURN IN PROCESS
Return In Progress	3700.03	RETURN IN PROCESS
Return Processed	3700.05	RETURN IN PROCESS
Return Invoiced	3950.01	RETURN IN PROCESS
Received at Return Center	3950.100	RETURN IN PROCESS
Inspection Passed	3950.200	RETURN IN PROCESS
Inspection Escalate	3950.300	RETURN IN PROCESS
Inspection Denied	3950.400	RETURN IN PROCESS
Inspected And Invoiced	3950.01.100	RETURN IN PROCESS
Return Denied	3700.06	RETURN DENIED
CSR Refund	3950.700	CSR REFUND
Inspected And Invoiced	3950.01100	RETURN PROCESSED
Exchange Order Created	3950.02.01	EXCHANGE CREATED
Awaiting Exchange Order Creation	3950.02	EXCHANGE IN PROCESS
CREATED		Created (Only for Reserve Orders)
UNRESERVED		UnReserved(Only for Reserve Orders)

API Quick Reference

Table 8: Order History Endpoints

Endpoint Name	Path	HTTP Method
Order Summary (https://developer.niketech.com/docs/projects/User%20order%20summary?tab=api)	/order_mgmt/ user_order_summary/v2	GET
Order Details (https://developer.niketech.com/docs/projects/User%20order%20details?tab=api)	/order_mgmt/ user_order_detail/ v2/{orderNumber}	GET

Best Practices

Listed below are some best practices for working with Order Summary and Order Details.

Conditions for Retries

For all Nike Cloud APIs, the general rule is that HTTP 4XX error codes (except for 429) should not be retried, but HTTP 5XX errors can be retried. For general information on Nike error retry practices, see [API Error Patterns \(https://confluence.nike.com/display/NEA/API+Standards#APIStandards-Errors \)](https://confluence.nike.com/display/NEA/API+Standards#APIStandards-Errors) on Confluence.

Testing

It is recommended to test all Order endpoints in the production environment as opposed to the test environment. Using the test environment can have unpredictable results, due to the many downstream dependencies required to provide ‘production-like’ responses.

Q: What are the boundaries for testing in production?

Performance tests at high volumes should **never** be done in production. All performance tests should be done in test.

Q: Is this service available in the test environment?

All services are available in the test environment, however, the data and services are not always

available for end-to-end testing.

Q: Why are our integration tests (that use the test environment) failing?

When integrating for the first time, we can help ensure basic connectivity in the test environment before you deploy to production. However, we do not recommend relying on connections to the test environment on an ongoing basis, and provide no guarantees on the availability or retention of the data.

Teams should not introduce breaking changes in their contracts, so **mocking downstream dependencies** is often recommended to decouple development & testing between teams.

TIP: Tools like [WireMock \(http://wiremock.org \)](http://wiremock.org) allow you to mock out services for integration testing, or to do dark deployments & traffic shadowing in Prod to validate new functionality.

Q: Why is an order not showing up in the test environment?

There are not as many system resources dedicated to the test environment, causing delays in asynchronous processing.

Production Support

Recommended steps:

1. Check if `Extn_Event_processor` table has records. If so, then clear the records before performing a fresh test. Note: all records going forward will go to order repo.
2. Run as many instances of `OrderDroptoS3AgentServer`

Sample Query:

```
select eep.* from DOM.extn_event_processor eep, dom.YFS_ORDER_HEADER yoh
where yoh.ORDER_NO='04073122561'
and eep.EXTN_DATA_KEY = yoh.ORDER_HEADER_KEY
and eep.extn_status = 'NEW';
```

Caching Data

None of the endpoints described in this document support caching.

Troubleshooting

Here are some troubleshooting tips:

- Use the general troubleshooting tips in the [Using Nike APIs \(https://developer.nike.com/nde-docs/doc/getting-started/using-nike-apis.html#troubleshooting \)](https://developer.nike.com/nde-docs/doc/getting-started/using-nike-apis.html#troubleshooting) guide.
- Use a Splunk query (requires access) to check for issues with your request.
- Contact the Orders team on the [#mp-athena \(https://nikedigital.slack.com/messages/C1H7ZM7J4 \)](https://nikedigital.slack.com/messages/C1H7ZM7J4) Slack channel for assistance.

Terms of Service

Following are the terms of service for the Order History APIs.

Authorization

Access Tokens

Most calls through the Nike API gateway (api.nike.com) require an access token be sent in the request header. This allows Nike to verify that your app is authorized to perform the action on behalf of the user.

Access tokens are obtained by calling Nike Unite services prior to calling the API which you ultimately want to reach.

To find out more on how to call Unite services to obtain access tokens, see the Authorization section of the [Using Nike APIs \(https://developer.nike.com/nde-docs/doc/getting-started/using-nike-apis.html#authorization \)](https://developer.nike.com/nde-docs/doc/getting-started/using-nike-apis.html#authorization) guide.

JSON Web Token

Neither the Order Summary nor Order Details endpoints require the additional authorization of a JSON Web Token (JWT). For more, see the JWT section of [Using Nike APIs \(https://developer.nike.com/nde-docs/doc/getting-started/using-nike-apis.html#jwt-json-web-token \)](https://developer.nike.com/nde-docs/doc/getting-started/using-nike-apis.html#jwt-json-web-token).

Sample Requests

Sample requests included throughout this guide contain unique IDs and access tokens that are spent/expired in the Production environment, so you will not be able to use them as-is for testing purposes. Reuse what you can and replace with valid IDs/access tokens when necessary.

User Types

The Order APIs support 3 distinct user types:

- Member: user has logged in with their Nike+ account credentials
- Guest: user has not logged in (anonymous user)
- Employee: user is an employee of Nike or a subsidiary and has logged in with swoosh.com credentials (also known as Swoosh user type)

Required Request Headers

Listed below are the required request headers based on user type. Since most Order Summary and Order Details requests come through the Nike Edge router, these header values will be set automatically, provided your app calls the Unite services first to get an access token and passes that token in the request.

Table 9: Required Order History Request Headers by User Type

Header Name	Description	Member	Guest * guest consumers are supported in the Order Details API only	Employee
Accept	Content type you will accept in response, application/json is only value allowed	X	X	X
Content-Type	Content type of the request, application/json is only value allowed	X	X	X
Authorization	Your access token in the format of <code>Bearer {token}</code> indicating the consumer is logged in	X	X	X
x-nike-visitorid	Unique identifier for the guest, validated by the Edge router and passed through to the		X	

ADDING ORDER HISTORY TO YOUR EXPERIENCE

Header Name	Description	Member	Guest * guest consumers are supported in the Order Details API only	Employee
	service. Applies only to Order Details API.			
x-nike-visitid	Integer identifying the guest's session. Applies only to Order Details API.		X	
appld	Application making the API request e.g. com.nike.sport.running.ios	X	X	X

TIP: For the Authorization header, use the token for the consumer's login session that you obtained from Nike Unite/Identity, prefixed by `Bearer` (note the single space after Bearer). This is necessary for Nike to verify that your app is authorized to perform the requested operation on behalf of the consumer.

See the User Types section of the [Using Nike APIs \(https://developer.niketech.com/nde-docs/doc/getting-started/using-nike-apis.html#user-types \)](https://developer.niketech.com/nde-docs/doc/getting-started/using-nike-apis.html#user-types) guide for more information.

Common Questions

Q: Is it okay to call Order APIs if my app is hosted in an Amazon Web Services VPC?

Yes. The APIs are exposed publicly, so it does not matter where you are calling from. If you are calling repeatedly from a small set of IP addresses, it might be possible that Nike's bot-mitigation tools could interfere with your ability to make calls. If you are having issues, reach out to Slack channel [#mp-athena \(https://nikedigital.slack.com/messages/C1H7ZM7J4 \)](https://nikedigital.slack.com/messages/C1H7ZM7J4) for help.

Q: How do I get my appld on the allowed list?

Reach out to @athena-integration-support in our [#mp-athena-integration-support](#) Slack channel to get help with adding your appld to the allowed list.

Q: What is the vip address for Order Details?

The vip address for Order Details is order_mgmt-order_detail-v2.

Q: Does Order Details purge any data?

Order Details does not purge data. This service has data from February 2012 onward.

Q: What are the major differences between the Order Details v1 and v2 schemas?

Order Details v2 responds with orders that match either the v1 or v2 (Source Aware) schema. To see the differences between the two payloads, please see [Analysis - Source Aware - Order Repo changes \(https://confluence.nike.com/pages/viewpage.action?spaceKey=CE&title=Analysis+-+Source+Aware+-+Order+Repo+changes \)](https://confluence.nike.com/pages/viewpage.action?spaceKey=CE&title=Analysis+-+Source+Aware+-+Order+Repo+changes)

Q: What is the difference between `channel` and `originApplication`?

Each `channel` value, e.g. `nike.digital.web`, is split into 3 different sections:

- Order creator (e.g. `nike`, `swoosh`, or partner name)
- Cross-channel details (e.g. `digital`)
- Platform (e.g. `web`)

The `originApplication` values are app IDs that describe where the order was placed, e.g. `com.nike.commerce.checkout.web` for Checkouts, or `com.tmall.web` for Tmall.

Q: Is `cancellableFlag` and `returnableFlag` dynamic?

Yes, these flags are dynamic. The value assigned to these flags are dictated by OrderReview.

Q: Could you explain how `orderlines.originalStoreReceiptInformation` will be used?

`originalStoreReceiptInformation` is populated when a consumer returns a product at store. It contains the details of the original order. If a store order is returned at a store, this segment will have the complete original store details (transaction no, register no, transaction date, etc.). If a digital order is returned at store, this segment will have the original order number.

Q: How do we identify order lines that have Nike By You (NBY) products?

To identify NBY products, check that `orderLine` contains a `customizedProductReference` with a value in it.

Q: How do I get invoice information?

Order Details has invoice identifiers in

`chargeTransactionDetails.invoiceCollectionDetails.invoiceNumber`. With this value, a call can be made to the [Order Invoice API \(https://developer.niketech.com/docs/](https://developer.niketech.com/docs/)

[projects/Order%20Invoice%20API?tab=api](#)).

Q: Where are promotions located, and are they removable after having been applied to the order line?

Promotions, if any, will be present in `orderLines.promotions` , and cannot be removed from an order line.

Q: What if there is a cancellation on an order line? Would the `orderLines.promotions` section be updated?

No, the promotion will still be applied, regardless of order status.

Q: When will `parentSalesOrderNumber` be populated?

`parentSalesOrderNumber` will be populated for the following scenarios:

- Return orders
- Global store orders and store orders
 - Store orders can also have return lines

Q: Is `customerProfileReference` the same as `upmid` ?

Yes.

Q: Is the time in UTC or local time?

All times in Order History will be in UTC Zulu with no offset, e.g. 2020-03-20T01:06:53Z.

Q: How do we decipher VAT and NON-VAT fields, and their respective tax amounts?

VAT (Inclusive tax)

- `object.headerTax` and `object.orderLines.lineTaxes`.
 - `effectiveTaxPercentage`
 - `effectiveTaxAmount`

Non-Vat (Exclusive tax)

- `object.headerTax` and `object.orderLines.lineTaxes`.
 - `taxPercentage`
 - `taxAmount`

Q: Does `totalAmount` include tax?

Yes, total amount includes tax.

Q: How do we identify different types of order? (BOPIS,PUPS,RESERVE, ShipToStore)

To identify an order a combination of the following attributes are required:

- orderVersion
- orderLines.fulfillmentMethod
- orderLines.shipTo.address.pickUpLocationType
- orderLines.shipTo.location.type
- orderLines.shipTo.address.pickUpLocationIdentifier

BOPIS:

- If the order payload matches the v1 schema
 - if orderVersion!=v2 and orderLines.fulfillmentMethod==PICKUP and orderLines.shipTo.address.pickUpLocationType==store_pickup and orderline.orderLineType==INLINE (In this case store address will be present in orderLines.shipTo.address)
- If the order payload matches the v2 schema
 - if orderVersion==v2 and orderLines.fulfillmentMethod==PICKUP and orderLines.shipTo.location.type==store/store_views (In this case you need to call store/store_views service with orderLines.shipTo.location.id to get the address) PUPS
- If the order payload matches the v1 schema
 - if orderVersion!=v2 and orderLines.shippingMethod:CPG and orderLines.fulfillmentMethod:SHIP and orderLines.shipTo.address.pickUpLocationIdentifier==null (In this case store address will be present in orderLines.shipTo.address)
- If the order payload matches the v2 schema
 - if orderVersion==v2 and orderLines.shippingMethod:CPG and orderLines.fulfillmentMethod:SHIP and orderLines.shipTo.location.type= ship/pickup_points (In this case you need to call store/store_views service with orderLines.shipTo.location.id to get the address) Reserve
- If the order payload matches the v1 schema
 - if orderVersion!=v2 and orderLines.fulfillmentMethod==RESERVE and orderLines.shipTo.address.pickUpLocationType==store_pickup and orderline.orderLineType==RESERVE (In this case store address will be present in orderLines.shipTo.address)
- If the order payload matches the v2 schema
 - if orderVersion==v2 and orderLines.fulfillmentMethod==RESERVE and orderLines.shipTo.location.type==store/store_views (In this case you need to call store/store_views service with orderLines.shipTo.location.id to get the address) ShipToStore

- ShipToStore orders has fulfillmentMethod=SHIP and also has shipToStoreNumber associated with them

Q: How do we identify different types of cancelled or voided orders?

Each `orderLine` can contain a `cancellationReason`, `lineNotes`, and a `storeOrderLineDetail` object. CancellationReason at the orderLine level express why the orderLine was cancelled. A `lineNotes` object will contain a `reasonCode` field. The `storeOrderLineDetail` will contain a `transactionType` with the value of VOID.

Q: How do we distinguish between pure B&M, mixed cart, and pure digital orders? (orderClassification)

Two key identifiers to understand the diversity of an order are OrderClassification and OrderLineType.

OrderClassification values describe the kind of order. See below for an incomplete list of orderClassifications.

Examples:

- STANDARD - Digitally fulfilled orders from APPS, Web, Partners
- STORE - Order created in a retail store - Point of Sale as well as Mobile point of sale
- CONV_STORE - An order paid by Konbini or Convenience store mode of payment
- CSORDER - Order created by consumer services from Internal L3 menu
- COD - Cash on Delivery order

Please see [List of Values included in the Order Classification Field \(https://confluence.nike.com/display/MOM/List+of+Values+included+in+the+Order+Classification+Field\)](https://confluence.nike.com/display/MOM/List+of+Values+included+in+the+Order+Classification+Field) for other order classifications:

The values in `orderLine.orderLineType` describe the type of `orderLine`. See below for an incomplete list of `orderLineType`.

Examples:

- INLINE - Order placed online.
- STORE - Order placed in store.

Please leverage the combination of `orderClassification` and `orderLineType`.

Q: What does `modificationDate` represent?

`modificationDate` represents not only when the order was modified but also when it was re-

indexed (for internal purposes).

Q: How do I obtain Estimated Delivery Date (EDD) info?

- If the order payload matches the v1 schema:
 - The EDD information can be obtained from `orderLines.estimateDeliveryDate` field.
- If the order payload matches the v2 schema:
 - The EDD information can be obtained from `orderLines.estimatedDelivery` object.

Q: What fields do I use to identify an order with a pickup location?

- If the order payload matches the v1 schema:
 - `orderLines.shipTo.address.pickUpLocationIdentifier`
 - `orderLines.shipTo.address.pickUpLocationType`
 - `orderLines.shipTo.address.pickUpLocation`
- If the order payload matches the v2 schema:
 - `orderLines.shipTo.address.pickUpLocationIdentifier`
 - `orderLines.shipTo.address.pickUpLocationType`

Q: What fields do I use to identify store transactions?

Store information is at the order level for both v1 and v2:

- `store.registerNumber`
- `store.storeNumber`
- `store.storeId`
- `store.transactionBeginDate`
- `store.transactionEndDate`
- `store.transactionNumber`
- `store.customerZipCode`
- `store.firstSalesPostingRequired`

TIP: `storeId` can also be used to call the [Store Views API \(https://developer.niketech.com/docs/projects/Store%20Views%20V2?tab=api\)](https://developer.niketech.com/docs/projects/Store%20Views%20V2?tab=api).

Q: How do we identify where the order was captured from (i.e. the origin of the order?)

- If the order payload matches the v1 schema:
 - Use `originApplication` field
- If the order payload matches the v2 schema:
 - Use `channel` field

Examples:

originApplication

- com.nike.commerce.checkout.web
- com.nike.commerce.snkrs.web
- com.nike.sport.running.ios

channel

- nike.digital.web
- nike.omega.web

Q: Why is `orderHeaderKey` optional?

In order to provide order details to consumers after an order is submitted, we publish the initial snapshot to the Order Details API while the order is published to DOMS. This snapshot will not have the `orderHeaderKey` because this value is populated by subsequent updates from DOMS. If the status of the snapshot is CREATED, the `orderHeaderKey` will be null, which is why this field is optional in the Order Details API.

Q: There is gift-card-related info in the response. Should I be concerned about data security?

Order Details does not expose sensitive gift card info to external clients, so security should not be a concern in that regard.

Q: Is there a way to search for orders using the consumer's gift card number?

No.

Q: How do we identify discounts on a header or line level? Do we have an `isDiscount Flag`?

The discounts at header level or line level can be identified using the corresponding `chargeCategory` at header/line level. Charge Category Discount details page provides all the possible ENUM values for the different charge categories, and whether each charge category is discounted or not.

Q: How do we correlate Nike sales order numbers to partner order numbers?

`marketplaceDetail` is an object at the order level which contains information regarding the integrator/partner order number.

Q: Can I use `parentReturnOrder` to link the original sales order to return order?

No, `parentReturnOrder` is only used for exchange orders. If you wish to link the original sales

order number to the return order number, you will have to leverage an Order Summary collection call.

Q: How do we link sales orders to return orders?

Each return order has a `parentSalesOrderNumber` that is a one-way link from the return order to sales order. If you want to acquire all return orders associated with a sales order, call Order Summary with a `parentSalesOrderNumber` as a filter.

Q: How do I obtain the total price of an order?

- `totalAmount`
- `orderTotalDetails.orderTotal`

Q: What events trigger the status of an order to be updated?

Order Management has series of life cycle events, and there are also modifications triggered by customers, CSP, and Track and Trace. See [Order Status Mapping for Consumers \(<https://confluence.nike.com/display/MOM/Order+Status+Mapping+for+Consumers> \)](https://confluence.nike.com/display/MOM/Order+Status+Mapping+for+Consumers) for more information regarding status.

Q: How do we identify employee purchases?

To identify orders placed by employees, the order must be created using their respective Swoosh profile.

- If the order payload matches the v1 schema:
 - The division field will have a value of 55
- If the order payload matches the v2 schema:
 - The division field will have a value of 55
 - `userInfo.userType` field will have the value of `nike:swoosh`.

Q: How do we identify a cancelled quantity on an order?

To identify a cancelled quantity, use the `orderLine.statuses.description` and `orderLine.statuses.quantity` fields. These fields will have the value of “Cancelled” and an integer, respectively.

Q: How do we decipher between exchange and return orders?

For returns orders the `orderType` would be equal to `RETURN_ORDER`. For exchange orders the `orderType` will be `SALES_ORDER`, and the `parentReturnOrder` will be populated.

Q: Do Apple and Nike products have the same return window?

No, Apple products must be returned within 14 days. Nike products have a standard return policy of 30 days, but that policy can fluctuate based on market strategies.

Q: Does Order Detail have Converse orders?

Yes, Order Detail has Converse orders, and they can be identified by checking the `appId` field for the value `converseus`.

Q: What are XPO orders?

XPO allows Nike to ship product(s) between its stores.

Q: How do can I identify EMEA fiscal fields?

Check whether `additionalAddress.addressType == FISCAL`, and whether the `fiscalInformation` object is present. Below is a list of EMEA fiscal fields in Order Details v2:

- ENUM: `FISCAL` to `additionalAddress.addressType`.
- `fiscalInformation`.
 - `customer`
 - `customerType`
 - `vatNumber`
 - `profession`
 - `customerNumber`
 - `lotteryNumber`
 - `invoice`
 - `invoiceType`
 - `invoiceNumber`
 - `sequenceNumber`

Contacting the Team

Need to contact the Orders team?

Slack	#mp-athena
Confluence Space	Order Management (https://confluence.nike.com/display/CE/Order+Management#OrderManagement-CSF
Team Contacts	Intake, new requirements, onboarding Betty Ashok Betty.Ashok@nike.com

ADDING ORDER HISTORY TO YOUR EXPERIENCE

	Krishnamurthy Ramakrishnan Krishnamurthy.Ramakrishnan@nike.com API or service-related issues Vishibha Anand Vishibha.Anand@nike.com
Intake	Please fill out an intake form (https://nike.sharepoint.com/teams/na23/CommerceEngines/Lists/MP%20Intake/NewForm.aspx?Source=https%3A%2F%2Fnike%2Esharepoint%2Ecom%2Fteams%2Fna23%2FCommerceEngines/Lists/MP%20Intake/NewForm.aspx) to initiate a requirement request. For more information, see the Marketplace Platform Intake Process (https://nike.sharepoint.com/teams/na23/CommerceEngines/Lists/MP%20Intake/NewForm.aspx?Source=https%3A%2F%2Fnike%2Esharepoint%2Ecom%2Fteams%2Fna23%2FCommerceEngines/Lists/MP%20Intake/NewForm.aspx)

Document Change Log

Summary	Date
Initial publish	10/25/2018
Updated for v2 of both endpoints, updated doc format	02/17/2021
Added Common Questions section & content	04/02/2021

Next Steps

You've learned how to add Order History to your experience. Here are some next steps.

- [Using Nike APIs](https://developer.niketech.com/nde-docs/doc/getting-started/using-nike-apis.html) (<https://developer.niketech.com/nde-docs/doc/getting-started/using-nike-apis.html>)
- [Glossary](https://developer.niketech.com/nde-docs/doc/commerce/reference/glossary.html) (<https://developer.niketech.com/nde-docs/doc/commerce/reference/glossary.html>)