



## Table of Contents

|                                           |                   |
|-------------------------------------------|-------------------|
| <a href="#">Introduction.....</a>         | <a href="#">2</a> |
| <a href="#">Address Validation .....</a>  | <a href="#">2</a> |
| <a href="#">Address Geocoding .....</a>   | <a href="#">2</a> |
| <a href="#">API Quick Reference .....</a> | <a href="#">3</a> |
| <a href="#">Contacting the Team .....</a> | <a href="#">3</a> |
| <a href="#">Document Change Log .....</a> | <a href="#">4</a> |
| <a href="#">Next Steps .....</a>          | <a href="#">4</a> |

# Adding Address Tools to Your Experience

Last Updated: 04/19/2021

Read this guide to learn how to use address tools in your experience.

## Introduction

Nike’s address tools provide valuable address management functionality.

- Use the **Address Validation** service before the consumer places their order to ensure their packages will be shipped to a deliverable address.
- Call the **Address Geocoding** service to turn an address into longitude and latitude coordinates in order to call other Nike APIs that require geocodes, such as [Fulfillment Offerings \( https://nde-devportal-docs.niketech.com/doc/commerce/checkout/use-fulfillment-offerings.html \)](https://nde-devportal-docs.niketech.com/doc/commerce/checkout/use-fulfillment-offerings.html).

## Address Validation

- ✔ **Ensure a shipping address is deliverable**
- ✔ **Ensure a billing address is valid**

Validate a consumer-supplied address with the [Validate Address \( https://developer.niketech.com/docs/projects/AddressValidator?tab=api \)](https://developer.niketech.com/docs/projects/AddressValidator?tab=api) service. This endpoint can validate any type of address such as shipping and billing addresses.

This service calls a third party vendor to validate the address passed in the request against an address database. The service response contains a `verificationCode`, `score`, and an address. Based on the quality of the address match, the service returns either the original address or a corrected one. See the table below to understand how the `verificationCode` and `score` work together to determine what actions the consumer needs to take next.

Table 1: Address Validator Verification Codes and Scores with Next Steps

| Verification Code                                                    | Score         | Consumer needs to                                                                                                                                                                                                          |
|----------------------------------------------------------------------|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>VERIFIED</b>                                                      | 95 or greater | Address provided by the consumer is verified and is returned in the response. No further action is required by the consumer.                                                                                               |
| <b>VERIFIED</b>                                                      | less than 95  | Address provided by the consumer is missing information and a recommended address is returned in the response. Consumer needs to review the recommended address and decide to accept it or retry with a different address. |
| <b>PARTIALLY_VERIFIED, UNVERIFIED, AMBIGUOUS, CONFLICT, REVERTED</b> | any           | Address provided by the consumer could not be verified and is returned in the response. Consumer needs to correct the address and retry.                                                                                   |

**TIP:** The third party address validation service has a 512 character limit restriction on each address field and a 1024 character limit for the entire address. The client should truncate characters in any address field exceeding the field limit or address limit before making the request.

See the [Address Validation Service \( https://confluence.nike.com/pages/viewpage.action?pageId=270586569 \)](https://confluence.nike.com/pages/viewpage.action?pageId=270586569) page for more information on request and response field mappings between the Address Validator API and the third party.

Listed below is a sample **Address Valdidate** POST request URI. This is a synchronous endpoint and is not JWT-protected:

https://api.nike.com/location/address\_validator/v1

## Address Geocoding

- ✔ **Turn an address into latitude and longitude coordinates**

Need to call an API that requires the consumer’s latitude and longitude location coordinates but you only have the consumer’s address? Call the **Get Geocodes from Address API** passing address information as query parameters.

## Get geographic coordinates from an address

The [Geocoding API \( https://developer.niketech.com/docs/projects/Geocoding?tab=api \)](https://developer.niketech.com/docs/projects/Geocoding?tab=api) allows you to exchange an address for latitude and longitude geo coordinates. This service is not JWT-protected.

Table 2: Request Query Parameters for the Get Geocodes from Address Endpoint

| Parameter Name | Description                                                                           | Required? | Example            |
|----------------|---------------------------------------------------------------------------------------|-----------|--------------------|
| country        | 2-alpha character ISO 3166 country code                                               | Required  | US                 |
| address1       | String                                                                                | Optional  | One Bowerman Drive |
| address2       | String                                                                                | Optional  | 1st Floor          |
| address3       | String                                                                                | Optional  | Suite 100          |
| city           | String                                                                                | Optional  | Beaverton          |
| state          | ISO 3166-2 subdivision code. 2-alpha character ISO 3166-2 state code for US addresses | Optional  | OR                 |
| county         | String. Holds regional data for non-US addresses                                      | Optional  | Washington         |
| postalCode     | String. Both 5 digit and 5 digit-4 digit formats are supported for US addresses       | Optional  | 97005              |

**Tip:** If address values contain spaces, enclose the value in quotes for example, filter=address1("1 Bowerman Drive").

Sample [Get Geocodes from Address \( https://developer.niketech.com/docs/projects/Geocoding?tab=api \)](https://developer.niketech.com/docs/projects/Geocoding?tab=api)  
cURL GET request:

```
curl -X GET "https://api.nike.com/buy/geocodes/v1?filter=country(US)&filter=address1("1 Bowerman Drive")&filter=city("Beaverton")&filter=state(OR)&filter=postalCode(97005)" -H "accept: application/json; charset=UTF-8"
```

A successful 200 response contains the country passed in the request, latitude, longitude and in some cases, geoDistance. geoDistance represents the accuracy radius in meters between the geocode coordinates and the physical location.

## API Quick Reference

### Address Validator

- [Validate Address \( https://developer.niketech.com/docs/projects/AddressValidator?tab=api \)](https://developer.niketech.com/docs/projects/AddressValidator?tab=api)

### Address Geocoding

- [Get Geocodes \(coordinates\) from Address \( https://developer.niketech.com/docs/projects/Geocoding?tab=api \)](https://developer.niketech.com/docs/projects/Geocoding?tab=api)

## Contacting the Team

|                  |                                                                                                                                                                                                                           |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Slack            | Address Verification: <a href="#">#cic-payment ( https://nikedigital.slack.com/archives/C0Z9P2E5Q )</a><br>Address Geocoding: <a href="#">#cic-order-integration ( https://nikedigital.slack.com/messages/C38BE20SV )</a> |
| Confluence Space | Address Verification: <a href="#">Payment ( https://confluence.nike.com/display/PHYLON/Payment+Team+Playbook )</a><br>Address Geocoding: <a href="#">Buy ( https://confluence.nike.com/display/BUY/Buy+Domain )</a>       |
| Team Contacts    | Address Verification: <a href="#">Sree Krishna</a><br>Address Geocoding: <a href="#">Saket Shrivastava</a>                                                                                                                |

# Document Change Log

| Summary         | Date       |
|-----------------|------------|
| Initial publish | 04/19/2021 |

## Next Steps

You’ve learned how to use address tools in your experience. Here are some related topics.

- [Wishlist \( https://nde-devportal-docs.niketech.com/doc/commerce/checkout/use-wishlists.html \)](https://nde-devportal-docs.niketech.com/doc/commerce/checkout/use-wishlists.html)
- [Checkout \( https://nde-devportal-docs.niketech.com/doc/commerce/checkout/use-checkout.html \)](https://nde-devportal-docs.niketech.com/doc/commerce/checkout/use-checkout.html)
- [Fulfillment Offerings \( https://nde-devportal-docs.niketech.com/doc/commerce/checkout/use-fulfillment-offerings.html \)](https://nde-devportal-docs.niketech.com/doc/commerce/checkout/use-fulfillment-offerings.html)
- [Payment \( https://nde-devportal-docs.niketech.com/doc/commerce/payment/use-payment.html \)](https://nde-devportal-docs.niketech.com/doc/commerce/payment/use-payment.html)
- [Using Nike APIs \( https://nde-devportal-docs.niketech.com/doc/getting-started/using-nike-apis.html \)](https://nde-devportal-docs.niketech.com/doc/getting-started/using-nike-apis.html)
- [Glossary \( https://nde-devportal-docs.niketech.com/doc/commerce/reference/glossary.html \)](https://nde-devportal-docs.niketech.com/doc/commerce/reference/glossary.html)
- [Supported Countries \( https://nde-devportal-docs.niketech.com/doc/commerce/reference/global.html \)](https://nde-devportal-docs.niketech.com/doc/commerce/reference/global.html)