



Table of Contents

Introduction.....	2
Wishlists.....	2
API Quick Reference	8
Troubleshooting	8
Contacting the Team	8
Document Change Log	9
Next Steps.....	9

Adding Wishlists to Your Experience

Last Updated: 04/28/2019

Help Nike members save their favorites for later purchase by adding **Wishlists** to your experience.

TIPS:

- Before using this guide, read **Using Nike APIs** (<https://nde-devportal-docs.niketech.com/doc/getting-started/using-nike-apis.html>) and **Cart & Checkout Overview** (<https://nde-devportal-docs.niketech.com/doc/commerce/checkout/overview-checkout.html>).
- Use this guide as a supplement to the API Reference for detailed use cases. See **API Quick Reference** for links to all the API Reference docs discussed here.

Introduction

Sometimes consumers want to set aside items or services to buy at a later date. They can do this by creating a wishlist.

How is a Wishlist different from a Cart?

Wishlists provide consumers a more flexible way of organizing their future purchases than the cart can. Here are some considerations:

- Consumers can have an unlimited number of wishlists but only one cart.
- Consumers can name their wishlists but not their cart.
- All Nike consumers can use cart but only Nike members and employees can use wishlists.

Wishlists

✓ Manage a Nike member's or an employee's wishlist of products and services

Step 1: Create a Wishlist

Execute a request to the **Create or Update a List** (<https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-operations-create-or-update-a-list-put>) endpoint to create an empty wishlist. **Step 2** explains how to add items to a wishlist.

- Wishlist `name` must be unique for a user/country combination.
- Consumers can create wishlists for multiple countries but they can have only one default wishlist per country.
- A wishlist can only be set as the country default when it is created. This flag cannot be changed after the wishlist is created.
- When a consumer's wishlist is created with the `isDefault` flag set to true, this flag is set to false on the rest of the wishlists for the same country.

- If the `id` path parameter does not match the `id` of the wishlist, a new wishlist is created.

TIP: You need to generate the unique **wishlist** `id` in UUID format and pass it as a path parameter.

Listed below is a sample **Create or Update a List** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-create-or-update-a-list-put>) PUT request URI that creates a new wishlist with `id` 93a333a2-907b-46f1-b9ac-469489909057. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/lists/v1/93a333a2-907b-46f1-b9ac-469489909057
```

Step 2: Modify a Wishlist

Now that you've created a wishlist for the consumer, allow them to add or remove items, delete the list, or rename it.

Add Item to List

To add a product or service to an existing wishlist, execute a request to the **Add Item to List** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-add-item-to-list-put>) endpoint.

- Current product pricing is provided in the response.
- If you add a product that is already on the list, the product will be replaced.
- Only the product being added is included in the response, not all products in the list.
- The **wishlist item** `country` will override the **wishlist** `country` when looking up prices.
- Because this endpoint can replace items, the response includes `isCurrentPriceChanged` set to true when an item's `currentPrice` has changed since creation.
- The response contains an `isAvailable` flag indicating whether or not the product is purchasable. This value is determined by the **Availability service** (<https://developer.nike.com/docs/projects/Availability?tab=api>).

TIP: You need to generate the unique **wishlist item** `id` in UUID format and pass it in the path parameter.

Listed below is a sample **Add Item to List** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-add-item-to-list-put>) PUT request URI that creates a new wishlist item with `id` 93a333a2-907b-46f1-b9ac-469489909123. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/list_items/v1/93a333a2-907b-46f1-b9ac-469489909123
```

Add Multiple Items to List

To add more than one item at a time to one or more wishlists, execute a request to the **Add Item to List** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-add-item-to-list-patch>) endpoint.

- You can add new items to the wishlist but not replace them.
- Current product pricing is provided in the response.

- The **wishlist item** `country` will override the **wishlist** `country` when looking up prices.
- You can add items to different wishlists in the same call by supplying different `wishlistIds` in each value object in the PATCH request body.
- Unless you supply filter query parameters to restrict the result set, all newly-added items are returned in the response.
- The response contains an `isAvailable` flag indicating whether or not the product is purchasable. This value is determined by the [Availability service \(https://developer.niketech.com/docs/projects/Availability?tab=api \)](https://developer.niketech.com/docs/projects/Availability?tab=api).

TIP: You need to generate each unique wishlist item `id` in UUID format and pass them in the PATCH request body.

Listed below is a sample [Add Item to List \(https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-add-item-to-list-patch \)](https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-add-item-to-list-patch) PATCH request limiting the response to include only the added items from wishlists with 93a333a2-907b-46f1-b9ac-469489909057 and 93a333a2-907b-46f1-b9ac-469489909000 IDs. This endpoint is not JWT-restricted.

```
http://api.nike.com/buy/list_items/
v1?filter=wishlistId(93a333a2-907b-46f1-b9ac-469489909057,93a333a2-907b-46f1-b9ac-46948990
9000)
```

Remove Item from List

To delete a single item from a list, execute a request to the [Remove Item from List \(https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-item-from-list-delete \)](https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-item-from-list-delete) endpoint passing the **wishlist item** `id` as a path parameter.

TIP: You do not need to send the `wishlistId` in the DELETE request. You only need to send the wishlist item `id` you want to delete in the path parameter.

Listed below is a sample [Remove Item from List \(https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-item-from-list-delete \)](https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-item-from-list-delete) DELETE request URI to delete wishlist item with `id` 93a333a2-907b-46f1-b9ac-469489909123. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/list_items/v1/93a333a2-907b-46f1-b9ac-469489909123
```

Remove Multiple Items from List

To delete several items from a wishlist, execute a request to the [Remove Items from List \(https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-items-from-list-delete \)](https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-items-from-list-delete) endpoint passing the list of **wishlist item** IDs as a filter query parameter.

TIP: You do not need to send the `wishlistId` in the DELETE request. You only need to send the **wishlist item** `id` you want to delete in the filter query parameter.

Listed below is a sample [Remove Items from List \(https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-items-from-list-delete \)](https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-items-from-list-delete)

Wishlist?tab=api#list-item-operations-remove-items-from-list-delete) DELETE request to delete wishlist items with `id` 93a333a2-907b-46f1-b9ac-469489909057 and 93a333a2-907b-46f1-b9ac-469489909000. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/list_items/
v1?filter=id(93a333a2-907b-46f1-b9ac-469489909057,93a333a2-907b-46f1-b9ac-469489909000)
```

Delete a List

To delete a wishlist, execute a request to the **Delete a List** (<https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-operations-delete-a-list-delete>) endpoint passing the **wishlist** `id` as a path parameter. Note that **all of the items on the list will be removed**.

Listed below is a sample **Delete a List** (<https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-operations-delete-a-list-delete>) DELETE request URI that deletes wishlist 93a333a2-907b-46f1-b9ac-469489909057 and all of its items. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/lists/v1/93a333a2-907b-46f1-b9ac-469489909057
```

Change the Name of the Wishlist

Make a request to the **Create or Update a List** (<https://developer.niketech.com/docs/projects/Buy%20Lists?tab=api#list-operations-create-or-update-a-list-put>) endpoint to update the name of an existing wishlist.

- Pass the same `country` and `brand` values used when the wishlist was created while also passing an updated wishlist name.
- name must be unique for a user/country combination.
- If the `id` path parameter does not match the `id` of the wishlist, a new wishlist will be created.

TIP: Pass the same wishlist `id` as the one used to create it in the path parameter.

Sample **Create or Update a List** (<https://developer.niketech.com/docs/projects/Buy%20Lists?tab=api#list-operations-create-or-update-a-list-put>) PUT request URI that updates the name of wishlist with `id` 93a333a2-907b-46f1-b9ac-469489909057. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/lists/v1/93a333a2-907b-46f1-b9ac-469489909057
```

Step 3: Get a Wishlist

Allow the consumer to view the **header info** of all their wishlists, or just one.

Retrieve Lists for Authenticated User

To retrieve **header info** for all wishlists for an authenticated consumer, execute a request to the **Retrieve Lists for Authenticated User** (<https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-operations->

retrieve-lists-for-authenticated-user-get) endpoint.

- The list items are **not** included in the response. To get the list items, execute a request to the **Retrieve Items by List** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-items-by-list-get>) endpoint with the appropriate list identifier.
- You can use filter and field query parameters to restrict the result set.

Listed below is a sample **Retrieve Lists for Authenticated User** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-lists-for-authenticated-user-get>) GET request URI that retrieves all of a consumer's wishlists for the US. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/lists/v1?filter=country(US)
```

Retrieve a List by ID

To retrieve **header info** for a single wishlist for an authenticated consumer, execute a request to the **Retrieve a List by ID** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-a-list-by-id-get>) endpoint passing the wishlist `id` as a path parameter.

Listed below is a sample **Retrieve a List by ID** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-a-list-by-id-get>) GET request URI for wishlist `id` 93a333a2-907b-46f1-b9ac-469489909057. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/lists/v1/93a333a2-907b-46f1-b9ac-469489909057
```

Step 4: Get a Wishlist Item

Retrieve one or more wishlist items from one or more of a consumer's wishlists.

Retrieve Items in a List by ID

To retrieve the productIds and skuIds (if available) in a single wishlist, execute a request to the **Retrieve Items in a List by ID** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-the-items-in-a-list-by-id-get>) endpoint passing the wishlist `id` as a path parameter.

Listed below is a sample **Retrieve Items in a List by ID** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-the-items-in-a-list-by-id-get>) GET request URI. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/lists/v1/93a333a2-907b-46f1-b9ac-469489909057/items
```

Retrieve Items by List

To retrieve all or a filtered set of items from all of a consumer's wishlists, execute a request to the **Retrieve Items by List** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-items-by-list-get>) endpoint. The response contains detailed information for each wishlist item.

You can use filter, anchor, count, fields, and sort query parameters to restrict the result set.

Listed below is a sample **Retrieve Items by List** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-items-by-list-get>) GET request URI that returns all items in the wishlist with `id 3ebf8798-2c86-4e29-a67b-7435ebad62af`. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/list_items/
v1?filter=wishlistId(3ebf8798-2c86-4e29-a67b-7435ebad62af)
```

Retrieve Item by ID

To retrieve a single list item, execute a request to the **Retrieve Item by ID** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-item-by-id-get>) endpoint, passing the client generated wishlist item `id` as a URL parameter. The response contains detailed information for the wishlist item.

You can use the fields query parameter to restrict the result set.

Listed below is a sample **Retrieve Item by ID** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-item-by-id-get>) GET request URI. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/list_items/v1/93a333a2-907b-46f1-b9ac-469489909057
```

Step 5: Purchase from a Wishlist

Follow the steps below to allow consumers to purchase items from their wishlist:

1. Call **Retrieve Lists for Authenticated User** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-lists-for-authenticated-user-get>) to get the wishlist ID or call **Retrieve a List by ID** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-a-list-by-id-get>) if you already know the wishlist ID.
2. Call **Retrieve Items by List** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-items-by-list-get>) to get the wishitem ID or call **Retrieve Item by ID** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-item-by-id-get>) if you already know the wishlist item ID.
3. Using the wishlist data from **Step 1** and the wishlist item data from **Step 2**, call **Create or Update a Cart** (<https://developer.nike.com/docs/projects/Carts%20V2?tab=api#cart-operations-create-or-update-a-cart-by-cart-id-put>) to add the wishlist item to Cart.
4. Using the wishlist item ID from **Step 2**, call **Remove Item from List** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-item-from-list-delete>).
5. (Optional) If there are no items left in the wishlist, call **Delete a List** (<https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-delete-a-list-delete>).

API Quick Reference

Wishlist endpoints

- **Create or Update a List** (<https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-operations-create-or-update-a-list-put>)
- **Delete a List** (<https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-operations-delete-a-list-delete>)
- **Retrieve a List by ID** (<https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-a-list-by-id-get>)
- **Retrieve Lists for Authenticated User** (<https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-lists-for-authenticated-user-get>)

Wishlist item endpoints

- **Add Item to List** (<https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-add-item-to-list-put>)
- **Add Item to List (PATCH)** (<https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-add-item-to-list-patch>)
- **Retrieve Items in a List by ID** (<https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-the-items-in-a-list-by-id-get>)
- **Retrieve Items by List** (<https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-items-by-list-get>)
- **Retrieve Item by ID** (<https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-item-by-id-get>)
- **Remove Item from List** (<https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-item-from-list-delete>)
- **Remove Items from List** (<https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-items-from-list-delete>)

Troubleshooting

Listed below are ways to troubleshoot unexpected responses using this API.

Use Troubleshooting Tools

- Use the general troubleshooting tips in the **Using Nike APIs** (<https://nde-devportal-docs.niketech.com/doc/getting-started/using-nike-apis.html#troubleshooting>) guide.
- Use a Splunk query (requires access) to check for issues with your request.
- Contact the Buy team on the **#cic-order-integration** (<https://nikedigital.slack.com/messages/C38BE20SV>) Slack channel for assistance.

Contacting the Team

Need to contact the team?

Slack	#cic-order-integration (https://nikedigital.slack.com/messages/C38BE20SV)
Confluence Space	CiC Order Capture (https://confluence.nike.com/pages/viewpage.action?pagelId=163654070)
Team Contacts	Dan Robertson, Saket Shrivastava

Document Change Log

Summary	Date	Description
Initial draft	06/20/2019	Initial Draft
Converted to stand-alone guide	03/20/2019	Content moved from Cart & Checkout use-case guide
Revised Next Steps section links	04/28/2020	Updated links

Next Steps

You've learned how to add wishlists to your experience. Here are some related topics.

- [Cart & Cart Review \(https://nde-devportal-docs.niketech.com/doc/commerce/checkout/use-carts.html \)](#)
- [Checkout \(https://nde-devportal-docs.niketech.com/doc/commerce/checkout/use-checkout.html \)](#)
- [Fulfillment Offerings \(https://nde-devportal-docs.niketech.com/doc/commerce/checkout/use-fulfillment-offerings.html \)](#)
- [Payment \(https://nde-devportal-docs.niketech.com/doc/commerce/payment/use-payment.html \)](#)
- [Using Nike APIs \(https://nde-devportal-docs.niketech.com/doc/getting-started/using-nike-apis.html \)](#)
- [Glossary \(https://nde-devportal-docs.niketech.com/doc/commerce/reference/glossary.html \)](#)
- [Supported Countries \(https://nde-devportal-docs.niketech.com/doc/commerce/reference/global.html \)](#)