



Table of Contents

Introduction.....	2
Wishlists.....	2
API Quick Reference	5
Troubleshooting	6
Contacting the Team.....	6
Document Change Log	6
Next Steps.....	6

Adding Wishlists to Your Experience

Last Updated: 04/28/2019

Help Nike members save their favorites for later purchase by adding [Wishlists](#) to your experience.

TIPS:

- Before using this guide, read [Using Nike APIs \(https://nde-devportal-docs.niketech.com/doc/getting-started/using-nike-apis.html \)](https://nde-devportal-docs.niketech.com/doc/getting-started/using-nike-apis.html) and [Cart & Checkout Overview \(https://nde-devportal-docs.niketech.com/doc/commerce/checkout/overview-checkout.html \)](https://nde-devportal-docs.niketech.com/doc/commerce/checkout/overview-checkout.html).
- Use this guide as a supplement to the API Reference for detailed use cases. See [API Quick Reference](#) for links to all the API Reference docs discussed here.

Introduction

Sometimes consumers want to set aside items or services to buy at a later date. They can do this by creating a wishlist.

How is a Wishlist different from a Cart?

Wishlists provide consumers a more flexible way of organizing their future purchases than the cart can. Here are some considerations:

- Consumers can have an unlimited number of wishlists but only one cart.
- Consumers can name their wishlists but not their cart.
- All Nike consumers can use cart but only Nike members and employees can use wishlists.

Wishlists

✔ **Manage a Nike member’s or an employee’s wishlist of products and services**

Step 1: Create a Wishlist

Execute a request to the [Create or Update a List \(https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-operations-create-or-update-a-list-put \)](https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-operations-create-or-update-a-list-put) endpoint to create an empty wishlist. [Step 2](#) explains how to add items to a wishlist.

- Wishlist name must be unique for a user/country combination.
- Consumers can create wishlists for multiple countries but they can have only one default wishlist per country.
- A wishlist can only be set as the country default when it is created. This flag cannot be changed after the wishlist is created.
- When a consumer’s wishlist is created with the isDefault flag set to true, this flag is set to false on the rest of the wishlists for the same country.
- If the id path parameter does not match the id of the wishlist, a new wishlist is created.

TIP: You need to generate the unique **wishlist** id in UUID format and pass it as a path parameter.

Listed below is a sample [Create or Update a List \(https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-operations-create-or-update-a-list-put \)](https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-operations-create-or-update-a-list-put) PUT request URI that creates a new wishlist with id 93a333a2-907b-46f1-b9ac-469489909057. This endpoint is not JWT-restricted.

`https://api.nike.com/buy/lists/v1/93a333a2-907b-46f1-b9ac-469489909057`

Step 2: Modify a Wishlist

Now that you’ve created a wishlist for the consumer, allow them to add or remove items, delete the list, or rename it.

Add Item to List

To add a product or service to an existing wishlist, execute a request to the [Add Item to List \(https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-add-item-to-list-put \)](https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-add-item-to-list-put) endpoint.

- Current product pricing is provided in the response.
- If you add a product that is already on the list, the product will be replaced.
- Only the product being added is included in the response, not all products in the list.
- The **wishlist item** country will override the **wishlist** country when looking up prices.
- Because this endpoint can replace items, the response includes isCurrentPriceChanged set to true when an item’s currentPrice has changed since creation.
- The response contains an isAvailable flag indicating whether or not the product is purchasable. This value is determined

by the [Availability service \(https://developer.nike.com/docs/projects/Availability?tab=api \)](https://developer.nike.com/docs/projects/Availability?tab=api).

TIP: You need to generate the unique **wishlist item** id in UUID format and pass it in the path parameter.

Listed below is a sample [Add Item to List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-add-item-to-list-put \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-add-item-to-list-put) PUT request URI that creates a new wishlist item with id 93a333a2-907b-46f1-b9ac-469489909123. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/list_items/v1/93a333a2-907b-46f1-b9ac-469489909123
```

Add Multiple Items to List

To add more than one item at a time to one or more wishlists, execute a request to the [Add Item to List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-add-item-to-list-patch \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-add-item-to-list-patch) endpoint.

- You can add new items to the wishlist but not replace them.
- Current product pricing is provided in the response.
- The **wishlist item** country will override the **wishlist** country when looking up prices.
- You can add items to different wishlists in the same call by supplying different wishlistIds in each value object in the PATCH request body.
- Unless you supply filter query parameters to restrict the result set, all newly-added items are returned in the response.
- The response contains an `isAvailable` flag indicating whether or not the product is purchasable. This value is determined by the [Availability service \(https://developer.nike.com/docs/projects/Availability?tab=api \)](https://developer.nike.com/docs/projects/Availability?tab=api).

TIP: You need to generate each unique wishlist item id in UUID format and pass them in the PATCH request body.

Listed below is a sample [Add Item to List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-add-item-to-list-patch \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-add-item-to-list-patch) PATCH request limiting the response to include only the added items from wishlists with 93a333a2-907b-46f1-b9ac-469489909057 and 93a333a2-907b-46f1-b9ac-469489909000 IDs. This endpoint is not JWT-restricted.

```
http://api.nike.com/buy/list_items/
v1?filter=wishlistId(93a333a2-907b-46f1-b9ac-469489909057,93a333a2-907b-46f1-b9ac-469489909000)
```

Remove Item from List

To delete a single item from a list, execute a request to the [Remove Item from List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-item-from-list-delete \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-item-from-list-delete) endpoint passing the **wishlist item** id as a path parameter.

TIP: You do not need to send the `wishlistId` in the DELETE request. You only need to send the wishlist item id you want to delete in the path parameter.

Listed below is a sample [Remove Item from List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-item-from-list-delete \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-item-from-list-delete) DELETE request URI to delete wishlist item with id 93a333a2-907b-46f1-b9ac-469489909123. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/list_items/v1/93a333a2-907b-46f1-b9ac-469489909123
```

Remove Multiple Items from List

To delete several items from a wishlist, execute a request to the [Remove Items from List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-items-from-list-delete \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-items-from-list-delete) endpoint passing the list of **wishlist item** IDs as a filter query parameter.

TIP: You do not need to send the `wishlistId` in the DELETE request. You only need to send the **wishlist item** id you want to delete in the filter query parameter.

Listed below is a sample [Remove Items from List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-items-from-list-delete \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-items-from-list-delete) DELETE request to delete wishlist items with id 93a333a2-907b-46f1-b9ac-469489909057 and 93a333a2-907b-46f1-b9ac-469489909000. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/list_items/
v1?filter=id(93a333a2-907b-46f1-b9ac-469489909057,93a333a2-907b-46f1-b9ac-469489909000)
```

Delete a List

To delete a wishlist, execute a request to the [Delete a List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-delete-a-list-delete \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-delete-a-list-delete) endpoint passing the **wishlist** id as a path parameter. Note that **all of the items on the list will be removed**.

Listed below is a sample [Delete a List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-delete-a-list-delete \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-delete-a-list-delete) DELETE request URI that deletes wishlist 93a333a2-907b-46f1-b9ac-469489909057 and all of its items. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/lists/v1/93a333a2-907b-46f1-b9ac-469489909057
```

Change the Name of the Wishlist

Make a request to the [Create or Update a List \(https://developer.nike.com/docs/projects/Buy%20Lists?tab=api#list-operations-create-or-update-a-list-put \)](https://developer.nike.com/docs/projects/Buy%20Lists?tab=api#list-operations-create-or-update-a-list-put) endpoint to update the name of an existing wishlist.

- Pass the same country and brand values used when the wishlist was created while also passing an updated wishlist name.
- name must be unique for a user/country combination.
- If the id path parameter does not match the id of the wishlist, a new wishlist will be created.

TIP: Pass the same wishlist id as the one used to create it in the path parameter.

Sample [Create or Update a List \(https://developer.nike.com/docs/projects/Buy%20Lists?tab=api#list-operations-create-or-update-a-list-put \)](https://developer.nike.com/docs/projects/Buy%20Lists?tab=api#list-operations-create-or-update-a-list-put) PUT request URI that updates the name of wishlist with id 93a333a2-907b-46f1-b9ac-469489909057. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/lists/v1/93a333a2-907b-46f1-b9ac-469489909057
```

Step 3: Get a Wishlist

Allow the consumer to view the **header info** of all their wishlists, or just one.

Retrieve Lists for Authenticated User

To retrieve **header info** for all wishlists for an authenticated consumer, execute a request to the [Retrieve Lists for Authenticated User \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-lists-for-authenticated-user-get \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-lists-for-authenticated-user-get) endpoint.

- The list items are **not** included in the response. To get the list items, execute a request to the [Retrieve Items by List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-items-by-list-get \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-items-by-list-get) endpoint with the appropriate list identifier.
- You can use filter and field query parameters to restrict the result set.

Listed below is a sample [Retrieve Lists for Authenticated User \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-lists-for-authenticated-user-get \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-lists-for-authenticated-user-get) GET request URI that retrieves all of a consumer's wishlists for the US. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/lists/v1?filter=country(US)
```

Retrieve a List by ID

To retrieve **header info** for a single wishlist for an authenticated consumer, execute a request to the [Retrieve a List by ID \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-a-list-by-id-get \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-a-list-by-id-get) endpoint passing the wishlist id as a path parameter.

Listed below is a sample [Retrieve a List by ID \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-a-list-by-id-get \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-a-list-by-id-get) GET request URI for wishlist id 93a333a2-907b-46f1-b9ac-469489909057. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/lists/v1/93a333a2-907b-46f1-b9ac-469489909057
```

Step 4: Get a Wishlist Item

Retrieve one or more wishlist items from one or more of a consumer's wishlists.

Retrieve Items in a List by ID

To retrieve the productIds and skulds (if available) in a single wishlist, execute a request to the [Retrieve Items in a List by ID \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-the-items-in-a-list-by-id-get \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-the-items-in-a-list-by-id-get) endpoint passing the wishlist id as a path parameter.

Listed below is a sample [Retrieve Items in a List by ID \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-the-items-in-a-list-by-id-get \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-the-items-in-a-list-by-id-get) GET request URI. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/lists/v1/93a333a2-907b-46f1-b9ac-469489909057/items
```

Retrieve Items by List

To retrieve all or a filtered set of items from all of a consumer's wishlists, execute a request to the [Retrieve Items by List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-items-by-list-get \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-items-by-list-get) endpoint. The response contains detailed information for each wishlist item.

You can use filter, anchor, count, fields, and sort query parameters to restrict the result set.

Listed below is a sample [Retrieve Items by List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-items-by-list-get \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-items-by-list-get) GET request URI that returns all items in the wishlist with id 3ebf8798-2c86-4e29-a67b-7435ebad62af. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/list_items/v1?filter=wishlistId(3ebf8798-2c86-4e29-a67b-7435ebad62af)
```

Retrieve Item by ID

To retrieve a single list item, execute a request to the [Retrieve Item by ID \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-item-by-id-get \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-item-by-id-get) endpoint, passing the client generated wishlist item id as a URL parameter. The response contains detailed information for the wishlist item.

You can use the fields query parameter to restrict the result set.

Listed below is a sample [Retrieve Item by ID \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-item-by-id-get \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-item-by-id-get) GET request URI. This endpoint is not JWT-restricted.

```
https://api.nike.com/buy/list_items/v1/93a333a2-907b-46f1-b9ac-469489909057
```

Step 5: Purchase from a Wishlist

Follow the steps below to allow consumers to purchase items from their wishlist:

1. Call [Retrieve Lists for Authenticated User \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-lists-for-authenticated-user-get \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-lists-for-authenticated-user-get) to get the wishlist ID or call [Retrieve a List by ID \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-a-list-by-id-get \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-a-list-by-id-get) if you already know the wishlist ID.
2. Call [Retrieve Items by List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-items-by-list-get \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-items-by-list-get) to get the wishitem ID or call [Retrieve Item by ID \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-item-by-id-get \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-item-by-id-get) if you already know the wishlist item ID.
3. Using the wishlist data from **Step 1** and the wishlist item data from **Step 2**, call [Create or Update a Cart \(https://developer.nike.com/docs/projects/Carts%20V2?tab=api#cart-operations-create-or-update-a-cart-by-cart-id-put \)](https://developer.nike.com/docs/projects/Carts%20V2?tab=api#cart-operations-create-or-update-a-cart-by-cart-id-put) to add the wishlist item to Cart.
4. Using the wishlist item ID from **Step 2**, call [Remove Item from List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-item-from-list-delete \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-item-from-list-delete).
5. (Optional) If there are no items left in the wishlist, call [Delete a List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-delete-a-list-delete \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-delete-a-list-delete).

API Quick Reference

Wishlist endpoints

- [Create or Update a List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-create-or-update-a-list-put \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-create-or-update-a-list-put)
- [Delete a List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-delete-a-list-delete \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-delete-a-list-delete)
- [Retrieve a List by ID \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-a-list-by-id-get \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-a-list-by-id-get)
- [Retrieve Lists for Authenticated User \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-lists-for-authenticated-user-get \)](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-lists-for-authenticated-user-get)

Wishlist item endpoints

- [Add Item to List \(https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-add-](https://developer.nike.com/docs/projects/Wishlist?tab=api#list-item-operations-add-)

- [item-to-list-put \)](#)
- [Add Item to List \(PATCH\) \(https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-add-item-to-list-patch \)](https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-add-item-to-list-patch)
- [Retrieve Items in a List by ID \(https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-the-items-in-a-list-by-id-get \)](https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-operations-retrieve-the-items-in-a-list-by-id-get)
- [Retrieve Items by List \(https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-items-by-list-get \)](https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-items-by-list-get)
- [Retrieve Item by ID \(https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-item-by-id-get \)](https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-retrieve-item-by-id-get)
- [Remove Item from List \(https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-item-from-list-delete \)](https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-item-from-list-delete)
- [Remove Items from List \(https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-items-from-list-delete \)](https://developer.niketech.com/docs/projects/Wishlist?tab=api#list-item-operations-remove-items-from-list-delete)

Troubleshooting

Listed below are ways to troubleshoot unexpected responses using this API.

Use Troubleshooting Tools

- Use the general troubleshooting tips in the [Using Nike APIs \(https://nde-devportal-docs.niketech.com/doc/getting-started/using-nike-apis.html#troubleshooting \)](https://nde-devportal-docs.niketech.com/doc/getting-started/using-nike-apis.html#troubleshooting) guide.
- Use a Splunk query (requires access) to check for issues with your request.
- Contact the Buy team on the [#cic-order-integration \(https://nikedigital.slack.com/messages/C38BE20SV \)](https://nikedigital.slack.com/messages/C38BE20SV) Slack channel for assistance.

Contacting the Team

Need to contact the team?

Slack	#cic-order-integration (https://nikedigital.slack.com/messages/C38BE20SV)
Confluence Space	CiC Order Capture (https://confluence.nike.com/pages/viewpage.action?pageId=163654070)
Team Contacts	Dan Robertson , Saket Shrivastava

Document Change Log

Summary	Date	Description
Initial draft	06/20/2019	Initial Draft
Converted to stand-alone guide	03/20/2019	Content moved from Cart & Checkout use-case guide
Revised Next Steps section links	04/28/2020	Updated links

Next Steps

You’ve learned how to add wishlists to your experience. Here are some related topics.

- [Cart & Cart Review \(https://nde-devportal-docs.niketech.com/doc/commerce/checkout/use-carts.html \)](https://nde-devportal-docs.niketech.com/doc/commerce/checkout/use-carts.html)
- [Checkout \(https://nde-devportal-docs.niketech.com/doc/commerce/checkout/use-checkout.html \)](https://nde-devportal-docs.niketech.com/doc/commerce/checkout/use-checkout.html)
- [Fulfillment Offerings \(https://nde-devportal-docs.niketech.com/doc/commerce/checkout/use-fulfillment-offerings.html \)](https://nde-devportal-docs.niketech.com/doc/commerce/checkout/use-fulfillment-offerings.html)
- [Payment \(https://nde-devportal-docs.niketech.com/doc/commerce/payment/use-payment.html \)](https://nde-devportal-docs.niketech.com/doc/commerce/payment/use-payment.html)
- [Using Nike APIs \(https://nde-devportal-docs.niketech.com/doc/getting-started/using-nike-apis.html \)](https://nde-devportal-docs.niketech.com/doc/getting-started/using-nike-apis.html)
- [Glossary \(https://nde-devportal-docs.niketech.com/doc/commerce/reference/glossary.html \)](https://nde-devportal-docs.niketech.com/doc/commerce/reference/glossary.html)
- [Supported Countries \(https://nde-devportal-docs.niketech.com/doc/commerce/reference/global.html \)](https://nde-devportal-docs.niketech.com/doc/commerce/reference/global.html)