



ADDING ORDER HISTORY TO YOUR EXPERIENCE

Last Updated: 10/5/2018

Overview

Retrieve a complete order history for your consumers.

TIP: Before using this guide you should have already completed [Adding Checkout to Your Experience](#).

Adding order history to your app is a two-step process.

- 1 Your application makes an API request to [retrieve all or a filtered list of a consumer's orders](#).
- 2 Using information from an order returned in the order summary response, your application makes a second API request to [get detailed information for one consumer order](#).

What is an Order?

A Nike order consists of the following:

- Consumer's purchased items/services
- Consumer's payment method(s) and billing address(es)
- Consumer's shipping method(s) and shipping address(es)
- Pricing
- Taxes
- Discounts

[Insert diagram of high-level steps in the process]

Providing consumers a way to access their past orders enables them to check the progress of product shipment and to view their product and payment history, no phone call required.

Step 1: List a consumer's orders

Use the order summary API to get all of a consumer's Nike orders. You could make this information accessible to the consumer as a self-service in your app. The information returned for each order is a limited set of data. If you need more detailed information about a consumer's order, see [List the details of a consumer's order](#).

The order summary API requires that you pass certain headers in the request depending upon whether the consumer is logged in, is a guest or an employee. For more information, see [Required Request Headers](#).

Customizing Your Results

Filtering

Sorting

You can sort the consumer's orders in several ways using the `sort` query parameter.

Understanding Order Status

Step 2: List the details of a consumer's order

[Overview Description]

The order details API requires that you pass certain headers in the request depending upon whether the consumer is logged in, a guest or an employee. For more information, see [Required Request Headers](#).

required path parameter order id

https://api.nike.com/order_mgmt/user_order_details/v1/

C00000554850?filter=email(jane.moore@nike.com) if email is missing, get 404

API Endpoint Quick Reference

Order Summary [Get a list of a consumer's orders](#)

Order Details [Get the details of a consumer's order](#)

Sending Your First Request

For your first request, send a request to the *User Order Summary* endpoint of the BFF Order Summary V1 API to list a consumer's orders.

1. Gather Info for the Request

Our example endpoint *User Order Summary*, only supports the HTTP GET method. To list orders, send a GET request with (at minimum) the required request headers.

Assume that consumer for whom you are getting a list of orders for is a Nike+ member who has logged in with their Nike+ credentials. This indicates which request headers are required.

For the request headers, the following considerations apply (at minimum):

1. Always send `application/json` in both the **Accept** and **Content-Type** headers.
2. Send the user's access token as obtained from Unite services in the **Authorization** header.

```
Accept: application/json
Content-Type: application/json
Authorization: Bearer {your access token}
```

2. Create the URL

The [API.md](#) states that the required URL format is `/order_mgmt/user_order_summary/v1/`.

To build the full URL, prepend `https://api.nike.com` to the above path.

The complete URL is then `https://api.nike.com/order_mgmt/user_order_summary/v1/`.

3. Execute the request

Execute the request with a cURL command. Using the values gathered in steps 1 and 2, the final cURL command is:



4. Parse the Response

Assuming no errors, you will receive a response body similar to the following:



Best Practices

Conditions for Retries

For all Order APIs, the general rule is that HTTP 4XX error codes (except for 429) should not be retried but HTTP 5XX errors can be retried. For general information on Nike error retry practices, see [API Error Patterns](#) on Confluence.

Honor the ETAs for Best Performance

For async endpoints that return an ETA, i.e. the estimated time for the job to be completed, it is important for your app to honor the ETA for best performance. For example, if the ETA is 2000ms, your app should wait 2000ms to start polling the /jobs endpoint to avoid consuming network and other resources unnecessarily.

Test Scenarios

Test Environment

It is recommended to test all Order endpoints in the production environment as opposed to the test environment. Using the test environment can have unpredictable results due to the many downstream services which these endpoints are reliant upon in order to provide typical ‘production-like’ responses.

There are boundaries for testing in production:

- Performance tests at high volumes should never be done in production.

Caching Data

None of the endpoints described in this document support caching.

Error Handling:

Troubleshooting

Terms of Service

It is recommended that you send a caller ID header in every request to this API to help troubleshoot unexpected responses. See the Registration section of the [Using NDe APIs](#) guide on how to create and register your caller ID.

Authorization

Access Tokens

Most calls through the Nike API gateway (api.nike.com) require an access token be sent in the request header. This allows Nike to verify that your app is authorized to perform the action on behalf of the user.

Access tokens are obtained by calling Nike Unite services prior to calling the API which you ultimately want to reach.

To find out more on how to call Unite services to obtain access tokens, see the Authorization section of the [Using NDe APIs](#) guide.

JSON Web Token

Neither the *BFF Order Summary* nor *BFF Order Details* endpoints require the additional authorization of a JSON Web Token (JWT). For more, see the JWT section of [Using NDe APIs](#).

Listed below are ways to troubleshoot unexpected responses using this API.

Sample Requests

The sample requests included throughout this guide often contain unique IDs and access tokens that are spent/expired in the Production environment, so you will not be able to copy and use them as-is for testing purposes. However, since other values in the request may still be valid and thus reusable, it may be convenient for you to copy the samples and change only the spent/expired values.

User Types

The Nike Order APIs support 3 distinct user types:

- Member: user has logged in with their Nike+ account credentials
- Guest: user has not logged in (anonymous user)

- Employee: user is an employee of Nike or a subsidiary and has logged in with swoosh.com credentials (also known as Swoosh user type)

Depending on user type, certain aspects of the calls that you make to the Order APIs might need to be modified. This will be called out whenever applicable in the detailed endpoint sections which follow in this guide. Also, consider that not all user types might apply to your app (e.g. you might only support Members).

See the User Types section of the [Using NDe APIs](#) guide for more information.

Use Troubleshooting Tools

- Use the general troubleshooting tips in the [Using NDe APIs](#) guide.
- Use a Splunk query (requires access) to check for issues with your request.
- Contact the Buy team on the [#cic-order-integration](#) Slack channel for assistance.

Common Questions

Is it okay to call Order APIs if my app is hosted in an Amazon Web Services VPC?

Yes. The APIs are exposed publicly so it does not matter where you are calling from. If you are calling repeatedly from a small set of IP addresses, it might be possible that Nike's bot-mitigation tools could interfere with your ability to make calls. If you are having issues, reach out to us for help.

Request Headers

Edge Router

Required request headers:

Header Name	Description	Member	Guest	Employee
Accept	Content type you will accept in response,	X	X	X

Header Name	Description	Member	Guest	Employee
	application/json is only value allowed			
Content-Type	Content type of the request, application/json is only value allowed	X	X	X
Authorization	Your access token in the format of Bearer {token} indicating the consumer is logged in	X		X
x-nike-visitorid	Unique identifier for the guest, validated by the Edge router and passed through to the service		X	
x-nike-visitid	Integer identifying the guest's		X	

Header Name	Description	Member	Guest	Employee
	session			
appld	Application making the API request e.g. com.nike.sport.running ios		X	

TIP: For the Authorization header, use the token for the user's login session that you obtained from Nike Unite/Identity, prefixed by ****Bearer **** (note the single space after Bearer). This is necessary for Nike to verify that you are authorized to perform the requested operation on behalf of the user.

Glossary

See the [Glossary](#)

Document Change Log

Summary	Date	Description
Initial draft 10/5/2018	Initial Draft	

Related Links

[NDe Documentation Home](#)