

# CIRCUIT BREAKER BEST PRACTICES



## Table of Contents

|                                    |    |
|------------------------------------|----|
| Service Call Best Practices .....  | 2  |
| Buy Service .....                  | 3  |
| Availability .....                 | 6  |
| Launch Service .....               | 7  |
| Merchandised Product Service ..... | 7  |
| Payment Service.....               | 10 |
| Product Feeds Service.....         | 14 |
| Related Links .....                | 16 |

# Circuit Breaker Best Practices

Last Updated: 02/04/2020

---

This guide discusses best practices for calling Nike services in peak traffic periods such as during a product launch. High-heat launches put an intense load on services and system resources. The goal of this document is to outline best practices to avoid putting further stress on system health from clients. In addition to the general recommendations listed in the [Service Call Best Practices](#) section, specific performance, retry and fallback best practices are listed by service.

## Service Call Best Practices

Many factors can affect microservice performance and availability such as heavy network traffic and instance and database under scaling. Eureka instability also contributes to the problem by leaving services unable to know where to send requests. While these factors are not in the control of the service caller, there are actions that callers should take to help ensure system health.

### Use the Circuit Breaker Pattern

Use the [Circuit Breaker Pattern \( https://martinfowler.com/bliki/CircuitBreaker.html \)](https://martinfowler.com/bliki/CircuitBreaker.html) when calling other services (either internal or external) to avoid waiting indefinitely for a response from a non-responsive service and to provide fallback behavior for a service failure. [Hystrix \( https://github.com/Netflix/Hystrix \)](https://github.com/Netflix/Hystrix) and [FastBreak \( https://github.com/Nike-Inc/fastbreak \)](https://github.com/Nike-Inc/fastbreak) are examples of Circuit Breaker libraries currently used by Nike microservices.

### Use the Exponential Backoff Retry Pattern

Unless otherwise noted, callers should follow the [Exponential Backoff Retry Pattern \( https://dzone.com/articles/understanding-retry-pattern-with-exponential-back \)](https://dzone.com/articles/understanding-retry-pattern-with-exponential-back) to determine how long to wait in between retries without modifying the request when the service returns a 429 or 5xx error. To use this pattern, a backoff increment value is used to calculate the wait time between retries. Wait time is calculated by wait time + backoff increment. For example, when the backoff increment is 100ms, the first four retry wait times are listed below.

- 1st retry: 100ms
- 2nd retry: 200ms
- 3rd retry: 400ms
- 4th retry: 800ms

### Use Jitter

Clients should consider using [Jitter \( https://aws.amazon.com/blogs/architecture/exponential-backoff-and-jitter/ \)](https://aws.amazon.com/blogs/architecture/exponential-backoff-and-jitter/) to more randomly distribute retry calls to decrease load on the service.

Visit [API Error Patterns \( https://confluence.nike.com/display/DAHP/API+-+Error+Patterns#API-ErrorPatterns-RetrylogicbasedonHTTPstatuscode \)](https://confluence.nike.com/display/DAHP/API+-+Error+Patterns#API-ErrorPatterns-RetrylogicbasedonHTTPstatuscode) for more information on retry recommendations.

## Use Distributed Tracing

Many of Nike's microservices make calls to other services, quickly fanning out processing control. This complexity can make it difficult to troubleshoot bottlenecks and debug problems. Distributed tracing can help this situation by stepping through the round trip of a request and illuminating problems. [Wingtips \( https://github.com/Nike-Inc/wingtips \)](https://github.com/Nike-Inc/wingtips) is the recommended distributed tracing tool.

## Be Aware of Bot Rules

Bot rules are in place that block calls to these APIs by IP and upmid for a period of time when more than 300 calls per minute come through the public and edge routers. Service-to-service calls are not affected by these limits. For more information visit [Bot Monitoring and Mitigation \( https://confluence.nike.com/pages/viewpage.action?pagelId=154879250 \)](https://confluence.nike.com/pages/viewpage.action?pagelId=154879250).

## Buy Service

Listed below are the best practices for calling each Buy service.

- [Carts](#)
- [Cart Reviews](#)
- [Shipping Options](#)
- [Checkout Preview](#)
- [Checkout Preview Job](#)
- [Checkout Submit](#)
- [Checkout Submit Job](#)
- [Launch Checkout Submit](#)

## Carts

**Endpoint:** `/buy/carts/v2/`

Table 1: Circuit Breaker Best Practices for Carts

| Topic              | Best Practice                                                                                                                                                                       |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Validation</b>  | Pass in all Checkout items and a valid two-digit ISO country. When updating an existing cart, ensure the request brand, channel and region matches the saved cart.                  |
| <b>Performance</b> | Multiple Checkout items may slow down the response because Carts validates each one. Regardless, always pass in all Checkout items.<br>When updating the cart, use the PATCH method |

| Topic                                    | Best Practice                                                                                                                                                                                                         |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                          | instead of PUT for best performance.                                                                                                                                                                                  |
| <b>Circuit breaker trigger</b>           | Carts repeated call failure to the Merchandised Product, Merchandised Skus, Availability, Value-added service, Merchandised Price, Product Content and Exclusive Access services for validation can open the circuit. |
| <b>Circuit breaker fallback behavior</b> | None                                                                                                                                                                                                                  |
| <b>Retry pattern for API callers</b>     | None                                                                                                                                                                                                                  |
| <b>Fallback behavior for API callers</b> | None                                                                                                                                                                                                                  |

## Cart Reviews

**Endpoint:** /buy/cart\_reviews/v1/

Table 2: Circuit Breaker Best Practices for Cart Reviews

| Topic                                    | Best Practice                                                                                                                     |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| <b>Retry pattern for API callers</b>     | 429 and 5xx error responses can be retried up to 6 times. Use the Exponential Backoff Retry Pattern, waiting 100ms between calls. |
| <b>Fallback behavior for API callers</b> | When the retry limit has been reached, callers can skip and proceed processing since Cart Reviews is not required for checkout.   |

## Shipping Options

**Endpoint:** /buy/shipping\_options/v2

Table 3: Circuit Breaker Best Practices for Shipping Options

| Topic                                    | Best Practice                                                                                                                     |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| <b>Retry pattern for API callers</b>     | 429 and 5xx error responses can be retried up to 6 times. Use the Exponential Backoff Retry Pattern, waiting 100ms between calls. |
| <b>Fallback behavior for API callers</b> | None                                                                                                                              |

## Checkout Preview

**Endpoint:** /buy/checkout\_previews/v2

Table 4: Circuit Breaker Best Practices for Checkout Previews

| Topic                                    | Best Practice                                                                                                                               |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Retry pattern for API callers</b>     | 429 and 5xx error responses can be retried up to 6 times. Use the Exponential Backoff Retry Pattern, waiting 100ms between calls.           |
| <b>Fallback behavior for API callers</b> | When the retry limit has been reached, callers can skip and proceed to Checkout Submit since Checkout Preview is not required for checkout. |

## Checkout Preview Job

**Endpoint:** /buy/checkout\_previews/v2/jobs/

Table 5: Circuit Breaker Best Practices for Checkout Preview Job

| Topic                                    | Best Practice                                                                                                                               |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Retry pattern for API callers</b>     | 404, 429 and 5xx error responses can be retried up to 6 times. Use the Exponential Backoff Retry Pattern, waiting 100ms between calls.      |
| <b>Fallback behavior for API callers</b> | When the retry limit has been reached, callers can skip and proceed to Checkout Submit since Checkout Preview is not required for checkout. |

## Checkout Submit

**Endpoint:** /buy/checkouts/v2/

Table 6: Circuit Breaker Best Practices for Checkout Submit

| Topic                                    | Best Practice                                                                                                                     |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| <b>Retry pattern for API callers</b>     | 429 and 5xx error responses can be retried up to 6 times. Use the Exponential Backoff Retry Pattern, waiting 100ms between calls. |
| <b>Fallback behavior for API callers</b> | None                                                                                                                              |

## Checkout Submit Job

**Endpoint:** /buy/checkouts/v2/jobs/

Table 7: Circuit Breaker Best Practices for Checkout Submit Job

| Topic                                    | Best Practice                                                                                                                          |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>Retry pattern for API callers</b>     | 404, 429 and 5xx error responses can be retried up to 6 times. Use the Exponential Backoff Retry Pattern, waiting 100ms between calls. |
| <b>Fallback behavior for API callers</b> | None                                                                                                                                   |

## Launch Checkout Submit

**Endpoint:** /buy/launch\_checkouts/v2/

Table 8: Circuit Breaker Best Practices for Launch Checkout Submit

| Topic                                    | Best Practice                                                                                                                     |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| <b>Retry pattern for API callers</b>     | 429 and 5xx error responses can be retried up to 6 times. Use the Exponential Backoff Retry Pattern, waiting 100ms between calls. |
| <b>Fallback behavior for API callers</b> | None                                                                                                                              |

## Availability

Listed below are the best practices for calling each Availability service.

- [Product Inventory Availability](#)
- [SKU Availability](#)

## Product Availability

**Endpoint:** /deliver/available\_products/v1/

Table 9: Circuit Breaker Best Practices for Product Availability

| Topic                                    | Best Practice                                                                                           |
|------------------------------------------|---------------------------------------------------------------------------------------------------------|
| <b>Performance</b>                       | When calling the <code>Product Availability List</code> endpoint, send 5 productids in batch at a time. |
| <b>Circuit breaker trigger</b>           | Product Availability's repeated call failure to the Merchandised Product service                        |
| <b>Circuit breaker fallback behavior</b> | None                                                                                                    |
| <b>Retry pattern for API callers</b>     | Use the Exponential Backoff Retry Pattern, waiting 100ms between calls. The caller should determine the |

| Topic                                    | Best Practice                                |
|------------------------------------------|----------------------------------------------|
|                                          | retry limit.                                 |
| <b>Fallback behavior for API callers</b> | Caller should default availability to false. |

## SKU Availability

**Endpoint:** /deliver/available\_skus/v1/

Table 10: Circuit Breaker Best Practices for SKU Availability

| Topic                                    | Best Practice                                                                                                               |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| <b>Performance</b>                       | When calling the <code>Get SKU Availability Multi</code> endpoint, send up to 25 skuids or 5 productids in batch at a time. |
| <b>Circuit breaker trigger</b>           | Available SKUs' repeated call failure to the Merchandised Product service or Merchandised SKU service                       |
| <b>Circuit breaker fallback behavior</b> | None                                                                                                                        |
| <b>Retry pattern for API callers</b>     | Use the Exponential Backoff Retry Pattern, waiting 100ms between calls. The caller should determine the retry limit.        |
| <b>Fallback behavior for API callers</b> | Caller should default availability to false.                                                                                |

## Launch Service

Coming soon

## Merchandised Product Service

Listed below are the best practices for calling each Merchandised Product service.

- [Merchandised Product Caching](#)
- [Merchandised Product](#)
- [Merchandised Product SKUs](#)
- [Merchandised Product Prices](#)
- [Product Content](#)
- [Merchandised Value-added Services](#)

## Merchandised Product Caching

Because product and SKU information does not change frequently, service-to-service calls made to the

Merchandised Product service should use distributed caching. Pre-loading of the cache prior to launch is recommended so no consumer has a degraded shopping experience while the service loads the data into its cache. During launch, retrieve the merchandised product data from cache if available rather than calling the service.

Experiences calling the Merchandised Product services directly should not cache these endpoints. Rather, if the Cache-Control header is set, the browser will cache product data for that time period.

## Merchandised Product

**Endpoint:** /merch/products/v2/

Table 11: Circuit Breaker Best Practices for Merchandised Product

| Topic                                    | Best Practice                                                                                                                                                                                                                                                                                                                      |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Performance</b>                       | <p>If you have one product UUID, call the <code>Merchandised Product by ID</code> endpoint.</p> <p>If you have a list of product UUIDs, call the <code>Merchandised Product List</code> endpoint with the <code>id</code> filter to list the products in batch.</p> <p>When filtering by id, request 25 ids or less at a time.</p> |
| <b>Retry pattern for API callers</b>     | Use the Exponential Backoff Retry Pattern. The caller should determine the wait time between calls and retry limit.                                                                                                                                                                                                                |
| <b>Fallback behavior for API callers</b> | None                                                                                                                                                                                                                                                                                                                               |

## Merchandised Product SKUs

**Endpoint:** /merch/skus/v2/

Table 12: Circuit Breaker Best Practices for Merchandised Product SKUs

| Topic                                | Best Practice                                                                                                                                                                                                                                                                                                              |
|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Performance</b>                   | <p>If have one SKU UUID, call the <code>Merchandised Product SKU by ID</code> endpoint.</p> <p>If you have a list of SKU UUIDs, call the <code>Merchandised Product SKU List</code> endpoint with the <code>id</code> filter to list the SKUs in batch.</p> <p>When filtering by id, request 25 ids or less at a time.</p> |
| <b>Retry pattern for API callers</b> | Use the Exponential Backoff Retry Pattern. The caller should determine the wait time between calls and retry limit.                                                                                                                                                                                                        |



| Topic                                    | Best Practice |
|------------------------------------------|---------------|
| <b>Fallback behavior for API callers</b> | None          |

## Merchandised Product Prices

**Endpoint:** /merch/prices/v2/

Table 13: Circuit Breaker Best Practices for Merchandised Product Prices

| Topic                                    | Best Practice                                                                                                                                                                                                                                                                                                                              |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Performance</b>                       | <p>If you have one price UUID, call the <code>Merchandised Product Prices by ID</code> endpoint.</p> <p>If you have a list of price UUIDs, call the <code>Merchandised Product Prices List</code> endpoint with the <code>id</code> filter to list the prices in batch.</p> <p>When filtering by id, request 25 ids or less at a time.</p> |
| <b>Retry pattern for API callers</b>     | Use the Exponential Backoff Retry Pattern. The caller should determine the wait time between calls and retry limit.                                                                                                                                                                                                                        |
| <b>Fallback behavior for API callers</b> | None                                                                                                                                                                                                                                                                                                                                       |

## Product Content

**Endpoint:** /merch/contents/v1/

Table 14: Circuit Breaker Best Practices for Product Content

| Topic                                    | Best Practice                                                                                                                                                                                                                               |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Performance</b>                       | <p>If you need the content or images for only one product, call a single product endpoint with the <code>style-color</code>.</p> <p>When calling a multiple product endpoint, request 25 style-colors or less in the request at a time.</p> |
| <b>Retry pattern for API callers</b>     | Use the Exponential Backoff Retry Pattern. The caller should determine the wait time between calls and retry limit.                                                                                                                         |
| <b>Fallback behavior for API callers</b> | None                                                                                                                                                                                                                                        |

## Merchandised Value-Added Services

**Endpoint:** /merch/value\_added\_services/v1/

Table 15: Circuit Breaker Best Practices for Merchandised Value-Added Services

| Topic                                    | Best Practice                                                                                                                                                                                                                          |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Performance</b>                       | <p>If you have one product UUID, call the Merchandised Value Added Services by ID endpoint.</p> <p>When calling the Merchandised Value Added Services List endpoint filtering by ID, send 25 IDs or less in the request at a time.</p> |
| <b>Retry pattern for API callers</b>     | Use the Exponential Backoff Retry Pattern. The caller should determine the wait time between calls and retry limit.                                                                                                                    |
| <b>Fallback behavior for API callers</b> | None                                                                                                                                                                                                                                   |

## Payment Service

Listed below are the best practices for calling each Payment service.

- [Payment Options](#)
- [Payment Stored Payments](#)
- [Payment Preview](#)
- [Payment Approval](#)
- [Payment Credit Card Submit](#)
- [Payment Apple Pay](#)
- [Payment Wallet](#)
- [Payment Deferred Payment](#)

## Payment Options

**Endpoints:** /payment/options/v2/, /payment/validate\_payments/v2/

Table 16: Circuit Breaker Best Practices for Payment Options

| Topic                          | Best Practice                                                                                                                                                |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Validation</b>              | Pass in all Checkout items when available.                                                                                                                   |
| <b>Performance</b>             | <p>Multiple Checkout items may slow down the response because Payment Options validates each one. Regardless, pass in all Checkout items when available.</p> |
| <b>Circuit breaker trigger</b> | Payment Option's repeated call failure to the Merchandised Product Service for Checkout item validation.                                                     |

| Topic                                    | Best Practice                                                                                                                        |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| <b>Circuit breaker fallback behavior</b> | Payment Options assumes the Checkout item product type is <b>inline</b> for validation purposes and continues processing.            |
| <b>Retry pattern for API callers</b>     | 429 responses can be retried twice. Wait the amount of time sent in the Retry-After header between calls.                            |
| <b>Fallback behavior for API callers</b> | When a caller reaches the retry limit, it can default to a non-stored credit card as a payment option in all countries except China. |

## Payment Stored Payments

**Endpoint:** /consumer/storedpayments/

Table 17: Circuit Breaker Best Practices for Payment Stored Payments

| Topic                                    | Best Practice                                                                                                                                                                                                                                                                                                  |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Validation</b>                        | When available, always pass in the shipping address to the <code>FETCH SAVED PAYMENTS FOR A UP MID</code> endpoint to determine if the consumer must validate the stored credit card's CVV before submitting the order.                                                                                        |
| <b>Performance</b>                       | When gift card balance is not needed, set the <code>includeBalance</code> flag to false so the stored gift card balance is not retrieved when gathering the consumer's stored payments.                                                                                                                        |
| <b>Circuit breaker triggers</b>          | Payment Stored Payments' repeated call failure to the Payment Gift Card service when saving a Gift Card or retrieving the balance<br>Payment PayPal service when saving a new PayPal payment type to the consumer's profile<br>Payment Cybersource service trying to store or update a consumer's credit card. |
| <b>Circuit breaker fallback behavior</b> | None                                                                                                                                                                                                                                                                                                           |
| <b>Retry pattern for API callers</b>     | 429 responses can be retried twice. Wait the amount of time sent in the Retry-After header between calls.                                                                                                                                                                                                      |
| <b>Fallback behavior for API callers</b> | None                                                                                                                                                                                                                                                                                                           |

## Payment Preview

**Endpoint:** /payment/preview/v2

Table 18: Circuit Breaker Best Practices for Payment Preview

| Topic                                    | Best Practice                                                                                                                                                                                                                                                                                                                                          |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Performance</b>                       | When a consumer selects to pay by stored credit card, check the validateCVV flag on the response from the Stored Payments Service. If the value is true, allow the consumer to verify their CVV number in your experience and send it to the Payment Credit Card Submit service. Otherwise, Payment Preview will fail due to an unverified CVV number. |
| <b>Circuit breaker trigger</b>           | Payment Preview's repeated call failure to the Payment Gift Card service when retrieving the balance<br>Stored Payment service when retrieving the consumer's stored payment details<br>Credit Card Submit service when validating the credit card info id                                                                                             |
| <b>Circuit breaker fallback behavior</b> | None                                                                                                                                                                                                                                                                                                                                                   |
| <b>Retry pattern for API callers</b>     | 429 responses can be retried twice. Wait the amount of time sent in the Retry-After header between calls.                                                                                                                                                                                                                                              |
| <b>Fallback behavior for API callers</b> | None                                                                                                                                                                                                                                                                                                                                                   |

## Payment Approval

**Endpoint:** /payment/approval/v2/

Table 19: Circuit Breaker Best Practices for Payment Approval

| Topic                                    | Best Practice                                                                                                                                                               |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Circuit breaker trigger</b>           | Payment Approval calls several Cloud service endpoints, many of which call third party systems. Repeated call failure to any of these services triggers the circuit breaker |
| <b>Circuit breaker fallback behavior</b> | Payment Approval marks the fraud decision as "unknown" so fraud scoring is retried downstream.                                                                              |

| Topic                                    | Best Practice                                                                                             |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| <b>Retry pattern for API callers</b>     | 429 responses can be retried twice. Wait the amount of time sent in the Retry-After header between calls. |
| <b>Fallback behavior for API callers</b> | None                                                                                                      |

## Payment Credit Card Submit

**Endpoint:** /services/, /creditcardsubmit/

Table 20: Circuit Breaker Best Practices for Payment Credit Card Submit

| Topic                                    | Best Practice                                                                                                                                          |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Performance</b>                       | If the consumer is not required to supply credit card information or cvv, do not call a Credit Card Submit endpoint that loads the credit card iFrame. |
| <b>Retry pattern for API callers</b>     | 429 responses can be retried twice. Wait the amount of time sent in the Retry-After header between calls.                                              |
| <b>Fallback behavior for API callers</b> | None                                                                                                                                                   |

## Payment Apple Pay

**Endpoint:** /payment/applepay\_sessions/v2/

Table 21: Circuit Breaker Best Practices for Payment Apple Pay

| Topic                                    | Best Practice                                                                                             |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| <b>Circuit breaker trigger</b>           | Payment Apple Pay's repeated call failure to the Apple gateway to start the ApplePay web session          |
| <b>Circuit breaker fallback behavior</b> | None                                                                                                      |
| <b>Retry pattern for API callers</b>     | 429 responses can be retried twice. Wait the amount of time sent in the Retry-After header between calls. |
| <b>Fallback behavior for API callers</b> | None                                                                                                      |

## Payment Wallet

**Endpoint:** /payment/paypal\_details/, /payment/paypal\_express/v1/, /payment/paypal\_mark/v1/

Table 22: Circuit Breaker Best Practices for Payment Wallet

| Topic                                    | Best Practice                                                                                                                                                              |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Circuit breaker trigger</b>           | Payment Wallet calls other Cloud service endpoints, some of which call third party systems. Repeated call failure to these external services triggers the circuit breaker. |
| <b>Circuit breaker fallback behavior</b> | None                                                                                                                                                                       |
| <b>Retry pattern for API callers</b>     | 429 responses can be retried twice. Wait the amount of time sent in the Retry-After header between calls.                                                                  |
| <b>Fallback behavior for API callers</b> | None                                                                                                                                                                       |

## Payment Deferred Payment

**Endpoint:** /payment/deferred\_wechat\_payments/v1/, /payment/deferred\_payment\_forms/v1/, /payment/deferred\_payment\_status/v1/

Table 23: Circuit Breaker Best Practices for Payment Deferred Payment

| Topic                                    | Best Practice                                                                                                                                                                        |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Circuit breaker trigger</b>           | Payment Deferred Payment calls other Cloud service endpoints, many of which call third party systems. Repeated call failure to these external services triggers the circuit breaker. |
| <b>Circuit breaker fallback behavior</b> | None                                                                                                                                                                                 |
| <b>Retry pattern for API callers</b>     | 429 responses can be retried twice. Wait the amount of time sent in the Retry-After header between calls.                                                                            |
| <b>Fallback behavior for API callers</b> | None                                                                                                                                                                                 |

## Product Feeds Service

Listed below are the best practices for calling each Product Feeds Service.

- [Product Feed V2](#)
- [Product Feed Rollups V2](#)
- [Product Feed Exclusive Threads V2](#)

### Product Feed V2

**Endpoint:** /product\_feed/threads/v2

Table 24: Circuit Breaker Best Practices for Product Feed

| Topic                                    | Best Practice                                                                                                       |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| <b>Circuit breaker trigger</b>           | None                                                                                                                |
| <b>Circuit breaker fallback behavior</b> | None                                                                                                                |
| <b>Retry pattern for API callers</b>     | Use the Exponential Backoff Retry Pattern. The caller should determine the wait time between calls and retry limit. |
| <b>Fallback behavior for API callers</b> | None                                                                                                                |

## Product Feed Rollups V2

**Endpoint:** /product\_feed/rollup\_threads/v2

Table 25: Circuit Breaker Best Practices for Product Feed Rollups

| Topic                                    | Best Practice                                                                                                       |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| <b>Circuit breaker trigger</b>           | Product Feed Rollups calls Smart Search. Repeated call failure to this service triggers the circuit breaker.        |
| <b>Circuit breaker fallback behavior</b> | None                                                                                                                |
| <b>Retry pattern for API callers</b>     | Use the Exponential Backoff Retry Pattern. The caller should determine the wait time between calls and retry limit. |
| <b>Fallback behavior for API callers</b> | None                                                                                                                |

## Product Feed Exclusive Threads V2

**Endpoint:** /product\_feed/exclusive\_threads/v2

Table 26: Circuit Breaker Best Practices for Product Feed Exclusive Threads

| Topic                                    | Best Practice                                                                                                       |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| <b>Circuit breaker trigger</b>           | None                                                                                                                |
| <b>Circuit breaker fallback behavior</b> | None                                                                                                                |
| <b>Retry pattern for API callers</b>     | Use the Exponential Backoff Retry Pattern. The caller should determine the wait time between calls and retry limit. |
| <b>Fallback behavior for API callers</b> | None                                                                                                                |

## Related Links

- [Using Nike APIs \( https://nde-devportal-docs.niketech.com/doc/getting-started/using-nike-apis.html \)](https://nde-devportal-docs.niketech.com/doc/getting-started/using-nike-apis.html)
- [Glossary \( https://nde-devportal-docs.niketech.com/doc/commerce/reference/glossary.html \)](https://nde-devportal-docs.niketech.com/doc/commerce/reference/glossary.html)