



Customization Builder Reference

(DRAFT)

Table of Contents

Basic Integration 2

Builder API 5

Methods 19

Contacting the Team 30

Document Change Log 30

Next Steps..... 30

CUSTOMIZATION BUILDER REFERENCE (DRAFT)

Last Updated: 05/17/2019

This is the official reference for the features and functionality of the Customization Experience Builder, a product in the [Customization Experience Platform \(CXP\)](https://developer.nike.com/nde-docs/doc/commerce/customization/overview-customization.html) (<https://developer.nike.com/nde-docs/doc/commerce/customization/overview-customization.html>)

TIP: Also see [Customization Overview](https://developer.nike.com/nde-docs/doc/commerce/customization/overview-customization.html) (<https://developer.nike.com/nde-docs/doc/commerce/customization/overview-customization.html>) and [Adding Customization To Your Experience](https://developer.nike.com/nde-docs/doc/commerce/customization/use-customization.html) (<https://developer.nike.com/nde-docs/doc/commerce/customization/use-customization.html>).

The Builder is a JavaScript bundle that is your main interface with CXP. It offers the following:

- **UX:** Returns a fully-styled UX for customizing products
- **Data API:** Interact with [Build Data](#) and CXP REST APIs

Basic Integration

This section describes how to complete a basic integration of the Builder into a web view or browser-based application.

TIP: For more detailed integration instructions see [Adding Customization To Your Experience](https://developer.nike.com/nde-docs/doc/commerce/customization/use-customization.html) (<https://developer.nike.com/nde-docs/doc/commerce/customization/use-customization.html>).

1. Include the Builder Bundle

In your app's source (e.g. in an HTML template), include the Builder JavaScript bundle in a

`<script>` tag in the `<body>` like:

```
<script src=
"https://assets.commerce.nikecloud.com/nikeid/builder/dist/
b16Builder.bundle.min.js"
type="text/javascript"></script>
```

This loads the Builder bundle when the page is rendered.

Bundle URIs

The bundle URIs to be used in the Test and Production environments are provided below.

Test

- Builder UI: <https://assets.test.commerce.nikecloud.com/nikeid/builder/dist/b16Builder.bundle.min.js> (<https://assets.test.commerce.nikecloud.com/nikeid/builder/dist/b16Builder.bundle.min.js>)
- Product API: <https://assets.test.commerce.nikecloud.com/nikeid/builder/dist/b16ProductApi.bundle.min.js> (<https://assets.test.commerce.nikecloud.com/nikeid/builder/dist/b16ProductApi.bundle.min.js>)

Production

- Builder UI: <https://assets.commerce.nikecloud.com/nikeid/builder/dist/b16Builder.bundle.min.js> (<https://assets.commerce.nikecloud.com/nikeid/builder/dist/b16Builder.bundle.min.js>)
- Product API: <https://assets.commerce.nikecloud.com/nikeid/builder/dist/b16ProductApi.bundle.min.js> (<https://assets.commerce.nikecloud.com/nikeid/builder/dist/b16ProductApi.bundle.min.js>)

2. Add a `<div>` for the Builder to Load Into

Add a `<div>` in the `<body>` with an `id="nikeid-app"` attribute like:

```

<div id="nikeid-app-container" style=
"width: 1000px; height: 800px;">
  <div id="nikeid-app">
  </div>
</div>

```

You can name the `id` attribute however you want, just be sure to use the same name in the next step.

3. Initialize the Builder

Initialize the Builder by invoking the `nikeIdBuilder(rootElement, config)` function in a `<script>` tag in the `<body>` like:

```

<script>
  const builderApi = nikeIdBuilder(document.getElementById(
    'nikeid-app'), {
    'nike-api-caller-id': 'com.nike:commerce.b16.localhost',
    pathName: 'KobeAD2exoFA18'
  })
</script>

```

This returns the **Builder API** and renders the Customization UX into the specified `HTMLElement`.

TIPS:

- Make sure to use the same `id` used in Step 2 in the `document.getElementById()` argument.
- The `nikeIdBuilder` function is described in detail in [Builder API](#)

4. Navigate to the URI to Launch the Experience

Launch the Customization experience locally by navigating to the URI with at least the `?pathName` query parameter. The value in `?pathName` must match what you set in the

`pathName` property when the Builder was initialized, like:

```
http://localhost:3000/?pathName=KobeAD2exoFA18
```

Additional Query Params

- `imageSize`: sets the size of images returned by the Builder in pixels (max 666)
- `imageQuality`: sets the quality (as bit-depth) of the PNG images returned by the Builder (8/24)
- `hideMenu`: shows/hides the harnessMenu on page load (true/false)

Example:

```
http://localhost:3000/?imageSize=666&imageQuality=8&hideMenu=true&pathName=metcon2
```

Integration Flow

- Invoke `nikeIdBuilder(rootElement, config)` to get the Builder API. The returned object also contains a method for `api.onApiReady`, which indicates that the Builder has loaded.
- Listen to price change, analytic, and “done” events coming from the Builder.
- For buying tools, use `setSizeType` and `setAnswer` for answering the size related questions.
- Invoke `setBuild` for loading a new build by prebuild id, metric id, or raw build data. This is mainly meant to “reset” the Builder.

Builder API

Invoking the `nikeIdBuilder(rootElement, config)` function returns the Builder API.

Usage:

```

/**
 * Function nikeIdBuilder returns the Builder API
 * @param {HTMLElement} rootElement The DOM element in which to
inject the Builder
 * @param {Object} config The configuration properties that
identify which Builder instance to be returned
 * @return {Object} Returns the exposed builderApi handlers
 */
var rootElement = document.getElementById( 'my-app-location' );
var config = {
  'nike-api-caller-id': 'XXXXX',
  locale: 'en_US',
  country: 'US',
  pathName: 'af1High14_July',
  bridge: {
    // ...
  }
  // ... etc, documented below
};

var builderApi = nikeIdBuilder(rootElement, config)

```

Parameters

rootElement

The argument for the `rootElement` parameter must be an `HTMLElement` target to mount the Builder application into.

Example: `document.getElementById( 'nike-id-builder-app' );`

config

The argument for the `config` parameter must include the configuration properties that identify which Builder instance to be returned.

At minimum, the `pathName` and `nike-api-caller-id` properties are required in order to initialize the Builder.

```

{
  // required properties
  'nike-api-caller-id': 'com.nike:test',
  pathName: 'af1High14_July',

  // sometimes required properties
  productId: 'PROD359583',
  country: 'US',
  locale: 'en_US',

  // suggested bridge
  bridge: {
    onAnalyticsEvent: function() {},
    onApiReady: function(api) {}, // api ready not build
    onDone: function(buildData) {},
    onError: function(error){},
    onPriceUpdate: function(priceData) {},
    onProductLoad: function(buildData) {} // build ready
  }

  // optional properties
  abTestCookieName: null,
  builderMode: 'default',
  currentEnv: 'PROD',
  dataAsStrings: false,
  disablePalette: false,
  eMerchId: 123456,
  enableAnimationInit: false,
  fetchCapacity: false,
  fitToContainer: document.getElementById('nikeid-app-container'),
  hasTouch: true,
  isColorMatching: false,
  metricId: '42',
  prebuildId: '42',
  sizeTypeRegion: 'US',

  // optional skip price info
  skipPriceInfo: false,
  colorCode: '994',
  styleCode: 'A1617'
}

```

Required Properties

<code>pathName</code>	String	The product pathName for the requested build.
<code>nike-api-caller-id</code>	String	A platform-unique key («domain name»:«appid») that identifies the API caller to customization services

Getting a `nike-api-caller-id`

Please contact a team member in [#nikeid-dev-systems \(https://nikedigital.slack.com/messages/C0L8C4UM7 \)](https://nikedigital.slack.com/messages/C0L8C4UM7) or email Lst-digitaltech.customization.id.systems@nike.com to obtain a key for your platform in advance of making API calls. The current list of supported values is shown below (Note: items marked with * are for internal tracking purposes):

Platform	Value
Nike.com Desktop PDP	com.nike:commerce.idpdp.desktop
Nike.com Mobile PDP	com.nike:commerce.idpdp.mobile
Nike.com Jersey PDP	com.nike:commerce.jerseyidpdp.desktop
Nike.com Jersey Mobile PDP	com.nike:commerce.jerseyidpdp.mobile
Nike.com Desktop 3D Builder	com.nike:commerce.3d.builder.desktop
Nike.com Mobile 3D Builder	com.nike:commerce.3d.builder.mobile
Converse.com Desktop PDP	com.converse:commerce.idpdp.desktop
Converse.com Mobile PDP	com.converse:commerce.idpdp.mobile
Converse.com Europe Desktop PDP	com.converse.eu:commerce.idpdp.desktop
Converse.com Europe Mobile PDP	com.converse.eu:commerce.idpdp.mobile
Nike App iOS	com.nike.commerce.omega.ios
Nike App Android	com.nike.commerce.omega.droid
NikeElite.com Desktop PDP	com.nike.elite:commerce.idpdp.desktop

Platform	Value
NikeElite.com Mobile PDP	com.nike.elite:commerce.idpdp.mobile
Nike Cultivator Desktop	com.nike.cultivator:commerce.desktop
Nike Cultivator Mobile	com.nike.cultivator:commerce.mobile
Nike Factory Collab (FC) (includes FC Lite)	com.nike.commerce.fc
Nike DOMS	com.nike.commerce.doms
Nike CSP	com.nike.commerce.csp
Nike Order Capture (OCP)	com.nike.commerce.ocp
Nike PI	com.nike.commerce.pi
Nike Email	com.nike.commerce.email
WIP Tool*	com.nike:wip
Test*	com.nike:test
Localhost*	com.nike:commerce.b16.localhost

Properties With Dependencies

productId	String	Product ID for the requested build. Only required when using b16Builder and passing config: builderMode: 'wip'
country	String	The current country two character abbreviation, e.g. <code>US</code> , <code>GB</code> , <code>CN</code> . Only required when using builderProductApi
locale	String	The current locale abbreviation, e.g. <code>en_US</code> , <code>en_GB</code> , <code>zn_CN</code> . Only required when using builderProductApi

Optional Properties

abTestCookieName	String	A unique user id for Optimizely to use for it's a/b tests. If
------------------	--------	---

		<code>anonymousId</code> cookie is present, it will be used over the <code>abTestCookieName</code> .
<code>builderMode</code>	String	Determines which services are used by the Builder for product data and scene7 calls. In <code>default</code> mode, the production app uses a service call to the V4 Product service in production. In <code>wip</code> mode, the Builder uses the idedit preview product service and you must also supply the <code>productId</code> to be passed along in the service call.
<code>currentEnv</code>	String	Determines the environment to be used for Builder backend services. Possible values: <code>PROD</code> , <code>ecnXX</code> (any ecn environment), <code>prdvtools1</code> (any preview environment). If this config value is not set, the Builder will attempt to derive it from the client host URL, and if unsuccessful will default to <code>PROD</code> .
<code>dataAsStrings</code>	Boolean	Pass <code>true</code> to have the Builder API methods return data as a string, avoiding unwanted marshaling side effects.
<code>disablePalette</code>	Boolean	Pass <code>true</code> to disable/hide the marketing components/palette navigation.
<code>eMerchId</code>	String	The prodigy product ID. This can be used to fetch VAS SKU data required for jerseys.
<code>enableAnimationInit</code>	Boolean	Pass <code>true</code> if you want to await palette item animations until <code>builderApi.setIsVisible(true)</code> is called on the Builder
<code>fetchCapacity</code>	Boolean	Pass <code>true</code> to fetch capacity information along with the product.
<code>fitToContainer</code>	HTML Element	When set to a DOM element (e.g <code>document.getElementById('container')</code>), the experience will only flex to the size of that container rather than attempting to use 100vh or calculating UI dimensions based on the window.
<code>hasTouch</code>	Boolean	Pass <code>true</code> if the experience supports touch input.

<code>isColorMatching</code>	Boolean	Passing <code>true</code> hides the harness menu and control buttons. This supports color matching work flow in the WIP Builder.
<code>metricId</code>	String	Passing a <code>prebuildId</code> or <code>metricId</code> in config will force the Builder to load the build for the product and apply all the selections in the build to the loaded product. <code>metricId</code> will always be preferred over <code>prebuildId</code> if both are supplied.
<code>prebuildId</code>	String	Passing a <code>prebuildId</code> or <code>metricId</code> in config will force the Builder to load the build for the product and apply all the selections in the build to the loaded product. <code>metricId</code> will always be preferred over <code>prebuildId</code> if both are supplied.
<code>sizeTypeRegion</code>	String	The sizeTypeRegion corresponding to the list of sizeTypes that should be returned in the build data. Valid values are <code>US</code> , <code>EU</code> , <code>JP</code> , <code>CN</code> , <code>XP</code> .
<code>viewPortSize</code>	String	Sets viewport size, and creates values for <code>imageSize</code> and <code>imageQuality</code> . Can be <code>'S'</code> , <code>'M'</code> , <code>'L'</code> , <code>'XL'</code> , <code>'S8'</code> , <code>'M8'</code> , <code>'L8'</code> , <code>'XL8'</code> .
<code>imageQuality</code>	Number	Sets the PNG bit depth. Can be either <code>8</code> or <code>24</code> .
<code>imageSize</code>	Number	Number of pixels at which the main shoe image will be rendered.
<code>skipPriceInfo</code>	Boolean	If set to <code>true</code> , the pricing information won't be returned but style-color code will still be returned. Use for any product that is not setup in Prodigy. This flag is added to support Converse EU products.
<code>styleCode</code>	String	Mandatory when <code>skipPriceInfo</code> is set to <code>true</code> . Causes the build to be saved with the styleCode from the input config.
<code>colorCode</code>	String	Mandatory when <code>skipPriceInfo</code> is set to <code>true</code> . Causes the build to be saved with the colorCode from the input config.

Bridge Properties

The bridge is a set of callbacks provided to the Builder config under the `config.bridge` property. They allow you to be notified by actions within the Builder.

onAnalyticsEvent(type, payload)

Called upon user invoked events for capturing analytics data.

The `type` property will be an event name that is exposed for analytics. This list includes:

- **ANALYTICS_APPLY_CUSTOMIZATION**: When the user makes any customization change
- **ANALYTICS_COMPLETE_BUILD**: When the user presses 'done' to complete the build
- **ANALYTICS_MARKETING_COMPONENT_SELECTED**: When the user selects a marketing component
- **ANALYTICS_SELECT_VIEW**: When the user selects a view from the carousel
- **ANALYTICS_ZOOM_IN**: When the user requests a higher-res image

The `payload` property contains meta information about the event type. For example, the meta information for `ANALYTICS_SELECT_VIEW` would include the selected view number. The same applies for `ANALYTICS_MARKETING_COMPONENT_SELECTED`, which will include the id and name of the marketing component.

onApiReady(api)

Called when the API is ready, shortly after the product has loaded. This returns the API object.

NOTE: The build is not always ready at this point. Please use `bridge.onProductLoad(buildData)` for initial build. Then use `api.getBuild()` after that.

onDone(buildData)

Called with the current buildData whenever is "done" editing their build.

onError(error)

Called when an error response is returned from product data fetching or when a initialization

error occurs on the client. Error may be either a string or a native JavaScript error.

onPriceUpdate(priceData)

Called with price information whenever the user makes selection changes.

onProductLoad(buildData)

Called with the current buildData state of the Builder whenever a new product is loaded, or a build is applied.

Build Data

The Builder returns a `buildData` object (also referred to as Build Data), which describes the current state of the with sizing information, style/color, current product question/answer pairs, and more.

Here is a [sample buildData object \(https://developer.niketech.com/nde-docs/doc/commerce/customization/buildDataExample.html \)](https://developer.niketech.com/nde-docs/doc/commerce/customization/buildDataExample.html).

Build Data Fields

Field	Type	Description	Example
<code>pathName</code>	String	The product pathName for this build.	"ER2teamSP19_barca"
<code>productId</code> String	The product ID for this build.	"PROD372041"	
<code>consumerQuesAnswers</code>	Array	Collection of product question-and-answer pairs representing the current state of the Builder's pid selections.	See here (https://developer.niketech.com/nde-docs/doc/commerce/customization/buildDataExample.html)
<code>productQuesAnswers</code>	Array	A collection of product question-	See here (

Field	Type	Description	Example
		and-answer pairs representing the current state of the Builder's combination selections.	https://developer.niketech.com/nde-docs/doc/commerce/customization/buildDataExample.html)
sizeMarketingComponent	Object	See here (https://developer.niketech.com/nde-docs/doc/commerce/customization/buildDataExample.html)	
viewNumbers	String	Comma-separated list of views currently being displayed by the Builder, in the order in which they are being displayed. Provides a way to template scene7 urls for each angle of the product currently being shown within the Builder for your own product carousels or display pages.	"1,2,3,4,5,6"
color	String	The product color code for this build.	"994"
price	String	The product price formatted as string with the currency symbol.	\$180
rawPrice	Number	The product price formatted as a number.	180
style	String	The product style code.	"CK3977"
country	String	The current country code for this build.	"US"
locale	String	The current locale code for this build.	"en_US"

Field	Type	Description	Example
<code>viewService</code>	String	The host of the service call used to request images of the product represented by the buildData. Use in conjunction with the <code>viewUrlTemplate</code> field to build scene7 request urls.	See here (https://developer.niketech.com/nde-docs/doc/commerce/customization/buildDataExample.html)
<code>viewUrlTemplate</code>	String	Scene7 parameterized url for making requests for product images. Provided with a <code>{VIEW_NUMBER}</code> template string which you should target for replacement with a <code>viewNumber</code> which you would like to request. Use this field in conjunction with <code>viewNumbers</code> and <code>viewService</code> in order to template scene7 urls in order to request product images represented by the current buildData.	See here (https://developer.niketech.com/nde-docs/doc/commerce/customization/buildDataExample.html)
<code>sizeTypes</code>	Array	A collection of sizeTypes based on the sizeTypeRegion that was requested in the config data.	See here (https://developer.niketech.com/nde-docs/doc/commerce/customization/buildDataExample.html)
<code>sizingData</code>	Array	Contains arrays of gender, width, size, and size chart data. Used for “buying” and “size” tools.	See here (https://developer.niketech.com/nde-docs/doc/commerce/customization/buildDataExample.html)

More about sizingData

- Render the gender, width, and size questions and answer them using the `setAnswer` and `setsizeAnswer` methods as the consumer makes selections.
- It is required that you provide `fetchCapacity: true` and a value for the `sizeTypeRegion` field when initializing the Builder. If not provided, all of the sizes will be out of stock and the `sizeType` will default to “us-womens” or “us-mens”.
- Capacity, inventory, restrictions, sizeType and prior answers to sizing questions are all taken into consideration when generating this collection of objects.

Sample sizingData:

```

[
  {
    "displayName": "Size Chart",

    "questionId": "huarRunESS1702:LTITEM8538:LTITEM8112:LTITEM8010:LTITEM380033",
    "type": "SzChart",
    "answers":
    [
      {
        "path": "/v2/sizecharts/men_footwear_default.xml",
        "answerId": "LTITEM10027",
        "type": "SzChart",
        "isDefault": true
      }
    ]
  },
  {
    "displayName": "Gender",
    "questionId": "huarRunESS1702:LTITEM8538:LTITEM8112",
    "type": "Gender",
    "answers":
    [
      {
        "displayName": "Mens",
        "questionId": "huarRunESS1702:LTITEM8538:LTITEM8112",
        "answerId": "LTITEM8010",
        "type": "Gender",
        "isDefault": true,
        "isSelected": false,
        "isRestricted": false
      },
      {
        "displayName": "Womens",
        "questionId": "huarRunESS1702:LTITEM8538:LTITEM8112",
        "answerId": "LTITEM8011",
        "type": "Gender",
        "isDefault": false,
        "isSelected": false,
        "isRestricted": false
      }
    ]
  }
]

```

Methods

clearMessage

Description: Clears the message in the Builder.

Usage:

```
builderApi.clearMessage()
```

getAffectedQuestionMap

Description: Return questionsMappingInfo based on the questionId

Usage:

```
/**
 * @returns {Array}
 */
builderApi.getAffectedQuestionMap()
```

getAnswersByCode

Description: Returns answers and their matching questionId which can then be used to display an answer. Useful for tapping into specific question or answer nodes.

Usage:

```
/**
 * @returns {Array} List of normalized questions
 */
builderApi.getAnswersByCode('jersey')
```

getBuild

Description: Returns the current build snapshot.

Usage:

```
/**
 * @return {Object} The current build snapshot
 */
builderApi.getBuild()
```

getCapacity

Description: Returns promise to fetch capacity information for current or passed-in product configuration.

Usage:

```
/**
 * @returns {Promise->Object} a promise to return capacity data
 */
builderApi.getCapacity().then()
// or
builderApi.getCapacity({ country, pathName }).then()
```

getLeadTimeMessage

Description: Returns promise to fetch lead time information for current or passed-in product configuration.

```
/**
 * @returns {Promise->Object} a promise to return leadTimeMessage
data
 */
builderApi(getLeadTimeMessage)
```

getMarketingComponents

Description: Returns a list of normalized marketing components with nested question keys. The questions index can be used to lookup nested question values.

Usage:

```
/**
 * @returns {Object} the current prouduct marketing components data
 */
builderApi.getMarketingComponents()
```

getProductColorPalette

Description: Returns a list of unique colors for the loaded builder.

Usage:

```
/**
 * @return {Array} List of selected color answers unique by hex
 */
builderApi.getProductColorPalette()
```

getProductFillColors

Description: Returns a list of unique colors applicable to all marketing components for the loaded Builder

Usage:

```
/**
 * @returns {Array} List of selected color answers unique by hex
 */
builderApi.getProductFillColors()
```

getQuestionsIndex

Description: Returns a normalized array of questions keyed by their ID. Effectively, this is a flattened tree of all questions contained in the product data with nested questions as keys.

Usage:

```
/**
 * @returns {Array} List of normalized questions
 */
builderApi.getQuestionsIndex()
```

Example:

```
{
  pathName:questionId: {
    id: 'pathName:questionId',
    isHidden: false,
    questions: [
      0: 'pathName:questionId:nestedQuestionId'
    ]
  }
}
```

getSelectedColors

Description: Returns a collection of all selected colors from the current build, unique by hex(attribute).

Usage:

```
/**
 * @returns {Array} List of selected color answers unique by hex
 */
builderApi.getSelectedColors()
```

getSelectedColorsPatterns

Description: Returns a collection of all selected colors and patterns from the current build.

Colors are unique by hex(attribute) and patterns are unique by src(attribute).

Usage:

```
/**
 * @returns {Array} List of selected color answers unique by hex &
 * pattern type questions unique by src
 */
builderApi.getSelectedColorsPatterns
```

getSelectedPalette

Description: Returns a list of unique colors for the selected answers of the loaded builder.

Usage:

```
/**
 * @returns {Array} List of selected color answers unique by
 * displayName
 */
builderApi.getSelectedPalette()
```

getSelectedPatterns

Description: Returns a collection of all selected patterns from the current build, unique by src(attribute).

Usage:

```
/**
 * @returns {Array} List of selected pattern answers unique by src
 */
builderApi.getSelectedPatterns
```

getSelectedQuestionAnswerPairs

Description: Returns a collection of all answered questions along with their answer. For most products this will return the majority of questions, as defaults are selected in B16 APIs.

Usage:

```
/**
 * @returns {Array}
 */
builderApi.getSelectedQuestionAnswerPairs
```

getUpCharges

Description: Returns an array of applicable up-charge objects corresponding to the answered questions.

Usage:

```
/**
 * @returns {Object}
 */
builderApi.getUpCharges( )
```

Example:

```
[
  {
    answer: "ANSWER_ID",
    displayName: "Display Name",
    question: "QUESTION:PATH",
    upCharge: "$0"
  }
]
```

isPidAllowed

Description: Returns true if the profanity service allowed the string (no stop word was matched). String passed must match records in the capacity service exactly. Only single strings are supported.

Usage:

```
/**
 * @returns {Promise->Boolean} a promise to return profanity result
 */
builderApi.isPidAllowed( 'MYPID' )
```

openHighResImageUrl

Description: Returns the high-resolution image URL in a new window.

```
builderApi.openHighResImageUrl( )
```

saveBuild

Description: Persists build data and returns promise to send back a metric ID for that build.

Usage:

```
/**
 * @returns {Promise->String}
 */

builderApi.saveBuild( )
```

setAnswer

Description: Returns the current build snapshot after changing the answer to a question in the Builder. Send the full question path, e.g.

"af1High14_July:LTITEM8170:LTITEM12012:LTITEM236023:LTITEM213006" and the ID of the answer you would like to apply for that question, e.g. "LTITEM167036".

Usage:

```
/**
 * @param {String} questionId
 * @param {String} answerId
 * @param {String} pidValue
 * @returns {Object} Updated build snapshot
 */
builderApi.setAnswer(questionId, answerId, pidValue)
```

setBuild

Description: Allows reloading the Builder with a new product by passing one of the following:

Param	Type	Result
metricId	String	Build is loaded and applied to the product data.
prebuildId	String	Build is loaded and applied to the product data.
buildData	Object	Product for that build is reloaded and has the build data applied to the product.

After calling this method the `bridge.onProductLoad` callback is called with the `buildData` for the newly-applied build.

Usage:

```
/**
 * @param {Object} buildData
 */
builderApi.setBuild(buildData)
```

setIsVisible

Description: Informs the Builder whether it is visible on-screen or not. To take effect, `enableAnimationInit: true` needs to be passed in the initialization config options.

Usage:

```
builderApi.setIsVisible(true)
```

setMessage

Description: Causes the Builder to display a message. Takes a message object consisting of the following properties:

header	String	The text displayed at the top of the message.
content	String	The text displayed under the header.
type	String	The type of the message to be displayed, which also affects how the message is displayed. Possible values: 'COUNTDOWN', 'COUNTDOWN_URGENT', 'COUNTDOWN_EXPIRED'. Default is 'COUNTDOWN'.

Usage:

```
/**  
 * @param {Object} message  
 */  
builderApi.setMessage(message)
```

Examples:

```

var countdownMessage = { header: 'Available for', content:
'22:14:54:06', type: 'COUNTDOWN' };
builderApi.setMessage(countdownMessage);

var countdownUrgentMessage = { header: 'Available for', content:
'00:00:10:06', type: 'COUNTDOWN_URGENT' };
builderApi.setMessage(countdownUrgentMessage);

var countdownExpiredMessage = { header: 'Great choice but...',
content:
'This one sold out fast. Check back soon for availability. Keep
customizing, save your design and share it with friends.'
, type: 'COUNTDOWN_EXPIRED' };
builderApi.setMessage(countdownExpiredMessage);

```

setSizeAnswer

Description: Given a question ID and answer ID, answer the corresponding question in the build.

Usage:

```

/**
 * @param {String} questionId
 * @param {String} answerId
 * @param {String} sizeType
 * @returns {Object} Updated build snapshot
 */
setSizeAnswer(questionId, answerId, sizeType)

```

setSizeType

Description: Allows updating the Builder's internal state for selected size type, which updates the size, price, and color data when the Builder creates the buildData.

Usage:

```
/**
 * @param {String} sizeType
 */
builderApi.setSizeType(sizeType)
```

showNotification

Description: Causes the Builder to display a notification. It takes a message object consisting of the following properties:

type	String	The type of message. Only one message of a given type will be displayed.
message	String	The message text.
level	String	Optional - Determines the message level. Possible values: 'alert', undefined/null.
title	String	Optional - The message title.

Usage:

```
/**
 * @param {Object} message
 */
builderApi.showNotification(message)
```

Examples:

```

var alert = { message: 'This is an alert with the orange thing',
level: 'alert', type: 'some val' };
builderApi.showNotification(alert);

var titled = { message:
'This is just a plain message, but with a title', title: 'Hey yo!',
type: 'some val' };
builderApi.showNotification(titled);

var plain = { message:
'just a plain old message. not that fun, sorry.', type: 'some val'
};
builderApi.showNotification(plain);

```

Contacting the Team

Slack	#cxp (https://nikedigital.slack.com/messages/GFH2GM02C)
Confluence Space	NikeiD Systems Home (https://confluence.nike.com/display/NIDS/NikeiD+Systems+Home)
Team Contacts	Jason Mueller, Product Manager

Document Change Log

Summary	Date
Initial draft	05/17/2019

Next Steps

- [Adding Customization To Your Experience \(https://developer.niketech.com/nde-](https://developer.niketech.com/nde-)

[docs/doc/commerce/customization/use-customization.html](#))

- [Using NDe APIs \(https://developer.niketech.com/nde-docs/doc/getting-started/using-nike-apis.html \)](#)