



Python Data Structures Cheat Sheet

List

Package/Method	Description	Code Example
	Syntax:	<pre>1. 1 1. list_name.append(element)</pre>
append()	The `append()` method is used to add an element to the end of a list.	<div>Copied!</div> <div>Example:</div> <pre>1. 1 2. 2 1. fruits = ["apple", "banana", "orange"] 2. fruits.append("mango") print(fruits)</pre> <div>Copied!</div> <div>Example 1:</div>
copy()	The `copy()` method is used to create a shallow copy of a list.	<pre>1. 1 2. 2 3. 3 1. my_list = [1, 2, 3, 4, 5] 2. new_list = my_list.copy() print(new_list) 3. # Output: [1, 2, 3, 4, 5]</pre> <div>Copied!</div>
count()	The `count()` method is used to count the number of occurrences of a specific element in a list in Python.	<div>Example:</div> <pre>1. 1 2. 2 3. 3 1. my_list = [1, 2, 2, 3, 4, 2, 5, 2] 2. count = my_list.count(2) print(count) 3. # Output: 4</pre> <div>Copied!</div>
Creating a list	A list is a built-in data type that represents an ordered and mutable collection of elements. Lists are enclosed in square brackets [] and elements are separated by commas.	<div>Example:</div> <pre>1. 1 1. fruits = ["apple", "banana", "orange", "mango"]</pre> <div>Copied!</div>
del	The `del` statement is	<div>Example:</div>

used to remove an element from list. `del` statement removes the element at the specified index.

```
1. 1
2. 2
3. 3

1. my_list = [10, 20, 30, 40, 50]
2. del my_list[2] # Removes the element at index 2 print(my_list)
3. # Output: [10, 20, 40, 50]
```

Copied!

Syntax:

```
1. 1
```

The `extend()` method is used to add multiple elements to a list. It takes an iterable (such

```
1. list_name.extend(iterable)
```

Copied!

Example:

```
1. 1
2. 2
3. 3
4. 4
```

```
1. fruits = ["apple", "banana", "orange"]
2. more_fruits = ["mango", "grape"]
3. fruits.extend(more_fruits)
4. print(fruits)
```

Copied!

Indexing in a list allows you to access individual elements by their position.

Example:

```
1. 1
2. 2
3. 3
4. 4
5. 5
```

In Python, indexing starts from 0 for the first element and goes up to `length_of_list - 1`.

```
1. my_list = [10, 20, 30, 40, 50]
2. print(my_list[0])
3. # Output: 10 (accessing the first element)
4. print(my_list[-1])
5. # Output: 50 (accessing the last element using negative indexing)
```

Copied!

Syntax:

```
1. 1
```

```
1. list_name.insert(index, element)
```

Copied!

The `insert()` method is used to insert an element.

Example:

```
1. 1
2. 2
3. 3
```

```
1. my_list = [1, 2, 3, 4, 5]
2. my_list.insert(2, 6)
3. print(my_list)
```

Copied!

Example:

```
1. 1
2. 2
3. 3
4. 4
```

```
1. my_list = [10, 20, 30, 40, 50]
2. my_list[1] = 25 # Modifying the second element
3. print(my_list)
4. # Output: [10, 25, 30, 40, 50]
```

Copied!

Example 1:

```
1. 1
2. 2
3. 3
4. 4
5. 5
6. 6
7. 7
```

`pop()` method is another way to remove an element from a list in Python. It removes and returns the element at the specified index. If you don't provide an index to the `pop()` method, it will remove and return the last element of the list by default

```
1. my_list = [10, 20, 30, 40, 50]
2. removed_element = my_list.pop(2) # Removes and returns the element at index 2
3. print(removed_element)
4. # Output: 30
5.
6. print(my_list)
7. # Output: [10, 20, 40, 50]
```

Copied!

Example 2:

```
1. 1
2. 2
3. 3
4. 4
5. 5
6. 6
7. 7
```

```
1. my_list = [10, 20, 30, 40, 50]
2. removed_element = my_list.pop() # Removes and returns the last element
3. print(removed_element)
4. # Output: 50
5.
6. print(my_list)
7. # Output: [10, 20, 30, 40]
```

Copied!

Example:

To remove an element from a list. The `remove()` method removes the first occurrence of the specified value.

```
1. 1
2. 2
3. 3
4. 4
```

```
1. my_list = [10, 20, 30, 40, 50]
2. my_list.remove(30) # Removes the element 30
3. print(my_list)
4. # Output: [10, 20, 40, 50]
```

Copied!

Example 1:

The `reverse()` method is used to reverse the order of elements in a list

```
1. 1
2. 2
3. 3
```

```
1. my_list = [1, 2, 3, 4, 5]
2. my_list.reverse() print(my_list)
3. # Output: [5, 4, 3, 2, 1]
```

Copied!

Syntax:

```
1. 1
1. list_name[start:end:step]
```

Copied!

Example:

```
1. 1
2. 2
```

pop()

remove()

reverse()

Slicing

```
3. 3
4. 4
5. 5
6. 6
7. 7
8. 8
9. 9
10. 10
11. 11
12. 12

1. my_list = [1, 2, 3, 4, 5]
2. print(my_list[1:4])
3. # Output: [2, 3, 4] (elements from index 1 to 3)
4.
5. print(my_list[:3])
6. # Output: [1, 2, 3] (elements from the beginning up to index 2)
7.
8. print(my_list[2:])
9. # Output: [3, 4, 5] (elements from index 2 to the end)
10.
11. print(my_list[::2])
12. # Output: [1, 3, 5] (every second element)
```

Copied!

Example 1:

```
1. 1
2. 2
3. 3
4. 4

1. my_list = [5, 2, 8, 1, 9]
2. my_list.sort()
3. print(my_list)
4. # Output: [1, 2, 5, 8, 9]
```

Copied!

Example 2:

```
1. 1
2. 2
3. 3
4. 4

1. my_list = [5, 2, 8, 1, 9]
2. my_list.sort(reverse=True)
3. print(my_list)
4. # Output: [9, 8, 5, 2, 1]
```

Copied!

Dictionary

Package/Method	Description	Code Example
		Syntax: <pre>1. 1 1. Value = dict_name["key_name"]</pre>
Accessing Values	You can access the values in a dictionary using their corresponding 'keys'.	Example: <pre>1. 1 2. 2 1. name = person["name"] 2. age = person["age"]</pre>
Add or modify	Inserts a new key-value pair into the dictionary. If the key	Syntax: <pre>1. 1</pre>

already exists, the

value will be updated;
otherwise, a new entry
is created.

```
1. dict_name[key] = value
```

Copied!

Example:

```
1. 1
2. 2
```

```
1. person["Country"] = "USA" # A new entry will be created.
2. person["city"] = "Chicago" # Update the existing value for the same key
```

Copied!

Syntax:

```
1. 1
```

```
1. dict_name.clear()
```

Copied!

The `clear()` method
empties the dictionary,
removing all key-
value pairs within it.
After this operation,
the dictionary is still
accessible and can be
used further.

clear()

Example:

```
1. 1
```

```
1. grades.clear()
```

Copied!

Syntax:

```
1. 1
```

Creates a shallow
copy of the dictionary.
The new dictionary
contains the same key-
value pairs as the
original, but they
remain distinct objects
in memory.

copy()

```
1. new_dict = dict_name.copy()
```

Copied!

Example:

```
1. 1
2. 2
```

```
1. new_person = person.copy()
2. new_person = dict(person) # another way to create a copy of dictionary
```

Copied!

A dictionary is a built-
in data type that
represents a collection
of key-value pairs.
Dictionaries are
enclosed in curly
braces `{}`.

Creating a
Dictionary

Example:

```
1. 1
2. 2
```

```
1. dict_name = {} #Creates an empty dictionary
2. person = { "name": "John", "age": 30, "city": "New York"}
```

Copied!

Syntax:

```
1. 1
```

```
1. del dict_name[key]
```

Copied!

Removes the specified
key-value pair from
the dictionary. Raises
a `KeyError` if the
key does not exist.

del

Example:

```
1. 1
```

```
1. del person["Country"]
```

Copied!

Retrieves all key-
value pairs as tuples
and converts them into
a list of tuples. Each
tuple consists of a key

items()

Syntax:

```
1. 1
```

```
1. items_list = list(dict_name.items())
```

and its corresponding value.

Copied!

Example:

```
1. 1
1. info = list(person.items())
```

Copied!

Example:

You can check for the existence of a key in a dictionary using the ``in`` keyword

```
1. 1
2. 2
1. if "name" in person:
2.     print("Name exists in the dictionary.")
```

Copied!

Syntax:

```
1. 1
```

Retrieves all keys from the dictionary and converts them into a list. Useful for iterating or processing keys using list methods.

```
1. keys_list = list(dict_name.keys())
```

Copied!

Example:

```
1. 1
1. person_keys = list(person.keys())
```

Copied!

Syntax:

```
1. 1
```

The ``update()`` method merges the provided dictionary into the existing dictionary, adding or updating key-value pairs.

```
1. dict_name.update({key: value})
```

Copied!

Example:

```
1. 1
1. person.update({"Profession": "Doctor"})
```

Copied!

Syntax:

```
1. 1
```

Extracts all values from the dictionary and converts them into a list. This list can be used for further processing or analysis.

```
1. values_list = list(dict_name.values())
```

Copied!

Example:

```
1. 1
1. person_values = list(person.values())
```

Copied!

key existence

keys()

update()

values()

Sets

Package/Method	Description	Code Example
add()	Elements can be added to a set using the <code>`add()`</code> method. Duplicates are automatically removed, as sets only store unique values.	<p>Syntax:</p> <pre>1. 1 1. set_name.add(element)</pre> <p>Copied!</p>

Example:

```
1. 1
1. fruits.add("mango")
```

Copied!

Syntax:

```
1. 1
1. set_name.clear()
```

Copied!

Example:

```
1. 1
1. fruits.clear()
```

Copied!

Syntax:

```
1. 1
1. new_set = set_name.copy()
```

Copied!

Example:

```
1. 1
1. new_fruits = fruits.copy()
```

Copied!

Example:

```
1. 1
2. 2

1. empty_set = set() #Creating an Empty Set
2. fruits = {"apple", "banana", "orange"}
```

Copied!

Syntax:

```
1. 1
1. set_name.discard(element)
```

Copied!

Example:

```
1. 1
1. fruits.discard("apple")
```

Copied!

Syntax:

```
1. 1
1. is_subset = set1.issubset(set2)
```

Copied!

Example:

```
1. 1
1. is_subset = fruits.issubset(colors)
```

clear()

The `clear()` method removes all elements from the set, resulting in an empty set. It updates the set in-place.

copy()

The `copy()` method creates a shallow copy of the set. Any modifications to the copy won't affect the original set.

Defining Sets

A set is an unordered collection of unique elements. Sets are enclosed in curly braces `{}`. They are useful for storing distinct values and performing set operations.

discard()

Use the `discard()` method to remove a specific element from the set. Ignores if the element is not found.

issubset()

The `issubset()` method checks if the current set is a subset of another set. It returns True if all elements of the current set are present in the other set, otherwise False.

Copied!

Syntax:

```
1. 1
```

```
1. is_superset = set1.issuperset(set2)
```

Copied!

Example:

```
1. 1
```

```
1. is_superset = colors.issuperset(fruits)
```

Copied!

Syntax:

```
1. 1
```

```
1. removed_element = set_name.pop()
```

Copied!

Example:

```
1. 1
```

```
1. removed_fruit = fruits.pop()
```

Copied!

Syntax:

```
1. 1
```

```
1. set_name.remove(element)
```

Copied!

Example:

```
1. 1
```

```
1. fruits.remove("banana")
```

Copied!

Syntax:

```
1. 1
```

```
2. 2
```

```
3. 3
```

```
4. 4
```

```
1. union_set = set1.union(set2)
```

```
2. intersection_set = set1.intersection(set2)
```

```
3. difference_set = set1.difference(set2)
```

```
4. sym_diff_set = set1.symmetric_difference(set2)
```

Copied!

Example:

```
1. 1
```

```
2. 2
```

```
3. 3
```

```
4. 4
```

```
1. combined = fruits.union(colors)
```

```
2. common = fruits.intersection(colors)
```

```
3. unique_to_fruits = fruits.difference(colors)
```

```
4. sym_diff = fruits.symmetric_difference(colors)
```

Copied!

issuperset()

The `'issuperset()'` method checks if the current set is a superset of another set. It returns `True` if all elements of the other set are present in the current set, otherwise `False`.

pop()

The `'pop()'` method removes and returns an arbitrary element from the set. It raises a `'KeyError'` if the set is empty. Use this method to remove elements when the order doesn't matter.

remove()

Use the `'remove()'` method to remove a specific element from the set. Raises a `'KeyError'` if the element is not found.

Set Operations

Perform various operations on sets: `'union'`, `'intersection'`, `'difference'`, `'symmetric difference'`.

Syntax:

```
1. 1
```

```
1. set_name.update(iterable)
```

The `update()` method adds elements from another iterable into the set. It maintains the uniqueness of elements.

Copied!

Example:

```
1. 1
```

```
1. fruits.update(["kiwi", "grape"])
```

Copied!



Skills Network