

# Package ‘binancer’

August 14, 2025

**Type** Package

**Title** Wrapper for Binance REST and WebSocket API in R.

**Version** 0.1.0

**Author** Beniamino Sartini

**Maintainer** Beniamino Sartini <beniaminosartini@gmail.com>

**Description** Provides a comprehensive R interface for the Binance REST and WebSocket API.

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**Depends** R (>= 3.5.0)

**Imports** cli (>= 3.4.0),  
dplyr (>= 1.1.3),  
httr (>= 1.4.4),  
jsonlite (>= 1.8.4),  
lubridate (>= 1.9.2),  
purrr (>= 1.0.2),  
readr (>= 2.1.2),  
stringr (>= 1.5.0),  
R6 (>= 2.5.1),  
digest (>= 0.6.27),  
utils,  
stats,  
websocket (>= 1.4.1)

**Suggests** DT,  
knitr,  
rmarkdown,  
xts (>= 0.12.2),  
testthat (>= 2.1.0)

**RoxygenNote** 7.3.2

**Roxygen** list(markdown = TRUE)

**URL** <http://www.cryptoverser.org>

**BugReports** <https://github.com/beniamino98/binancer/issues>

**VignetteBuilder** knitr

## Contents

|                                      |           |
|--------------------------------------|-----------|
| binancer . . . . .                   | 2         |
| binanceWebSocket . . . . .           | 3         |
| binance_account_balance . . . . .    | 5         |
| binance_account_info . . . . .       | 6         |
| binance_account_trades . . . . .     | 6         |
| binance_avg_price . . . . .          | 7         |
| binance_book_ticker . . . . .        | 7         |
| binance_cancel_order . . . . .       | 8         |
| binance_credentials . . . . .        | 9         |
| binance_depth . . . . .              | 10        |
| binance_exchange_info . . . . .      | 11        |
| binance_futures_stats . . . . .      | 12        |
| binance_get_order . . . . .          | 14        |
| binance_klines . . . . .             | 14        |
| binance_last_open_interest . . . . . | 16        |
| binance_last_trades . . . . .        | 17        |
| binance_new_order . . . . .          | 18        |
| binance_open_interest . . . . .      | 20        |
| binance_ping . . . . .               | 21        |
| binance_query . . . . .              | 22        |
| binance_ticker24h . . . . .          | 23        |
| binance_ticker_day . . . . .         | 24        |
| binance_ticker_price . . . . .       | 25        |
| binance_time . . . . .               | 26        |
| binance_trades . . . . .             | 27        |
| binance_vision_klines . . . . .      | 28        |
| OrderBook . . . . .                  | 29        |
| <b>Index</b>                         | <b>31</b> |

---

binancer

*binancer: Wrapper for Binance REST and Websocket API in R.*


---

## Description

Wrapper for Binance REST API in R

## See Also

Useful links:

- <http://www.cryptoverser.org>
- Report bugs at <https://github.com/beniamino98/binancer/issues>

binanceWebSocket

*R6 Class for Binance Web Socket***Description**

Binance web socket description

**Details**

Binance web socket details

**Active bindings**

stream Get all streams

info Get all streams info

**Methods****Public methods:**

- `binanceWebSocket$new()`
- `binanceWebSocket$add_depth_snapshot()`
- `binanceWebSocket$add_trades_snapshot()`
- `binanceWebSocket$add_klines_snapshot()`
- `binanceWebSocket$subscribe()`
- `binanceWebSocket$unsubscribe()`
- `binanceWebSocket$connect()`
- `binanceWebSocket$close()`
- `binanceWebSocket$get_stream()`
- `binanceWebSocket$get_info()`
- `binanceWebSocket$clone()`

**Method** `new()`: Initialize a `binanceWebSocket` object.*Usage:*

```
binanceWebSocket$new(
  pair = "BTCUSDT",
  api = "spot",
  subscription,
  interval,
  update_speed
)
```

*Arguments:*`pair` Character. Trading pair, e.g. "BTCUSDT".`subscription` type of subscription, can be `aggTrade`, `bookTicker`, `depth`, `kline`, `miniTicker`, `ticker`, `trade`.`interval` time interval, can be 1s, 1m, 3m, 5m, 15m, 30m, 1h, 2h, 4h, 6h, 12h, 1d, 3d, 1w, 1M.`update_speed` update speed in millisecond, for spot api 1000ms. For others apis 500ms.*Returns:* A new `binanceWebSocket` object.**Method** `add_depth_snapshot()`: Add a snapshot of the order book.

*Usage:*

```
binanceWebSocket$add_depth_snapshot(pair, subscription, update_speed)
```

*Arguments:*

pair Character. Trading pair, e.g. "BTCUSDT".

subscription type of subscription, depth.

update\_speed update speed in millisecond, for spot api 1000ms. For others apis 500ms.

**Method** add\_trades\_snapshot(): Add trades*Usage:*

```
binanceWebSocket$add_trades_snapshot(pair, subscription, from, to)
```

*Arguments:*

pair Character. Trading pair, e.g. "BTCUSDT".

subscription type of subscription, aggTrades or trades.

from Character or [POSIXt](#) object. Start time for historical data. If it is missing, the default, will be used as start date `Sys.time()-lubridate::days(1)`.

to Character or [POSIXt](#) object. End time for historical data. If it is missing, the default, will be used as end date `Sys.time()`.

**Method** add\_klines\_snapshot(): Add a snapshot of the klines.*Usage:*

```
binanceWebSocket$add_klines_snapshot(pair, subscription, interval, from, to)
```

*Arguments:*

pair Character. Trading pair, e.g. "BTCUSDT".

subscription type of subscription, klines.

interval time interval, can be 1s,1m,3m,5m,15m,30m,1h,2h,4h,6h,12h,1d,3d,1w,1M.

from Character or [POSIXt](#) object. Start time for historical data. If it is missing, the default, will be used as start date `Sys.time()-lubridate::days(1)`.

to Character or [POSIXt](#) object. End time for historical data. If it is missing, the default, will be used as end date `Sys.time()`.

**Method** subscribe(): Subscribe to a stream.*Usage:*

```
binanceWebSocket$subscribe(pair, subscription, interval, update_speed)
```

*Arguments:*

pair Character. Trading pair, e.g. "BTCUSDT".

subscription type of subscription, can be aggTrade,bookTicker,depth,kline,miniTicker,ticker,trade.

interval time interval, can be 1s,1m,3m,5m,15m,30m,1h,2h,4h,6h,12h,1d,3d,1w,1M.

update\_speed update speed in millisecond, for spot api 1000ms. For others apis 500ms.

**Method** unsubscribe(): Unsubscribe from a stream.*Usage:*

```
binanceWebSocket$unsubscribe(pair, subscription, interval, update_speed)
```

*Arguments:*

pair Character. Trading pair, e.g. "BTCUSDT".

subscription type of subscription, can be aggTrade,bookTicker,depth,kline,miniTicker,ticker,trade.

interval time interval, can be 1s,1m,3m,5m,15m,30m,1h,2h,4h,6h,12h,1d,3d,1w,1M.

update\_speed update speed in millisecond, for spot api 1000ms. For others apis 500ms.

**Method connect():** Open the connection.

*Usage:*

binanceWebSocket\$connect()

**Method close():** Close all the connections.

*Usage:*

binanceWebSocket\$close()

**Method get\_stream():** Get a stream.

*Usage:*

binanceWebSocket\$get\_stream(pair, subscription, interval, update\_speed, id)

*Arguments:*

pair pair

subscription type of subscription, can be aggTrade,bookTicker,depth,kline,miniTicker,ticker,trade.

interval time interval, can be 1s,1m,3m,5m,15m,30m,1h,2h,4h,6h,12h,1d,3d,1w,1M.

update\_speed update speed in millisecond, for spot api 1000ms. For others apis 500ms.

**Method get\_info():** Get the info of all the streams opened.

*Usage:*

binanceWebSocket\$get\_info(pair, subscription, interval, update\_speed, id)

*Arguments:*

pair pair

subscription type of subscription, can be aggTrade,bookTicker,depth,kline,miniTicker,ticker,trade.

interval time interval, can be 1s,1m,3m,5m,15m,30m,1h,2h,4h,6h,12h,1d,3d,1w,1M.

update\_speed update speed in millisecond, for spot api 1000ms. For others apis 500ms.

**Method clone():** The objects of this class are cloneable with this method.

*Usage:*

binanceWebSocket\$clone(deep = FALSE)

*Arguments:*

deep Whether to make a deep clone.

---

binance\_account\_balance

*Binance Account Balances*

---

## Description

Get current balances of the connected account.

## Usage

binance\_account\_balance()

## Value

A [tibble](#).

---

binance\_account\_info    *Binance Account Information*

---

### Description

Get current general Binance account information.

### Usage

```
binance_account_info()
```

### Value

A [tibble](#).

---

binance\_account\_trades    *Binance Account Trades*

---

### Description

Get trades for a specific account and symbol.

### Usage

```
binance_account_trades(pair, from, to, from_id, limit, quiet = FALSE)
```

### Arguments

|         |                                                                                                                                                                  |
|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pair    | Character. Trading pair, e.g. "BTCUSDT".                                                                                                                         |
| from    | Character or <a href="#">POSIXt</a> object. Start time for historical trades. If it is missing, the default, retrieved the last 1000 trades from to date.        |
| to      | Character or <a href="#">POSIXt</a> object. End time for historical trades. If it is missing, the default, will be used as end date <a href="#">Sys.time()</a> . |
| from_id | Numeric. The last id from which retrieve the trades. Default is missing.                                                                                         |
| limit   | Integer. The maximum number of trades to retrieve. If missing, the default, will be used the maximum value that is 1000.                                         |
| quiet   | Logical. Default is FALSE. If TRUE suppress messages and warnings.                                                                                               |

### Value

A [tibble](#).

---

|                   |                              |
|-------------------|------------------------------|
| binance_avg_price | <i>Current Average Price</i> |
|-------------------|------------------------------|

---

**Description**

Get the average price of a trading pair in the last 5 minutes.

**Usage**

```
binance_avg_price(pair, quiet = FALSE)
```

**Arguments**

`quiet` Logical. Default is FALSE. If TRUE suppress messages and warnings.

**Details**

The IP weight for this API call is 2. This function implements the endpoint [api/v3/avgPrice](#) of spot API.

**Value**

Numeric. Average price in last 5 minutes.

**Examples**

```
# Average price for BTCUSDT
binance_avg_price("BTCUSDT")
# Average price for BNBUSDT
binance_avg_price("BNBUSDT")
```

---

|                     |                                 |
|---------------------|---------------------------------|
| binance_book_ticker | <i>Symbol Order Book Ticker</i> |
|---------------------|---------------------------------|

---

**Description**

Get best ASK and BID price and quantities on the order book for a pair or a list of pairs.

**Usage**

```
binance_book_ticker(pair, api, quiet = FALSE)
```

**Arguments**

|       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pair  | Character. Trading pair, e.g. "BTCUSDT". Multiple pairs are allowed only if api is "spot". If missing, the default, will be returned the book ticker for all the trading pairs.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| api   | Character. Reference API. If it is missing, the default, will be used "spot". Available options are: <ul style="list-style-type: none"> <li>"spot": for endpoint <code>api/v3/ticker/bookTicker</code>. The ip weight is 2 if a symbol is submitted, otherwise is 4. The maximum ip weight is 200. The ip weight depends on the number of pairs requested. The maximum ip weight is 80.</li> <li>"fapi": for endpoint <code>fapi/v1/ticker/bookTicker</code>. The ip weight is 2 if a symbol is submitted, otherwise is 5.</li> <li>"dapi": for endpoint <code>dapi/v1/ticker/bookTicker</code>. The ip weight is 2 if a symbol is submitted, otherwise is 5.</li> </ul> |
| quiet | Logical. Default is FALSE. If TRUE suppress messages and warnings.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

**Value**

A `data.frame` with 8 columns:

- date: `POSIXt`, time of the snapshot.
- pair: Character, reference trading pair, present only if api is "dapi".
- symbol: Character, trading pair.
- market: Character, reference API.
- ask: Numeric, best ASK price.
- bid: Numeric, best BID price.
- ask\_quantity: Numeric, quantity at best ASK price.
- bid\_quantity: Numeric, quantity at best BID price.

**Examples**

```
# Get book ticker for all pairs
binance_book_ticker(api = "spot")
binance_book_ticker(api = "fapi")
binance_book_ticker(api = "dapi")

# Get book ticker for BTCUSDT
binance_book_ticker(pair = "BTCUSDT", api = "spot")
```

---

binance\_cancel\_order    *Binance Cancel Order*


---

**Description**

Cancel an active order.



**Usage**

```
binance_cancel_order(pair, order_id, client_order_id)
```

**Arguments**

|                 |                                                            |
|-----------------|------------------------------------------------------------|
| pair            | Character. Trading pair, e.g. "BTCUSDT".                   |
| order_id        | Numeric. Order id that uniquely identify the trade.        |
| client_order_id | Numeric. Client order id that uniquely identify the trade. |

---

|                     |                             |
|---------------------|-----------------------------|
| binance_credentials | <i>Set Binance API Keys</i> |
|---------------------|-----------------------------|

---

**Description**

Sets the API key and secret to interact with the Binance API

**Usage**

```
binance_credentials(key, secret)
```

**Arguments**

|        |                        |
|--------|------------------------|
| key    | Character. Api key.    |
| secret | Character. Api secret. |

**Value**

No return values, setting config in the package namespace.

**Examples**

```
## Not run:  
# Add api keys  
binance_credentials('foo', 'bar')  
# Remove api keys  
binance_credentials()  
  
## End(Not run)
```

---

|               |                                    |
|---------------|------------------------------------|
| binance_depth | <i>Binance Order Book Snapshot</i> |
|---------------|------------------------------------|

---

## Description

Retrieve a snapshot of the order book for a trading pair.

## Usage

```
binance_depth(pair, api, quiet = FALSE)
```

## Arguments

|       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pair  | Character. Trading pair, e.g. "BTCUSDT".                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| api   | Character. Reference API. If it is missing, the default, will be used "spot". Available options are: <ul style="list-style-type: none"> <li>"spot": for endpoint <a href="#">api/v3/depth</a>. The ip weight is 250.</li> <li>"fapi": for endpoint <a href="#">fapi/v1/depth</a>. The ip weight is 20.</li> <li>"dapi": for endpoint <a href="#">dapi/v1/depth</a>. The ip weight is 20.</li> <li>"eapi": for endpoint <a href="#">eapi/v1/depth</a>. The ip weight is 1.</li> </ul> |
| quiet | Logical. Default is FALSE. If TRUE suppress messages and warnings.                                                                                                                                                                                                                                                                                                                                                                                                                   |

## Value

A [tibble](#) with 7 columns:

- last\_update\_id: Integer, id of the last snapshot.
- date: [POSIXt](#), time of the snapshot.
- market: Character, reference API.
- pair: Character, trading pair.
- side: Character, side of the limit orders in the book. Can be "ASK" or "BID".
- price: Numeric, price level.
- quantity: Numeric, quantity for each price level.

## Examples

```
# Get the order book for BTCUSDT
binance_depth(pair = "BTCUSDT", api = "spot")
binance_depth(pair = "BTCUSDT", api = "fapi")

# Get the order book for BTCUSD_PERP
binance_depth(pair = "BTCUSD_PERP", api = "dapi")

# Get the order book for a put option on BTC
binance_depth(pair = "BTC-240628-30000-P", api = "eapi")
```

---

binance\_exchange\_info *Binance Market Information*


---

## Description

Obtain market information and available trading pairs.

## Usage

```
binance_exchange_info(api, permissions, pair, quiet = FALSE)
```

## Arguments

|             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| api         | Character. Reference API. If it is missing, the default, will be used "spot". Available options are: <ul style="list-style-type: none"> <li>"spot": for endpoint <a href="#">api/v3/exchangeInfo</a>. The ip weight is 20.</li> <li>"fapi": for endpoint <a href="#">fapi/v1/exchangeInfo</a>. The ip weight is 1.</li> <li>"dapi": for endpoint <a href="#">dapi/v1/exchangeInfo</a>. The ip weight is 1.</li> <li>"eapi": for endpoint <a href="#">eapi/v1/exchangeInfo</a>. The ip weight is 1.</li> </ul> |
| permissions | Character, optional. Used only if api = "spot". Types of trading pairs to return. If "all", the default, all available types of pairs will be returned. Available options are: <ul style="list-style-type: none"> <li>"all": trading pairs in all markets.</li> <li>"spot": trading pairs only in spot markets.</li> <li>"margin": trading pairs only in margin markets.</li> <li>"leveraged": trading pairs only in leveraged markets.</li> </ul>                                                            |
| pair        | Character, optional. Trading pair, e.g. "BTCUSDT". If NULL, the default, all available pairs will be returned.                                                                                                                                                                                                                                                                                                                                                                                                |
| quiet       | Logical. Default is FALSE. If TRUE suppress messages and warnings.                                                                                                                                                                                                                                                                                                                                                                                                                                            |

## Value

A [tibble](#).

## Examples

```
# Get all pairs in all markets
binance_exchange_info(api = "spot", permissions = "all", pair = NULL)

# Get all pairs only in spot markets
binance_exchange_info(api = "spot", permissions = "spot", pair = NULL)

# Get all pairs only in margin markets
binance_exchange_info(api = "spot", permissions = "margin", pair = NULL)

# Get all pairs only in leveraged market
binance_exchange_info(api = "spot", permissions = "leveraged", pair = NULL)

# Get information only for BTCUSDT in all markets
binance_exchange_info(api = "spot", permissions = "all", pair = "BTCUSDT")
```

```
# Get information for multiple pairs in all markets
binance_exchange_info(api = "spot",
                      permissions = "all",
                      pair = c("BTCUSDT", "BNBUSDT"))

# Get information for multiple pairs only in margin and leveraged markets
binance_exchange_info(api = "spot",
                      permissions = c("margin", "leveraged"),
                      pair = c("BTCBUSDT", "ETHBUSDT"))

# Get all pairs in futures USD-m markets
binance_exchange_info(api = "fapi")

# Get all pairs in futures COIN-m markets
binance_exchange_info(api = "dapi")

# Get all pairs in options markets
binance_exchange_info(api = "eapi")
```

---

## binance\_futures\_stats *Futures Statistics*

---

### Description

Get the historical statistics for futures.

### Usage

```
binance_futures_stats(pair, api, interval, indicator, from, to, quiet = FALSE)
```

### Arguments

- |           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pair      | Character. Trading pair, e.g. "BTCUSDT" or "BTCUSD".                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| api       | Character, reference API. Available options are "fapi" or "dapi".                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| interval  | Character. Default is "1h". Time interval for open interest data. Available intervals are: <ul style="list-style-type: none"> <li>• Minutely: "5m", "15m" and "30m".</li> <li>• Hourly: "1h", "2h", "4h", "6h", "8h" and "12h".</li> <li>• Daily: "1d".</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| indicator | Character reference statistic. Available indicators are: <ul style="list-style-type: none"> <li>• takerlongshortRatio: only when api = "fapi", for the endpoint <a href="#">futures/data/takerlongshortRatio</a>. Taker Buy/Sell Volume. Taker Buy Volume: the total volume of buy orders filled by takers within the period. Taker Sell Volume: the total volume of sell orders filled by takers within the period.</li> <li>• takerBuySellVol: only when api = "dapi", for the endpoint <a href="#">futures/data/takerBuySellVol</a>. Taker Buy/Sell Volume.</li> <li>• globalLongShortAccountRatio: for the endpoint <a href="#">futures/data/globalLongShortAccountRatio</a>. The proportion of net long and net short positions to total open positions.</li> </ul> |

- `topLongShortPositionRatio`: for the endpoint `futures/data/topLongShortPositionRatio`. The proportion of net long and net short positions to total open positions of the top 20% users with the highest margin balance.
- `topLongShortAccountRatio`: for the endpoint `futures/data/topLongShortAccountRatio`. The proportion of net long and net short accounts to total accounts of the top 20% users with the highest margin balance. Each account is counted once only.

|                    |                                                                                                                                                                                                                   |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>from</code>  | Character or <code>POSIXt</code> object. Start time for historical data, only last 30 days are available. If it is missing, the default, will be used as start date <code>Sys.time()-lubridate::days(30)</code> . |
| <code>to</code>    | Character or <code>POSIXt</code> object. End time for historical data, only last 30 days are available. If it is missing, the default, will be used as start date <code>Sys.time()</code> .                       |
| <code>quiet</code> | Logical. Default is FALSE. If TRUE suppress messages and warnings.                                                                                                                                                |

## Details

The IP weight for this API call is 1, and the data source is memory. The historical open interest data are only available for the last 30 days.

## Value

A `tibble`

## Examples

```
# Statistics in USD-m market
binance_futures_stats(pair = "BTCUSDT",
  api = "fapi",
  interval = "1d",
  indicator = "takerlongshortRatio",
  from = Sys.Date()-2)
binance_futures_stats(pair = "BTCUSDT",
  api = "fapi",
  interval = "1d",
  indicator = "globalLongShortAccountRatio",
  from = Sys.Date()-2)
binance_futures_stats(pair = "BTCUSDT",
  api = "fapi",
  interval = "1d",
  indicator = "topLongShortPositionRatio",
  from = Sys.Date()-2)
binance_futures_stats(pair = "BTCUSDT",
  api = "fapi",
  interval = "1d",
  indicator = "topLongShortAccountRatio",
  from = Sys.Date()-2)

# Statistics in COIN-m market
binance_futures_stats(pair = "BTCUSD",
  api = "dapi",
  interval = "1d",
  indicator = "takerBuySellVol",
  from = Sys.Date()-2)
binance_futures_stats(pair = "BTCUSD",
  api = "dapi",
  interval = "1d",
```

```

        indicator = "globalLongShortAccountRatio",
        from = Sys.Date()-2)
binance_futures_stats(pair = "BTCUSD",
        api = "dapi",
        interval = "1d",
        indicator = "topLongShortPositionRatio",
        from = Sys.Date()-2)
binance_futures_stats(pair = "BTCUSD",
        api = "dapi",
        interval = "1d",
        indicator = "topLongShortAccountRatio",
        from = Sys.Date()-2)

```

---

|                   |                          |
|-------------------|--------------------------|
| binance_get_order | <i>Binance Get Order</i> |
|-------------------|--------------------------|

---

### Description

Get information about an order.

### Usage

```
binance_get_order(pair, order_id, client_order_id)
```

### Arguments

|                 |                                                            |
|-----------------|------------------------------------------------------------|
| pair            | Character. Trading pair, e.g. "BTCUSDT".                   |
| order_id        | Numeric. Order id that uniquely identify the trade.        |
| client_order_id | Numeric. Client order id that uniquely identify the trade. |

---

|                |                             |
|----------------|-----------------------------|
| binance_klines | <i>Get candlestick data</i> |
|----------------|-----------------------------|

---

### Description

Get klines/candlestick data for a trading pair.

### Usage

```

binance_klines(
  pair,
  api,
  interval,
  from,
  to,
  contract_type,
  uiKlines = FALSE,
  indexPrice = FALSE,
  markPrice = FALSE,

```

```

    indexPremium = FALSE,
    as_xts = FALSE,
    quiet = FALSE
  )

```

## Arguments

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pair          | Character. Trading pair, e.g. "BTCUSDT".                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| api           | Character. Reference API. If it is missing, the default, will be used "spot". Available options are: <ul style="list-style-type: none"> <li>"spot": for endpoint <a href="#">api/v3/klines</a>. The ip weight is 2.</li> <li>"fapi": for endpoint <a href="#">fapi/v1/klines</a>. The ip weight is 10.</li> <li>"dapi": for endpoint <a href="#">dapi/v1/klines</a>. The ip weight is 10.</li> <li>"eapi": for endpoint <a href="#">eapi/v1/klines</a>. The ip weight is 1.</li> </ul> |
| interval      | Character. Default is "1d". Time interval for klines data. Available intervals are: <ul style="list-style-type: none"> <li>Secondly: "1s", available only if api = "spot".</li> <li>Minutely: "1m", "3m", "5m", "15m" and "30m".</li> <li>Hourly: "1h", "2h", "4h", "6h", "8h" and "12h".</li> <li>Daily: "1d" and "3d".</li> <li>Weekly: "1w".</li> <li>Monthly: "1M".</li> </ul>                                                                                                     |
| from          | Character or <a href="#">POSIXt</a> object. Start time for historical data. If it is missing, the default, will be used as start date <code>Sys.time()-lubridate::days(1)</code> .                                                                                                                                                                                                                                                                                                     |
| to            | Character or <a href="#">POSIXt</a> object. End time for historical data. If it is missing, the default, will be used as end date <code>Sys.time()</code> .                                                                                                                                                                                                                                                                                                                            |
| contract_type | Character. Used only if api is "fapi" or "dapi". Available contract's types are: <ul style="list-style-type: none"> <li>"perpetual": perpetual futures.</li> <li>"current_quarter": futures with maturity in the current quarter.</li> <li>"next_quarter": futures with maturity in the next quarter.</li> </ul>                                                                                                                                                                       |
| uiKlines      | Logical. Default is FALSE. If TRUE will be used the endpoint continuousKlines.                                                                                                                                                                                                                                                                                                                                                                                                         |
| indexPrice    | Logical, default is FALSE. Used only when api is equal to "fapi" or "dapi". When TRUE is used the endpoint indexPriceKlines.                                                                                                                                                                                                                                                                                                                                                           |
| markPrice     | Logical, default is FALSE. Used only when api is equal to "fapi" or "dapi". When TRUE is used the endpoint markPriceKlines.                                                                                                                                                                                                                                                                                                                                                            |
| indexPremium  | Logical, default is FALSE. Used only when api is equal to "fapi" or "dapi". When TRUE is used the endpoint premiumIndexKlines.                                                                                                                                                                                                                                                                                                                                                         |
| as_xts        | Logical. Default is FALSE. If TRUE convert the data into an <a href="#">xts</a> object.                                                                                                                                                                                                                                                                                                                                                                                                |
| quiet         | Logical. Default is FALSE. If TRUE suppress messages and warnings.                                                                                                                                                                                                                                                                                                                                                                                                                     |

## Value

A [tibble](#) with 13 columns:

- date: [POSIXt](#), the opening date of the candle.
- date\_close: [POSIXt](#), the closing date of the candle.
- market: Character, API.

- pair: Character, trading pair.
- open: Numeric, open price (price in date).
- high: Numeric, highest price from date up to date\_close.
- low: Numeric, lowest price from date up to date\_close.
- close: Numeric, close price or price in date\_close.
- volume: Numeric, volume in asset value.
- volume\_quote: Numeric, volume in quote asset value.
- trades: Numeric, number of trades from date up to date\_close.
- taker\_buy: Numeric, taker buy volume in asset value.
- taker\_buy\_quote: Numeric, taker buy volume in quote asset value.

### Examples

```
# Get 1-hour OHLC data for BTCUSDT in the spot market
binance_klines(pair = "BTCUSDT", api = "spot", interval = "1h")

# Get 30-minute OHLC data for BTCUSDT in USD-m market
# Perpetual contracts
binance_klines(pair = "BTCUSDT", api = "fapi", interval = "30m", uiKlines = FALSE)
binance_klines(pair = "BTCUSDT", api = "fapi", interval = "30m",
               uiKlines = TRUE, contract_type = "perpetual")
# Futures contracts with maturity in current quarter
binance_klines(pair = "BTCUSDT", api = "fapi", interval = "30m",
               uiKlines = TRUE, contract_type = "current_quarter")
# Futures contracts with maturity in next quarter
binance_klines(pair = "BTCUSDT", api = "fapi", interval = "30m",
               uiKlines = TRUE, contract_type = "next_quarter")

# Get 15-minute OHLC data for BTCUSD in COIN-m market
# Perpetual contracts
binance_klines(pair = "BTCUSD", api = "dapi", interval = "15m",
               contract_type = "perpetual", uiKlines = FALSE)
binance_klines(pair = "BTCUSD", api = "dapi", interval = "15m",
               uiKlines = TRUE, contract_type = "perpetual")
# Futures contracts with maturity in current quarter
binance_klines(pair = "BTCUSD", api = "dapi", interval = "15m",
               uiKlines = TRUE, contract_type = "current_quarter")
# Futures contracts with maturity in next quarter
binance_klines(pair = "BTCUSD", api = "dapi", interval = "1h",
               uiKlines = TRUE, contract_type = "next_quarter")

# Get 1-hour OHLC data for a put option on BTCUSDT.
# Strike of 30000 and maturity on 2024-06-28.
binance_klines(pair = "BTC-240628-30000-P", api = "eapi", interval = "1h")
```

---

binance\_last\_open\_interest

*Binance Open Interest*

---



**Description**

Get the current open interest data for a trading pair.

**Usage**

```
binance_last_open_interest(pair, api, expiration, quiet = FALSE)
```

**Arguments**

|            |                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pair       | Character. Trading pair, e.g. "BTCUSDT".                                                                                                                                                                                                                                                                                                                                                                              |
| api        | Character. Reference API. If it is missing, the default, will be used "fapi". Available options are: <ul style="list-style-type: none"> <li>"fapi": for endpoint <a href="#">fapi/v1/openInterest</a>. The ip weight is 1.</li> <li>"dapi": for endpoint <a href="#">dapi/v1/openInterest</a>. The ip weight is 1.</li> <li>"eapi": for endpoint <a href="#">eapi/v1/openInterest</a>. The ip weight is 0.</li> </ul> |
| expiration | Character or <a href="#">POSIXt</a> object. Used only if api = "eapi". Expiration date for options contracts. If it is missing, the default, will be used <a href="#">Sys.time()</a> .                                                                                                                                                                                                                                |
| quiet      | Logical. Default is FALSE. If TRUE suppress messages and warnings.                                                                                                                                                                                                                                                                                                                                                    |

**Value**

A [tibble](#) with 4 columns:

- date: [POSIXt](#), observation date.
- market: Character, API.
- pair: Character, trading pair.
- open\_interest: Numeric, open interest in base currency.

**Examples**

```
# Get the open interest data for BTCUSDT
binance_last_open_interest(pair = "BTCUSDT", api = "fapi")

# Get the open interest data for BTCUSD_PERP
binance_last_open_interest(pair = "BTCUSD_PERP", api = "dapi")

# Get the open interest data for options on BTC
binance_last_open_interest(pair = "BTC", api = "eapi", expiration = Sys.Date() + 1)
```

---

binance\_last\_trades      *Get Recent Trades*

---

**Description**

Get the last 1000 trades for a trading pair.

**Usage**

```
binance_last_trades(pair, api, quiet = FALSE)
```

**Arguments**

|       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pair  | Character. Trading pair, e.g. "BTCUSDT".                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| api   | Character. Reference API. If it is missing, the default, will be used "spot". Available options are: <ul style="list-style-type: none"> <li>• "spot": for endpoint <code>api/v3/trades</code>. The ip weight is 25.</li> <li>• "fapi": for endpoint <code>fapi/v1/trades</code>. The ip weight is 5.</li> <li>• "dapi": for endpoint <code>dapi/v1/trades</code>. The ip weight is 5.</li> <li>• "eapi": for endpoint <code>eapi/v1/trades</code>. The ip weight is 5.</li> </ul> |
| quiet | Logical. Default is FALSE. If TRUE suppress messages and warnings.                                                                                                                                                                                                                                                                                                                                                                                                                |

**Value**

A `tibble` with 7 columns:

- date: `POSIXt`, trade execution date.
- market: Character, selected API.
- pair: Character, trading pair.
- price: Numeric, trade price.
- quantity: Numeric, trade quantity.
- side: Character, trade side. Can be "BUY" or "SELL".
- trade\_id: Integer, trade id.

**Examples**

```
# Get last 1000 trades for BTCUSDT
binance_last_trades(pair = "BTCUSDT", api = "spot")
binance_last_trades(pair = "BTCUSDT", api = "fapi")

# Get last 1000 trades for BTCUSD_PERP
binance_last_trades(pair = "BTCUSD_PERP", api = "dapi")

# Get last 1000 trades for a put option on BTC
binance_last_trades(pair = "BTC-240628-30000-P", api = "eapi")
```

---

|                   |                            |
|-------------------|----------------------------|
| binance_new_order | <i>Create a Spot Order</i> |
|-------------------|----------------------------|

---

**Description**

Send in a new order in spot market.

**Usage**

```
binance_new_order(
    pair,
    side,
    type,
    time_in_force,
    quantity,
    price,
    stop_price,
    trailing_delta,
    iceberg_qty,
    test = TRUE,
    quiet = FALSE
)
```

**Arguments**

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pair          | Character. Trading pair, e.g. "BTCUSDT".                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| side          | Character. Side of the trade. Can be "BUY" or "SELL".                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| type          | Character. Type of order. Available orders's types are: <ul style="list-style-type: none"> <li>• "MARKET": A Market Order is an order to buy or sell immediately at the current market price. It ensures swift execution but may not guarantee the exact price you see at the moment of placing the order, especially during periods of high volatility.</li> <li>• "LIMIT" or "LIMIT_MAKER": A Limit order is an order to buy or sell at a specific price. It will only execute at the specified price or a more favorable one. This type of order allows traders to set a target price and wait for the market to reach it.</li> <li>• "STOP_LOSS" or "TAKE_PROFIT": A Stop Market Order is similar to the Stop Limit Order, but once the stop price is reached, it becomes a market order, and the trade is executed at the prevailing market price. This ensures execution but may not guarantee the exact price.</li> <li>• "STOP_LOSS_LIMIT" or "TAKE_PROFIT_LIMIT": A Stop Limit Order combines elements of a stop order and a limit order. You set a stop price and a limit price. When the stop price is triggered, it becomes a limit order, and it will only execute at or better than the limit price. This order type is useful for entering or exiting positions once a certain price level is reached.</li> </ul> |
| time_in_force | Character. Time in force, specify the conditions under which the trade expiry. The default "GTC". More details can be found on <a href="#">Binance Academy</a> . Available time in force are: <ul style="list-style-type: none"> <li>• "GTC": <b>Good 'til canceled</b> orders stipulate that a trade should be kept open until it's either executed or manually canceled.</li> <li>• "IOC": <b>Immediate or cancel</b> orders stipulate that any part of the order that isn't immediately filled must be canceled.</li> <li>• "FOK": <b>Fill or kill</b> orders are either filled immediately, or they're canceled.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| quantity      | Numeric. Quantity of the asset to be bought or sold. For example when pair = "BTCUSDT" and quantity = 1, if side = "BUY" we are sending an order to buy 1 BTC, otherwise if side = "SELL" we are sending an order to sell 1 BTC.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| price         | Numeric, optional. Limit price, used only for limit orders.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

|                |                                                                                                                                                                                                 |
|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| stop_price     | Numeric, optional. Stop price, used only for stop loss and take profit orders. Can be specified a stop price or a trailing delta, if specified both will be used trailing delta by default.     |
| trailing_delta | Numeric, optional. Trailing delta, used only for stop loss and take profit orders. Can be specified a stop price or a trailing delta, if specified both will be used trailing delta by default. |
| iceberg_qty    | Numeric, iceberg quantity.                                                                                                                                                                      |
| test           | Logical. If TRUE, the default, the order will be a test order.                                                                                                                                  |
| quiet          | Logical. Default is FALSE. If TRUE suppress messages and warnings.                                                                                                                              |

---

binance\_open\_interest *Binance Historical Open Interest*

---

## Description

Get the historical open interest for a trading pair. The data are only available for the last 30 days.

## Usage

```
binance_open_interest(
  pair,
  api,
  interval,
  from,
  to,
  contract_type,
  quiet = FALSE
)
```

## Arguments

|               |                                                                                                                                                                                                                                                                                                                                                               |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pair          | Character. Trading pair, e.g. "BTCUSDT".                                                                                                                                                                                                                                                                                                                      |
| api           | Character. Reference API. Available options are: <ul style="list-style-type: none"> <li>"fapi": for endpoint <a href="#">fapi/v1/openInterestHist</a>. The ip weight is 0.</li> <li>"dapi": for endpoint <a href="#">dapi/v1/openInterestHist</a>. The ip weight is 0.</li> </ul>                                                                             |
| interval      | Character. Time interval for open interest data. Default is "1h". Available intervals are: <ul style="list-style-type: none"> <li>Minutely: "5m", "15m" and "30m".</li> <li>Hourly: "1h", "2h", "4h", "6h", "8h" and "12h".</li> <li>Daily: "1d".</li> </ul>                                                                                                  |
| from          | Character or <a href="#">POSIXt</a> object. Start time for historical data, only last 30 days are available. If it is missing, the default, will be used as start date <code>Sys.time()-lubridate::days(30)</code> .                                                                                                                                          |
| to            | Character or <a href="#">POSIXt</a> object. End time for historical data, only last 30 days are available. If it is missing, the default, will be used as start date <code>Sys.time()</code> .                                                                                                                                                                |
| contract_type | Character. Used only if api = "dapi". Available contract's types are: <ul style="list-style-type: none"> <li>"all": for all types of contracts.</li> <li>"perpetual": for perpetual futures.</li> <li>"current_quarter": for futures with maturity in the current quarter.</li> <li>"next_quarter": for futures with maturity in the next quarter.</li> </ul> |
| quiet         | Logical. Default is FALSE. If TRUE suppress messages and warnings.                                                                                                                                                                                                                                                                                            |

**Value**

A `tibble` with 5 columns:

- `date`: `POSIXt`, observation date.
- `market`: Character, API.
- `pair`: Character, trading pair.
- `open_interest`: Numeric, open interest in base currency.
- `open_interest_usd`: Numeric, open interest in USD.

**Examples**

```
# Historical open interest for BTCUSDT
binance_open_interest(pair = "BTCUSDT",
                      api = "fapi",
                      interval = "1d",
                      from = Sys.time()-lubridate::days(15),
                      to = Sys.time()-lubridate::days(5))

# Historical open interest for BTCUSD
binance_open_interest(pair = "BTCUSD",
                      api = "dapi",
                      interval = "1d",
                      from = Sys.time()-lubridate::days(15),
                      to = NULL)
```

---

|              |                                 |
|--------------|---------------------------------|
| binance_ping | <i>Ping to Binance REST API</i> |
|--------------|---------------------------------|

---

**Description**

Check the connection to the Binance API.

**Usage**

```
binance_ping(api, quiet = FALSE)
```

**Arguments**

|                    |                                                                                                                                                                                                                                                                                                                                     |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>api</code>   | Character. Reference API. If it is missing, the default, will be used "spot". Available options are: <ul style="list-style-type: none"> <li>• "spot": for <b>spot API</b>.</li> <li>• "fapi": for <b>futures USD-m API</b>.</li> <li>• "dapi": for <b>futures COIN-m API</b>.</li> <li>• "eapi": for <b>options API</b>.</li> </ul> |
| <code>quiet</code> | Logical. Default is FALSE. If TRUE suppress messages and warnings.                                                                                                                                                                                                                                                                  |

**Details**

The IP weight for this API call is 1 for all the APIs.

**Value**

A logical value. It is TRUE if the connection was successful, otherwise it is FALSE.

**Examples**

```
# Test connection to spot api
binance_ping("spot")
# Test connection to futures usd-m api
binance_ping("fapi")
# Test connection to futures coin-m api
binance_ping("dapi")
# Test connection to options api
binance_ping("eapi")
```

---

|               |                                  |
|---------------|----------------------------------|
| binance_query | <i>Query to Binance REST API</i> |
|---------------|----------------------------------|

---

**Description**

Execute a query to Binance REST API.

**Usage**

```
binance_query(
  api,
  path = NULL,
  query = list(),
  method = "GET",
  sign = FALSE,
  use_base_path = TRUE,
  quiet = FALSE
)
```

**Arguments**

|        |                                                                                                                                                                                                                                                                                                                                                                               |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| api    | Character. Reference API. If it is missing, the default, will be used "spot". Available options are: <ul style="list-style-type: none"> <li>• "spot": for <b>spot API</b>.</li> <li>• "fapi": for <b>futures USD-m API</b>.</li> <li>• "dapi": for <b>futures COIN-m API</b>.</li> <li>• "eapi": for <b>options API</b>.</li> <li>• "sapi": for <b>wallet API</b>.</li> </ul> |
| path   | Character vector. API path, NULL or NA elements will be excluded.                                                                                                                                                                                                                                                                                                             |
| query  | Named list. Query parameters for the API call, NULL or NA elements will be excluded.                                                                                                                                                                                                                                                                                          |
| method | Character. A method between "GET", "POST" and "DELETE".                                                                                                                                                                                                                                                                                                                       |
| sign   | Logical. Default is FALSE. TRUE if signature is required.                                                                                                                                                                                                                                                                                                                     |

|               |                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| use_base_path | Logical. When TRUE, the default, to path argument will be added a base_bath based on the selected API. Available base_bath are: <ul style="list-style-type: none"> <li>• "spot": base path is "api/v3".</li> <li>• "fapi": base path is "fapi/v1".</li> <li>• "dapi": base path is "dapi/v1".</li> <li>• "eapi": base path is "eapi/v1".</li> <li>• "sapi": base path is "sapi/v1".</li> </ul> |
| quiet         | Logical. Default is FALSE. If TRUE suppress messages and warnings.                                                                                                                                                                                                                                                                                                                             |

### Value

An R object parsed as character. See more on [content](#)

### Examples

```
# Execute a call to spot API with base path
binance_query(api = "spot",
              path = "time",
              query = NULL,
              use_base_path = TRUE)

# Execute a call to spot API without base path
binance_query(api = "spot",
              path = c("api", "v3", "time"),
              query = NULL,
              use_base_path = FALSE)
```

---

|                   |                                          |
|-------------------|------------------------------------------|
| binance_ticker24h | <i>Binance 24-Hour Ticker Statistics</i> |
|-------------------|------------------------------------------|

---

### Description

Get 24-hour ticker statistics for a specified trading pair from the selected reference API.

### Usage

```
binance_ticker24h(pair, api, type, quiet = FALSE)
```

### Arguments

|      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pair | Character. Trading pair, e.g. "BTCUSDT". Multiple pairs are allowed only if api is "spot". If missing, the default, will be returned the 24hr ticker for all the trading pairs.                                                                                                                                                                                                                                                                                                          |
| api  | Character. Reference API. If it is missing, the default, will be used "spot". Available options are: <ul style="list-style-type: none"> <li>• "spot": for endpoint <a href="#">api/v3/ticker/24hr</a>. The ip weight depends on the number of pairs requested. The maximum ip weight is 80.</li> <li>• "fapi": for endpoint <a href="#">fapi/v1/ticker/24hr</a>. The ip weight is 1.</li> <li>• "dapi": for endpoint <a href="#">dapi/v1/ticker/24hr</a>. The ip weight is 1.</li> </ul> |

|       |                                                                                                                                                                                                                                                           |
|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|       | <ul style="list-style-type: none"> <li>• "eapi": for endpoint <a href="#">eapi/v1/ticker</a>. The ip weight is 5.</li> </ul>                                                                                                                              |
| type  | Character. Type of ticker data. Used only if api = "spot". Default is "full". Available options are: <ul style="list-style-type: none"> <li>• "mini": data without ask and bid prices and quantities.</li> <li>• "full": complete ticker data.</li> </ul> |
| quiet | Logical. Default is FALSE. If TRUE suppress messages and warnings.                                                                                                                                                                                        |

### Value

A [tibble](#) with 13 columns containing 24-hour ticker statistics, including: open, high, low, close prices, volume, and more.

### Examples

```
# Get full 24-hour ticker for all pairs
binance_ticker24h(api = "spot")
binance_ticker24h(api = "fapi")
binance_ticker24h(api = "dapi")
binance_ticker24h(api = "eapi")

# Get full 24-hour ticker for BTCUSDT
binance_ticker24h(pair = "BTCUSDT", api = "spot", type = "full")

# Get mini 24-hour ticker for BTCUSDT
binance_ticker24h(pair = "BTCUSDT", api = "spot", type = "mini")

# Get 24-hour ticker for BTCUSDT
binance_ticker24h(pair = "BTCUSDT", api = "fapi")

# Get 24-hour ticker for BTCUSD_PERP
binance_ticker24h(pair = "BTCUSD_PERP", api = "dapi")

# Get 24-hour ticker for a put option on BTCUSDT
binance_ticker24h(pair = "BTC-240628-30000-P", api = "eapi")
```

---

|                    |                                  |
|--------------------|----------------------------------|
| binance_ticker_day | <i>Symbol Trading Day Ticker</i> |
|--------------------|----------------------------------|

---

### Description

Price change statistics for a trading day.

### Usage

```
binance_ticker_day(pair, time_zone = 0, quiet = FALSE)
```

### Arguments

|           |                                                                                                        |
|-----------|--------------------------------------------------------------------------------------------------------|
| pair      | Character. Trading pair, e.g. "BTCUSDT". Multiple pairs are allowed with a maximum of 100 per request. |
| time_zone | Character, reference time zone.                                                                        |
| quiet     | Logical. Default is FALSE. If TRUE suppress messages and warnings.                                     |



**Value**

A **tibble** with 14 columns:

- date: **POSIXt**, open date of the reference period.
- date\_close: **POSIXt**, close date of the reference period.
- symbol: Character, trading pair.
- market: Character, reference API.
- first\_id: Numeric, first trade id.
- last\_id: Numeric, last trade id.
- open: Numeric, open price.
- high: Numeric, highest price.
- low: Numeric, lowest price.
- last: Numeric, last price.
- weighted\_price: Numeric, volume-weighted price.
- volume: Numeric, volume.
- volume\_quote: Numeric, volume in terms of quote asset.
- trades: Numeric, number of trades

**Examples**

```
# Get day ticker for BTCUSDT
binance_ticker_day("BTCUSDT")
```

---

|                      |                           |
|----------------------|---------------------------|
| binance_ticker_price | <i>Symbol Book Ticker</i> |
|----------------------|---------------------------|

---

**Description**

Get last price for a symbol or symbols.

**Usage**

```
binance_ticker_price(pair, api, quiet = FALSE)
```

**Arguments**

|       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pair  | Character. Trading pair, e.g. "BTCUSDT". Multiple pairs are allowed only if api is "spot". If missing, the default, will be returned the book ticker for all the trading pairs.                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| api   | Character. Reference API. If it is missing, the default, will be used "spot". Available options are: <ul style="list-style-type: none"> <li>• "spot": for endpoint <b>api/v3/ticker/price</b>. The ip weight is 2 if a symbol is submitted, otherwise is 4. The ip weight depends on the number of pairs requested. The maximum ip weight is 80.</li> <li>• "fapi": for endpoint <b>fapi/v1/ticker/price</b>. The ip weight is 1 if a symbol is submitted, otherwise is 2.</li> <li>• "dapi": for endpoint <b>dapi/v1/ticker/price</b>. The ip weight is 1 if a symbol is submitted, otherwise is 2.</li> </ul> |
| quiet | Logical. Default is FALSE. If TRUE suppress messages and warnings.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

**Value**

A **tibble** with 8 columns:

- date: **POSIXt**, time of the snapshot.
- pair: Character, reference trading pair, present only if api is "dapi".
- symbol: Character, trading pair.
- market: Character, reference API.
- ask: Numeric, best ASK price.
- bid: Numeric, best BID price.
- ask\_quantity: Numeric, quantity at best ASK price.
- bid\_quantity: Numeric, quantity at best BID price.

**Examples**

```
# Get book ticker for all pairs
binance_ticker_price(api = "spot")
binance_ticker_price(api = "fapi")
binance_ticker_price(api = "dapi")

# Get book ticker for BTCUSDT
binance_ticker_price(pair = "BTCUSDT", api = "spot")
```

---

|              |                            |
|--------------|----------------------------|
| binance_time | <i>Binance Server Time</i> |
|--------------|----------------------------|

---

**Description**

Get the current server time from Binance API.

**Usage**

```
binance_time(api, quiet = FALSE)
```

**Arguments**

|       |                                                                                                                                                                                                                                                                                                                                     |
|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| api   | Character. Reference API. If it is missing, the default, will be used "spot". Available options are: <ul style="list-style-type: none"> <li>• "spot": for <b>spot API</b>.</li> <li>• "fapi": for <b>futures USD-m API</b>.</li> <li>• "dapi": for <b>futures COIN-m API</b>.</li> <li>• "eapi": for <b>options API</b>.</li> </ul> |
| quiet | Logical. Default is FALSE. If TRUE suppress messages and warnings.                                                                                                                                                                                                                                                                  |

**Details**

The IP weight for this API call is 1.

**Value**

A [POSIXt](#) object. The server time for the reference API.

**Examples**

```
# Get the server time
binance_time("spot")
binance_time("fapi")
binance_time("dapi")
binance_time("eapi")
```

---

|                |                                             |
|----------------|---------------------------------------------|
| binance_trades | <i>Binance Aggregated Historical Trades</i> |
|----------------|---------------------------------------------|

---

**Description**

Get aggregated historical trades data for a trading pair.

**Usage**

```
binance_trades(pair, api, from, to, quiet = FALSE)
```

**Arguments**

|       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pair  | Character. Trading pair, e.g. "BTCUSDT".                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| api   | Character. Reference API. If it is missing, the default, will be used "spot". Available options are: <ul style="list-style-type: none"> <li>"spot": for endpoint <a href="#">api/v3/aggTrades</a>. The ip weight is 4.</li> <li>"fapi": for endpoint <a href="#">fapi/v1/aggTrades</a>. The ip weight is 20.</li> <li>"dapi": for endpoint <a href="#">dapi/v1/aggTrades</a>. The ip weight is 20.</li> <li>"eapi": for endpoint <a href="#">eapi/v1/aggTrades</a>.</li> </ul> |
| from  | Character or <a href="#">POSIXt</a> object. Start time for historical data. If it is missing, the default, will be used as start date <code>Sys.time()-lubridate::minutes(10)</code> .                                                                                                                                                                                                                                                                                         |
| to    | Character or <a href="#">POSIXt</a> object. End time for historical data. If it is missing, the default, will be used as end date <code>Sys.time()</code> .                                                                                                                                                                                                                                                                                                                    |
| quiet | Logical. Default is FALSE. If TRUE suppress messages and warnings.                                                                                                                                                                                                                                                                                                                                                                                                             |

**Value**

A [tibble](#) with 9 columns:

- date: [POSIXt](#), trade execution date;
- market: Character, API.
- pair: Character, trading pair.
- price: Numeric, trade price.
- quantity: Numeric, trade quantity.
- side: Character, trade side. Can be "BUY" or "SELL".
- agg\_id: Integer, aggregated trade id.
- first\_id: Integer, first trade id for aggregation.
- last\_id: Integer, last trade id for aggregation.

## Examples

```
# Get trades in last 10 minutes for BTCUSDT
binance_trades(pair = "BTCUSDT", api = "spot", from = NULL, to = NULL)

# Get trades in last 10 minutes for LAZIOUSD
binance_trades(pair = "LAZIOUSD", api = "spot", from = "2023-01-01", to = "2023-01-02")

# Get trades in last 10 minutes for BTCUSDT
binance_trades(pair = "BTCUSDT", api = "fapi", from = NULL, to = NULL)

# Get trades in last 10 minutes for BTCUSD_PERP
binance_trades(pair = "BTCUSD_PERP", api = "dapi", from = NULL, to = NULL)
```

---

binance\_vision\_klines *Historical Klines data from Binance Vision*

---

## Description

Historical Kline data for a trading pair from the Binance Vision database.

## Usage

```
binance_vision_klines(pair, api, interval, from, to, quiet = FALSE)
```

## Arguments

|          |                                                                                                                                                                                                                                                                                                                            |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pair     | Character. Trading pair, e.g., "BTCUSDT".                                                                                                                                                                                                                                                                                  |
| api      | Character. Reference API. If it is missing, the default, will be used "spot". Available options are: <ul style="list-style-type: none"> <li>"spot": for <b>spot API</b>.</li> <li>"fapi": for <b>futures USD-m API</b>.</li> <li>"dapi": for <b>futures COIN-m API</b>.</li> </ul>                                         |
| interval | Character. Default is "1d". Time interval for klines data. Available intervals are: <ul style="list-style-type: none"> <li>Secondly: "1s", available only if api = "spot".</li> <li>Minutely: "1m", "3m", "5m", "15m" and "30m".</li> <li>Hourly: "1h", "2h", "4h", "6h", "8h" and "12h".</li> <li>Daily: "1d".</li> </ul> |
| from     | Character or an object of class " <b>POSIXt</b> ", the start time for data retrieval. If NULL, the default is Sys.Date()-lubridate::days(4).                                                                                                                                                                               |
| to       | Character or an object of class " <b>POSIXt</b> ", the end time for data retrieval. If NULL, the default is Sys.Date()-lubridate::days(2).                                                                                                                                                                                 |
| quiet    | Logical, suppress informational messages if TRUE. Default FALSE.                                                                                                                                                                                                                                                           |

## Value

A **tibble**.

**Examples**

```

pair <- "BTCUSDT"
api <- "spot"
from <- to <- "2023-01-01"
interval <- "1m"
binance_vision_klines(pair, api = api,
                      interval = interval, from = from, to = from)
binance_vision_klines(pair, api = "fapi",
                      interval = interval, from = from, to = from)
binance_vision_klines("BTCUSD_PERP", api = "dapi",
                      interval = interval, from = from, to = from)

```

---

|           |                   |
|-----------|-------------------|
| OrderBook | <i>Order Book</i> |
|-----------|-------------------|

---

**Description**

Create and structure an order book from depth data.

**Usage**

```

OrderBook(data = NULL,
          min_price = NULL,
          max_price = NULL,
          levels = NULL,
          trades = NULL,
          as_datatable = FALSE)

```

**Arguments**

|                           |                                                                                  |
|---------------------------|----------------------------------------------------------------------------------|
| <code>data</code>         | A <a href="#">data.frame</a> with at least 3 columns (price, quantity and side). |
| <code>min_price</code>    | Numeric. Minimum price for the aggregation of order book.                        |
| <code>max_price</code>    | Numeric. Maximum price for the aggregation of order book.                        |
| <code>levels</code>       | Integer. Number of levels for the aggregated order book.                         |
| <code>trades</code>       | A <a href="#">data.frame</a> containing trades data.                             |
| <code>as_datatable</code> | Logical, if TRUE return the order book as a datatable. Default is FALSE.         |

**Value**

A [tibble](#) or [datatable](#) object. Depth data aggregated for a specified price range.

**Examples**

```

# Generate an order book for BTCUSDT
depth_data <- binance_depth("BTCUSDT", api = "spot")
depth <- 0.01
best_ask <- min(depth_data[depth_data$side == "ASK",]$price)
best_bid <- max(depth_data[depth_data$side == "BID",]$price)
OrderBook(data = depth_data,
          min_price = best_bid*(1 - depth),

```

```
max_price = best_ask*(1 + depth),  
levels = 10,  
trades = NULL,  
as_datatable = FALSE)
```

# Index

## \* **AccountEndpoints**

- binance\_account\_balance, [5](#)
- binance\_account\_info, [6](#)
- binance\_account\_trades, [6](#)
- binance\_credentials, [9](#)

## \* **TradingEndpoints**

- binance\_cancel\_order, [8](#)
- binance\_get\_order, [14](#)
- binance\_new\_order, [18](#)

## \* **binanceVision**

- binance\_vision\_klines, [28](#)

## \* **generalEndpoints**

- binance\_exchange\_info, [11](#)
- binance\_ping, [21](#)
- binance\_time, [26](#)

## \* **marketEndpoints**

- binance\_avg\_price, [7](#)
- binance\_book\_ticker, [7](#)
- binance\_depth, [10](#)
- binance\_futures\_stats, [12](#)
- binance\_klines, [14](#)
- binance\_last\_open\_interest, [16](#)
- binance\_last\_trades, [17](#)
- binance\_open\_interest, [20](#)
- binance\_ticker24h, [23](#)
- binance\_ticker\_day, [24](#)
- binance\_ticker\_price, [25](#)
- binance\_trades, [27](#)

## \* **utils**

- binance\_query, [22](#)

- binance\_account\_balance, [5](#)
- binance\_account\_info, [6](#)
- binance\_account\_trades, [6](#)
- binance\_avg\_price, [7](#)
- binance\_book\_ticker, [7](#)
- binance\_cancel\_order, [8](#)
- binance\_credentials, [9](#)
- binance\_depth, [10](#)
- binance\_exchange\_info, [11](#)
- binance\_futures\_stats, [12](#)
- binance\_get\_order, [14](#)
- binance\_klines, [14](#)
- binance\_last\_open\_interest, [16](#)

- binance\_last\_trades, [17](#)

- binance\_new\_order, [18](#)

- binance\_open\_interest, [20](#)

- binance\_ping, [21](#)

- binance\_query, [22](#)

- binance\_ticker24h, [23](#)

- binance\_ticker\_day, [24](#)

- binance\_ticker\_price, [25](#)

- binance\_time, [26](#)

- binance\_trades, [27](#)

- binance\_vision\_klines, [28](#)

- binancer, [2](#)

- binancer-package (binancer), [2](#)

- binanceWebSocket, [3](#)

- content, [23](#)

- data.frame, [8](#), [29](#)

- datatable, [29](#)

- DELETE, [22](#)

- GET, [22](#)

- OrderBook, [29](#)

- POSIXt, [4](#), [6](#), [8](#), [10](#), [13](#), [15](#), [17](#), [18](#), [20](#), [21](#),  
[25–28](#)

- POST, [22](#)

- Sys.time(), [4](#), [6](#), [15](#), [17](#), [20](#), [27](#)

- tibble, [5](#), [6](#), [10](#), [11](#), [13](#), [15](#), [17](#), [18](#), [21](#), [24–29](#)

- xts, [15](#)