

Logistic Regression: Testing

To test your model, you would run a subset of your data, known as the validation set, on your model to get predictions. The predictions are the outputs of the sigmoid function. If the output is ≥ 0.5 , you would assign it to a positive class. Otherwise, you would assign it to a negative class.

$$\begin{aligned} & \bullet X_{val} Y_{val} \theta \\ & h(X_{val} \cdot \theta) \\ & pred = h(X_{val} \cdot \theta) \geq 0.5 \end{aligned} \quad \begin{bmatrix} 0.3 \\ 0.8 \\ 0.5 \\ \vdots \\ h_m \end{bmatrix} \geq 0.5 = \begin{bmatrix} 0.3 \geq 0.5 \\ 0.8 \geq 0.5 \\ 0.5 \geq 0.5 \\ \vdots \\ pred_m \geq 0.5 \end{bmatrix} = \begin{bmatrix} 0 \\ 1 \\ 1 \\ \vdots \\ pred_m \end{bmatrix}$$

In the video, I briefly mentioned X validation. In reality, given your X data you would usually split it into three components. X_{train} , X_{val} , X_{test} . The distribution usually varies depending on the size of your data set. However, an 80, 10, 10 split usually works fine.

To compute accuracy, you solve the following equation:

$$\text{Accuracy} \longrightarrow \sum_{i=1}^m \frac{(pred^{(i)} == y_{val}^{(i)})}{m}$$

In other words, you go over all your training examples, m of them, and then for every prediction, if it was right you add a one. You then divide by m .

✓ Complete

[Go to next item](#)