GENERAL ASSEMBLY

CLUSTERING

Naumaan Nayyar

EXIT TICKETS

- Review Logit / Sigmoid
- What is a link function, conceptually? When would we use arctan? Neural Networks
- How to optimize for lower false positives or negatives? ROC Curve
- Can logistic regression work with more than two classes? Yep and see here
- How would we measure the accuracy of the classification of any given point with logistic regression?
- Are there any practice notebooks?

LEARNING OBJECTIVES

- Supervised vs unsupervised algorithms
- Understand and apply k-means clustering
- Density-based clustering: DBSCAN
- Silhouette Metric

UNSUPERVISED LEARNING

UNSUPERVISED LEARNING

- So far all the algorithms we have used are *supervised*: each observation (row of data) came with one or more *labels*, either *categorical variables* (classes) or *measurements* (regression)
- **Unsupervised learning** has a different goal: **feature discovery**
- **Clustering** is a common and fundamental example of unsupervised learning
- **Clustering** algorithms try to find meaningful groups within data

CLUSTERING

CLUSTERING: Types of clustering algorithms

- Clustering algorithms are of several types based on model assumptions:
  - Centroid-based
  - Density-based
  - Hierarchical (connectivity- or linkage-based)
  - Distribution-based

CLUSTERING: Centroids



Source: http://stackoverflow.com/questions/24645068/k-means-clustering-major-understanding-issue

ACTIVITY: KNOWLEDGE CHECK

ANSWER THE FOLLOWING QUESTIONS

1. Why might data often appear in centered clusters?

DELIVERABLE

Answers to the above questions

CLUSTERING: Density-Based





Source: http://www.sthda.com/english/wiki/dbscan-density-based-clustering-for-discovering-clusters-in-large-datasets-with-noise-unsupervised-machine-learning

ACTIVITY: KNOWLEDGE CHECK

ANSWER THE FOLLOWING QUESTIONS

1. Why might data often appear in density-based clusters?

DELIVERABLE

Answers to the above questions

ACTIVITY: KNOWLEDGE CHECK



See also: http://www4.ncsu.edu/~jakatz2/files/dialectposter.png

CLUSTERING: Hierarchical

- Build hierarchies that form clusters
- Based on classification trees (next lesson)



ACTIVITY: KNOWLEDGE CHECK

ANSWER THE FOLLOWING QUESTIONS

1. How is unsupervised learning different from classification?

DELIVERABLE

Answers to the above questions

CLUSTERING

- There are many clustering algorithms



ACTIVITY: KNOWLEDGE CHECK

ANSWER THE FOLLOWING QUESTIONS

1. Can you think of a real-world clustering application?

DELIVERABLE

Answers to the above questions

ACTIVITY: KNOWLEDGE CHECK

ANSWERS

1. Recommendation Systems e.g. Netflix genres
2. Medical Imaging: differentiate tissues
3. Identifying market segments
4. Discover communities in social networks
5. Lots of applications for genomic sequences (homologous sequences, genotypes)
6. Earthquake epicenters
7. Fraud detection

K-MEANS: CENTRIOD CLUSTERING

K-MEANS CLUSTERING

- k-Means clustering is a popular centroid-based clustering algorithm
- Basic idea: find k clusters in the data centrally located around various mean points
- Awesome Demo

K-MEANS CLUSTERING

- k-Means seeks to minimize the sum of squares about the means

- Precisely, find k subsets S_1, … S_k of the data with means mu_1, …, mu_k that minimizes:

$$\arg\min_{\mathbf{S}} \sum_{i=1}^{k} \sum_{\mathbf{x} \in S_i} \left\| \mathbf{x} - \boldsymbol{\mu}_i \right\|^2$$

K-MEANS CLUSTERING

- This is a computationally difficult problem to solve so we rely on heuristics

- The “standard” heuristic is called “Lloyd’s Algorithm”:
  - Start with k initial mean values
  - Data points are then split up into a Voronoi diagram
    - Each point is assigned to the “closest” mean
  - Calculate new means based on centroids of points in the cluster
  - Repeat until clusters do not change

K-MEANS CLUSTERING

- Start with initial k mean values
- Data points are then split up into a Voronoi diagram
- Calculate new means based on centroids



K-MEANS CLUSTERING

- from sklearn.cluster import KMeans
- est = KMeans(n_clusters=3)
- est.fit(X)
- labels = est.labels_

Let's try it out!

ACTIVITY: KNOWLEDGE CHECK

ANSWER THE FOLLOWING QUESTIONS

1. How do we assign meaning to the clusters we find?
2. Do clusters always have meaning?

DELIVERABLE

Answers to the above questions

K-MEANS CLUSTERING

- Assumptions are important! k-Means assumes:
  - k is the correct number of clusters
  - the data is isotropically distributed (circular/spherical distribution)
  - the variance is the same for each variable
  - clusters are roughly the same size

Nice counterexamples / cases where assumptions are not met:

- http://varianceexplained.org/r/kmeans-free-lunch/
- Scikit-Learn Examples

K-MEANS CLUSTERING

- Netflix prize: Predict how users will rate a movie
  - How might you do this with clustering?
  - Cluster similar users together and take the average rating for a given movie by users in the cluster (which have rated the movie)
  - Use the average as the prediction for users that have not yet rated the movie

- In other words, fit a model to users in a cluster for each cluster and make predictions per cluster

- k-Means for the Netflix Prize

DBSCAN: DENSITY BASED CLUSTERING

DBSCAN CLUSTERING

- DBSCAN: Density-based spatial clustering of applications with noise (1996)

- Main idea: Group together closely-packed points by identifying
  - Core points
  - Reachable points
  - Outliers (not reachable)

- Two parameters:
  - min_samples
  - eps

DBSCAN CLUSTERING

- Core points: at least **min_samples** points within **eps** of the core point
  - Such points are *directly reachable* from the core point
- Reachable: point q is reachable from p if there is a path of core points from p to q
- Outlier: not reachable



DBSCAN CLUSTERING

- A cluster is a collection of connected core and reachable points



CLUSTERING: Density-Based

- Another example: Page 6
- Awesome Demo

DBSCAN CLUSTERING

- from sklearn.cluster import DBSCAN
- est = DBSCAN(eps=0.5, min_samples=10)
- est.fit(X)
- labels = est.labels_

Let's try it out!

ACTIVITY: KNOWLEDGE CHECK

ANSWER THE FOLLOWING QUESTIONS

1. How does DBSCAN differ from k-means?

DELIVERABLE

Answers to the above questions

DBSCAN CLUSTERING

- DBSCAN advantages:
  - Can find arbitrarily-shaped clusters
  - Don’t have to specify number of clusters
  - Robust to outliers

- DBSCAN disadvantages:
  - Doesn’t work well when clusters are of varying densities
    - hard to chose parameters that work for all clusters
  - Can be hard to chose correct parameters regardless

HIERARCHICAL CLUSTERING

CLUSTERING: Hierarchical

- Build hierarchies that form clusters
- Based on classification trees (next lesson)



HIERARCHICAL CLUSTERING

We'll discuss the details once we cover decision trees. For now we can black box the model and fit with sklearn

- from sklearn.cluster import AgglomerativeClustering
- est = AgglomerativeClustering(n_clusters=4)
- est.fit(X)
- labels = est.labels_

Let's try it out!

CLUSTERING METRICS

CLUSTERING METRICS

- As usual we need a metric to evaluate model fit

- For clustering we use a metric called the Silhouette Coefficient
  - **a** is the mean distance between a sample and all other points in the cluster
  - **b** is the mean distance between a sample and all other points in the *nearest* cluster

- The Silhouette Coefficient is:

$$\frac{b - a}{\max(a, b)}$$

- Ranges between 1 and -1
- Average over all points to judge the cluster algorithm

CLUSTERING METRICS

- from sklearn import metrics
- from sklearn.cluster import KMeans
- kmeans_model = KMeans(n_clusters=3, random_state=1).fit(X)
- labels = kmeans_model.labels_
- metrics.silhouette_score(X, labels, metric='euclidean')

CLUSTERING METRICS

- There are a number of other metrics based on:
  - Mutual Information
  - Homogeneity
  - Adjusted Rand Index (when you know the labels on the training data)

CLUSTERING, CLASSIFICATION, AND REGRESSION

ACTIVITY: KNOWLEDGE CHECK

ANSWER THE FOLLOWING QUESTIONS

1. How might we combine clustering and regression or classification?

DELIVERABLE

Answers to the above questions

CLUSTERING, CLASSIFICATION, AND REGRESSION

- We can use clustering to discover new features and then use those features for either classification or regression
- For classification, we could use e.g. k-NN to classify new points into the discovered clusters
- For regression, we could use a dummy variable for the clusters as a variable in our regression

ACTIVITY: CLUSTERING + REGRESSION

EXERCISE

1. Follow along as we do an example of clustering with regression.

DELIVERABLE

A completed notebook

TOPIC REVIEW

REVIEW AND NEXT STEPS

- Clustering is used to discover features, e.g. segment users or assign labels (such as species)

- Clustering may be the goal (user marketing) or a step in a data science pipeline

BEFORE NEXT CLASS

BEFORE NEXT CLASS

UPCOMING

- Final Project part 2
    - Due Date: June 15th

LESSON

Q & A

LESSON

EXIT TICKET

DON’T FORGET TO FILL OUT YOUR EXIT TICKET