

Care & Maintenance

Cleaning method by material for cellular, roller, Roman, sheer, faux wood, vinyl and shutter products.

FOR FACILITIES TEAMS

MAINTENANCE

Care and maintenance

Cleaning method by material, the products that void a finish, and a 15-minute seasonal check for a facilities schedule.

The rule that covers everything

Dry dust brushes away. Damp dust becomes a stain. So dust every window covering regularly and only introduce water where the material can take it.

Quick reference

MATERIAL	METHOD
Cellular	Dust, spot only
Roller	Damp wipe
Roman	Dust only
Sheer	Dust only
Faux wood	Damp wipe
Vinyl vertical	Damp wipe
Fabric vane	Hand wash
Shutters	Dust, damp wipe

Method by material

Cellular shades

Vacuum with a soft brush attachment on low suction, working across the cells rather than into them. Spot clean with a barely damp white cloth and blot dry. Never submerge a blackout shade: the foil liner can separate from the face fabric.

Roller and solar shades

Lower the shade fully and wipe the flat face with a damp microfibre cloth. Screen fabrics tolerate a little mild soap. Let it dry fully lowered before you roll it up, or you will trap moisture on the tube.

Roman and sheer shades

Dust only, then spot clean gently. Use a professional cleaner for anything larger than a spot. Washing removes the sizing that holds the folds and the shade will never hang the same way again.

Faux wood blinds

The easy one. Close the slats one way, wipe with a damp cloth, flip and repeat. A drop of dish soap handles kitchen grease. Skip furniture polish, which leaves a dust-attracting film.

Vinyl and fabric verticals, DualDrape™

Vinyl louvres wipe clean in place. Fabric vanes unclip: hand wash cool, hang flat to dry, re-clip. Never machine dry a vane.

Shutters

Dust the louvres closed in one direction, then reverse them and do the other side. Pay attention to the frame corners. On a painted finish, no solvents and no polish.

VOIDS THE FINISH

Never use bleach, ammonia, solvent cleaners, steam cleaners, or a magic-eraser sponge. All of them remove finish, and finish damage is not a manufacturing defect.

Seasonal check, 15 minutes

- 1 Raise and lower every shade fully. Anything that binds needs attention now.
- 2 Check that brackets are still tight; seasonal movement loosens screws.
- 3 Look at the bottom hem for curl or fraying.
- 4 Top up motorized battery packs before the low-battery warning appears.

FOR FACILITIES TEAMS

A cleaning method that damages a finish is not a manufacturing defect and is excluded from the warranty. Where a cleaning contractor is engaged, issue this document with the scope.

Published method at venetawindowfashions.com/how-to-clean. Questions: 1-855-558-1222.