

Safety data sheet

Page: 1/77

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Potassium Metabisulfite food grade (E224)

Chemical name: Dipotassium disulphite; potassium metabisulfite

CAS Number: 16731-55-8

REACH registration number: 01-2119537422-45-0001

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: food additive(s)

Recommended use: inorganic reducing agents, initial product for chemical syntheses, Chemical

For the detailed identified uses of the product see appendix of the safety data sheet.

1.3. Details of the supplier of the safety data sheet

Company:

BASF SE
67056 Ludwigshafen
GERMANY

Contact address:

BASF plc
PO Box 4, Earl Road, Cheadle Hulme,
Cheadle, Cheshire
SK8 6QG, UNITED KINGDOM

Telephone: +44 161 485-6222

E-mail address: product-safety-north@basf.com

1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

According to Regulation (EC) No 1272/2008 [CLP]

Eye Dam./Irrit. 1

H318

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

Globally Harmonized System, EU (GHS)

Pictogram:



Signal Word:

Danger

Hazard Statement:

H318 Causes serious eye damage.

Precautionary Statements (Prevention):

P280 Wear eye/face protection.

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

Labeling of special preparations (GHS):

EUH031: Contact with acids liberates toxic gas.

According to Regulation (EC) No 1272/2008 [CLP]

Hazard determining component(s) for labelling: dipotassium disulphite

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Chemical nature

Dipotassium disulphite

CAS Number: 16731-55-8

EC-Number: 240-795-3

K₂S₂O₅

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

3.2. Mixtures

Not applicable

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Remove contaminated clothing.

If inhaled:

If difficulties occur after dust has been inhaled, remove to fresh air and seek medical attention. After inhalation of decomposition products: Immediately administer a corticosteroid from a controlled/metered dose inhaler.

On skin contact:

Wash thoroughly with soap and water.

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Rinse mouth and then drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: allergic symptoms

Hazards: Risk of sulfur dioxide formation by reaction with gastric acid after swallowing.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:
foam

5.2. Special hazards arising from the substance or mixture

Sulphur dioxide

The substances/groups of substances mentioned can be released if the product is involved in a fire.

5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

Contaminated extinguishing water must be disposed of in accordance with official regulations. In case of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Ensure adequate ventilation. Avoid dust formation. Avoid contact with eyes.

6.2. Environmental precautions

Do not discharge into drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Sweep/shovel up. Correctly dispose of recovered product immediately.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Use only in well-ventilated areas. Avoid dust formation.

Protection against fire and explosion:

The substance/product is non-combustible. No special precautions necessary.

7.2. Conditions for safe storage, including any incompatibilities

Segregate from acids and acid forming substances. Segregate from oxidants.

Do not store with: Sodium nitrate, sodium nitrite, disodium sulfide; sodium sulfide

Further information on storage conditions: Keep in a cool place. Keep container dry. Keep container in a well-ventilated place.

7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

7681-57-4: sodium metabisulphite

TWA value 5 mg/m³ (WEL/EH 40 (UK))

The substance mentioned develops if the regulation/notes for storage and handling are not observed.

7446-09-5: Sulphur dioxide

PNEC

freshwater: 1.17 mg/l

marine water: 0.12 mg/l

sediment (freshwater):

Exposure of sediment is not expected

sediment (marine water):

Exposure of sediment is not expected

STP: 88.1 mg/l

DNEL

worker:

Long-term exposure- systemic effects, Inhalation: 263 mg/m³

consumer:

Long-term exposure- systemic effects, Inhalation: 78 mg/m³

consumer:

Long-term exposure- systemic effects, oral: 10 mg/kg

worker:

Inhalation

The nuisance dust limit (inhalativ fraction) was used as basis for the DNEL.

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Breathing protection if dusts are formed. Suitable respiratory protection for lower concentrations or short-term effect: Particle filter with low efficiency for solid particles (e.g. EN 143 or 149, Type P1 or FFP1) Breathing protection if breathable aerosols/dust are formed. Combination filter for gases/vapours of organic, inorganic, acid inorganic, alkaline compounds and toxic particles (e. g. EN 14387 Type ABEK-P3)

Hand protection:

Chemical resistant protective gloves (EN 374)

Suitable chemical resistant safety gloves (EN 374) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) etc.

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Do not inhale vapours or dust. Hands and/or face should be washed before breaks and at the end of the shift.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form:	powder
Colour:	white
Odour:	faint odour, of sulfur dioxide
Odour threshold:	Not determined due to potential health hazard by inhalation.

pH value:	3.8 - 4.6 (5 %(m))	
decomposition point:	approx. 150 °C Literature data.	
Melting point:	The substance / product decomposes therefore not determined.	
Boiling point:	not applicable	
Flash point:	not applicable	
Evaporation rate:	The product is a non-volatile solid.	
Flammability:	not flammable	(other)
Lower explosion limit:	For solids not relevant for classification and labelling.	
Upper explosion limit:	For solids not relevant for classification and labelling.	
Vapour pressure:	not applicable	
Density:	2.3 g/cm ³ (20 °C) Literature data.	
Relative density:	2.3 (20 °C) Literature data.	
Solubility in water:	Literature data. 495 g/l (25 °C)	
Partitioning coefficient n-octanol/water (log K _{ow}):	not applicable	
Self ignition:	not self-igniting	Test type: Self-ignition at high temperatures.
	not self-igniting	Test type: Spontaneous self- ignition at room-temperature.
Thermal decomposition:	> 150 °C To avoid thermal decomposition, do not overheat.	
Viscosity, dynamic:	not applicable	
Explosion hazard:	Based on the chemical structure there is no indicating of explosive properties.	
Fire promoting properties:	Based on its structural properties the product is not classified as oxidizing.	

9.2. Other information

Burning rate:	
Self heating ability:	Study scientifically not justified. It is not a substance capable of spontaneous heating.
Bulk density:	1,100 - 1,300 kg/m ³
pKA:	not applicable
Surface tension:	(other) Based on chemical structure, surface activity is not to be expected.

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Formation of flammable gases:	Remarks:	Forms no flammable gases in the presence of water.
-------------------------------	----------	--

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

Reacts with nitrites. Reacts with nitrates. Reacts with oxidizing agents.

10.4. Conditions to avoid

Avoid humidity.

10.5. Incompatible materials

Substances to avoid:
acids, oxidizing agents, nitrites, nitrates, sulfides

10.6. Hazardous decomposition products

Hazardous decomposition products:
Sulphur dioxide

SECTION 11: Toxicological Information

11.1. Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Of low toxicity after single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Experimental/calculated data:

LD50 rat (oral): approx. 2,300 mg/kg (BASF-Test)

LC50 rat (by inhalation): > 5.5 mg/l 4 h (OECD Guideline 403)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. Tested as dust aerosol.

LD50 rat (dermal): > 2,000 mg/kg (OECD Guideline 402)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Irritation

Assessment of irritating effects:

Risk of serious damage to eyes. Not irritating to the skin.

Experimental/calculated data:

Skin corrosion/irritation rabbit: non-irritant (BASF-Test)

Serious eye damage/irritation rabbit: irreversible damage (OECD Guideline 405)

Respiratory/Skin sensitization

Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. A sensitizing effect on particularly sensitive individuals cannot be excluded.

Experimental/calculated data:

Mouse Local Lymph Node Assay (LLNA) mouse: Non-sensitizing. (OECD Guideline 429)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Germ cell mutagenicity

Assessment of mutagenicity:

No mutagenic effect was found in various tests with bacteria and mammalian cell culture. The substance was not mutagenic in a test with mammals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity:

In long-term animal studies in which the substance was given in the drinking water in high doses, a carcinogenic effect was not observed.

Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Developmental toxicity

Assessment of teratogenicity:

No indications of a developmental toxic / teratogenic effect were seen in animal studies.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

No substance-specific organotoxicity was observed after repeated administration to animals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aspiration hazard

not applicable

SECTION 12: Ecological Information**12.1. Toxicity**

Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms.

Toxicity to fish:

LC50 (96 h) 460 - 1000 mg/l, *Brachydanio rerio* (OECD 203; ISO 7346; 84/449/EEC, C.1, static)
Nominal concentration.

Aquatic invertebrates:

EC50 (48 h) 89 mg/l, *Daphnia magna* (Directive 79/831/EEC, static)

Nominal concentration. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aquatic plants:

EC50 (72 h) 43.8 mg/l (growth rate), *Scenedesmus subspicatus* (Algal growth inhibition test, static)

Nominal concentration. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Microorganisms/Effect on activated sludge:

No observed effect concentration (180 min) $\geq$ 1,000 mg/l, (OECD Guideline 209, aquatic)

Nominal concentration. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Chronic toxicity to fish:

No observed effect concentration (34 d) $\geq$ 316 mg/l, Brachydanio rerio (OECD Guideline 210, Flow through.)

The details of the toxic effect relate to the nominal concentration. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Chronic toxicity to aquatic invertebrates:

No observed effect concentration (21 d) $>$ 10 mg/l, Daphnia magna (OECD Guideline 211, semistatic)

Nominal concentration. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Assessment of terrestrial toxicity:

Study does not need to be conducted.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H₂O):

Inorganic product which cannot be eliminated from water by biological purification processes.

Study scientifically not justified.

Assessment of stability in water:

According to structural properties, hydrolysis is not expected/probable.

Study scientifically not justified.

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface. Study scientifically not justified.

Adsorption in soil: Adsorption to solid soil phase is not expected. Study scientifically not justified.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

(Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative). Self classification

12.6. Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

12.7. Additional information

Sum parameter

Chemical oxygen demand (COD): (calculated) approx. 140 mg/g

Other ecotoxicological advice:

Higher concentrations of the substance may cause a strong chemical oxygen consumption in biological sewage-treatment plants and/or waterways. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

The UK Environmental Protection (Duty of Care) Regulations (EP) and amendments should be noted (United Kingdom).

This product and any uncleaned containers must be disposed of as hazardous waste in accordance with the 2005 Hazardous Waste Regulations and amendments (United Kingdom)

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

SECTION 14: Transport Information

Land transport

ADR

	Not classified as a dangerous good under transport regulations
UN number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for	None known

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

user

RID

	Not classified as a dangerous good under transport regulations
UN number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Inland waterway transport

ADN

	Not classified as a dangerous good under transport regulations
UN number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

	Not classified as a dangerous good under transport regulations
UN number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Air transport

IATA/ICAO

	Not classified as a dangerous good under transport regulations
UN number:	Not applicable

UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

14.1. UN number

See corresponding entries for "UN number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation:	Not evaluated
Shipment approved:	Not evaluated
Pollution name:	Not evaluated
Pollution category:	Not evaluated
Ship Type:	Not evaluated

SECTION 15: Regulatory Information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

The data should be considered when making any assessment under the Control of Substances Hazardous to Health Regulations (COSHH), and related guidance, for example, 'COSHH Essentials' (United Kingdom).

15.2. Chemical Safety Assessment

Chemical Safety Assessment performed

SECTION 16: Other Information

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Eye Dam./Irrit. 1
Acute Tox. 5 (oral)
Aquatic Acute 3

Any other intended applications should be discussed with the manufacturer.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Eye Dam./Irrit.	Serious eye damage/eye irritation
H318	Causes serious eye damage.

If you have any queries relating to this MSDS, its contents or any other product safety related questions, please write to the following e-mail address: product-safety-north@basf.com

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. The data do not describe the product's properties (product specification). Neither should any agreed property nor the suitability of the product for any specific purpose be deduced from the data contained in the safety data sheet. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

Annex: Exposure Scenarios

Index

1. Manufacture of substance, Industrial applications, (handling as solid in solution), (liquid preparations)
SU3; SU3, SU4, SU6b, SU7, SU8, SU9, SU10, SU16, SU20; ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC6d, ERC7, ERC8b; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC12, PROC13, PROC14, PROC15, PROC16, PROC17, PROC18, PROC19; PC1, PC2, PC3, PC4, PC7, PC8, PC9a, PC9b, PC13, PC14, PC15, PC17, PC18, PC19, PC20, PC23, PC24, PC25, PC26, PC28, PC30, PC31, PC32, PC34, PC35, PC37, PC38, PC39, PC40

2. Manufacture of substance, Industrial applications, (granules, low dustiness)
SU3; SU3, SU4, SU6b, SU7, SU8, SU9, SU10, SU16, SU20; ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC6d, ERC7, ERC8b; PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15, PROC16, PROC17, PROC18, PROC19, PROC21, PROC22, PROC23, PROC24, PROC25, PROC26; PC1, PC2, PC3, PC4, PC7, PC8, PC9a, PC9b, PC13, PC14, PC15, PC17, PC18, PC19, PC20, PC23, PC24, PC25, PC26, PC28, PC30, PC31, PC32, PC34, PC35, PC37, PC38, PC39, PC40

3. Manufacture of substance, Industrial applications, (mid powder, medium dustiness)
SU3; SU3, SU4, SU6b, SU7, SU8, SU9, SU10, SU16, SU20; ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC6d, ERC7, ERC8b; PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15, PROC16, PROC17, PROC18, PROC19, PROC22, PROC23, PROC24, PROC25, PROC26; PC1, PC2, PC3, PC4, PC7, PC8, PC9a, PC9b, PC13, PC14, PC15, PC17, PC18, PC19, PC20, PC23, PC24, PC25, PC26, PC28, PC30, PC31, PC32, PC34, PC35, PC37, PC38, PC39, PC40

4. Manufacture of substance, Industrial applications, (fine powder, high dustiness)
SU3; SU3, SU4, SU6b, SU7, SU8, SU9, SU10, SU16, SU20; ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC6d, ERC7, ERC8b; PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15, PROC16, PROC17, PROC18, PROC19, PROC22, PROC23, PROC24, PROC25, PROC26; PC1, PC2, PC3, PC4, PC7, PC8, PC9a, PC9b, PC13, PC14, PC15, PC17, PC18, PC19, PC20, PC23, PC24, PC25, PC26, PC28, PC30, PC31, PC32, PC34, PC35, PC37, PC38, PC39, PC40

5. Professional applications, (liquid preparations), (handling as solid in solution)
SU22; SU22; ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC6d, ERC7, ERC8b; PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC12, PROC13, PROC14, PROC15, PROC16, PROC17, PROC18, PROC19, PROC20; PC30

6. Professional applications, (granules, low dustiness)
SU22; SU22; ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC6d, ERC7, ERC8b; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC15, PROC16, PROC17, PROC18, PROC19, PROC21, PROC22, PROC23, PROC24, PROC25, PROC26; PC30

7. Professional applications, (mid powder, medium dustiness)
SU22; SU22; ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC6d, ERC7, ERC8b; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC15, PROC16, PROC17, PROC18, PROC19, PROC22, PROC23, PROC24, PROC25, PROC26; PC30

8. Professional applications, (fine powder, high dustiness)

SU22; SU22; ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC6d, ERC7, ERC8b; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC15, PROC16, PROC17, PROC18, PROC19, PROC22, PROC23, PROC24, PROC25, PROC26; PC30

9. Use in/as Photochemicals, (consumer use)

SU21; SU21; ERC8b; PC30

1. Short title of exposure scenario

Manufacture of substance, Industrial applications, (handling as solid in solution), (liquid preparations)
 SU3; SU3, SU4, SU6b, SU7, SU8, SU9, SU10, SU16, SU20; ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC6d, ERC7, ERC8b; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC12, PROC13, PROC14, PROC15, PROC16, PROC17, PROC18, PROC19; PC1, PC2, PC3, PC4, PC7, PC8, PC9a, PC9b, PC13, PC14, PC15, PC17, PC18, PC19, PC20, PC23, PC24, PC25, PC26, PC28, PC30, PC31, PC32, PC34, PC35, PC37, PC38, PC39, PC40

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	PROC1: Use in closed process, no likelihood of exposure. PROC2: Use in closed, continuous process with occasional controlled exposure. PROC12: Use of blow agents in manufacture of foam. Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	pasty
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Exposure estimate and reference to its source	
PROC1, PROC2, PROC12	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.001 mg/m ³
Risk Characterization Ratio (RCR)	< 0.001
PROC1, PROC2, PROC12	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC3: Use in closed batch process (synthesis or formulation). PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). PROC13: Treatment of articles by dipping and pouring. PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation. PROC15: Use a laboratory reagent. PROC16: Using material as fuel sources, limited exposure to unburned product to be expected. Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	pasty
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC3, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC16	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Exposure estimate	0.01 mg/m ³
Risk Characterization Ratio (RCR)	0.001
PROC3, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC16	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario

Use descriptors covered	PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact). PROC8a: Transfer of substance or preparation (charging/discharging) from/to ves-sels/large containers at non-dedicated facilities PROC10: Roller application or brushing PROC19: Hand-mixing with intimate contact and only PPE available. Use domain: industrial
--------------------------------	--

Operational conditions

Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	pasty
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

Risk Management Measures

Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	

Exposure estimate and reference to its source

PROC4, PROC5, PROC8a, PROC10, PROC19	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.05 mg/m ³
Risk Characterization Ratio (RCR)	0.005
PROC4, PROC5, PROC8a, PROC10, PROC19	
Assessment method	Qualitative assessment
	Worker - contact with eyes

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	pasty
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Provide extract ventilation to points where emissions occur (LEV).	Effectiveness: 78.0 %
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC7	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	4.4 mg/m ³
Risk Characterization Ratio (RCR)	0.44
PROC7	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC17: Lubrication at high energy conditions and in partly open process. PROC18: Greasing at high energy conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	pasty
Duration and Frequency of activity	480 min 5 days per week

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC17, PROC18	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.1 mg/m ³
Risk Characterization Ratio (RCR)	0.01
PROC17, PROC18	
Assessment method	Qualitative assessment
	Worker - contact with eyes
Contributing exposure scenario	
Use descriptors covered	As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

2. Short title of exposure scenario

Manufacture of substance, Industrial applications, (granules, low dustiness)

SU3; SU3, SU4, SU6b, SU7, SU8, SU9, SU10, SU16, SU20; ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC6d, ERC7, ERC8b; PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15, PROC16, PROC17, PROC18, PROC19, PROC21, PROC22, PROC23, PROC24, PROC25, PROC26; PC1, PC2, PC3, PC4, PC7, PC8, PC9a, PC9b, PC13, PC14, PC15, PC17, PC18, PC19, PC20, PC23, PC24, PC25, PC26, PC28, PC30, PC31, PC32, PC34, PC35, PC37, PC38, PC39, PC40

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	PROC1: Use in closed process, no likelihood of exposure. PROC2: Use in closed, continuous process with occasional controlled exposure. Use domain: industrial

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC1, PROC2	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.01 mg/m ³
Risk Characterization Ratio (RCR)	0.001
PROC1, PROC2	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC3: Use in closed batch process (synthesis or formulation). PROC6: Calendering operations PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). PROC13: Treatment of articles by dipping and pouring. PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation. PROC15: Use a laboratory reagent. PROC16: Using material as fuel sources, limited exposure to unburned product to be expected. Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

	Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC3, PROC6, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC16	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.1 mg/m ³
Risk Characterization Ratio (RCR)	0.01
PROC3, PROC6, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC16	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact). PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC10: Roller application or brushing PROC19: Hand-mixing with intimate contact and only PPE available. PROC21: Low energy manipulation of substances bound in materials and/or articles Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC4, PROC5, PROC8a, PROC10, PROC19, PROC21	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.5 mg/m ³
Risk Characterization Ratio (RCR)	0.05
PROC4, PROC5, PROC8a, PROC10, PROC19, PROC21	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying PROC17: Lubrication at high energy conditions and in partly open process. PROC18: Greasing at high energy conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC7, PROC17, PROC18	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	1 mg/m ³
Risk Characterization Ratio (RCR)	0.1
PROC7, PROC17, PROC18	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC22: Potentially closed processing operations (with minerals) at elevated temperature Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Melted mass, Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC22	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	7 mg/m ³
Risk Characterization Ratio (RCR)	0.7
PROC22	
Assessment method	Qualitative assessment
	Worker - contact with eyes

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Contributing exposure scenario	
Use descriptors covered	PROC23: Open processing and transfer operations (with minerals) at elevated temperature PROC25: Other hot work operations with metals Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Melted mass, Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC23, PROC25	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	2 mg/m ³
Risk Characterization Ratio (RCR)	0.2
PROC23, PROC25	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC24: High (mechanical) energy work-up of substances bound in materials and/or articles Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC24	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5.5 mg/m ³
Risk Characterization Ratio (RCR)	0.55
PROC24	
Assessment method	Qualitative assessment
	Worker - contact with eyes
Contributing exposure scenario	
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature. Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
PROC26	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	1.5 mg/m ³
Risk Characterization Ratio (RCR)	0.15
PROC26	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

3. Short title of exposure scenario

Manufacture of substance, Industrial applications, (mid powder, medium dustiness)
 SU3; SU3, SU4, SU6b, SU7, SU8, SU9, SU10, SU16, SU20; ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC6d, ERC7, ERC8b; PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15, PROC16, PROC17, PROC18, PROC19, PROC22, PROC23, PROC24, PROC25, PROC26; PC1, PC2, PC3, PC4, PC7, PC8, PC9a, PC9b, PC13, PC14, PC15, PC17, PC18, PC19, PC20, PC23, PC24, PC25, PC26, PC28, PC30, PC31, PC32, PC34, PC35, PC37, PC38, PC39, PC40

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	PROC1: Use in closed process, no likelihood of exposure. Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC1	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.01 mg/m ³
Risk Characterization Ratio (RCR)	0.001
PROC1	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC2: Use in closed, continuous process with occasional controlled exposure. Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
PROC2	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.5 mg/m ³
Risk Characterization Ratio (RCR)	0.05
PROC2	
Assessment method	Qualitative assessment

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

	Worker - contact with eyes
--	----------------------------

Contributing exposure scenario	
Use descriptors covered	PROC3: Use in closed batch process (synthesis or formulation). PROC13: Treatment of articles by dipping and pouring. PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation. Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC3, PROC13, PROC14	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	1 mg/m ³
Risk Characterization Ratio (RCR)	0.1
PROC3, PROC13, PROC14	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact). PROC6: Calendering operations PROC8a: Transfer of substance or preparation (charging/discharging) from/to ves-sels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

	(charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). PROC10: Roller application or brushing PROC16: Using material as fuel sources, limited exposure to unburned product to be expected. PROC19: Hand-mixing with intimate contact and only PPE available. Use domain: industrial
--	--

Operational conditions

Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

Risk Management Measures

Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	

Exposure estimate and reference to its source

PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC16, PROC19	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5 mg/m ³
Risk Characterization Ratio (RCR)	0.5
PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC16, PROC19	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario

Use descriptors covered	PROC7: Industrial spraying PROC17: Lubrication at high energy conditions and in partly open process. PROC18: Greasing at high energy conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Physical state	Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Provide extract ventilation to points where emissions occur (LEV).	Effectiveness: 78 %
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC7, PROC17, PROC18	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	4.4 mg/m ³
Risk Characterization Ratio (RCR)	0.44
PROC7, PROC17, PROC18	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC15	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.5 mg/m ³
Risk Characterization Ratio (RCR)	0.05
PROC15	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC22: Potentially closed processing operations (with minerals) at elevated temperature Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Melted mass, Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC22	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	7 mg/m ³

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Risk Characterization Ratio (RCR)	0.7
-----------------------------------	-----

Contributing exposure scenario	
Use descriptors covered	PROC23: Open processing and transfer operations (with minerals) at elevated temperature PROC25: Other hot work operations with metals Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Melted mass, Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC23, PROC25	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	2 mg/m ³
Risk Characterization Ratio (RCR)	0.2
PROC23, PROC25	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC24: High (mechanical) energy work-up of substances bound in materials and/or articles Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – medium dustiness

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC24	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5.5 mg/m ³
Risk Characterization Ratio (RCR)	0.5
PROC24	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature. Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	

Contributing exposure scenario	
Use descriptors covered	As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

4. Short title of exposure scenario

Manufacture of substance, Industrial applications, (fine powder, high dustiness)

SU3; SU3, SU4, SU6b, SU7, SU8, SU9, SU10, SU16, SU20; ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC6d, ERC7, ERC8b; PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15, PROC16, PROC17, PROC18, PROC19, PROC22, PROC23, PROC24, PROC25, PROC26; PC1, PC2, PC3, PC4, PC7, PC8, PC9a, PC9b, PC13, PC14, PC15, PC17, PC18, PC19, PC20, PC23, PC24, PC25, PC26, PC28, PC30, PC31, PC32, PC34, PC35, PC37, PC38, PC39, PC40

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	PROC1: Use in closed process, no likelihood of exposure. Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Exposure estimate and reference to its source	
PROC1	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.01 mg/m ³
Risk Characterization Ratio (RCR)	0.001
PROC1	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed batch process (synthesis or formulation). Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 9 % - <= 100 %
Physical state	Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC2, PROC3	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	1 mg/m ³
Risk Characterization Ratio (RCR)	0.1
PROC2, PROC3	
Assessment method	Qualitative assessment
	Worker - contact with eyes
Contributing exposure scenario	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Use descriptors covered	PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact). PROC6: Calendaring operations PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities Use domain: industrial
--------------------------------	--

Operational conditions

Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

Risk Management Measures

Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Provide extract ventilation to points where emissions occur (LEV).	Effectiveness: 78 %
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	

Exposure estimate and reference to its source

PROC4, PROC5, PROC6, PROC8b	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5.5 mg/m ³
Risk Characterization Ratio (RCR)	0.55
PROC4, PROC5, PROC6, PROC8b	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario

Use descriptors covered	PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC17: Lubrication at high energy conditions and in partly open process. PROC18: Greasing at high energy conditions. Use domain: industrial
--------------------------------	--

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Provide extract ventilation to points where emissions occur (LEV).	Effectiveness: 78 %
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes. Wear a respirator mask FFP1 conforming to DIN EN 149	
Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	2.75 mg/m ³
Risk Characterization Ratio (RCR)	0.275
Assessment method	Qualitative assessment
	Worker - contact with eyes
Guidance to Downstream Users	
For scaling see: http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Provide extract ventilation to points	Effectiveness: 78 %

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

where emissions occur (LEV).	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes. Wear a respirator mask FFP1 conforming to DIN EN 149	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5.5 mg/m ³
Risk Characterization Ratio (RCR)	0.55
Assessment method	Qualitative assessment
	Worker - contact with eyes
Guidance to Downstream Users	
For scaling see: http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Provide extract ventilation to points where emissions occur (LEV).	Effectiveness: 78 %
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC9	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	4.4 mg/m ³
Risk Characterization Ratio (RCR)	0.44
PROC9	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation. PROC16: Using material as fuel sources, limited exposure to unburned product to be expected. PROC26: Handling of solid inorganic substances at ambient temperature. Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Provide extract ventilation to points where emissions occur (LEV).	Effectiveness: 78 %
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC10, PROC14, PROC16, PROC26	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	2.2 mg/m ³

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Risk Characterization Ratio (RCR)	0.22
PROC10, PROC14, PROC16, PROC26	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC13, PROC15	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5 mg/m ³
Risk Characterization Ratio (RCR)	0.5
PROC13, PROC15	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC19: Hand-mixing with intimate contact and only PPE available. Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

	Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes. Wear a respirator mask FFP1 conforming to DIN EN 149	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	6.25 mg/m ³
Risk Characterization Ratio (RCR)	0.625
Assessment method	Qualitative assessment
	Worker - contact with eyes
Guidance to Downstream Users	
For scaling see: http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php	

Contributing exposure scenario	
Use descriptors covered	PROC21: Low energy manipulation of substances bound in materials and/or articles Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Melted mass, Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC22	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	7 mg/m ³
Risk Characterization Ratio (RCR)	0.7
PROC22	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC23: Open processing and transfer operations (with minerals) at elevated temperature PROC25: Other hot work operations with metals Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Melted mass, Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC23, PROC25	
Assessment method	MEASE

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

	Worker - inhalation, long-term - systemic
Exposure estimate	2 mg/m ³
Risk Characterization Ratio (RCR)	0.2
PROC23, PROC25	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC24: High (mechanical) energy work-up of substances bound in materials and/or articles Use domain: industrial
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC24	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5.5 mg/m ³
Risk Characterization Ratio (RCR)	0.55
PROC24	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

5. Short title of exposure scenario

Professional applications, (liquid preparations), (handling as solid in solution)

SU22; SU22; ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC6d, ERC7, ERC8b; PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC12, PROC13, PROC14, PROC15, PROC16, PROC17, PROC18, PROC19, PROC20; PC30

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	PROC2: Use in closed, continuous process with occasional controlled exposure. PROC12: Use of blow agents in manufacture of foam. PROC20: Heat and pressure transfer fluids in dispersive use but closed systems Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	pasty
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.001 mg/m ³
Risk Characterization Ratio (RCR)	< 0.001
Assessment method	Qualitative assessment
	Worker - contact with eyes
Guidance to Downstream Users	
For scaling see: http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Contributing exposure scenario	
Use descriptors covered	PROC3: Use in closed batch process (synthesis or formulation). PROC15: Use a laboratory reagent. Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	pasty
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC3, PROC15	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.01 mg/m ³
Risk Characterization Ratio (RCR)	0.001
PROC3, PROC15	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact). PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation. Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Physical state	pasty
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC4, PROC5, PROC14	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.1 mg/m ³
Risk Characterization Ratio (RCR)	0.01
PROC4, PROC5, PROC14	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or preparation (charging/discharging) from/to ves-sels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring. PROC19: Hand-mixing with intimate contact and only PPE available. Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	pasty
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC19	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.05 mg/m ³
Risk Characterization Ratio (RCR)	0.005
PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC19	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	pasty
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes. Wear a respirator mask FFP1 conforming to DIN EN 149	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5 mg/m ³
Risk Characterization Ratio (RCR)	0.5
Assessment method	Qualitative assessment
	Worker - contact with eyes
Guidance to Downstream Users	
For scaling see: http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php	

Contributing exposure scenario	
Use descriptors covered	PROC16: Using material as fuel sources, limited exposure to unburned product to be expected. PROC18: Greasing at high energy conditions. Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	pasty
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC16, PROC18	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.5 mg/m ³
Risk Characterization Ratio (RCR)	0.05
PROC16, PROC18	
Assessment method	Qualitative assessment
	Worker - contact with eyes

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Contributing exposure scenario	
Use descriptors covered	PROC17: Lubrication at high energy conditions and in partly open process. Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	pasty
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC17	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	1 mg/m ³
Risk Characterization Ratio (RCR)	0.1
PROC17	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

6. Short title of exposure scenario

Professional applications, (granules, low dustiness)

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

SU22; SU22; ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC6d, ERC7, ERC8b; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC15, PROC16, PROC17, PROC18, PROC19, PROC21, PROC22, PROC23, PROC24, PROC25, PROC26; PC30

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	PROC2: Use in closed, continuous process with occasional controlled exposure. Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC2	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.01 mg/m ³
Risk Characterization Ratio (RCR)	0.001
PROC2	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC3: Use in closed batch process (synthesis or formulation). PROC15: Use a laboratory reagent. Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

	Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC3, PROC15	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.1 mg/m ³
Risk Characterization Ratio (RCR)	0.01
PROC3, PROC15	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact). PROC6: Calendering operations PROC11: Non industrial spraying PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation. Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC4, PROC5, PROC6, PROC11, PROC14	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	1 mg/m ³
Risk Characterization Ratio (RCR)	0.1
PROC4, PROC5, PROC6, PROC11, PROC14	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring. PROC19: Hand-mixing with intimate contact and only PPE available. PROC21: Low energy manipulation of substances bound in materials and/or articles Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC19, PROC21	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.5 mg/m ³
Risk Characterization Ratio (RCR)	0.05
PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC19, PROC21	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC16: Using material as fuel sources, limited exposure to unburned product to be expected. PROC18: Greasing at high energy conditions. Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC16, PROC18	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5 mg/m ³

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Risk Characterization Ratio (RCR)	0.5
PROC16, PROC18	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC17: Lubrication at high energy conditions and in partly open process. Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes. Wear a respirator mask FFP1 conforming to DIN EN 149	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC17	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	2.5 mg/m ³
Risk Characterization Ratio (RCR)	0.25
PROC17	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC22: Potentially closed processing operations (with minerals) at elevated temperature Use domain: professional
Operational conditions	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Melted mass, Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes. Wear a respirator mask FFP1 conforming to DIN EN 149	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC22	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	2.5 mg/m ³
Risk Characterization Ratio (RCR)	0.25
PROC22	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC23: Open processing and transfer operations (with minerals) at elevated temperature Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Melted mass, Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
PROC23	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5 mg/m ³
Risk Characterization Ratio (RCR)	0.5
PROC23	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC24: High (mechanical) energy work-up of substances bound in materials and/or articles Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC24	
Assessment method	MEASE

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

	Worker - inhalation, long-term - systemic
Exposure estimate	5.5 mg/m ³
Risk Characterization Ratio (RCR)	0.55
PROC24	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC25: Other hot work operations with metals Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Melted mass, Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	CONTROLLED
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC25	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	4 mg/m³
Risk Characterization Ratio (RCR)	0.4
PROC25	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature. Use domain: professional
Operational conditions	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Solid – low dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC26	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	3 mg/m ³
Risk Characterization Ratio (RCR)	0.3
PROC26	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

7. Short title of exposure scenario

Professional applications, (mid powder, medium dustiness)

SU22; SU22; ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC6d, ERC7, ERC8b; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC15, PROC16, PROC17, PROC18, PROC19, PROC22, PROC23, PROC24, PROC25, PROC26; PC30

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

	batch process (synthesis or formulation). Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	1 mg/m ³
Risk Characterization Ratio (RCR)	0.1
Assessment method	Qualitative assessment
	Worker - contact with eyes
Guidance to Downstream Users	
For scaling see: http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php	

Contributing exposure scenario	
Use descriptors covered	PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact). PROC6: Calendering operations PROC8a: Transfer of substance or preparation (charging/discharging) from/to ves-sels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring. PROC14: Production of preparations or articles by

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

	tableting, compression, extrusion, pelettisation. PROC19: Hand-mixing with intimate contact and only PPE available. Use domain: professional
--	--

Operational conditions

Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per year
Indoor/Outdoor	Indoor

Risk Management Measures

Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	

Exposure estimate and reference to its source

PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC19	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5 mg/m ³
Risk Characterization Ratio (RCR)	0.5
PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC19	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario

Use descriptors covered	PROC11: Non industrial spraying PROC16: Using material as fuel sources, limited exposure to unburned product to be expected. Use domain: professional
--------------------------------	--

Operational conditions

Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes. Wear a respirator mask FFP1 conforming to DIN EN 149	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC11, PROC16	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5 mg/m ³
Risk Characterization Ratio (RCR)	0.5
PROC11, PROC16	
Assessment method	Qualitative assessment
	Worker - contact with eyes
Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Risk Management Measures are based on qualitative risk characterisation.	
Use suitable eye protection.	
Risk Management Measures are	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC15	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	0.5 mg/m ³
Risk Characterization Ratio (RCR)	0.05
PROC15	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	Indoor Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes. Wear a respirator mask FFP2 conforming to DIN EN 149	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC17, PROC18	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5 mg/m ³
Risk Characterization Ratio (RCR)	0.5
PROC17, PROC18	
Assessment method	Qualitative assessment
	Worker - contact with eyes

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Contributing exposure scenario	
Use descriptors covered	PROC22: Potentially closed processing operations (with minerals) at elevated temperature Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Melted mass, Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes. Wear a respirator mask FFP1 conforming to DIN EN 149	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC22	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	2.5 mg/m ³
Risk Characterization Ratio (RCR)	0.25
PROC22	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC23: Open processing and transfer operations (with minerals) at elevated temperature Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Melted mass, Solid – medium dustiness

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC23	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5 mg/m ³
Risk Characterization Ratio (RCR)	0.5
PROC23	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC24: High (mechanical) energy work-up of substances bound in materials and/or articles Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC24	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5.5 mg/m ³
Risk Characterization Ratio (RCR)	0.55
PROC24	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Melted mass, Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC25	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	4 mg/m ³
Risk Characterization Ratio (RCR)	0.4
PROC25	
Assessment method	Qualitative assessment
	Worker - contact with eyes
Contributing exposure scenario	
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature.

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

	Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – medium dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC26	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	8 mg/m ³
Risk Characterization Ratio (RCR)	0.8
PROC26	
Assessment method	Qualitative assessment
	Worker - contact with eyes
Contributing exposure scenario	
Use descriptors covered	As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

8. Short title of exposure scenario

Professional applications, (fine powder, high dustiness)

SU22; SU22; ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC6d, ERC7, ERC8b; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC15, PROC16, PROC17, PROC18, PROC19, PROC22, PROC23, PROC24, PROC25, PROC26; PC30

Control of exposure and risk management measures

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Contributing exposure scenario	
Use descriptors covered	PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed batch process (synthesis or formulation). PROC13: Treatment of articles by dipping and pouring. PROC15: Use a laboratory reagent. Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5 mg/m ³
Risk Characterization Ratio (RCR)	0.5
Assessment method	Qualitative assessment
	Worker - contact with eyes
Guidance to Downstream Users	
For scaling see: http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php	

Contributing exposure scenario	
Use descriptors covered	PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact). PROC6: Calendering operations PROC8a: Transfer of substance or preparation (charging/discharging) from/to ves-sels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

	dedicated facilities PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation. PROC16: Using material as fuel sources, limited exposure to unburned product to be expected. PROC19: Hand-mixing with intimate contact and only PPE available. Use domain: professional
--	--

Operational conditions

Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

Risk Management Measures

Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes. Wear a respirator mask FFP2 conforming to DIN EN 149	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	

Exposure estimate and reference to its source

Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5 mg/m ³
Risk Characterization Ratio (RCR)	0.5
Assessment method	Qualitative assessment
	Worker - contact with eyes

Guidance to Downstream UsersFor scaling see: <http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php>**Contributing exposure scenario**

Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). PROC26: Handling of solid inorganic substances at ambient temperature. Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

	Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes. Wear a respirator mask FFP1 conforming to DIN EN 149	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC9, PROC26	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5 mg/m ³
Risk Characterization Ratio (RCR)	0.5
PROC9, PROC26	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

suitable working clothes. Wear a respirator mask FFP1 conforming to DIN EN 149	
Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
PROC10	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	2.5 mg/m ³
Risk Characterization Ratio (RCR)	0.25
PROC10	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying PROC17: Lubrication at high energy conditions and in partly open process. PROC18: Greasing at high energy conditions. Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Solid – high Dustiness
Duration and Frequency of activity	< 60 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes. Wear a respirator mask FFP2 conforming to DIN EN 149	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	4 mg/m ³

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Risk Characterization Ratio (RCR)	0.4
Assessment method	Qualitative assessment
	Worker - contact with eyes
Guidance to Downstream Users	
For scaling see: http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php	

Contributing exposure scenario	
Use descriptors covered	PROC22: Potentially closed processing operations (with minerals) at elevated temperature Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Melted mass, Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	CONTROLLED
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes. Wear a respirator mask FFP1 conforming to DIN EN 149	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	2.5 mg/m³
Risk Characterization Ratio (RCR)	0.25
Assessment method	Qualitative assessment
	Worker - contact with eyes
Guidance to Downstream Users	
For scaling see: http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php	

Contributing exposure scenario	
Use descriptors covered	PROC23: Open processing and transfer operations (with minerals) at elevated temperature Use domain: professional

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Melted mass, Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5 mg/m ³
Risk Characterization Ratio (RCR)	0.5
Assessment method	Qualitative assessment
	Worker - contact with eyes
Guidance to Downstream Users	
For scaling see: http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php	

Contributing exposure scenario	
Use descriptors covered	PROC24: High (mechanical) energy work-up of substances bound in materials and/or articles Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: $\geq 0\%$ - $\leq 100\%$
Physical state	Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC24	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic
Exposure estimate	5.5 mg/m ³
Risk Characterization Ratio (RCR)	0.55
PROC24	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	PROC25: Other hot work operations with metals Use domain: professional
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 0 % - <= 100 %
Physical state	Melted mass, Solid – high Dustiness
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Clean equipment and the work area every day. Avoid frequent and direct contact with substance.	
Wear suitable face shield Use suitable chemically resistant gloves. Wear suitable working clothes.	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Risk Management Measures are based on qualitative risk characterisation.	
Exposure estimate and reference to its source	
PROC25	
Assessment method	MEASE
	Worker - inhalation, long-term - systemic

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

Exposure estimate	4 mg/m ³
Risk Characterization Ratio (RCR)	0.4
PROC25	
Assessment method	Qualitative assessment
	Worker - contact with eyes

Contributing exposure scenario	
Use descriptors covered	As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

9. Short title of exposure scenario

Use in/as Photochemicals, (consumer use)

SU21; SU21; ERC8b; PC30

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	PC30: Photochemicals. exposure of adults
Operational conditions	
Concentration of the substance	Dipotassium disulphite Content: >= 10 % - <= 20 %
Physical state	liquid
Duration and Frequency of activity	< 15 min 1 uses per day
Indoor/Outdoor	Indoor
Exposed skin area	Palm of both hands (430 cm ²), Both hands (820 cm ²), Fingertips (36 cm ²)
Risk Management Measures	
Application Area	Consumer use
Route of exposure	Eye
Consumer Measures	Use suitable eye protection.
	Risk Management Measures are based on qualitative risk characterisation.
Exposure estimate and reference to its source	
Assessment method	Qualitative assessment
	Consumer - inhalation, long-term - systemic
	Exposure is considered negligible.
Assessment method	Qualitative assessment
	Consumer - contact with eyes

Contributing exposure scenario	
Use descriptors covered	As no environmental hazard was identified no

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 05.02.2016

Version: 9.0

Product: **Potassium Metabisulfite food grade (E224)**

(ID no. 30042359/SDS_GEN_GB/EN)

Date of print 06.02.2016

	environmental-related exposure assessment and risk characterization was performed.
--	---

ORIGINAL CONTROLLED