

MATERIAL SAFETY DATA SHEET

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name : ECOM A-105 BK

Chemical Name and Synonyms: Polypropylene with Flame retardant

Chemical Family: Polyolefin

Manufacturer's Name: Siam Eco-Kasei co.,ltd.

Address: 3/4 Moo 1, Pimpawas Rd., Pimpa, Bangpakong,
Chachoengsao , 24180, Thailand

Emergency Telephone No: 038-570401

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	WT.%	CAS#
Polypropylene	≥ 95	9003-07-0
Brominated Flame retardant	2 - 3	84852-53-9
Antimony Trioxide	0.5 - 1	1309-64-4
Additives and colorant	1 - 2	Trade secret

Additional Information :

- This product is not considered to be hazardous under normal processing conditions.

SECTION 3 - HAZARDS IDENTIFICATION

- **POTENTIAL HEALTH EFFECTS**

EYE : Process vapors irritate eyes.

SKIN : Exposure to molten resin may cause thermal burns.

INHALATION : Process vapors may cause respiratory tract irritation.

INGESTION : Not Applicable.

- **SIGNS AND SYMPTOMS OF OVEREXPOSURE**

EYE : Irritation or redness.

SKIN : Not Applicable.

INGESTION : Not Applicable.

INHALATION : Irritation of the nose, throat and respiratory tract.

SECTION 4 - FIRST AID MEASURES

- **EYE**

Flush eyes with water for 15 minutes. Get medical attention.

- **SKIN**

Molten Resin: If molten material comes in contact with the skin, cool under ice water or a running stream of water. Do not attempt to remove the material from the skin. Remove could result in severe tissue damage. Get medical attention.

- **INHALATION**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

- **INGESTION**

Not Applicable.

SECTION 5 - FIRE FIGHTING MEASURES

- **FLAMMABILITY CLASSIFICATION :** 1.5mm V-2.
- **AUTOIGNITION TEMPERATURE :** Not applicable.
- **EXTINGUISHING MEDIA :** All conventional media are suitable.
- **HAZARDOUS COMBUSTION PRODUCTS :** Carbon monoxide unidentified organic compounds.
- **FIRE FIGHTING INSTRUCTIONS :** Wear a self-contained breathing apparatus and protective clothing to prevent skin and eye contact in fire situations.

SECTION 6 - ACCIDENTAL RELEASE MEASURE

- **SMALL SPILL:** Sweep up material and place in a disposal container.
- **LARGE SPILL:** Vacuum or sweep up material and place in a disposal container.
- **ENVIRONMENTAL PRECAUTIONS**
 - Water Spill : keep pellets out from waterways.
 - Land Spill : Not Yet Determined.
 - Air Spill : Not Yet Determined.
- **GENERAL PROCEDURES:** Vacuum or sweep up material and in a disposals container.
- **RELEASE NOTE :** None
- **SPECIAL PROTECTIVE EQUIPMENT:** None.

SECTION 7 - STORAGE AND HANDLING

- **GENERAL PROCEDURES:** Keep away from heat, sparks and flame.
- **HANDLING:** Ground and bond containers when transferring material.
- **STORAGE TEMPERATURE:** Ambient Temperature.
- **LOADING TEMPERATURE:** Ambient Temperature.
- **STORAGE PRESSURE:** Atmospheric.
- **STORAGE PRECAUTIONS:** Store in a cool place, well-ventilated place away from incompatible materials. Store away from direct of sunlight, especially for extend period of storage.
- **LOADING TEMPERATURE NOTES:** Not Yet Determined.
- **SHELF LIFE:** Not Yet Determined.
- **SPECIAL SENSITIVITY:** Not Yet Determined.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- **PERSONAL PROTECTIVE EQUIPMENT:**

Eyes and Face : Wear safety glasses with side shields (or goggles).

Skin : When handling or processing resins at elevated temperatures or in a molten state, wear protective clothing over the skin to prevent contact.

Respiratory : Where concentrations in air may exceed the limits given, work practice or other means of exposure reduction are not adequate, approved respirators may be necessary to prevent overexposure by inhalation.



Protective Clothing : When handling or processing resins at elevated temperatures or in a molten state, wear protective clothing over the skin to prevent contact.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- **PHYSICAL STATE :** Solid(Pellets)
- **ODOR :** Slightly odor
- **APPEARANCE :** Pellet.
- **COLOR :** Black
- **FREEZING POINT :** Not Applicable.
- **MELTING POINT :** No data
- **DENSITY :** $\approx 0.93 \text{ g/cm}^3$
- **MOLECULAR WEIGHT :** Not Applicable.
- **VISCOSITY :** Not Applicable
- **(VOC)NOTES :** Not Yet Determined.
- COMMENTS :**
- **PERCENT VOLATILE :** Not Applicable.
- **VAPOR PRESSURE :** Not Applicable.
- **BOILING POINT:** Not Applicable.
- **WATER SOLUBILITY:** Insoluble.

SECTION 10 - STABILITY AND REACTIVITY

- **STABLE :** Yes. (under normal condition of handling and use)
- **HAZARDOUS POLYMERIZATION :** Combustion may produce CO, hydrocarbons,hydrogen.
- **CONDITIONS TO AVOID :** Keep way from heat, sparks and flame.

SECTION 11 - TOXICOLOGICAL INFORMATION

- **GENERAL COMMENTS :** Please refer to Section 3 for available information on potential health effects.

SECTION 12 - ECOLOGICAL INFORMATION

- **ENVIRONMENTAL DATA :** Not Available.
- **ECOTOXICOLOGICAL INFORMATION :** Not Available.
- **DISTRIBUTION :** Not Available.
- **CHEMICAL FATE INFORMATION :** Not readily biodegradable.

SECTION 13 - DISPOSAL CONSIDERATIONS

- **DISPOSAL METHOD :**
 1. Recycle (reprocess).
 2. Incineration including energy recovery of waste material in a permitted facility in accordance with local, state or provincial and federal regulations.
 3. Land filling in a licensed facility in accordance with local, state or provincial and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

Not applicable, this product is not transport regulated.

SECTION 15 - OTHER INFORMATION

MANUFACTURER DISCLAIMER:

The information contained in this Material Safety Data Sheet has been compiled from sources which Siam Eco-Kasei co.,Ltd. considers reliable and accurate to the best of Siam Eco-Kasei co.,Ltd.'s knowledge. The information relates to the specific product described above, and not to use of the product in combination with another material. Customers and other users should read this MSDS and the product label carefully before using the product. Siam Eco-Kasei co.,Ltd.. neither assumes, nor authorizes anyone to assume on Siam Eco-Kasei co.,Ltd.'s behalf, any liability in connection with the use of the information in this MSDS.

Customers and other users should do their own testing before making commercial use of the product to ensure that the product is fit for the intended application and that the product can be used, and any waste material disposed of, safely, properly, and legally based on the customer's or other user's circumstances.

Siam Eco-Kasei co.,Ltd. makes no warranties, express or implied, with respect to the product, including (without limitation) warranties of merchantability or fitness for a particular purpose. The customer or other user of the product assumes all risk and liability arising out of the use of the product, whether used alone or in combination with other materials Siam Eco-Kasei co.,Ltd.'s liability, if any, for breach of contract, breach of warranty, negligence or other throat, strict liability, or any other claim shall not exceed in amount the purchase price of Siam Eco-Kasei co.,Ltd. products with respect to which such cause arose. In no event shall Siam Eco-Kasei co.,Ltd. be Liable for consequential, special, or incident damages.