



## SAFETY DATA SHEET

DOW CHEMICAL THAILAND LTD

**Product name:** 2-Ethylhexyl Acrylate, 15 ppm MEHQ

**Issue Date:** 01.03.2016

**Print Date:** 03.10.2017

DOW CHEMICAL THAILAND LTD encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

---

### 1. PRODUCT AND COMPANY IDENTIFICATION

---

**Product name:** 2-Ethylhexyl Acrylate, 15 ppm MEHQ

**Recommended use of the chemical and restrictions on use**

**Identified uses:** Manufacture of substance, industrial. Polymer production: Industrial (SU10) Uses in Coatings, industrial. Use in laboratories, industrial. Uses in Coatings, professional.

**COMPANY IDENTIFICATION**

DOW CHEMICAL THAILAND LTD  
15TH FLOOR, THE WHITE GROUP BUILDING 2,  
75 SOI RUBIA, SUKHUMVIT 42 ROAD,  
PRAKANONG, KLONGTOEY,  
THAILAND

**Customer Information Number:**

(66)2-3657000  
SDSQuestion@dow.com

**EMERGENCY TELEPHONE NUMBER**

**24-Hour Emergency Contact:** (66)38-925-400

**Local Emergency Contact:** 038-925-400

---

### 2. HAZARDS IDENTIFICATION

---

**Classification of the substance or mixture**

Flammable liquids - Category 4  
Acute toxicity - Category 5 - Oral  
Skin corrosion/irritation - Category 2  
Skin sensitisation - Sub-category 1B  
Specific target organ toxicity - single exposure - Category 3  
Aspiration hazard - Category 2  
Acute aquatic toxicity - Category 2  
Chronic aquatic toxicity - Category 3

**Label elements**

**Hazard pictograms**



Signal word: **WARNING!**

#### **Hazards**

Combustible liquid.  
May be harmful if swallowed.  
May be harmful if swallowed and enters airways.  
Causes skin irritation.  
May cause an allergic skin reaction.  
May cause respiratory irritation.  
Toxic to aquatic life.  
Harmful to aquatic life with long lasting effects.

#### **Precautionary statements**

##### **Prevention**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
Wash skin thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing should not be allowed out of the workplace.  
Avoid release to the environment.  
Wear protective gloves/ eye protection/ face protection.

##### **Response**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.  
IF ON SKIN: Wash with plenty of soap and water.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
Call a POISON CENTER or doctor/ physician if you feel unwell.  
Do NOT induce vomiting.  
If skin irritation or rash occurs: Get medical advice/ attention.  
Take off contaminated clothing and wash before reuse.  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

##### **Storage**

Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

##### **Disposal**

Dispose of contents/ container to an approved waste disposal plant.

#### **Other hazards**

No data available

---

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

---

This product is a substance.

| Component             | CASRN    | Concentration      |
|-----------------------|----------|--------------------|
| 2-Ethylhexyl acrylate | 103-11-7 | > 99.5 - < 100.0 % |

#### 4. FIRST AID MEASURES

##### Description of first aid measures

**General advice:** First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

**Skin contact:** Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands. Suitable emergency safety shower facility should be immediately available.

**Eye contact:** Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

**Ingestion:** Do not induce vomiting. Give one cup (8 ounces or 240 ml) of water or milk if available and transport to a medical facility. Do not give anything by mouth unless the person is fully conscious.

**Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

##### Indication of any immediate medical attention and special treatment needed

**Notes to physician:** May cause asthma-like (reactive airways) symptoms. Bronchodilators, expectorants, antitussives and corticosteroids may be of help. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. Maintain adequate ventilation and oxygenation of the patient. If burn is present, treat as any thermal burn, after decontamination. Due to irritant properties, swallowing may result in burns/ulceration of mouth, stomach and lower gastrointestinal tract with subsequent stricture. Aspiration of vomitus may cause lung injury. Suggest endotracheal/esophageal control if lavage is done. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

---

## **5. FIREFIGHTING MEASURES**

---

**Suitable extinguishing media:** Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

**Unsuitable extinguishing media:** None known.

**Special hazards arising from the substance or mixture**

**Hazardous combustion products:** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.

**Unusual Fire and Explosion Hazards:** Container may vent and/or rupture due to fire. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

**Advice for firefighters**

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Do not use direct water stream. May spread fire. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Avoid accumulation of water. Product may be carried across water surface spreading fire or contacting an ignition source. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

**Special protective equipment for firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

---

## **6. ACCIDENTAL RELEASE MEASURES**

---

**Personal precautions, protective equipment and emergency procedures:** Evacuate area. Refer to section 7, Handling, for additional precautionary measures. Only trained and properly protected personnel must be involved in clean-up operations. No smoking in area. Keep personnel out of low areas. Keep upwind of spill. Ventilate area of leak or spill. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Vapor explosion hazard. Keep out of sewers. For large spills, warn public of downwind explosion hazard. Check area with combustible gas detector before reentering area. Ground and bond all containers and handling equipment. See Section 10 for more specific information. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

**Environmental precautions:** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

**Methods and materials for containment and cleaning up:** Small spills: Absorb with materials such as: Sand. Sawdust. Large spills: Dike area to contain spill. Contain spilled material if possible.

Pump with explosion-proof equipment. If available, use foam to smother or suppress. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

---

## 7. HANDLING AND STORAGE

---

**Precautions for safe handling:** Keep away from heat, sparks and flame. Do not get on skin or clothing. Do not swallow. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Avoid breathing vapor. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling. Never use air pressure for transferring product. No smoking, open flames or sources of ignition in handling and storage area. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Electrically bond and ground all containers and equipment before transfer or use of material. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Use of non-sparking or explosion-proof equipment may be necessary, depending upon the type of operation.

**Conditions for safe storage:** Minimize sources of ignition, such as static build-up, heat, spark or flame. Keep container closed. Store in a dry place. Avoid moisture. Maintain inhibitor and dissolved oxygen level. Do not purge containers of this material with nitrogen. Recommended inhibitor level is: 10 to 20 ppm. Recommended oxygen level is: 5 to 8 vol. %. If storage is prolonged, the inhibitor concentration should be tested at least every 60 days. Flammable mixtures may exist within the vapor space of containers at room temperature. Uninhibited monomer vapors can polymerize and plug relief devices. Store away from incompatible materials. See STABILITY AND REACTIVITY section. Store in the following material(s): Glass-lined container. Opaque HDPE plastic container. Stainless steel. Aluminum. Carbon steel. Do not store in: Translucent container. See Section 10 for more specific information. Ask for a product brochure.

### Storage stability

**Storage temperature:** < 38 °C      **Shelf life: Use within** 12 Month

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### Control parameters

Exposure limits are listed below, if they exist.

| Component             | Regulation | Type of listing | Value/Notation |
|-----------------------|------------|-----------------|----------------|
| 2-Ethylhexyl acrylate | Dow IHG    | TWA             | 3 ppm          |

### Exposure controls

**Engineering controls:** Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

### Individual protection measures

**Eye/face protection:** Use safety glasses (with side shields). Safety glasses (with side shields) should be consistent with EN 166 or equivalent.

#### Skin protection

**Hand protection:** Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Polyethylene. Ethyl vinyl

alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Styrene/butadiene rubber. Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Avoid gloves made of: Neoprene. When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

Use the following CE approved air-purifying respirator: Organic vapor cartridge, type A (boiling point >65 °C)

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### Appearance

|                                      |                                           |
|--------------------------------------|-------------------------------------------|
| Physical state                       | Liquid.                                   |
| Color                                | Colorless                                 |
| Odor                                 | Sweet                                     |
| Odor Threshold                       | No test data available                    |
| pH                                   | No test data available                    |
| Melting point/range                  | Not applicable to liquids                 |
| Freezing point                       | -90 °C <i>Literature</i>                  |
| Boiling point (760 mmHg)             | 216 °C <i>Literature</i>                  |
| Flash point                          | <b>closed cup</b> 82 °C <i>Literature</i> |
| Evaporation Rate (Butyl Acetate = 1) | 0.03 <i>Literature</i>                    |
| Flammability (solid, gas)            | Not applicable to liquids                 |
| Lower explosion limit                | 0.7 % vol <i>Literature</i>               |
| Upper explosion limit                | 8.2 % vol <i>Literature</i>               |
| Vapor Pressure                       | 0.016 kPa at 20 °C <i>Literature</i>      |
| Relative Vapor Density (air = 1)     | 6.4 <i>Literature</i>                     |
| Relative Density (water = 1)         | 0.885 <i>Literature</i>                   |
| Water solubility                     | 0.01 % at 25 °C <i>Literature</i>         |

|                                        |                                                    |
|----------------------------------------|----------------------------------------------------|
| Partition coefficient: n-octanol/water | log Pow: 4.09 <i>Estimated.</i>                    |
| Auto-ignition temperature              | 252 °C <i>Literature</i>                           |
| Decomposition temperature              | No test data available                             |
| Dynamic Viscosity                      | 1.54 mPa.s at 25 °C <i>Literature</i>              |
| Kinematic Viscosity                    | No test data available                             |
| Explosive properties                   | No data available                                  |
| Oxidizing properties                   | No data available                                  |
| Liquid Density                         | 0.885 g/cm <sup>3</sup> at 20 °C <i>Literature</i> |
| Molecular weight                       | No test data available                             |

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

## 10. STABILITY AND REACTIVITY

---

**Reactivity:** No data available

**Chemical stability:** Stable under recommended storage conditions. See Storage, Section 7. Unstable at elevated temperatures. Hygroscopic

**Possibility of hazardous reactions:** Can occur. Elevated temperatures can cause hazardous polymerization. The inhibitor used with this monomer can separate if product becomes frozen. Polymerization can be catalyzed by: Absence of air. Free radical initiators. High temperature. Peroxides. Uninhibited monomer vapors can polymerize and plug relief devices. Presence of water can accelerate rate of polymerization.

**Conditions to avoid:** Avoid temperatures above 38 °C

Exposure to elevated temperatures can cause product to decompose. Avoid static discharge. Avoid moisture. Do not blanket or purge with an inert gas to avoid depleting the oxygen concentration. Avoid direct sunlight or ultraviolet sources.

**Inhibitor:** Methoxyphenol Inhibitor Concentration (ppm): 10 - 20  
Phenothiazine Inhibitor Concentration (ppm): 0.4 - 1.6

**Incompatible materials:** Avoid contact with oxidizing materials. Avoid contact with: Aldehydes. Amines. Azides. Ethers. Free radical initiators. Halides. Iron oxides (rust). Mercaptans. Mineral acids. Peroxides. Strong inorganic bases. Avoid contact with metals such as: Brass. Copper. Avoid unintended contact with: Activated carbon. Silica gel. Aluminum oxide. Avoid contact with absorbent materials such as: Clay-based absorbents. Avoid unintended contact with peroxides.

**Hazardous decomposition products:** Decomposition products depend upon temperature, air supply and the presence of other materials.

---

## 11. TOXICOLOGICAL INFORMATION

---

*Toxicological information appears in this section when such data is available.*



**Acute toxicity**

**Acute oral toxicity**

Low toxicity if swallowed. Swallowing may result in gastrointestinal irritation or ulceration. Swallowing may result in burns of the mouth and throat.

LD50, Rat, male and female, 4,435 mg/kg OECD 401 or equivalent

**Acute dermal toxicity**

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

LD50, Rabbit, 7,522 mg/kg

**Acute inhalation toxicity**

Prolonged excessive exposure may cause adverse effects. Excessive exposure may cause severe irritation to upper respiratory tract (nose and throat) and lungs. Signs and symptoms of excessive exposure may include: May cause dizziness and drowsiness. Headache. May cause pulmonary edema (fluid in the lungs.) Effects may be delayed.

LC50, Rat, male and female, 8 Hour, vapour, > 1.19 mg/l No deaths occurred following exposure to a saturated atmosphere.

**Skin corrosion/irritation**

Brief contact may cause severe skin irritation with pain and local redness.

Repeated contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage.

**Serious eye damage/eye irritation**

May cause slight temporary eye irritation.

Corneal injury is unlikely.

**Sensitization**

For skin sensitization:

Has caused allergic skin reactions in humans.

Has caused allergic skin reactions when tested in guinea pigs.

Has demonstrated the potential for contact allergy in mice.

For respiratory sensitization:

No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

May cause respiratory irritation.

Route of Exposure: Inhalation

Target Organs: Respiratory system

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

In animals, effects have been reported on the following organs:

Respiratory tract.

**Carcinogenicity**

Has caused tumors in skin painting tests in animals. Positive findings are believed to be secondary to chronic irritation/tissue injury.

**Teratogenicity**



Did not cause birth defects or other effects in the fetus even at doses which caused toxic effects in the mother.

**Reproductive toxicity**

In animal studies, did not interfere with reproduction. In animal studies, did not interfere with fertility.

**Mutagenicity**

In vitro genetic toxicity studies were predominantly negative. Animal genetic toxicity studies were negative.

**Aspiration Hazard**

May be harmful if swallowed and enters airways.

---

**12. ECOLOGICAL INFORMATION**

---

*Ecotoxicological information appears in this section when such data is available.*

**General Information**

Material is toxic to aquatic organisms (LC50/EC50/IC50 between 1 and 10 mg/L in the most sensitive species).

**Ecotoxicity****Acute toxicity to fish**

Material is toxic to aquatic organisms (LC50/EC50/IC50 between 1 and 10 mg/L in the most sensitive species).

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 1.81 mg/l, OECD Test Guideline 203 or Equivalent

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), static test, 48 Hour, 1.3 mg/l, OECD Test Guideline 202 or Equivalent

**Acute toxicity to algae/aquatic plants**

ErC50, Desmodesmus subspicatus (green algae), static test, 72 Hour, Growth rate inhibition, 1.71 mg/l, OECD Test Guideline 201 or Equivalent

**Chronic aquatic toxicity****Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), 21 d, number of offspring, 0.19 mg/l

**Persistence and degradability**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

**Biodegradation:** 70 - 80 %

**Exposure time:** 15 d

10-day Window: Not applicable

**Biodegradation:** > 90 %

**Exposure time:** 14 d

**Method:** OECD Test Guideline 301C or Equivalent

**Theoretical Oxygen Demand:** 2.60 mg/mg

**Bioaccumulative potential**

**Bioaccumulation:** Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

**Partition coefficient: n-octanol/water(log Pow):** 4.09 Estimated.

**Bioconcentration factor (BCF):** 270 - 282 Fish Estimated.

**Mobility in Soil**

Potential for mobility in soil is medium (Koc between 150 and 500).

**Partition coefficient(Koc):** 429 Estimated.

**Results of PBT and vPvB assessment**

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

**Other adverse effects**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

---

## **13. DISPOSAL CONSIDERATIONS**

---

**Disposal methods:** DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

This product when disposed of in its unused and uncontaminated state should be treated as a hazardous waste.

---

## **14. TRANSPORT INFORMATION**

---

**Classification for ROAD and Rail transport:**

Not regulated for transport

**Classification for SEA transport (IMO-IMDG):**

Not regulated for transport

**Transport in bulk  
according to Annex I or II  
of MARPOL 73/78 and the  
IBC or IGC Code**

Consult IMO regulations before transporting ocean bulk

**Classification for AIR transport (IATA/ICAO):**

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

---

## **15. REGULATORY INFORMATION**

---

### **Thailand: Hazardous Substance Act, B.E. 2535**

A component(s) of this product is classified according to Thai Hazardous Substance Acts- type 2.

### **Thailand: Notification of Department of Labour Protection and Welfare (List of Hazardous Chemicals)**

One or more components of this product are listed.

---

## **16. OTHER INFORMATION**

---

### **Product Literature**

Additional information on this product may be obtained by calling your sales or customer service contact. Ask for a product brochure. Additional information on this and other products may be obtained by visiting our web page.

### **Revision**

Identification Number: 101197063 / A176 / Issue Date: 01.03.2016 / Version: 5.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

### **Legend**

|         |                                  |
|---------|----------------------------------|
| Dow IHG | Dow Industrial Hygiene Guideline |
| TWA     | Time Weighted Average (TWA):     |

DOW CHEMICAL THAILAND LTD urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-

specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.