



SAFETY DATA SHEET

DOW CHEMICAL THAILAND LTD

Product name: Glycidyl Methacrylate

Issue Date: 20.12.2023

Print Date: 21.12.2023

DOW CHEMICAL THAILAND LTD encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Glycidyl Methacrylate

Recommended use of the chemical and restrictions on use

Identified uses: Chemical intermediate. We recommend that you use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact your sales or technical service representative.

Uses advised against: Unreacted monomer is not appropriate for use in cosmetic applications, such as artificial nail products.

COMPANY IDENTIFICATION

DOW CHEMICAL THAILAND LTD
111 TRUE DIGITAL PARK WEST,
UNICORN BUILDING, 8th FLOOR,
SUKHUMVIT ROAD, BANGCHAK, PRAKANONG
BANGKOK 10260
THAILAND

Customer Information Number:

(66)2-4917000
SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: (66)38-925-400

Local Emergency Contact: 038-925-400

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids - Category 4

Acute toxicity - Category 4 - Oral

Acute toxicity - Category 3 - Dermal

Skin corrosion/irritation - Category 1

Serious eye damage/eye irritation - Category 1

Skin sensitisation - Category 1

Germ cell mutagenicity - Category 2

Carcinogenicity - Category 1B

Reproductive toxicity - Category 1B

Specific target organ toxicity - single exposure - Category 3

Specific target organ toxicity - repeated exposure - Category 1 - Inhalation

Aspiration hazard - Category 2
Short-term (acute) aquatic hazard - Category 2

GHS label elements**Hazard pictograms**

Signal word: **DANGER!**

Hazard statements

Combustible liquid.
Harmful if swallowed.
May be harmful if swallowed and enters airways.
Toxic in contact with skin.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
May cause respiratory irritation.
Suspected of causing genetic defects.
May cause cancer.
May damage fertility or the unborn child.
Causes damage to organs (Respiratory Tract) through prolonged or repeated exposure if inhaled.
Toxic to aquatic life.

Precautionary statements**Prevention**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Do not breathe mist or vapours.
Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
Avoid release to the environment.
Wear protective gloves, protective clothing, eye protection and/or face protection.
Use personal protective equipment as required.

Response

IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

IF exposed or concerned: Get medical advice/ attention.

If skin irritation or rash occurs: Get medical advice/ attention.

Wash contaminated clothing before reuse.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal

Dispose of contents and/or container to an approved waste disposal plant.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a substance.

Component	CASRN	Concentration
2,3-Epoxypropyl methacrylate	106-91-2	>= 99.0 - < 100.0 %

4. FIRST AID MEASURES

Description of first aid measures**General advice:**

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin contact: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing. Seek medical attention if symptoms occur or irritation persists. Wash clothing before reuse. Suitable emergency safety shower facility should be immediately available.

Eye contact: Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: Do not induce vomiting. Call a physician and/or transport to emergency facility immediately.

Most important symptoms and effects, both acute and delayed:

Harmful if swallowed. May be harmful if swallowed and enters airways. Toxic in contact with skin. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. Suspected of causing genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure if inhaled. Causes severe burns.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Maintain adequate ventilation and oxygenation of the patient. If burn is present, treat as any thermal burn, after decontamination. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Because rapid absorption may occur through the lungs if aspirated and cause systemic effects, the decision of whether to induce vomiting or not should be made by a physician. Due to irritant properties, swallowing may result in burns and/or ulceration of mouth, stomach and lower gastrointestinal tract with subsequent stricture. Aspiration of vomitus may cause lung injury. Suggest endotracheal or esophageal control if lavage is done. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam. Dry chemical. Dry sand.

Unsuitable extinguishing media: High volume water jet. Do not use direct water stream..

Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides.

Unusual Fire and Explosion Hazards: Flash back possible over considerable distance.. Exposure to combustion products may be a hazard to health.. Heat can cause polymerization. Heated containers can explode.. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat.. Vapours may form explosive mixtures with air..

Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers.. Evacuate area.. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage.. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.. **EXPLOSION HAZARD.** Fight advanced fires from a protected location.. Do not use a solid water stream as it may scatter and spread fire.. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus.. Use personal protective equipment..

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Do not release the product to the aquatic environment above defined regulatory levels. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. Clean up remaining materials from spill with suitable absorbant. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Dispose of promptly. Contaminated monomer may be unstable. Add inhibitor to prevent polymerization. Absorbent can act as a contaminant (removes inhibitor) in liquid monomer. Avoid freestanding monomer with absorbent or add inhibitor to stabilize. Dispose of promptly. See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not get on skin or clothing. Do not breathe vapours or spray mist. Do not swallow. Do not get in eyes. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied. Use with local exhaust ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Conditions for safe storage: Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition. Material can burn; limit indoor storage to approved areas equipped with automatic sprinklers. Total absence of oxygen will inactivate the inhibitor. This product contains inhibitor to stabilize it during shipment and storage. The effectiveness of the inhibitor is dependent on the presence of dissolved oxygen. In order to maintain sufficient dissolved oxygen in the liquid to avoid polymerization, the monomer must always be stored with a vapor space oxygen concentration of 5% to 21%(air). Do not store under oxygen-free environment.

Storage stability

Storage temperature:	Shelf life: Use within
< 25 °C	12 Month

Do not store with the following product types: Strong oxidizing agents. Organic peroxides. Explosives. Gases.

Unsuitable materials for containers: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
2,3-Epoxypropyl methacrylate	US WEEL	TWA	0.5 ppm
	Further information: Skin; DSEN: Dermal Sensitization Notation		
	ACGIH	TWA	0.01 ppm
	Further information: DSEN: Dermal Sensitization; A2: Suspected human carcinogen; Skin: Danger of cutaneous absorption		
	Dow IHG	TWA	0.1 ppm
	Further information: SKIN, DSEN: Absorbed via Skin, Skin Sensitizer		

Exposure controls

Engineering controls: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles. If exposure causes eye discomfort, use a full-face respirator.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Styrene/butadiene rubber. Examples of acceptable glove barrier materials include: Butyl rubber. Avoid gloves made of: Viton. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state

Liquid.

Color

Colorless

Odor	Sharp
Odor Threshold	No test data available
pH	No test data available
Melting point/range	-41.5 °C <i>Literature</i>
Freezing point	-70 °C <i>Literature</i>
Boiling point (760 mmHg)	189 °C <i>Literature</i>
Flash point	closed cup 76 °C at 1 atm <i>EPA OPPTS 830.6315 (Flammability)</i>
Evaporation Rate (Butyl Acetate = 1)	No test data available
Flammability (solid, gas)	Not applicable to liquids
Flammability (liquids)	Not expected to be a static-accumulating flammable liquid.
Lower explosion limit	1.1 % vol <i>Literature</i>
Upper explosion limit	No test data available
Vapor Pressure	0.33 mmHg at 25 °C <i>Literature</i>
Relative Vapor Density (air = 1)	4.9 <i>Literature</i>
Relative Density (water = 1)	1.067 - 1.079 <i>DOWM 101229-TE92A</i>
Water solubility	50 g/L at 25 °C <i>OECD Test Guideline 105</i> insoluble
Partition coefficient: n-octanol/water	log Pow: 0.96 <i>Estimated.</i>
Auto-ignition temperature	389 °C at 1,013 hPa <i>EC Method A15</i>
Decomposition temperature	No data available
Dynamic Viscosity	2.53 mPa.s at 20 °C <i>Literature</i>
Kinematic Viscosity	No test data available
Explosive properties	Not explosive
Oxidizing properties	No
Liquid Density	1.067 - 1.079 g/cm ³ at 25 °C <i>Test method in development</i>
Molecular weight	142.2 g/mol <i>Literature</i>
Pour point	-90 °C <i>Literature</i>

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Excessive aging, heat, contamination with polymerization catalysts, oxygen-free atmosphere, inhibitor depletion or ultraviolet light (sunlight) may cause polymerization. Excessive aging, heat, contamination with polymerization catalysts, oxygen-free atmosphere, inhibitor depletion or ultraviolet light (sunlight) may cause polymerization.

Chemical stability: Unstable at elevated temperatures.

Possibility of hazardous reactions: An uncontrolled polymerization may produce a rapid release of energy with the potential for an explosion of unvented closed containers. Can react with strong oxidizing agents. Vapours may form explosive mixture with air. Inhibitor is added to this product to prevent polymerization. However, this material can undergo hazardous polymerization.

Conditions to avoid: Exposure to elevated temperatures can cause product to decompose. Do not blanket or purge with an inert gas to avoid depleting the oxygen concentration. Avoid direct sunlight or ultraviolet sources. Heat, flames and sparks.

Incompatible materials: Avoid contact with oxidizing materials.

Hazardous decomposition products

No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data are available.

Information on likely routes of exposure

Inhalation, Eye contact, Skin contact, Ingestion.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Acute Toxicity Endpoints:

Harmful if swallowed., Toxic in contact with skin.

Acute oral toxicity

Information for the Product:

Low toxicity if swallowed. Swallowing may result in gastrointestinal irritation or ulceration. Swallowing may result in burns of the mouth and throat.

Based on product testing:
LD50, Rat, 597 mg/kg

Information for components:

2,3-Epoxypropyl methacrylate

LD50, Rat, 597 mg/kg

Acute dermal toxicity

Information for the Product:

Prolonged or widespread skin contact may result in absorption of harmful amounts.

Based on product testing:
LD50, Rabbit, 480 mg/kg

Information for components:

2,3-Epoxypropyl methacrylate

LD50, Rabbit, 480 mg/kg

Acute inhalation toxicity

Information for the Product:

Prolonged excessive exposure may cause adverse effects. May cause dizziness and drowsiness. Vapor may cause severe irritation of the upper respiratory tract (nose and throat).

Based on product testing:

LC50, Rat, 4 Hour, vapour, > 2.4 mg/l No deaths occurred at this concentration.

Information for components:

2,3-Epoxypropyl methacrylate

Prolonged excessive exposure may cause adverse effects. May cause dizziness and drowsiness. Vapor may cause severe irritation of the upper respiratory tract (nose and throat).

LCLo, Rat, 4 Hour, vapour, > 2.4 mg/l No deaths occurred at this concentration.

Skin corrosion/irritation

Causes severe burns.

Information for the Product:

Based on product testing:

Brief contact may cause skin burns. Symptoms may include pain, severe local redness and tissue damage.

Information for components:

2,3-Epoxypropyl methacrylate

Brief contact may cause skin burns. Symptoms may include pain, severe local redness and tissue damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Information for the Product:

Based on product testing:

May cause severe eye irritation.

May cause severe corneal injury.

Effects may be slow to heal.

Vapor may cause corneal injury.

Information for components:

2,3-Epoxypropyl methacrylate

May cause severe eye irritation.
May cause severe corneal injury.
Effects may be slow to heal.
Vapor may cause corneal injury.

Sensitization

For skin sensitization:

May cause an allergic skin reaction.

For respiratory sensitization:

Not classified based on available information.

Information for the Product:

Skin contact may cause an allergic skin reaction.

For respiratory sensitization:

No relevant data found.

Information for components:

2,3-Epoxypropyl methacrylate

For skin sensitization:

Skin contact may cause an allergic skin reaction.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

May cause respiratory irritation.

Information for the Product:

May cause respiratory irritation.

Route of Exposure: Inhalation

Target Organs: Respiratory Tract

Information for components:

2,3-Epoxypropyl methacrylate

May cause respiratory irritation.

Route of Exposure: Inhalation

Target Organs: Respiratory Tract

Aspiration Hazard

May be harmful if swallowed and enters airways.

Information for the Product:

Aspiration into the respiratory system may occur during ingestion or vomiting. Due to corrosivity, tissue damage or lung injury may occur.

Information for components:**2,3-Epoxypropyl methacrylate**

Aspiration into the respiratory system may occur during ingestion or vomiting. Due to corrosivity, tissue damage or lung injury may occur.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Causes damage to organs (Respiratory Tract) through prolonged or repeated exposure if inhaled.

Information for the Product:

In animals, effects have been reported on the following organs after inhalation:
Nasal tissue.

Information for components:**2,3-Epoxypropyl methacrylate**

In animals, effects have been reported on the following organs after inhalation:
Nasal tissue.

Carcinogenicity

May cause cancer.

Information for the Product:

Based on the metabolite(s): Has caused cancer in laboratory animals.

Information for components:**2,3-Epoxypropyl methacrylate**

Based on the metabolite(s): Has caused cancer in laboratory animals.

Carcinogenicity**Component****2,3-Epoxypropyl methacrylate****List**

IARC

ACGIH

Classification

Group 2A: Probably carcinogenic to humans

A2: Suspected human carcinogen

Teratogenicity

May damage fertility or the unborn child.

Information for the Product:

Did not cause birth defects or other effects in the fetus even at doses which caused toxic effects in the mother.

Information for components:**2,3-Epoxypropyl methacrylate**

Did not cause birth defects or other effects in the fetus even at doses which caused toxic effects in the mother.

Reproductive toxicity

May damage fertility or the unborn child.

Information for the Product:

In animal studies, has been shown to interfere with fertility.

Information for components:**2,3-Epoxypropyl methacrylate**

In animal studies, has been shown to interfere with fertility.

Mutagenicity

Suspected of causing genetic defects.

Information for the Product:

In vitro genetic toxicity studies were positive. Animal genetic toxicity studies were negative in some cases and positive in other cases.

Information for components:**2,3-Epoxypropyl methacrylate**

In vitro genetic toxicity studies were positive. Animal genetic toxicity studies were negative in some cases and positive in other cases.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data are available.

Ecotoxicity**Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, *Oryzias latipes* (Orange-red killifish), semi-static test, 96 Hour, 2.8 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

EC50, *Daphnia magna* (Water flea), semi-static test, 48 Hour, 24.9 mg/l

Acute toxicity to algae/aquatic plants

EC50, *Pseudokirchneriella subcapitata* (green algae), static test, 72 Hour, Biomass, 14.6 mg/l

Long-term (chronic) aquatic hazard**Chronic toxicity to fish**

NOEC, *Oryzias latipes* (Orange-red killifish), flow-through test, 14 d, mortality, 1.2 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, 1.02 mg/l

Persistence and degradability

Biodegradability: Material is expected to be readily biodegradable.

10-day Window: Not applicable

Biodegradation: 100 %

Exposure time: 28 d

Method: OECD Test Guideline 301C or Equivalent

Theoretical Oxygen Demand: 1.8 mg/g

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	4 %
10 d	39 %
20 d	57 %
28 d	44 %

Bioaccumulative potential

Bioaccumulation: Bioconcentration potential is low ($BCF < 100$ or $\log Pow < 3$).

Partition coefficient: n-octanol/water(log Pow): 0.96 at 25 °C Estimated.

Mobility in Soil

Partition coefficient (Koc): 10 Estimated.

Results of PBT and vPvB assessment

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Other adverse effects

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Waste characterizations and compliance with applicable laws are the responsibility of the waste generator. FOR UNUSED & UNCONTAMINATED PRODUCT, dispose the product in a permitted industrial waste facility per applicable regulations. Consult the local waste disposal expert about the appropriate waste disposal method. Mechanical and chemical recycling or energy recovery are the preferred options. If not possible, consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Contaminated packaging: Empty containers may retain product residues and should be disposed of by an approved waste management facility. Label warnings should be followed even after container is

emptied. Improper disposal or reuse of this container may be dangerous and illegal. Consult with the respective regulating authorities to determine the available treatment and disposal facilities. All disposal practices must be in compliance with Federal, State/Provincial and local regulations.

14. TRANSPORT INFORMATION

Classification for ROAD and Rail transport:

Proper shipping name	CORROSIVE LIQUID, TOXIC, N.O.S., STABILIZED(Glycidyl methacrylate)
UN number	UN 2922
Class	8 (6.1)
Packing group	III

Classification for SEA transport (IMO-IMDG):

Proper shipping name	CORROSIVE LIQUID, TOXIC, N.O.S., STABILIZED(Glycidyl methacrylate)
UN number	UN 2922
Class	8 (6.1)
Packing group	III
Marine pollutant	No
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Proper shipping name	Corrosive liquid, toxic, n.o.s.. stabilized(Glycidyl methacrylate)
UN number	UN 2922
Class	8 (6.1)
Packing group	III

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Emergency Decree on Controlling the Use of Volatile Substances B.E. 2533

Not applicable

Hazardous Substance Act B.E. 2535

Department of Agriculture
Not applicable

Department of Energy Business
Not applicable

Department of Livestock
Not applicable

Department of Industrial Works
Not applicable

Food and Drug Administration
Not applicable

Department of Fisheries
Not applicable

16. OTHER INFORMATION

Product Literature

Additional information on this product may be obtained by calling your sales or customer service contact. Ask for a product brochure. Additional information on this and other products may be obtained by visiting our web page.

Hazard Rating System

NFPA

Health	Flammability	Instability
3	2	2

Revision

Identification Number: 35362 / A176 / Issue Date: 20.12.2023 / Version: 6.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
Dow IHG	Dow Industrial Hygiene Guideline
TWA	Time weighted average
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law

(Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

DOW CHEMICAL THAILAND LTD urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

TH