

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

- Trade name PROXITANE® 15:10

1.2 Relevant identified uses of the substance or mixture and uses advised against**Uses of the Substance/Mixture**

- Disinfectants
- Preservatives

1.3 Details of the supplier of the safety data sheet**Company**

SOLVAY PEROXYTHAI LIMITED
55, WAVE PLACE, 11&16 FL., WIRELESS ROAD,
KWANG LUMPINI, KHET PATHUMWAN,
BANGKOK, 10330
THAILAND
Tel: +66-2-6106470
Fax: +66-2-6106479

E-mail address

manager.sds@solvay.com

1.4 Emergency telephone number

001800 1 2066 6751 [CareChem 24] (toll-free, access from Thailand only)
MULTI LINGUAL EMERGENCY NUMBER (24/7)
Europe/Latin America/Africa : +44 1235 239 670 (UK)
Middle East/Africa speaking Arabic : +44 1235 239 671 (UK)
Asia Pacific : +65 3158 1074 (Singapore)
China : +86 512 8090 3042
North America : 800 424 9300

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Notification of the ministry of industry on the system of classification and hazard communication of hazardous substances B.E. 2555 (GHS 2009)**

Flammable liquids, Category 4	H227: Combustible liquid.
Organic peroxides, Type F	H242: Heating may cause a fire.
Corrosive to metals, Category 1	H290: May be corrosive to metals.
Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Acute toxicity, Category 4	H312: Harmful in contact with skin.
Skin corrosion, Category 1	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Specific target organ toxicity - single exposure Category 3	H335: May cause respiratory irritation. (Respiratory system)
Acute aquatic toxicity, Category 2	H401: Toxic to aquatic life.
Chronic aquatic toxicity, Category 1	H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements**Notification of the ministry of industry on the system of classification and hazard communication of hazardous substances B.E. 2555 (GHS 2009)****Hazardous products which must be listed on the label**

- | | |
|---------------------|-------------------|
| • CAS-No. 64-19-7 | Acetic acid |
| • CAS-No. 79-21-0 | Peroxyacetic acid |
| • CAS-No. 7722-84-1 | Hydrogen peroxide |

Pictogram**Signal word**

- Danger

Hazard statements

- H227 Combustible liquid.
- H242 Heating may cause a fire.
- H290 May be corrosive to metals.
- H302 + H312 + H332 Harmful if swallowed, in contact with skin or if inhaled
- H314 Causes severe skin burns and eye damage.
- H335 May cause respiratory irritation.
- H401 Toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

Precautionary statementsGeneral

- None

Prevention

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P220 Keep/Store away from clothing/ combustible materials.
- P234 Keep only in original container.
- P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
- P264 Wash skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

- P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.
- P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
- P363 Wash contaminated clothing before reuse.
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol resistant foam for extinction.
- P390 Absorb spillage to prevent material damage.
- P391 Collect spillage.

Storage

- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P406 Store in corrosive resistant stainless steel container with a resistant inner liner.
- P410 Protect from sunlight.
- P411 + P235 Store at temperatures not exceeding .? °C/ .? °F. Keep cool.
- P420 Store away from other materials.

Disposal

- P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards which do not result in classification

- None known.

SECTION 3: Composition/information on ingredients**3.1 Substance**

- Not applicable, this product is a mixture.

3.2 Mixture

- Synonyms PAA, Peroxyethanoic acid, Peracetic acid
- Formula CH3-COOOH
- Chemical nature Mixture

Information on Components and Impurities

Chemical name	CAS-No.	Identification number	GHS Classification	Concentration [%]
Acetic acid	64-19-7	Not applicable	Flammable liquids, Category 3 ; H226 Acute toxicity, Category 5 ; H303 Skin corrosion, Category 1 ; H314 Serious eye damage, Category 1 ; H318 Specific concentration limit: C: ≥ 90 %, Skin corrosion, Category 1A; H314 C: 25 - < 90 %, Skin corrosion, Category 1B; H314 C: 10 - < 25 %, Skin irritation, Category 2; H315 C: 10 - < 25 %, Eye irritation, Category 2; H319 C: 2.5 - < 10 %, Skin irritation, Category 3; H316	≥ 30 - < 40
Peroxyacetic acid	79-21-0	Not applicable	Flammable liquids, Category 3 ; H226 Organic peroxides, Type D ; H242 Acute toxicity, Category 4 ; H302 Acute toxicity, Category 4 ; H332 Acute toxicity, Category 4 ; H312 Skin corrosion, Category 1 ; H314 Serious eye damage, Category 1 ; H318 Specific target organ toxicity - single exposure, Category 3 ; H335 (Respiratory system) Acute aquatic toxicity, Category 1 ; H400 Chronic aquatic toxicity, Category 1 ; H410 Specific concentration limit: C: ≥ 1 %, Specific target organ toxicity - single exposure, Category 3; H335 C: ≥ 25 %, Chronic aquatic toxicity, Category 1; H410 C: 0.25 - < 2.5 %, Chronic aquatic toxicity, Category 2; H411 C: 0.025 - < 2.5 %, Chronic aquatic toxicity, Category 3; H412	≥ 15 - < 20

PROXITANE® 15:10

Revision Date 16.09.2016

			C: ≥ 25 %, Acute aquatic toxicity, Category 1; H400 C: 2.5 - < 25 %, Acute aquatic toxicity, Category 2; H401 C: 0.25 - < 25 %, Acute aquatic toxicity, Category 3; H402	
Hydrogen peroxide	7722-84-1	Not applicable	Oxidizing liquids, Category 1 ; H271 Acute toxicity, Category 4 ; H302 Skin corrosion, Category 1 ; H314 Serious eye damage, Category 1 ; H318 Specific target organ toxicity - single exposure, Category 3 ; H335 (Respiratory system) Acute aquatic toxicity, Category 2 ; H401 Chronic aquatic toxicity, Category 3 ; H412 Specific concentration limit: C: ≥ 70 %, Oxidizing liquids, Category 1; H271 C: 50 - < 70 %, Oxidizing liquids, Category 2; H272 C: ≥ 70 %, Skin corrosion, Category 1A; H314 C: 50 - < 70 %, Skin corrosion, Category 1B; H314 C: 35 - < 50 %, Skin irritation, Category 2; H315 C: 8 - < 50 %, Serious eye damage, Category 1; H318 C: 5 - < 8 %, Eye irritation, Category 2; H319 C: ≥ 35 %, Specific target organ toxicity - single exposure, Category 3; H335 C: ≥ 63 %, Chronic aquatic toxicity, Category 3; H412 C: < 63 %, Chronic aquatic toxicity, Category 4; Not classified	≥ 10 - < 15

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****In case of inhalation**

- Move to fresh air.
- Oxygen or artificial respiration if needed.
- Victim to lie down in the recovery position, cover and keep him warm.
- Call a physician immediately.

In case of skin contact

- Take off contaminated clothing and shoes immediately.
- Wash off immediately with plenty of water.
- Keep warm and in a quiet place.
- Call a physician or poison control centre immediately.
- Wash contaminated clothing before re-use.

In case of eye contact

- Call a physician or poison control centre immediately.
- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- In the case of difficulty of opening the lids, administer an analgesic eye wash (oxybuprocaine).
- Take victim immediately to hospital.

In case of ingestion

- Call a physician or poison control centre immediately.
- Take victim immediately to hospital.
- If swallowed, rinse mouth with water (only if the person is conscious).
- Do NOT induce vomiting.
- Artificial respiration and/or oxygen may be necessary.

4.2 Most important symptoms and effects, both acute and delayed**In case of inhalation****Symptoms**

- Breathing difficulties
- Cough
- Chemical pneumonitis
- pulmonary oedema

Effects

- Corrosive to respiratory system.

Repeated or prolonged exposure

- Nose bleeding
- Risk of chronic bronchitis

In case of skin contact**Symptoms**

- Redness
- Swelling of tissue

Effects

- Corrosive
- Causes severe burns.

In case of eye contact**Symptoms**

- Redness
- Lachrymation
- Swelling of tissue

Effects

- Corrosive
- Causes severe burns.
- May cause irreversible eye damage.
- May cause blindness.

In case of ingestion**Symptoms**

- Nausea
- Abdominal pain
- Bloody vomiting
- Diarrhoea
- Suffocation
- Cough
- Severe shortness of breath

Effects

- If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.
- Risk of respiratory disorder

4.3 Indication of any immediate medical attention and special treatment needed**Notes to physician**

- Take victim immediately to hospital.
- Immediate medical attention is required.
- Consult with an ophthalmologist immediately in all cases.
- Burns must be treated by a physician.
- If swallowed
- Avoid gastric lavage (risk of perforation).
- Keep under medical supervision for at least 48 hours.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

- Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Water
- Water spray

Unsuitable extinguishing media

- None

5.2 Special hazards arising from the substance or mixture

- Heating may cause a fire.
- Oxygen released in thermal decomposition may support combustion

5.3 Advice for firefighters**Special protective equipment for firefighters**

- In the event of fire, wear self-contained breathing apparatus.
- Use personal protective equipment.
- Wear chemical resistant oversuit
- Cool containers/tanks with water spray.
- Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****Advice for non-emergency personnel**

- Evacuate personnel to safe areas.
- Keep people away from and upwind of spill/leak.

Advice for emergency responders

- Use personal protective equipment.
- Drying of this product on clothing or combustible materials may cause fire.
- Keep wetted with water.
- Prevent further leakage or spillage.
- Keep away from incompatible products

6.2 Environmental precautions

- Discharge into the environment must be avoided.
- Do not flush into surface water or sanitary sewer system.
- In case of accidental release or spill, immediately notify the appropriate authorities if required by Federal, State/Provincial and local laws and regulations.

6.3 Methods and materials for containment and cleaning up

- Dam up.
- Soak up with inert absorbent material.
- Do not let product enter drains.
- Keep in suitable, closed containers for disposal.
- Keep in properly labelled containers.

6.4 Reference to other sections

- Refer to protective measures listed in sections 7 and 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Use only in well-ventilated areas.
- Before all operations, passivate the piping circuits and vessels according to the procedure recommended by the producer.
- Use only clean and dry utensils.
- Never return unused material to storage receptacle.
- May not get in touch with:
 - Organic materials
- Keep away from incompatible products
- Keep away from heat.

Hygiene measures

- Ensure that eyewash stations and safety showers are close to the workstation location.
- Take off contaminated clothing and shoes immediately.
- Wash contaminated clothing before re-use.
- When using do not eat, drink or smoke.
- Wash hands before breaks and at the end of workday.
- Handle in accordance with good industrial hygiene and safety practice.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

- Store in original container.
- Keep tightly closed in a dry, cool and well-ventilated place.
- Keep in properly labelled containers.
- Keep in a bonded area.
- Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- Electrical equipment should be protected to the appropriate standard.
- Keep away from incompatible products
- Organic Peroxide Storage (Burning Rate) Type IV according to the BGV B4 test method

Packaging material

Suitable material

- Approved grades of HDPE.

- Stainless steel cleaned and passivated.

7.3 Specific end use(s)

- Contact your supplier for additional information

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with national occupational exposure limits

Components	Value type	Value	Basis
Acetic acid	TWA	10 ppm 25 mg/m ³	Thailand. Occupational Exposure Limits

Components with other occupational exposure limits

Components	Value type	Value	Basis
Acetic acid	TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
Acetic acid	STEL	15 ppm	USA. ACGIH Threshold Limit Values (TLV)
Peroxyacetic acid	STEL	0.4 ppm	USA. ACGIH Threshold Limit Values (TLV)
Form of exposure : Inhalable fraction and vapor			
Hydrogen peroxide	TWA	1 ppm	USA. ACGIH Threshold Limit Values (TLV)

8.2 Exposure controls

Control measures

Engineering measures

- Ensure adequate ventilation.
- Apply technical measures to comply with the occupational exposure limits.

Individual protection measures

Respiratory protection

- In case of insufficient ventilation, wear suitable respiratory equipment.
- Respirator with a vapour filter (EN 141)
- Recommended Filter type: ABEK-P2

Hand protection

- Impervious gloves
- Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Suitable material

- butyl-rubber
- Break through time: > 480 min
- Glove thickness: >= 0.4 mm

Eye protection

- Chemical resistant goggles must be worn.
- If splashes are likely to occur, wear:

- Tightly fitting safety goggles
- Face-shield

Skin and body protection

- Apron/boots of butyl rubber if risk of splashing.

Hygiene measures

- Ensure that eyewash stations and safety showers are close to the workstation location.
- Take off contaminated clothing and shoes immediately.
- Wash contaminated clothing before re-use.
- When using do not eat, drink or smoke.
- Wash hands before breaks and at the end of workday.
- Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

- Dispose of rinse water in accordance with local and national regulations.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance**

Form: liquid
Physical state: liquid
Colour: colourless

Odour

pungent

Odour Threshold

no data available

pH

< 1.5

pKa: 8.2 (25 °C)

Melting point/freezing point

Freezing point: ca. -42 °C
Method: Calculation method

Initial boiling point and boiling range

ca. Boiling point/boiling range: 105 °C
Method: Calculation method

Flash point

68 - 81 °C Method: closed cup

Evaporation rate (Butylacetate = 1)

no data available

Flammability (liquids)

Not applicable

Heating may cause a fire.

Flammability/Explosive limit

Explosiveness:
Not explosive

Auto-ignition temperature

270 - 430 °C

Vapour pressure

ca. 32 hPa (25 °C)
Method: Calculation method

Vapour density

no data available

Density

<u>Relative density</u>	1.1
<u>Solubility</u>	<u>Water solubility:</u> 1,000 g/l (20 °C)completely miscible <u>Solubility in other solvents:</u> organic polar solvents : soluble Aromatic solvents : slightly soluble log Pow: -1.25 Method: Calculation method log Pow: -0.52 Method: measured value
<u>Partition coefficient: n-octanol/water</u>	
<u>Decomposition temperature</u>	>= 55 °C Self-Accelerating decomposition temperature (SADT)
<u>Viscosity</u>	no data available
<u>Explosive properties</u>	Not explosive
<u>Oxidizing properties</u>	Oxidizer

9.2 Other information

<u>Henry's Constant</u>	22 Pa.m3/mol not significant, Air, Volatility
<u>Corrosion of Metals</u>	Corrosive to metals
<u>Peroxides</u>	The substance or mixture is an organic peroxide classified as type F.

SECTION 10: Stability and reactivity

10.1 Reactivity

- Decomposes on heating.
- Heating may cause a fire.
- Potential for exothermic hazard

10.2 Chemical stability

- Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

- Contact with combustible material may cause fire.
- Contact with flammables may cause fire or explosions.
- Risk of explosion if heated under confinement.
- Fire or intense heat may cause violent rupture of packages.

10.4 Conditions to avoid

- Contamination
- To avoid thermal decomposition, do not overheat.

10.5 Incompatible materials

P00000016375
Version : 1.01 / TH (EN)
www.solvay.com



- Acids
- Bases
- Metals
- Heavy metal salts
- Powdered metal salts
- Reducing agents
- Organic materials
- Flammable materials

10.6 Hazardous decomposition products

- Oxygen

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Acute oral toxicity LD50 : 652 mg/kg - Rat
Test substance: 11,7 % PAA mixture

Acute inhalation toxicity LC50 - 4 h (dust/mist) 4 mg/l - Rat
Test substance: 5 % PAA mixture

Acute dermal toxicity LD50 1,957 mg/kg - Rabbit
Test substance: 11,7 % PAA mixture

Acute toxicity (other routes of administration) no data available

Skin corrosion/irritation Rabbit
Corrosive

Serious eye damage/eye irritation Rabbit
Causes serious eye damage.

Respiratory or skin sensitisation Guinea pig
Did not cause sensitization on laboratory animals.

Mutagenicity

Genotoxicity in vitro In vitro tests have shown mutagenic effects.

Genotoxicity in vivo Animal testing did not show any mutagenic effects.

Carcinogenicity no data available

Toxicity for reproduction and development

Toxicity to reproduction/Fertility No toxicity to reproduction

Developmental Toxicity/Teratogenicity Rat
Test substance: 15 % PAA mixture
No effect observed on development
Published data

STOT**STOT - single exposure**

May cause respiratory irritation.

STOT - repeated exposure

The substance or mixture is not classified as specific target organ toxicant, repeated exposure according to GHS criteria.

Ingestion 13 weeks - Rat

NOAEL: 0.75 mg/kg

Test substance: Peracetic acid

Oral 90-day - Mouse

NOAEL: 100 ppm

Test substance: Hydrogen peroxide

Inhalation 90-day - Rat

NOAEL: 7 ppm

Test substance: Hydrogen peroxide

Experience with human exposure**Experience with human exposure :**
Inhalation

no data available

Experience with human exposure :
Ingestion

no data available

CMR effects**Carcinogenicity**

Acetic acid

No evidence of carcinogenicity in animal studies.

Mutagenicity

Acetic acid

Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Aspiration toxicity

Not applicable

Further information

no data available

SECTION 12: Ecological information**12.1 Toxicity****Aquatic Compartment****Acute toxicity to fish**LC50 - 96 h : 1.1 mg/l - *Lepomis macrochirus* (Bluegill sunfish)

Test substance: Peracetic acid

Acute toxicity to daphnia and other aquatic invertebrates.EC50 - 48 h : 0.73 mg/l - *Daphnia magna* (Water flea)

Test substance: Peracetic acid

Toxicity to aquatic plantsEC50 - 96 h : 0.16 mg/l - *Pseudokirchneriella subcapitata* (green algae)

Test substance: Peracetic acid

Toxicity to microorganisms	no data available
Chronic toxicity to fish	NOEC: 0.00094 mg/l - 33 d - Danio rerio (zebra fish) Early-life Stage Test substance: Peracetic acid NOEC: 0.00094 mg/l - 33 Days - Danio rerio (zebra fish) Early-life Stage Test substance: Pure substance
Chronic toxicity to daphnia and other aquatic invertebrates.	no data available
Chronic Toxicity to aquatic plants	no data available
<u>M-Factor</u>	
Peroxyacetic acid	Acute aquatic toxicity = 1 Chronic aquatic toxicity = 10 (according to the Globally Harmonized System (GHS))

12.2 Persistence and degradability

Abiotic degradation no data available

Physical- and photo-chemical elimination no data available

Biodegradation

Biodegradability aerobic
Biodegradable.

Effects on waste water treatment plants
Inhibitor

Method: Abiotic degradation

Degradability assessment

Acetic acid	The product is considered to be rapidly degradable in the environment
Peroxyacetic acid	The product is considered to be rapidly degradable in the environment
Hydrogen peroxide	The product is considered to be rapidly degradable in the environment

12.3 Bioaccumulative potential**Partition coefficient: n-octanol/water**

Acetic acid	Not potentially bioaccumulable
Peroxyacetic acid	Not potentially bioaccumulable
Hydrogen peroxide	Not potentially bioaccumulable

Bioconcentration factor (BCF) Does not bioaccumulate.

12.4 Mobility in soil

Adsorption potential (Koc) Water
soluble
mobile

Soil/sediments
non-significant adsorption

Known distribution to environmental compartments

Acetic acid Ultimate destination of the product : Water
Structure-activity relationship (SAR)

Air
Structure-activity relationship (SAR)

Peroxyacetic acid Ultimate destination of the product : Water

Hydrogen peroxide Ultimate destination of the product : Water

12.5 Results of PBT and vPvB assessment

Acetic acid This substance is not considered to be persistent, bioaccumulating and toxic (PBT).
This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Peroxyacetic acid This substance is not considered to be persistent, bioaccumulating and toxic (PBT).
This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Hydrogen peroxide This substance is not considered to be persistent, bioaccumulating and toxic (PBT).
This substance is not considered to be very persistent and very bioaccumulating (vPvB).

12.6 Other adverse effects no data available

Ecotoxicity assessment

Acute aquatic toxicity Information refers to the main component.

Chronic aquatic toxicity Information refers to the main component.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product Disposal

- Contact manufacturer.
- Contact waste disposal services.
- In accordance with local and national regulations.

P00000016375

Version : 1.01 / TH (EN)

www.solvay.com



Advice on cleaning and disposal of packaging

- Empty containers.
- Clean container with water.
- Dispose of rinse water in accordance with local and national regulations.
- Where possible recycling is preferred to disposal or incineration.
- In accordance with local and national regulations.

SECTION 14: Transport information**ADR**

14.1 UN number	UN 3109
14.2 Proper shipping name	ORGANIC PEROXIDE TYPE F, LIQUID (Peroxyacetic acid, Type F, stabilized)
14.3 Transport hazard class	5.2
Subsidiary hazard class:	8
Label(s):	5.2 (8)
14.4 Packing group	
Packing group	
Classification Code	P1
14.5 Environmental hazards	YES
14.6 Special precautions for user	
For personal protection see section 8.	

RID

14.1 UN number	UN 3109
14.2 Proper shipping name	ORGANIC PEROXIDE TYPE F, LIQUID (Peroxyacetic acid, Type F, stabilized)
14.3 Transport hazard class	5.2
Subsidiary hazard class:	8
Label(s):	5.2 (8)
14.4 Packing group	
Packing group	
Classification Code	P1
14.5 Environmental hazards	YES
14.6 Special precautions for user	
For personal protection see section 8.	

Inland waterway transport (ADN)

14.1 UN number	UN 3109
14.2 Proper shipping name	ORGANIC PEROXIDE TYPE F, LIQUID (Peroxyacetic acid, Type F, stabilized)
14.3 Transport hazard class	5.2
Subsidiary hazard class:	8
Label(s):	5.2 (8)
14.4 Packing group	
Packing group	
Classification Code	P1
14.5 Environmental hazards	YES
14.6 Special precautions for user	
Hazard Identification Number:	539

For personal protection see section 8.

IMDG

14.1 UN number	UN 3109
14.2 Proper shipping name	ORGANIC PEROXIDE TYPE F, LIQUID (Peroxyacetic acid, Type F, stabilized)
14.3 Transport hazard class	5.2
Subsidiary hazard class:	8
Label(s):	5.2 (8)
14.4 Packing group	
Packing group	
14.5 Environmental hazards	YES
Marine pollutant	
14.6 Special precautions for user	
EmS	F-J , S-R

For personal protection see section 8.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
no data available

IATA

14.1 UN number	UN 3109
14.2 Proper shipping name	ORGANIC PEROXIDE TYPE F, LIQUID (Peroxyacetic acid, Type F, stabilized)
14.3 Transport hazard class	5.2
Subsidiary hazard class:	8
Label(s):	5.2 (8)
14.4 Packing group	
Packing instruction (cargo aircraft)	570
Max net qty/pkg	25.00 L
Packing instruction (passenger aircraft)	570
Max net qty/pkg	10.00 L
14.5 Environmental hazards	YES
14.6 Special precautions for user	
For personal protection see section 8.	

Note: The above regulatory prescriptions are those valid on the date of publication of this sheet. Given the possible evolution of transport regulations for hazardous materials, it would be advisable to check their validity with your sales office.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Local regulations****Hazardous Substance Act B.E. 2535**

- Banned and/or restricted : Peroxyacetic acid

Notification status

Inventory Information	Status
United States TSCA Inventory	- Listed on Inventory
Mexico INSQ (INSQ)	- Listed on Inventory
Canadian Domestic Substances List (DSL)	- Listed on Inventory
New Zealand. Inventory of Chemical Substances	- Listed on Inventory
Australia Inventory of Chemical Substances (AICS)	- Listed on Inventory
Japan. CSCL - Inventory of Existing and New Chemical Substances	- Listed on Inventory
Korea. Korean Existing Chemicals Inventory (KECI)	- Listed on Inventory
China. Inventory of Existing Chemical Substances in China (IECSC)	- Listed on Inventory
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	- Listed on Inventory
EU. European Registration, Evaluation, Authorisation and Restriction of Chemical (REACH)	- If product is purchased from Solvay in Europe it is in compliance with REACH, if not please contact the supplier.

SECTION 16: Other information**Full text of H-Statements**

- | | |
|--------|---|
| - H226 | Flammable liquid and vapour. |
| - H227 | Combustible liquid. |
| - H242 | Heating may cause a fire. |
| - H271 | May cause fire or explosion; strong oxidiser. |
| - H290 | May be corrosive to metals. |
| - H302 | Harmful if swallowed. |
| - H303 | May be harmful if swallowed. |
| - H312 | Harmful in contact with skin. |
| - H314 | Causes severe skin burns and eye damage. |
| - H318 | Causes serious eye damage. |
| - H332 | Harmful if inhaled. |
| - H335 | May cause respiratory irritation. |
| - H400 | Very toxic to aquatic life. |
| - H401 | Toxic to aquatic life. |
| - H410 | Very toxic to aquatic life with long lasting effects. |
| - H412 | Harmful to aquatic life with long lasting effects. |

Key or legend to abbreviations and acronyms used in the safety data sheet

- | | |
|--------|---------------------------|
| - STEL | Short-term exposure limit |
| - TWA | Time weighted average |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. Such information is only given as a guidance to help the user handle, use, process, store, transport, dispose and release the product in satisfactory safety conditions and is not to be considered as a warranty or quality specification. It should be used in conjunction with technical sheets but do not replace them. Thus, the information only relates to the designated specific product and may not be applicable if such product is used in combination with other materials or in any other manufacturing process, unless otherwise specifically indicated. It does not release the user from ensuring he is in conformity with all regulations linked to its activity.