

Vinyl acetate

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	25.08.2020	000000033649	Date of first issue: 25.08.2020

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Vinyl acetate

Product code : 000000000050001532

Manufacturer or supplier's details

Company : Celanese Pte Ltd

Address : 70 Anson Road #21-01/02 Hub Synergy Point
Singapore SG 079905

Telephone :

Emergency telephone number : CHEMTREC: +1 703 527 3887

Recommended use of the chemical and restrictions on use

Recommended use : Monomer

Restrictions on use : None known.

2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 2

Acute toxicity (Oral) : Category 5

Acute toxicity (Inhalation) : Category 4

Specific target organ toxicity - single exposure : Category 3

Carcinogenicity : Category 2

Short-term (acute) aquatic hazard : Category 3

GHS label elements

Hazard pictograms :   

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H303 May be harmful if swallowed.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H402 Harmful to aquatic life.

Vinyl acetate

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	25.08.2020	000000033649	Date of first issue: 25.08.2020

Precautionary statements

: **Prevention:**

P201 + P202 Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P312 Call a POISON CENTER or doctor/ physician if you feel unwell.
P370 + P378 In case of fire: Use alcohol-resistant foam, carbon dioxide or dry sand for extinction.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with local regulations.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Substance

Components**4. FIRST AID MEASURES**

General advice : Remove contaminated, soaked clothing immediately and dispose of safely
Pay attention to own protection
In any case show the physician the Safety Data Sheet

Vinyl acetate

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	25.08.2020	000000033649	Date of first issue: 25.08.2020

If inhaled	: Keep at rest. Move to fresh air. Call a physician or poison control centre immediately.
In case of skin contact	: Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
In case of eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.
If swallowed	: Rinse with plenty of water. If conscious, drink plenty of water. If swallowed, do not induce vomiting - seek medical advice.
Most important symptoms and effects, both acute and delayed	: Vapours may cause irritation to the eyes, respiratory system and the skin. Gastrointestinal discomfort Respiratory disorder
Notes to physician	: Treat symptomatically In case of lung irritation, first treatment with dexametason aerosol (spray).

5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Foam Dry chemical Carbon dioxide (CO ₂)
Specific hazards during fire-fighting	: Do not use a solid water stream as it may scatter and spread fire.
Specific extinguishing methods	: Cool containers/tanks with water spray.
Special protective equipment for firefighters	: Self-contained breathing apparatus (EN 133)

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Avoid contact with the skin and the eyes. Keep away from heat and sources of ignition. Provide adequate ventilation.
Environmental precautions	: Prevent further leakage or spillage. Do not flush into surface water. Do not allow uncontrolled discharge of product into the environment.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Dispose of in accordance with local regulations.

7. HANDLING AND STORAGE

Local/Total ventilation	: Ensure adequate ventilation.
Advice on protection against fire and explosion	: Keep away from heat and sources of ignition. No smoking. Take necessary action to avoid static electricity discharge

Vinyl acetate

Version 2.0 Revision Date: 25.08.2020 SDS Number: 000000033649 Date of last issue: -
Date of first issue: 25.08.2020

(which might cause ignition of organic vapours).
Ground/bond container and receiving equipment.

Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.
Conditions for safe storage : Keep in a dry, cool and well-ventilated place.
Store locked up.
Handle and open container with care
Store at temperatures not exceeding 38°C / 100 °F
Materials to avoid : Oxidizing agents
polymerisation initiators
Acids
Amines
Recommended storage temperature : 30 °C

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Vinyl acetate	108-05-4	PEL (long term)	10 ppm 35 mg/m ³	SG OEL
		PEL (short term)	15 ppm 53 mg/m ³	SG OEL
		TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH

Substances for which there are Community workplace exposure limits.

Personal protective equipment

Respiratory protection : Recommended Filter type:
Filter type : Organic vapour type
Hand protection
Material : butyl-rubber
Break through time : 240 min
Glove thickness : 0.7 mm
Protective index : Class 5
Remarks : Protective gloves
Eye protection : Tightly fitting safety goggles
In addition to goggles, wear a face shield if there is a reasonable chance for splash to the face.
Equipment should conform to EN 166.
Skin and body protection : Impervious clothing
Hygiene measures : Do not smoke.
Provide adequate ventilation.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Colour : colourless
Odour : fruity, sweet

Vinyl acetate

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	25.08.2020	000000033649	Date of first issue: 25.08.2020

Odour Threshold : 0.12 ppm

pH : neutral

Melting point/range : -93.2 °C

Boiling point/boiling range : 72.7 °C
(1,013 hPa)

Flash point : -8 °C
Method: closed cup

Evaporation rate : 8.9

Upper explosion limit / Upper flammability limit : 13.4 %(V)

Lower explosion limit / Lower flammability limit : 2.6 %(V)

Vapour pressure : 445 hPa (50 °C)

Relative vapour density : 3.0
(Air = 1.0)

Density : 0.932 g/cm³ (20 °C)

Solubility(ies)

Water solubility : 20 g/l (20 °C)

Solubility in other solvents : miscible
Solvent: Acetone

miscible
Solvent: Benzene

miscible
Solvent: Diethylether

miscible
Solvent: Ethanol

soluble
Solvent: Chloroform

Partition coefficient: n-octanol/water : log Pow: 0.73
measured data

Temperature of Polymerisation (SAPT) : 50 °C

Viscosity

Viscosity, dynamic : 0.42 - 0.43 mPa.s (20 °C)

Explosive properties : not applicable based on consideration of the structure

Vinyl acetate

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	25.08.2020	000000033649	Date of first issue: 25.08.2020

Oxidizing properties	:	not applicable based on consideration of the structure
Surface tension	:	23.95 mN/m, 20 °C
Molecular weight	:	86.09 g/mol

10. STABILITY AND REACTIVITY

Reactivity	:	Stable under normal conditions.
Chemical stability	:	No decomposition if used as directed. Decomposes on heating.
Possibility of hazardous reactions	:	Violent polymerisation may be caused by: Heating above the decomposition temperature
Conditions to avoid	:	Do not expose to temperatures above: 30 °C Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials	:	Oxidizing agents Strong acids Amines
Hazardous decomposition products	:	No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION**12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects**Product:**

Results of PBT and vPvB assessment	:	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
------------------------------------	---	--

13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues	:	Dispose of in accordance with local regulations. The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
---------------------	---	--

Vinyl acetate

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	25.08.2020	000000033649	Date of first issue: 25.08.2020

14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number	: UN 1301
Proper shipping name	: VINYL ACETATE, STABILIZED
Class	: 3
Packing group	: II
Labels	: 3

IATA-DGR

UN/ID No.	: UN 1301
Proper shipping name	: Vinyl acetate, stabilized
Class	: 3
Packing group	: II
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 364
Packing instruction (passenger aircraft)	: 353

IMDG-Code

UN number	: UN 1301
Proper shipping name	: VINYL ACETATE, STABILIZED
Class	: 3
Packing group	: II
Labels	: 3
EmS Code	: F-E, S-D
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

16. OTHER INFORMATION

Date format : dd.mm.yyyy

Full text of other abbreviations

Vinyl acetate

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	25.08.2020	000000033649	Date of first issue: 25.08.2020

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
SG OEL	:	Singapore. Workplace Safety and Health Act - First Schedule Permissible Exposure Limits of Toxic Substances
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
SG OEL / PEL (long term)	:	Permissible Exposure Level (PEL) Long Term
SG OEL / PEL (short term)	:	Permissible Exposure Level (PEL) Short Term

AICS - Australian Inventory of Chemical Substances; AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SG / EN