

Safety Data Sheet as per Globally Harmonized System (GHS)

Galaxy 2932

Version No. 3 Date of revision: June 17, 2019

§1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

GHS Product identifier

Trade Name : Galaxy 2932

Chemical identity of ingredients that contribute to classification : None

Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Ingredient in Personal Care products

Supplier's details : Galaxy Surfactants Limited
C-49/2, TTC Industrial Area
Pawne, Navi Mumbai, 400703, India
Tel: +91-22-27616666/+91-22-39135500
Fax: +91-22-27615886 / +91-22-27615883
e-mail: galaxy@galaxysurfactants.com

Emergency phone number : For product information: +91-9867673376/ +91-9923585099
(Language: English)
For Incident (Spill, Leak, Fire, Exposure, or Accident)
CHEMTREC (Day or Night): +1 703-741-5970 / 1-800-424-9300

§2. HAZARD IDENTIFICATION

Classification of the substance or mixture:

This mixture is not classified as hazardous according to Globally Harmonized System of Classification and Labelling of Chemicals

GHS label elements, including precautionary statements

This mixture does not fall under any hazard class as per Globally Harmonized System of Classification and Labelling of Chemicals

Other hazards which do not result in classification : Not known

Safety Data Sheet as per Globally Harmonized System (GHS)

Galaxy 2932

Version No. 3 Date of revision: June 17, 2019

§3. COMPOSITION/INFORMATION ON INGREDIENTS

INCI/Chemical Name	Synonyms	CAS Number	EC Number	% concentration
BHT	2,6-di-tert-butyl-p-cresol; 2,6-di-tert-butyl-4-methylphenol	128-37-0	204-881-4	< 0.1

4. FIRST- AID MEASURES

Description of necessary first-aid measures

Inhalation	: Remove to fresh air
Skin contact	: Wash with soap and plenty of water. Seek medical advice, if necessary
Eye contact	: Flush for at least 15 minutes under running water with eyelids held open forcibly. Seek medical advice, if necessary
Ingestion	: Immediately rinse mouth and then drink water (two glasses at most). If feeling unwell, after accidental swallowing, consult the doctor
Most important symptoms/effects, acute and delayed	: Data not available on toxic symptoms
Indication of immediate medical attention and special treatment needed, if necessary	: No information available

5. FIRE- FIGHTING MEASURES

Suitable extinguishing media	: Dry chemical powder, carbon dioxide, foam, water spray
Unsuitable extinguishing media	: High volume water jet
Specific hazards arising from the chemical	: Development of hazardous combustion products like oxides of carbon or vapours possible in the event of fire
Special protective equipment and precautions for fire-fighters	: Wear personal protective equipment and self-contained breathing apparatus

6. ACCIDENTAL RELEASE MEASURES

§Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Wash hands after exposure with the product. Avoid contact with skin, eyes and clothing
Environmental precautions	: Do not discharge into drains

Safety Data Sheet as per Globally Harmonized System (GHS)

Galaxy 2932

Version No. 3 Date of revision: June 17, 2019

Methods and materials for containment and cleaning up

: Small spill: Absorb with suitable absorbent material. Collect in suitable and properly labeled container.
Large spill: Contain spilled material if possible. Pump into suitable and properly labeled containers. Dispose off absorbed material/collected material in accordance with regulations

7. HANDLING AND STORAGE

Precautions for safe handling

: Follow general occupational hygiene such as, wash hands after use. Do not eat, drink or smoke in work areas. Remove contaminated clothing. Avoid spill. Follow safe procedures for loading and un-loading of product

§Conditions for safe storage, including any incompatibilities

: Store the material in a clean, dry place at 20-35°C away from direct heat and sunlight. In original sealed condition, when stored as suggested, the shelf life of the product is at least 2.5 years. Once carboy/IBC is opened, consume the product within a week. When taken in ISO container, it is recommended that material be consumed within one month's time, after unloading in storage tank. Colour of the product may deteriorate on exposure to sunlight. Keep the container tightly closed after use. Product may solidify, if stored at < -10°C. If solidifies, it is recommended to heat the jacketed ISO tank with hot water (55-60°C) or low pressure steam (< 2 kg/cm²) to bring the temperature 30-40°C. If the product becomes frozen in IBC/HMHDPE carboys, then keep the same in hot room of 30-40°C (avoid direct heating).

Stacking of carboys: Palletized/non-palletized: 1+1 both while transport and during storage

Stacking of IBC: 1+1 both while transport and during storage

Suitable packing materials

: Blue or black colour HMHDPE carboys/Blue or black colour IBC/ISO tank

Unsuitable packing materials

: White colour HMHDPE carboys/White colour IBC

Safety Data Sheet as per Globally Harmonized System (GHS)

Galaxy 2932

Version No. 3 Date of revision: June 17, 2019

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

§Occupational exposure limits

Occupational exposure limits for BHT (CAS Number: 128-37-0; EC Number: 204-881-4)

Country	Limit value - Eight hours		Limit value - Short term	
	ppm	mg/m ³	ppm	mg/m ³
Australia	-	10	-	-
Austria	-	10	-	-
Belgium	-	2	-	-
Canada - Ontario	-	2 (Inhalable aerosol and vapour)	-	-
Canada - Quebec	-	10	-	-
Denmark	-	10	-	20
Finland	-	10	-	20 (15 minutes average value)
France	-	10	-	-
Germany (AGS)	-	10 (Inhalable aerosol and vapour)	-	40 (Inhalable aerosol and vapour) (15 minutes reference period)
Germany (DFG)	-	10 (Inhalable fraction and vapour) (15 minutes reference period)	-	40 (Inhalable fraction and vapour) (15 minutes reference period)
Ireland	-	10	-	-
New Zealand	-	10	-	-
Singapore	-	10	-	-
South Korea	-	2	-	-
Switzerland	-	10 Inhalable aerosol	-	-
USA - NIOSH	-	10	-	-
United Kingdom	-	10	-	-

(Source: Based on GESTIS International Limit values Database via:
https://limitvalue.ifa.dguv.de/WebForm_ueliste2.aspx, as on date: 17.06.2019)

Biological limit values : Not known

Appropriate engineering controls : Proper plant design, technical measures and working operations should minimize human exposure

Individual protection measures, such as personal protective equipment (PPE) : Eye/face protection: Safety goggles
Skin protection: Apron, rubber gloves and shoes
Respiratory protection: Required when vapours / aerosols are generated

Safety Data Sheet as per Globally Harmonized System (GHS)

Galaxy 2932

Version No. 3 Date of revision: June 17, 2019

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	: Clear syrupy oily liquid
Colour	: Pale yellow
Odour	: Mild aromatic
Odour threshold	: No data available
pH	: Not applicable
Freezing point	: < - 10°C
Initial boiling point and boiling range	: No data available
Flash point	: 204°C
Evaporation rate	: No data available
Flammability (solid, gas)	: Not flammable
Upper/lower flammability or explosive limits	: Not applicable
Vapour pressure	: 0.3 hPa at 154°C
Vapour density	: No data available
Relative density	: 1.005 - 1.013 at 25°C
Solubility(ies)	: Water solubility: 0.22 - 0.75 mg/l at 21°C Miscible in: Isopropyl alcohol, ethanol, isopropyl myristate, mineral oil Immiscible in: Propylene glycol, glycerin
Partition coefficient: n-octanol/water	: Log K _{ow} : > 6 at 23°C
Auto-ignition temperature	: 392°C at 977 mBar
Decomposition temperature	: No data available
§Viscosity (Brookfield, LVT, #2, 12 rpm)	: < 100 cP at 28°C

10. STABILITY AND REACTIVITY

Reactivity	: No hazardous reactions, if stored and handled as prescribed (Refer Section 7)
Chemical stability	: Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure
Possibility of hazardous reactions	: Not anticipated when used or handled as prescribed

Safety Data Sheet as per Globally Harmonized System (GHS)

Galaxy 2932

Version No. 3 Date of revision: June 17, 2019

Conditions to avoid	: Sunlight, heat, flame and other sources of ignition
Incompatible materials	: Do not subject to strong acids, base and strong oxidizing agents
Hazardous decomposition products	: Will not form, if stored or handled as prescribed

§11. TOXICOLOGICAL INFORMATION

Toxicological information of BHT

Acute oral toxicity (Rat)	: LD ₅₀ : > 6000 mg/kg bw (male/female) (OECD Guideline 401)
Acute dermal toxicity (Rat)	: LD ₅₀ : > 2000 mg/kg bw (male/female) (OECD Guideline 402)
Acute inhalation toxicity (Mouse)	: RD ₅₀ (30 mins): about 546 mg/m ³ (59.7 ppm) (Other: Sensory irritation study of BHT)
Skin corrosion/irritation (Rabbit)	: Not irritating (OECD Guideline 404)
Serious eye damage/irritation (Rabbit)	: Not irritating (OECD Guideline 405)
Respiratory or skin sensitization	: No sensitization
Germ cell mutagenicity	
Bacterial reverse mutation assay (in vitro)	: Negative
In-vitro mammalian chromosome aberration test	: Negative
Chromosome aberration (in vivo)	: Negative
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Information on the likely routes of exposure	: Dermal and oral
Symptoms related to the physical, chemical and toxicological characteristics	: Data not available on toxic symptoms
Delayed and immediate effects and also chronic effects from short and long term exposure	: Short term exposure: Not known Long term exposure: Not known

Safety Data Sheet as per Globally Harmonized System (GHS)

Galaxy 2932

Version No. 3 Date of revision: June 17, 2019

§12. ECOLOGICAL INFORMATION

Ecological information of BHT

Short-term toxicity to fish	: LC ₅₀ (96 h): 0.199 mg/l (QSAR method)
Long-term toxicity to fish	: Oryzias latipes NOEC (30 d): 0.053 mg/l (OECD Guideline 210)
Short-term toxicity to aquatic invertebrates	: Daphnia magna EC ₅₀ (48 h): 0.48 mg/l (OECD Guideline 202 / EU Method C.2)
Long-term toxicity to aquatic invertebrates	: Daphnia magna NOEC (21 d): 0.069 mg/l (OECD Guideline 211)
Toxicity to aquatic algae	: EC ₅₀ (96 h): 0.758 mg/l (QSAR method) Pseudokirchneriella subcapitata EC ₅₀ (72 h): > 0.24 mg/l (based on growth rate) NOEC (72 h): 0.24 mg/l (based on growth rate) (OECD Guideline 201)
Persistency and degradability	: Not readily biodegradable; 4.5% BOD/ThOD after 28 d (Equivalent or similar to OECD Guideline 301 C)
Bioaccumulative potential	: BCF: 598.4 (EPI-Suite, BCFWIN v2.17)
Mobility in soil	: Adsorption coefficient: K _{oc} : 23030 (EPI-Suite, EPA (USA) / PCKOCWIN v1.66) Adsorption coefficient: K _{oc} : 14750 (QSAR estimation: KOCWIN v2.00: K _{oc} estimate from MCI) BHT is expected to adsorb to the solid soil phase
Other adverse effects	: No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods	: Dispose off contents/container in accordance with local/regional/ national/international regulations
------------------	---

Safety Data Sheet as per Globally Harmonized System (GHS)

Galaxy 2932

Version No. 3 Date of revision: June 17, 2019

14. TRANSPORT INFORMATION

Not classified as dangerous according to transport regulations

§15. REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product in question : Refer to all applicable national, international and local regulations or provisions

16. OTHER INFORMATION

Revision Number : GHS / Revision 2
Indication of changes : Indicated with symbol '§'
Legend/acronym : GHS - Globally Harmonized System
STOT - Specific Target Organ Toxicity
Source of information : In-house and literature

The information contained herein is based on data considered accurate. However, no warranty is expressed, or implied regarding the accuracy of this data, or the result to be obtained from the use thereof. Galaxy assumes no responsibility for injury to the user, or third person proximately caused by the material, if reasonable safety procedures are not adhered to, as stipulated in the safety data sheet. Galaxy assumes no responsibility for injury to the user, or third person proximately caused by abnormal use of the material, even if reasonable safety procedures are followed. Further, user assumes the risk in his use of the material.