



SAFETY DATA SHEET FOR ALKYL BENZENE SULPHONATE

RSAW LABSA

SDS No: AS088

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Address/Telephone number	Guangdong Resun Auway Industrial Co Ltd. No.12,Shihua 3rd ,Shatian Town,Dongguan City, Guangdong ,China Tel:0769-81710259 Fax:0769-81710259
Emergency telephone number	0532-83889090
Trade name	RSAW LABSA
Use	Sales product

2. HAZARDS IDENTIFICATION

Label elements:

Pictogram:



Warning:

Eye contact

Skin contact

Inhalation

Ingestion

dangerous

May be corrosive to eyes.

May be corrosive to the skin.

May be moderately to severely irritating to the respiratory tract and mucous membranes.

Ingestion may result in moderately severe burns to mouth and esophagus with more severe burns and damage to the stomach.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition	Content(%)
Linear Alkyl Benzene Sulphonic Acid	96.5
Dodecylbenzene	1.0
Sulfuric acid	1.2
water	1.3

4 FIRST AID MEASURES

Eye contact

Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Seek



Skin contact	medical attention at once. Immediately take off all contaminated clothing. Wash contaminated clothing before reuse. For skin contact flush with large amounts of water. Get medical attention or advice.
Inhalation	If symptoms are experienced, remove source of contamination or move victim to fresh air. If symptoms persist, get medical attention. If the affected person is not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.
Ingestion	If the material is swallowed, get immediate medical attention or advice. Do not induce vomiting.

5 FIRE-FIGHTING MEASURES

Extinguishing Media	Dry chemical, foam, carbon dioxide, water fog.
Special fire-fighting protective equipment	Firefighters should wear full fire-fighting turn-out gear including NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.
Combustion products	Irritating and toxic gases or fumes may be released during a fire.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Refer to section 8 for proper personal protective equipment.
Environmental precautions	Prevent entry into waterways, sewers, basements or confined areas.
Methods for cleaning up	Small Spills: Absorb with inert, sand or other non-combustible material and transfer to containers for later disposal. Large Spills: Dike or pad of liquid spill for later disposal. Dispose of in accordance with Federal, State and local authority regulations.
Other information	Surfaces may become slippery after spillage.

7. HANDLING AND STORAGE

Handling	Avoid contact with skin and eyes. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this
-----------------	--

Storage	material. Keep this material in a cool, well-ventilated place. Avoid freezing or excessive heat. Avoid contact with bases, alkalies (organic).
---------	---

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering measures	Local exhaust is suggested for use, where possible, in enclosed or confined spaces.
Eye/Face protection	Safety goggles and face shield recommended.
Skin protection	Protective overalls and safety shoes/boots recommended.
Hand protection	Impervious gloves recommended.
Respiratory protection	If vapors are present or irritation is experienced, NIOSH approved respiratory protection for acidic vapors should be worn.
Other	Eyewash and safety shower easily accessible to the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Viscous liquid, dark color
Odour:	Sulphuric odour
Specific Gravity (20 °C):	~1.080g/ml
Viscosity (25 °C):	1 500-2000mPa.s
Freezing Point	-10 °C
Water Solubility (20 °C):	Soluble
Solubility in ethanol(20 °C):	Soluble
Solubility in acetone (20 °C):	Insoluble
pH(20 °C):	> 1 as is
Flash Point (°C) :	> 93.9

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Conditions to Avoid	Avoid contact with bases, alkalies (organic).
Incompatibility	This product may react with strong oxidizing agents, alkalies.
Hazardous decomposition products	Upon decomposition, this product may yield sulfur dioxide and oxides of sulfur. Decomposition may yield sulfuric acid (H ₂ SO ₄).
Hazardous Polymerization	Will not occur.

11. TOXICOLOGICAL INFORMATION

LD50 Value	Oral LD50 >500-2000mg/kg
Carcinogenicity	Not available.
May cause some irritation of the mouth and upper digestive tract.	
May cause some irritation of respiratory system.	
May produce significant skin ulcers.	

May cause significant eye irritation. May cause irreversible damage to eyes.

12. ECOLOGICAL INFORMATION

This product is biodegradable.

13. DISPOSAL CONSIDERATIONS

Methods of Disposal

Dispose of in accordance with all applicable local and national regulation.

Contaminated packaging

Empty container retains product residue.
Observe all hazard precautions.

14. TRANSPORT INFORMATION

According to ADN/ADR/RID/IMDG/IATA not classified as dangerous goods.

This classification is in principle not valid for carriage by tank vessel on inland waterways.

Please refer to the manufacturer for further information.

UN number:2586

UN proper shipping name:ALKYLSULPHONIC ACIDS,LIQUID with not more than 5% free sulphuric acid

Transport hazard class(es) :8

Packing group : III

Environment hazards: Marine pollutant YES

Special precautions for user

See sections 6 to 8 of this Safety Data Sheet.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC-Code

Packing instruction: P001, IBC08, LP01;

Portable tanks and bulk containers: T4, TP1.

15. REGULATORY INFORMATION

Follow all applicable regulations for handling.

All waste must be handled in accordance with local waste disposal regulations.

16. OTHER INFORMATION

The information contained in this document is intended to describe the product only in terms of health, safety and environmental requirements for the purposes of its safe handling, use and disposal and is to the best of Guangdong Resun Auway's knowledge and belief correct. Guangdong Resun Auway's technical services will be pleased to give further advice and assistance but customers must satisfy themselves (by appropriate testing if necessary) that the product is suitable for their purpose and conditions of use and that their facilities and arrangements are suitable for handling or using the product.

The information does not comprise a technical or performance specification for the product and customers are preferred to any relevant product technical information or specification issued by Guangdong Resun Auway.
