

SAFETY DATA SHEET**1.CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Product Name	PENGUIN CEMENT 1547-T
Manufacturer Name	Sunstar Chemical (Thailand) Co.,Ltd.
Address	624 Moo 4 Bangpoo Industrial Estate Soi 7A Sukhumvit Rd., Praksa, Muang Samutprakarn, Samutprakarn 10280 Thailand
Telephone Number	+66 2709 4531
Fax Number	+66 2709 4541

2.HAZARDS IDENTIFICATION**PHYSICAL HAZARDS**

Not classified

HEALTH HAZARDS

Acute toxicity (Oral)	Not classified
Acute toxicity (Dermal)	Category 5
Acute toxicity (Inhalation: Gases)	Not applicable
Acute toxicity: (Inhalation: Vapours)	Classification not possible
Acute toxicity (Inhalation: Dusts and mists)	Category 5
Skin corrosion/irritation	Category 3
Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Not classified
Skin sensitization	Category 1
Germ cell mutagenicity	Classification not possible
Carcinogenicity	Classification not possible
Reproductive toxicity	Category 2
Specific target organ toxicity - Single exposure	Not classified
Specific target organ toxicity - Repeated exposure	Not classified
Aspiration hazard	Classification not possible

ENVIRONMENTAL HAZARDS

Hazardous to the aquatic environment (Acute)	Category 3
Hazardous to the aquatic environment (Long-term)	Category 3
Hazardous to the ozone layer	Classification not possible

ALLOCATION OF LABEL ELEMENTS**Hazard symbol****Signal word**

Warning

Hazard statement

H313 May be harmful in contact with skin.
H316 Causes mild skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H333 May be harmful if inhaled.
H361 Suspected of damaging fertility or the unborn child.
H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements**Prevention**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

- P321 Specific treatment (see label).
- P302+P312 IF ON SKIN: Call a POISON CENTER/doctor/...if you feel unwell.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P304+P312 IF INHALED: Call a POISON CENTER/doctor/...if you feel unwell.
- P308+P313 IF exposed or concerned: Get medical attention/advice.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

- P405 Store locked up.

Disposal

- P501 Dispose of contents/container to..... (in accordance with local/regional/national/international regulation).

3.COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Preparation		Preparation
General Name		Synthetic rubber type Adhesives
Components Contributing to the Hazard		
Components	Cas No	%WT
Epoxy resin	25068-38-6	<5
Calcium oxide	1305-78-8	<5

4.FIRST AND MEASURES**Inhalation**

Call a POISON CENTER/doctor/...if you feel unwell.

Skin Contact

Call a POISON CENTER/doctor/...if you feel unwell.

Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Ingestion

Get medical attention/advice.

5.FIRE-FIGHTING**Extinguishing Media**

Carbon dioxide, dry chemical, water, foam, dry sand

Special Hazards

Toxic gases (nitrogen oxides) will foam upon combustion.

Special Methods

Evacuate non essential personnel.

Move container from fire areas if it can be done without risk.

Keep personnel removed from and upwind of fire.

Protection of Firefighters

Wear self-contained breathing apparatus.

6.ACCIDENTAL RELEASE MEASURES**Personal Precautions**

Wear protective equipment and avoid contact with skin and eye.

Environmental Precautions

Avoid release to the environment.

Methods for Cleaning up

Absorb with liquid-binding materials (sand, sawdust etc.).

Scoop material into containers for disposal.

7. HANDLING AND STORAGE

Handling

Technical Measures

Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wash thoroughly after handling.
Contaminated work clothing should not be allowed out of the workplace.
Keep containers closed when not in use.

Precautions

Use in the well-ventilated areas.

Storage

Suitable Storage Conditions

Keep container tightly closed.
Store in a cool (<10°C) and well-ventilated place.
Protect material from direct sunlight.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Components	Cas No	ACGIH (2018,TWA)
Epoxy resin	25068-38-6	Not established
Calcium oxide	1305-78-8	2 mg/m ³

Personal Protective Equipment

Hand Protection

Protective gloves

Eye Protection

Safety glasses

Skin and Body Protection

Avoid contact with skin.

Hygiene Measures

Wash hands before taking a break and at the end of work.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State

Form	Paste
Color	White
Odor	Slightly odor
pH	Not established
Flash point	>190°C
Density	About 1.4
Solubility	Not established
Other data	Not established

10. STABILITY AND REACTIVITY

Stability

Stable under the condition of normal usage.

Possible Hazardous Reactions

Not established

Conditions to Avoid

Strong heat

Hazardous Decomposition Products

Nitrogen compound

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Epoxy resin :	LD50 (Oral) :	Rat	11,400 mg/kg	(CERI Hazard Data 2001-36 (2002))
Calcium oxide :	LD50 (Oral) :	Rat	5,000 mg/kg and 5,916 mg/kg	(Risk Assessment Report (Food Additives) (Food Safety Commission of Japan, 2013))

Skin corrosion/irritation

Epoxy resin : Category 2
Calcium oxide : Category 2

Serious eye damage/eye irritation

Epoxy resin : Category 2B
Calcium oxide : Category 1

Skin sensitization

Epoxy resin : Category 1

Germ cell mutagenicity

Epoxy resin : Not classified

Reproductive toxicity

Epoxy resin : Not classified

Specific target organ toxicity - Single exposure

Calcium oxide : Category 1 (respiratory organs)

Specific target organ toxicity - Repeated exposure

Calcium oxide : Category 1 (respiratory organs)

12.ECOLOGICAL INFORMATION

Hazardous to the aquatic environment (Acute)

Epoxy resin :	EC50 (48H) :	Crustacea (Daphnia magna)	1.7 mg/L	(CERI/NITE Hazard Assessment Report (preliminary version) (2006) and others)
---------------	--------------	---------------------------	----------	--

13.DISPORSAL CONSIDERATIONS

Waste from Residues

Follow the all regulations in your country.

Contaminated Packaging

Follow the all regulations in your country.

14.TRANSPORT INFORMATION

UN Class None

UN No None

Packing group None

Specific Precautionary Transport Measures and Conditions

Follow the all regulations in your country.

15.REGULATORY INFORMATION

Follow the all regulations in your country.

16.OTHER INFORMATION

The information herein is given in good faith, but no warranty, express or implied, is made.

The information presented herein is believed to be accurate but is not warranted. Recipients are advised to confirm in advance that the information is current, applicable and suitable to there circumstances.