

SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name	Glass Primer 435-41
Manufacturer Name	Sunstar Chemical (Thailand) Co.,Ltd.
Address	624 Moo 4 Bangpoo Industrial Estate Soi 7A Sukhumvit Rd., Praksa, Muang Samutprakarn, Samutprakarn 10280 Thailand
Telephone Number	+66 2709 4531
Fax Number	+66 2709 4541

2. HAZARDS IDENTIFICATION

PHYSICAL HAZARDS

Category 2 (Flammable liquids)

HEALTH HAZARDS

Acute toxicity: oral	Category 5
Acute toxicity: skin	Not classified
Acute toxicity: inhalation(gas)	Not applicable
Acute toxicity: inhalation(vapor)	Category 5
Acute toxicity: inhalation(mist)	Classification not possible
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Respiratory sensitization	Classification not possible
Skin sensitization	Classification not possible
Germ cell mutagenicity	Classification not possible
Carcinogenicity	Category 2
Toxic to reproduction	Not classified
Specific target organ systemic toxicity (single exposure)	Category 2 (Kidney)
Specific target organ systemic toxicity (repeated exposure)	Category 1 (Nervous system)
Aspiration hazard	Not classified

ENVIRONMENTAL HAZARDS

Aquatic toxicity (acute)	Not classified
Aquatic toxicity (chronic)	Not classified
Hazardous to the ozone layer	Classification not possible

ALLOCATION OF LABEL ELEMENTS

Hazard symbol



Signal word

Danger

Hazard statement

- H225 Highly flammable liquid and vapour
- H303 May be harmful if swallowed
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H333 May be harmful if inhaled.
- H351 Suspected of causing cancer
- H371 May cause damage to organs (Kidney)
- H372 Causes damage to organs through prolonged or repeated exposure (Nervous system)

Precautionary statements

Prevention

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, hot surface, sparks, open flames, and other ignition. No smoking.
- P233 Keep container tightly closed.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof (electric equipment, ventilator etc.) equipment.
- P242 Use only non-sparking tools.
- P243 Take action to prevent static discharges.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

- P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P303+P361+P353 IF ON SKIN(or hair): Take off immediately all contaminated clothing Rinse skin with water/shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYE: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P311 IF exposed or concerned: Call a POISON CENTER or doctor/physician if you feel unwell.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P312 Call a POISON CENTER/doctor, if you feel unwell.
 P314 Get medical attention if you feel unwell.
 P332+P313 If skin irritation occurs, Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P370+P378 In case of fire: Use appropriate media to extinguish.

Storage

- P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal

- P501 Dispose of contents/container to..... (in accordance with local/regional/national/international regulation).

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Preparation Preparation

General Name Primer

Components Contributing to the Hazard

Components	Cas No	%WT
Carbon Black	1333-86-4	5-15
Methyl ethyl ketone	78-93-3	65
Ethyl acetate	141-78-6	3
Xylene	1330-20-7	<1
Tri isopropanol Amine	122-20-3	<3
Ethyl benzene	100-41-4	<1

4. FIRST AID MEASURES**Inhalation**

- Remove to fresh air and get immediate medical attention
 Call a poison center or doctor/physician if you feel unwell.

Skin Contact

- Wash with plenty of soap and water. Take off contaminated clothing and wash before re-use.
 If skin irritation occurs, seek medical advice/attention.

Eye Contact

- Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing. Immediately call a poison center or doctor/physician.

Ingestion

- Call a poison center or doctor/physician if you feel unwell.
 Rinse mouth.

5. FIRE-FIGHTING**Extinguishing Media**

- Carbon dioxide, foam, dry sand

Special Hazards

- No data

Special Methods

- Evacuate non essential personnel
 Move container from fire areas if it can be done without risk
 Keep personnel removed from and upwind of fire

Protection of Firefighters

- Wear self-contained breathing apparatus

6. ACCIDENTAL RELEASE MEASURES**Personal Precautions**

- Wear protective equipment and avoid contact with skin and eye

Environmental Precautions

- Do not allow to enter sewers/surface or groundwater

Methods for Cleaning up

- Absorb with liquid - binding materials (sand, sawdust etc)
 Scoop material into containers for disposal

7. HANDLING AND STORAGE

Handling

Technical Measures

- Keep away from sources of ignition
- Avoid eye and skin contact
- Keep containers closed when not in use

Precautions

- Use in the well - ventilated areas

Storage

Suitable Storage Conditions

- Keep container closed
- Store in refrigerator (5-10°C)
- Protect material from direct sunlight

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Components

Carbon Black	ACGIH (2019,TLV)
Methyl ethyl ketone	3 mg/m ³
Ethyl acetate	200 ppm
Xylene	400 ppm
Tri isopropanol Amine	100 ppm
Ethyl benzene	-
	20 ppm

Personal Protective Equipment

Hand Protection

- Protective gloves

Eye Protection

- Safety glasses

Skin and Body Protection

- Avoid contact with skin

Hygiene Measures

- Wash hands before breaks and at the end of work

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State

Appearance	Liquid
Color	Black
Odour	Slight odor
pH	Not applicable
Melting point/freezing point	No data
Initial boiling point and boiling range	No data
Flashpoint	-2 °C
Evaporation rate	No data
Flammability	No data
Upper/lower flammability or explosive limits	No data
Vapour pressure	No data
Relative density	About 0.9
Solubility	Soluble in solvent
Partition coefficient:n-octanol/water	No data
Auto-ignition temperature	No data
Viscosity	No data

10. STABILITY AND REACTIVITY

Stability

- Stable under normal conditions

Possible Hazardous Reactions

- No data

Conditions to Avoid

- High Heat

Hazardous Decomposition Products

- Chlorine gas (in addition to CO, CO₂, H₂O)

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Carbon Black	LD50 (Oral)	Rat	8,000 mg/kg	SIDS (2007)
Methyl ethyl ketone	LD50 (Oral)	Rat	2,737mg/kg	MOE Risk Assessment Volume 6 (2008)
	LD50 (Dermal)	Rabbit	5,000mg/kg	PATTY (6th, 2012)
Ethyl acetate	LD50 (Oral)	Rat	4,940 mg/kg	PATTY (5th, 2001)
	LD50 (Dermal)	Rabbit	18000 mg/kg	DFGOT vol. 12 (1999)
Xylene	LD50 (Oral)	Rat	3,500-8,800 mg / kg	NITE Hazard Assessment Report (2008)
	LD50 (Dermal)	Rabbit	1,700 mg / kg	EPA Pesticide (2005)
Ethylbenzene	LD50 (Oral)	Rat	3,500 mg/kg	MOE Risk Assessment Vol. 13 (2015)
	LD50 (Dermal)	Rabbit	5,000 mg / kg	PATTY (6th, 2012)
Tri isopropanol Amine	LD50 (Oral)	Rat	4,730 mg/kg	PATTY (5th, 2001)
	LD50 (Dermal)	Rabbit	10,000 mg / kg	PATTY (5th, 2001)

Skin corrosion

Carbon Black	Not classified
Methyl ethyl ketone	Category 2
Ethyl acetate	Not classified
Xylene	Category 2
Ethylbenzene	Not classified
Tri isopropanol Amine	Category 2

Serious Eye Damage/Irritation

Carbon Black	Not classified
Methyl ethyl ketone	Category 2A
Ethyl acetate	Category 2B
Xylene	Category 2
Ethylbenzene	Category 2B
Tri isopropanol Amine	Category 2A

Skin Sensitisation

Ethyl acetate	Not classified
Tri isopropanol Amine	Not classified

Germ Cell Mutagenicity

Ethyl acetate	Not classified
Tri isopropanol Amine	Not classified

Carcinogenicity

Carbon Black	Category 2
Ethylbenzene	Category 2

Reproductive toxicity

Xylene	Category 1B
Ethylbenzene	Category 1B

Specific target organ systemic toxicity (single exposure)

Methyl ethyl ketone	Category 2 (kidney) Category 3 (respiratory irritation, anesthetic effect)
Ethyl acetate	Category3 (Respiratory tract irritation, Narcotic effects)
Xylene	Category1 (central nervous system, respiratory system, liver, kidney) Class 3 (narcotic effects)
Ethylbenzene	Category 3(Respiratory tract irritation, Narcotic effects)
Tri isopropanol Amine	Category 3 (narcotic action)

Specific target organ toxicity (Repeated exposure)

Carbon Black	Category 1 (respiratory organ)
Methyl ethyl ketone	Category 1 (nervous system)
Xylene	Category 1 (nervous system, respiratory system)
Ethylbenzene	Category 2 (auditory organ)

Aspiration hazard

Xylene	Category 1
Ethylbenzene	Category 1

12. ECOLOGICAL INFORMATION**Aquatic toxicity (acute)**

Carbon Black	EC50(72H)	Algae (Cenedesmus)	> 10000 mg / L	HSDB, 2009
	EC50(24H)	Crustacean (Daphnia magna)	> 5600 mg / L	HSDB, 2009
Methyl ethyl ketone	ErC5(72H)	Algae (Pseudokirchnerella subcapitata)	> 1200 mg / L	Ministry of the Environment risk assessment Vol. 6, 2008
	LC50(48H)	Crustacea (Daphnia magna)	> 1000 mg / L	Ministry of the Environment risk assessment Vol. 6, 2008
	LC50(96H)	Fish (rainbow trout)	> 100 mg / L	Ministry of the Environment risk assessment Vol. 6, 2008
Ethyl acetate	LC50(96H)	Fish (fathead minnow)	230 mg / L	SIDS, 2008
	LC50(24H)	Shellfish (Daphnia magna)	2,500 mg / L	SIDS, 2008
Xylene	LC50(96H)	Fish (rainbow trout)	3.3 mg / L	NITE initial risk assessment report, 2005
Ethylbenzene	LC50(96H)	Crustacea (Bay shrimp)	0.42 mg / L	NITE Initial Risk Assessment Report, 2007
Tri isopropanol Amine	EC50(72H)	Algae	35 mg/L	BUA, 1993

Aquatic toxicity (chronic)

Methyl ethyl ketone	NOEC(72H)	Algae (Pseudokirchnerella subcapitata)	93 mg / L	Ministry of the Environment Risk Assessment Vol. 6, 2008
Ethyl acetate	water solubility	-	80000 mg / L	PHYSPROP Database, 2009
Xylene	NOEC	Fish (rainbow trout)	1.3 mg / L	SIAP (Conclusions agreed Not classified because it is SIAM 16, 2003
Ethylbenzene	LC50(96H)	Fish (striped bass)	3.7 mg / L	NITE initial risk assessment report, 2007
Tri isopropanol Amine	BOD	-	3.40%	Existing check, 1978

13. DISPOSAL CONSIDERATIONS**Waste from Residues**

Follow the all regulations in your country.

Contaminated Packaging

Follow the all regulations in your country.

14. TRANSPORT INFORMATION

UN Class	3
UN No	1133 (Adhesive)
Packing group	II

Specific Precautionary Transport Measures and Conditions

Follow the all regulations in your country.

15. REGULATORY INFORMATION

Follow the all regulations in your country.

16. OTHER INFORMATION

The information herein is given in good faith, but no warranty, express or implied, is made.

The information presented herein is believed to be accurate but is not warranted. Recipients are advised to confirm in advance that the information is current, applicable and suitable to there circumstances.