

**HZT-519A**

Date : November 28, 2023

Safety Data Sheet

Section 1: Chemical Product and Company Identification

Material name : **HZT-519A**
 Manufacturer name : Riken (Thailand) Co., Ltd.
 Address : 143 Moo 5 Bangkadi Industrial Park, Tivanond Road, Bangkadi,
 Muang- Pathumthani, Pathumthani 12000, Thailand.
 Phone : (662) 501-1054
 Fax : (662) 501-1198

Section 2: Hazard Identification

GHS Classification (Refer Thai Hazardous Substance Act B.E. 2535)

Physical hazards : Irrelevant
 Environmental hazards : Irrelevant
 Health hazards : Irrelevant
Other hazards : Trace amount of hydrogen chloride may be generated from the PVC component if overheated. Volatiles from other additives which may be generated in trace amounts may prove sensitive to some individuals.

Section 3: Composition / Information on Ingredients

Chemical name/Synonyms : Polyvinyl chloride compound

Component	CAS No.	%approximate
Polyvinyl chloride resin	9002-86-2	40.9
Other Additives	-	59.1

Polyvinyl chloride compounds are mixtures of Polyvinyl chloride resin with various functional additives. Additives are bound up in the manufacturing process and not expected to create any hazard when handled or processed in accordance with good manufacturing and industrial hygiene practices.

Section 4: First Aid Measures

Skin contact :

The compound is not likely to be hazardous by skin contact but cleansing the skin after use is advisable. If molten material gets on skin, cool rapidly with cold water. Do no attempt to remove material from skin. Obtain medical treatment for thermal burn.

Eye contact :

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call physician.

Inhalation :

If inhaled, remove to fresh air. If no breathing, give artificial respiration. If breathing is difficult, give oxygen. Call physician.

**HZT-519A**

Date : November 28, 2023

Ingestion

No specific intervention is indicated as compound is not likely to be hazardous by ingestion.
Consult a physician if necessary.

Most important symptoms and effects, both acute and delayed

No data available.

Identification of any immediate medical and special treatment needed

Hazard : No data available.

Treatment : Treat symptomatically

Section 5: Fire Fighting Measures**Extinguishing Media**

Water, ABC dry chemical, Foam

Special Fire Fighting Procedure

Firefighter should be equipped with Self Contained Breathing Apparatus (SCBA) during and after a fire.

Combustion Products

When vinyl compound are burnt, they will generate hydrogen chloride, carbon monoxide, carbon dioxide, aliphatic olefins and trace amount of benzene, aliphatic and aromatic hydrocarbon. Hydrogen chloride is corrosive gas that effect on many metal so it should be taken by appropriate measure when exposure occurs.

Section 6: Accidental Release Measures

Vacuum or sweep into a closed container for reuse or disposal with personal protective equipment. (See section 8)

Section 7: Handling and Storage**Handling (Personnel)**

Avoid contact with eyes and skins. Avoid breathing vapor or dust.

Handling (Physical Aspects)

Avoid dust generation. Close container after each use. Keep away from heat, sparks and flames.

Storage

Store in original container in cool, dry area and protect from light. Keep away from heat, moisture, oxidizing agents, peroxides and water.

Section 8: Exposure Controls and Personal Protection**Engineering control**

Use local ventilation to control fumes from hot processing.

Protective equipment

Use gloves, respirators, safety glasses, coverall and safety shoes.

**HZT-519A**

Date : November 28, 2023

Section 9: Physical and Chemical Properties

Appearance	: Natural or color granule
Odor	: Odorless or bland odor
Flash point	: > 300 °C
Ignition temperature	: > 410 °C
Evaporation rate	: Not applicable
Flammability	: Not applicable
Vapor pressure	: Not applicable
Specific Gravity	: Range 1.0 ~ 1.8
Solubility in water	: Insoluble

Section 10: Stability and Reactivity**Chemical stability**

Stable at normal temperatures and storage conditions.

Possibility of hazardous reaction

Does not occur.

Condition to avoid

Do not leave materials for a long time at elevated temperatures in order to avoid decomposition.

Incompatible material

Avoid contact with acetal, acetal copolymers and amines all of which will cause rapid degradation of vinyl compound.

Hazardous decomposition products

Hydrogen chloride , Carbon Monoxide, Carbon Dioxide, Aliphatic Olefins. Trace amount of Benzene and Aromatic and Aliphatic Hydrocarbon.

Section 11: Toxicological Information

Acute toxicity	: No data available.
Eye effects	: No data available, but may cause eye irritation by decomposition gas.
Skin effects	: No data available, but may cause irritation by decomposition gas.
Inhalation effects	: No data available, but may cause irritation of nasal passages and throat by decomposition gas.

Section 12: Ecological Information

Ecological information: No data available.

Section 13: Disposal Condition

Incineration or landfill in accordance with local regulations as industrial waste.
Treat the not cleaned packaging same as the product.

Section 14: Transportation Information

UN number	: not applicable
IMDG	: not applicable
Needs to handle carefully not to get any damages on this product.	

**HZT-519A**

Date : November 28, 2023

Section 15: Regulatory Information

No information available

Section 16 :Other Information

The material on this SDS is designed for industrial purpose only. Riken (Thailand) Co., Ltd. should not have any responsibility and guarantee for use in different purposes, such as toys food contact films, and other than industrial design,

This information is based upon technical information believed to be reliable. It is subject to revision as additional knowledge and experience is gained.

This product should be stored, handled, and used in accordance with good industrial hygiene practices and in conformity with any legal regulation. Safe handling and use remain the responsibility of the customer.