

Issuing Date 16-Sep-2021
Revision date 09-Mar-2023
Revision Number 2

1. Identification

Product Name ThreeBond 1501

Details of the supplier of the safety data sheet

Supplier

ThreeBond Fine Chemical Co., Ltd.
1-1 Oyama-cho, Midori-ku, Sagamihara-shi, Kanagawa 252-0146 Japan

Emergency telephone number

+81-42-703-7126 (Inquiries regarding SDS content)
+81-42-670-5333 (Inquiries regarding the product or SDS claim)

Recommended use of the chemical and restrictions on use

Recommended use Adhesive, Sealant

Restrictions on use

Please be sure to confirm in advance the appropriateness and safety of using the product for the relevant application. If the product is to be used for applications other than those recommended, please seek professional judgment. This product is for industrial use and its use for household and medical implants is prohibited.

2. Hazard(s) identification

GHS Classification

Flammable liquids	Category 2
Acute toxicity - Oral	Classification not possible
Acute toxicity - Dermal	Classification not possible
Acute toxicity - Inhalation (Gases)	Classification not applicable
Acute toxicity - Inhalation (Vapors)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Classification not possible
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Classification not possible
Skin sensitization	Classification not possible
Germ cell mutagenicity	Classification not possible
Carcinogenicity	Classification not possible
Reproductive toxicity	Category 1A
Effects on or via lactation	Classification not possible
Specific target organ toxicity (single exposure)	Category 1, Category 3
Category 1 Central nervous system.	
Category 3 Target organ effects: Respiratory irritation, Narcotic effects.	
Specific target organ toxicity (repeated exposure)	Category 1
Category 1 Central nervous system, kidneys, nervous system.	
Aspiration hazard	Category 1
Acute aquatic toxicity	Category 2
Chronic aquatic toxicity	Category 3



Ozone	Classification not possible
-------	-----------------------------

GHS label elements



Signal word

Danger

Hazard statements

H225 - Highly flammable liquid and vapor

H332 - Harmful if inhaled

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H360 - May damage fertility or the unborn child

H370 - Causes damage to organs

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H372 - Causes damage to organs through prolonged or repeated exposure

H401 - Toxic to aquatic life

H412 - Harmful to aquatic life with long lasting effects

H304 - May be fatal if swallowed and enters airways

Causes damage to the following organs: Central nervous system.

Causes damage to the following organs through prolonged or repeated exposure: Central nervous system, kidneys, nervous system.

Precautionary statements

Prevention

- Do not handle until all safety precautions have been read and understood
- Wear protective gloves/protective clothing/eye protection/face protection
- Use only outdoors or in a well-ventilated area
- Wash face, hands and any exposed skin thoroughly after handling
- Do not breathe dust/fume/gas/mist/vapors/spray
- Do not eat, drink or smoke when using this product
- Avoid release to the environment
- Ground and bond container and receiving equipment
- Use non-sparking tools
- Take action to prevent static discharges
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- Keep container tightly closed
- Keep cool
- Obtain special instructions or technical data sheet before use
- Use explosion-proof electrical/ ventilating/ lighting/ equipment

Response

- IF exposed or concerned: Get medical advice/attention
- IF exposed or concerned: Call a POISON CENTER or doctor
- Specific treatment (see section 4 on this SDS)

Eyes

- Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention

Ingestion

- IF SWALLOWED: Immediately call a POISON CENTER or doctor
- Do NOT induce vomiting

Skin

- IF ON SKIN: Wash with plenty of water and soap
- If skin irritation occurs: Get medical advice/attention
- Take off contaminated clothing and wash it before reuse
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]

Inhalation

- IF INHALED: Remove person to fresh air and keep comfortable for breathing
- Call a POISON CENTER or doctor if you feel unwell

Fire

- In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed

Disposal

- Dispose of contents/container to an approved waste disposal plant

Other hazards

No information available.

3. Composition/information on ingredients

Pure substance/mixture

Mixture

Chemical name	CAS No	Weight-%	ENCS Number	ISHL No
Toluene	108-88-3	61	(3)-2,(3)-60	2-(8)-869
Hexane	110-54-3	16	(2)-6	(2)-6
Rosin	8050-09-7	0.1-<1		
Chloroprene Synthetic rubber, Synthetic resin	-	20-<30		

This product contains ≥ 0.1 - $< 1.0\%$ of substance(s) that are classified for Skin sensitization Category 1/1B.

Until March 31, 2023 Pollutant Release and Transfer Register (PRTR)

The amount of the relevant substance in certain cases referenced in article 4(i)(a) or 4(i)(b) of the Enforcement Order of the Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the Environment and Promotion of Improvements to the Management Thereof (PRTR Act) is calculated based on the conversion factors shown (with safety factor = 1 in cases where conversion factor information is not available)

Chemical name	Cabinet order name	Metal, CN, F, etc	Conversion coefficient	Content rate %	Category	Ordinance number	Control number
Toluene	Toluene			61	Class I designated chemical substance	1-300	300
*	N-Hexane			16	Class I designated chemical substance	1-392	392

* Refer to Cabinet order name

After April 1, 2023 Pollutant Release and Transfer Register (PRTR)

The amount of the relevant substance in certain cases referenced in article 4(i)(a) or 4(i)(b) of the Enforcement Order of the Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the Environment and Promotion of Improvements to the Management Thereof (PRTR Act) is calculated based on the conversion factors shown (with safety factor = 1 in cases where conversion factor information is not available)

Chemical name	Cabinet order name	Metal, CN, F, etc	Conversion coefficient	Content rate %	Category	Ordinance number	Control number
Toluene	Toluene			61	Class I designated chemical substance	1-347	300
Hexane	Hexane			16	Class I designated chemical substance	1-436	392

Industrial Safety and Health Law**ISHL Notifiable Substances**

Article 57-2 of the ISHL, Article 18-2, Item 1, Item 2, Table 9 and Item 3, Table 3 of Order for Enforcement

Chemical name	CAS No	Category	Ordinance number
Toluene	108-88-3	ISHL Notifiable Substances	Attached table 9-407
Hexane	110-54-3	ISHL Notifiable Substances	Attached table 9-520
Rosin	8050-09-7	ISHL Notifiable Substances	Attached table 9-632

Harmful Substances Whose Names Are to be Indicated on the Label

Article 57 of ISHL, Article 18, Item 1, Item 2, Table 9 and Item 3, Table 3 of Order for Enforcement

Chemical name	CAS No	Category	Ordinance number
Toluene	108-88-3	Harmful Substances Whose Names Are to be Indicated on the Label	Attached table 9-407
Hexane	110-54-3	Harmful Substances Whose Names Are to be Indicated on the Label	Attached table 9-520

Poisonous and Deleterious Substances Control Law

Not applicable

Act on the Evaluation of Chemical Substances and Regulation of Their Manufacture, etc. (CSCL)

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed

Chemical name	CAS No	Chemical Substances Control Law
Toluene	108-88-3	Priority assessment chemical substance
Hexane	110-54-3	Priority assessment chemical substance

4. First-aid measures**General advice**

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

In case of inhalation

Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur.

In case of skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.

In case of eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. If symptoms persist, call a physician. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

In case of ingestion

Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical advice/attention.

Most important symptoms/effects, acute and delayed

Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Burning sensation.

Self-protection of the first aider

Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin,

eyes or clothing.

Note to physicians

Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

5. Fire-fighting measures

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire, cool container with water spray.
Flammable properties	HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Containers may explode when heated. Many liquids are lighter than water.
Special Extinguishing Media	Cool container with water spray.
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
Other information	CAUTION: Use of water spray when fighting fire may be inefficient.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.
For emergency responders	Use personal protection recommended in Section 8.
Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

7. Handling and storage

Handling

Advice on safe handling

Take equipment measures listed in Section 8. Wear protection gear. Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep

in an area equipped with sprinklers. Use according to package label instructions. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse.

Hygiene Measures

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

Storage

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Exposure guidelines

Chemical name	Japan Society of Occupational Health	ISHL Working Environmental Evaluation Standards - Administrative Control Levels	ACGIH TLV
Toluene 108-88-3	TWA: 50 ppm TWA: 188 mg/m ³ S*	20 ppm	Ototoxicant - potential to cause hearing disorders TWA: 20 ppm
Hexane 110-54-3	TWA: 40 ppm TWA: 140 mg/m ³ S*	40 ppm	TWA: 50 ppm S*
Rosin 8050-09-7	-	-	dermal sensitizer;respiratory sensitizer TWA: 0.001 mg/m ³ total resin acids inhalable particulate matter

Biological occupational exposure limits

Chemical name	Japan Society of Occupational Health	ACGIH
Toluene 108-88-3	0.6 mg/L - blood (Toluene) - within 2 h prior to end of shift at end of work week 0.06 mg/L - urine (Toluene) - within 2 h prior to end of shift at end of work week	0.02 mg/L - blood (Toluene) - prior to last shift of workweek 0.03 mg/L - urine (Toluene) - end of shift 0.3 mg/g creatinine - urine (o-Cresol with hydrolysis) - end of shift
Hexane 110-54-3	3 mg/g creatine - urine (2,5-Hexanedione) - end of shift at end of work week 0.3 mg/g creatine - urine (2,5-Hexanedione) - end of shift at end of work week	0.5 mg/L - urine (2,5-Hexanedione without hydrolysis) - end of shift

Engineering controls

Showers
Eyewash stations
Ventilation systems.

Environmental exposure controls

Install safety shower, hand wash, and eye wash station. Clearly indicate the location. Install

local ventilation or seal source of substances.

Personal protective equipment

Respiratory protection	In case of inadequate ventilation wear respiratory protection.
Hand protection	Wear suitable gloves. Impervious gloves.
Eye/face protection	Tight sealing safety goggles.
Skin and body protection	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Liquid
Color	brown
Odor	Solvent odor
<u>Property</u>	<u>Values</u>
Melting point / freezing point	no data available
Initial boiling point and boiling range	67 °C or above
Flammability	no data available
Upper/lower flammability or explosive limits	
Upper flammability or explosive limits	no data available
Lower flammability or explosive limits	no data available
Flash point	-20 °C
Evaporation rate	no data available
Autoignition temperature	no data available
Decomposition temperature	no data available
pH	no data available
Viscosity	
Kinematic viscosity	
Dynamic viscosity	3.3 Pa • s
Water solubility	Slightly soluble
Solubility(ies)	no data available
Partition Coefficient	no data available
(n-octanol/water)	
Vapor pressure	no data available
Density and/or relative density	
Relative density	0.94
Liquid Density	no data available
Bulk density	no data available
Relative vapor density	no data available
Particle characteristics	
Particle Size	no data available
Particle Size Distribution	no data available

Other information

Explosive properties	no data available
Oxidizing properties	no data available

10. Stability and reactivity

Chemical stability	Stable under normal conditions
Possibility of hazardous reactions	React with strong oxidizing agent. Could cause fire.
Conditions to avoid	heating.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	May generate harmful gas by incineration.

11. Toxicological information

Acute toxicity

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal)	15,426.10 mg/kg
ATEmix (inhalation-vapor)	14.40 mg/l
ATEmix (inhalation-dust/mist)	12.935 mg/l

Unknown acute toxicity

21.45819 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Toluene	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
Hexane	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
Rosin	= 7600 mg/kg (Rat)	> 2500 mg/kg (Rabbit)	= 1.5 mg/L (Rat) 4 h

Abbreviations and acronyms

Rat: Rat

Rabbit: Rabbit

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes.
-----------------	--

Product Information

Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Inhalation	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract.
Skin contact	Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Eye contact	Specific test data for the substance or mixture is not available. Irritating to eyes. (based on components). Causes serious eye irritation.
Skin corrosion/irritation	Classification based on data available for ingredients. Irritating to skin.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization Classification not possible.

Germ cell mutagenicity Based on available data, the classification criteria are not met. Classification not possible.

Carcinogenicity Based on available data, the classification criteria are not met. Classification not possible.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Japan	IARC
Toluene 108-88-3	-	Group 3

Legend

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity Contains a known or suspected reproductive toxin. Classification based on data available for ingredients. May damage fertility or the unborn child.

STOT - single exposure Based on the classification criteria of the Globally Harmonized System as adopted in the country or region with which this safety data sheet complies, this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). Causes damage to organs. May cause respiratory irritation. May cause drowsiness or dizziness.

Causes damage to the following organs: Central nervous system.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Causes damage to the following organs through prolonged or repeated exposure: Central nervous system, kidneys, nervous system.

Aspiration hazard May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Crustacea
Toluene	EC50: >433mg/L (96h, Pseudokirchneriella subcapitata) EC50: =12.5mg/L (72h, Pseudokirchneriella subcapitata)	LC50: 15.22 - 19.05mg/L (96h, Pimephales promelas) LC50: =12.6mg/L (96h, Pimephales promelas) LC50: 5.89 - 7.81mg/L (96h, Oncorhynchus mykiss) LC50: 14.1 - 17.16mg/L (96h, Oncorhynchus mykiss) LC50: =5.8mg/L (96h, Oncorhynchus mykiss) LC50: 11.0 - 15.0mg/L (96h,	EC50: 5.46 - 9.83mg/L (48h, Daphnia magna) EC50: =11.5mg/L (48h, Daphnia magna)

		Lepomis macrochirus) LC50: =54mg/L (96h, Oryzias latipes) LC50: =28.2mg/L (96h, Poecilia reticulata) LC50: 50.87 - 70.34mg/L (96h, Poecilia reticulata)	
Hexane	-	LC50: 2.1 - 2.98mg/L (96h, Pimephales promelas)	-
Rosin	EC50: =400mg/L (72h, Desmodemus subspicatus)	-	EC50: 3.8 - 5.4mg/L (48h, Daphnia magna)

Percentage for unknown hazards

0.006 % of the mixture consists of component(s) of unknown hazards to the aquatic environment.

Persistence and degradability

No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Toluene 108-88-3	2.73
Hexane 110-54-3	4
Rosin 8050-09-7	7.7

Mobility in soil

No information available.

Hazardous to the ozone layer

Classification not possible. Based on available data, the classification criteria are not met.

Other adverse effects

No information available.

Endocrine Disruptor Information

13. Disposal considerations

Waste from residues/unused products

Dispose of in accordance with national, state and local regulations. Consult industrial waste management companies for waste. Do not release this product to natural environment nor reclaim.

Contaminated packaging

Dispose containers as same as residual of this product.

14. Transport information

IMDG

UN number or ID number UN1133
 UN proper shipping name Adhesives
 Description UN1133, Adhesives, 3, II, (-20°C c.c.), Marine pollutant
 Transport hazard class(es) 3
 Packing group II
 Marine pollutant NP
 EmS-No F-E, S-D

ADR

UN number or ID number UN1133
 UN proper shipping name Adhesives
 Description UN1133, Adhesives, 3, II, (D/E), Environmentally Hazardous

Transport hazard class(es)	3
Packing group	II
Environmental hazards	Yes
ERG Code	3L
Special Provisions	640C

IATA

UN number or ID number	UN1133
UN proper shipping name	Adhesives
Description	UN1133, Adhesives, 3, II
Transport hazard class(es)	3
Packing group	II
Special Provisions	A3

Japan

UN number or ID number	UN1133
UN proper shipping name	Adhesives
Description	UN1133, Adhesives, 3, II
Transport hazard class(es)	3
Packing group	II

15. Regulatory information

National regulations

Until March 31, 2023 Pollutant Release and Transfer Register (PRTR)

Applies See section 3 for more information

After April 1, 2023 Pollutant Release and Transfer Register (PRTR)

Applies See section 3 for more information

Industrial Safety and Health Law

Harmful Substances Requiring Workers to Subject to Medical Exams

Medical Examination - Industrial Safety and Health Law article 66, enforcement order article 22, and the Ordinance on Prevention of Hazards Due to Specified Chemical Substances, Table 5

Ordinance on Prevention of Organic Solvent Poisoning

Organic solvents class 2 - Industrial Safety and Health Law enforcement order Table 6-2 (related to article 6, article 21, article 22, and the Ordinance on Prevention of Organic Solvent Poisoning)

Harmful Substances Whose Names Are to be Indicated on the Label

Article 57 of ISHL, Article 18, Item 1, Item 2, Table 9 and Item 3, Table 3 of Order for Enforcement

ISHL Notifiable Substances

Article 57-2 of the ISHL, Article 18-2, Item 1, Item 2, Table 9 and Item 3, Table 3 of Order for Enforcement

Poisonous and Deleterious Substances Control Law

Not applicable

Explosives Control Law

Not applicable

High Pressure Gas Safety Act

Not applicable

Fire Service Law:

Flammable liquids, group 4, 1st class petroleums, water-insoluble, hazard rank II, 200 liters

Act on the Evaluation of Chemical Substances and Regulation of Their Manufacture, etc. (CSCL)

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed

Chemical name	CAS No	Chemical Substances Control Law
Toluene	108-88-3	Priority assessment chemical substance
Hexane	110-54-3	Priority assessment chemical substance

Ship (Marine Transportation) Safety Act

See section 14 for more information

Civil Aeronautics Act

See section 14 for more information

Act on Port Regulation Law

See section 14 for more information

16. Other information

Issuing Date 16-Sep-2021
Revision date 09-Mar-2023

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	Ceiling	Maximum limit value
*	Skin designation	+	Sensitizers

Key literature references and sources for data used to compile the SDS

JIS Z 7252:2019 Classification of chemicals based on "Globally Harmonized System of Classification and Labelling of Chemicals (GHS)". JIS Z 7253:2019 Hazard communication of chemicals based on GHS-Labelling and Safety Data Sheet (SDS).

Disclaimer

This SDS complies with the requirements of JIS Z 7252:2019 and JIS Z 7253:2019 (Japan). The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.