

Safety Data Sheet

Issued Date: November 12, 2008
Revised Date: November 21, 2008

1. IDENTIFICATION

PRODUCT NAME
ISSUED NUMBER
NAME OF MANUFACTURER
ADDRESS
NAME OF SECTION
TEL / FAX NUMBER
EMERGENCY TEL NUMBER
RECOMMENDED USE AND RESTRICTION ON USE

ThreeBond 1804
kenkyukanri 949-2
Three Bond Co., Ltd.
1456, Hazama-cho, Hachioji-shi, Tokyo, Japan
Administration Department Research Division
+81-42-661-1367 / +81-42-669-7235
+81-42-661-1367
Anti-corrosive agent and Lubricants

COPY

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATION
PHYSICAL HAZARDS

Flammable aerosols

Category 1

Flammable liquids

Category 4

HEALTH HAZARDS

Germ cell mutagenicity

Category 2

Reproductive toxicity

Category 2

Specific target organ toxicity

after single exposure

Category 2 (Lungs)

after repeated exposure

Category 1

(Skin, Lungs)

Aspiration toxicity

Category 1

*Not above mentioned hazard classification items; Not classified or Not classifiable.

LABEL ELEMENTS
SYMBOL



SIGNAL WORD

Danger

HAZARD STATEMENT

H222 Extremely flammable aerosol
H228 Flammable solid
H341 Suspected of causing genetic defects
H361 Suspected of damaging fertility or the unborn child
H371 May cause damage to organs; Lungs
H372 Causes damage to organs (Lungs, Skin) through prolonged or repeated
H305 May be harmful if swallowed and enters airways

NOTICE

SAFETY MEASURE

Keep away from heat/sparks/open flames/hot surfaces. -No smoking
Do not spray on open flame or other ignition source.

FIRST AID MEASURE

Wear appropriate chemical protectors; gloves, glasses when handling
If you feel unwell, remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF SWALLOWED: Rinse mouth. Do not induce vomiting.
IF ON SKIN: Wash with plenty of soap and water. Remove immediately all contaminated clothing.
If skin irritation or rash occurs: Get medical advice, attention.
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice, attention.

STORAGE

Protect from sunlight, and store at temperatures not exceeding 40 °C.

DISPOSAL

Solicit waste disposal management experts.

GHS Hazard Communication is mentioned in accordance with Japanese Law.



Safety Data Sheet

Issued Date: November 12, 2008

Revised Date: November 21, 2008

3. COMPOSITION / INFORMATION ON INGREDIENTS

SUBSTANCE/MIXTURE	Mixture		
CHEMICAL COMPOSITION			
INGREDIENTS	Wt%	Formula	CAS Number
Mineral oil	5 — 15	—	—
Isoparaffin, Petroleum sulfonate lubricant	25 — 35	—	—
Ethylene glycol monobutyl ether	< 1	C ₆ H ₁₄ O ₂	111-76-2
Butane (Propellant)	35 — 45	C ₄ H ₁₀	106-97-8
Propane (Propellant)	10 — 20	CH ₃ CH ₂ CH ₃	74-98-6
IMPURITIES AND STABILIZING ADDITIVES WHICH ARE THEMSELVES CLASSIFIED AND WHICH CONTRIBUTE TO THE CLASSIFICATION OF THE SUBSTANCE	No information		

4. FIRST-AID MEASURES

IF INHALED	In case of poisoning, remove victim to fresh air, calm down, keep warm then get medical advice, attention.
IF ON SKIN	Wash with soap and water. If skin irritation or rash occurs, get medical advice, attention.
IF IN EYES	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF SWALLOWED	Rinse mouth. Get medical advice, attention.

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA	Dry powder, alcohol-resistant foam and carbon dioxide extinguisher, dry sand, water spray
SPECIFIC HAZARDS ARISING FROM THE CHEMICAL	May produce poisonous and irritated gasses upon a fire. May burst the container upon heating.
SPECIFIC FIRE FIGHTING MEASURES	Workers should wear appropriate protectors (glasses, cloths, mask for poisonous gasses, etc.), then extinguish should be performed up wind. Transfer the product container from a fire area, if no danger around.

6. ACCIDENTAL RELEASE

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES	Wear appropriate protective equipment (refer to 8. Exposure Control/Personal Protection) to avoid contact to eyes, skin and inhalation.
ENVIRONMENTAL PRECAUTIONS, RECOVERY/NEUTRALIZATION	Take precaution to prevent product to flow into rivers and effect environment.
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	In case of a small spill, absorb with dry sand, soil, sawdust, cloth, etc., then place in a sealable container. In case of large spills, dike and prevent overflow. Guide to a safe place then dispose properly.
SECONDARY ACCIDENT PREVENTION MEASURE	All ignition sources should be quickly removed. (No smoking in vicinity, prohibit sparks or fire sources)

7. HANDLING AND STORAGE

HANDLING	
ENGINEERING MEASURES	Wear protective equipment. Perform engineering measures in accordance with 「8. Exposure Control / Personal Protection」.
LOCAL VENTILATION /GENERAL VENTILATION	Perform local and general ventilation in accordance with 「8. Exposure Control/Personal Protection」.
SAFETY HANDLING PRECAUTIONS	Fire strictly prohibited
STORAGE	
ENGINEERING MEASURES	Protect from sunlight, and store at temperatures not exceeding 40 °C. Refer to the technical data, specifications, and a product label about handling range of temperature.
CONTAINER AND PACKAGING MATERIALS	Keep only in original container. Do not transfer the product to another container.

Safety Data Sheet

Issued Date: November 12, 2008

Revised Date: November 21, 2008

8. EXPOSURE CONTROL / PERSONAL PROTECTION**CONTROL PARAMETERS**

	ACGIH TLV	OSHA PEL
Mineral oil	5 mg/m ³ (oil mist)	5 mg/m ³ (oil mist)
Ethyleneglycol monobutylether	20 ppm	25 ppm
Butane(Propellant)	1000 ppm	800 ppm
Propane(Propellant)	1000 ppm	1000 ppm

ENGINEERING MEASURES If handling this product indoors, seal off sources or use a local mechanical ventilation system, etc.

Place a safety shower, hand washing sink and an eye bath near work area and clearly marked.

PERSONAL PROTECTION EQUIPMENT

RESPIRATORY PROTECTION	Wear mask to prevent organic gas poisoning, if necessary.
HAND PROTECTION	Wear appropriate protective gloves (Polyethylene, rubber, etc., solvent impervious materials).
EYE PROTECTION	Use eye protection. (preferably goggles)
SKIN AND BODY PROTECTION	Wear personal protection apron, boots, if necessary. Do not work with short sleeve shirts.
SANITARY MEASURES	Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.

9. PHYSICAL AND CHEMICAL PROPERTIES**PHYSICAL STATE**

APPEARANCE	Liquid (Content)
COLOR	Transparent yellow-brown
ODOR	Distinctive odor
FLASHPOINT	79°C
SPECIFIC GRAVITY (DENSITY)	0.8 (Content)
SOLUBILITY	Slightly soluble in water
VISCOSITY	5 mPa·s

PHYSICAL STATE as Butane

MELTING POINT/FREEZING POINT	-138°C
BOILING POINT	-0.5°C
(INITIAL AND RANGE)	
SPECIFIC GRAVITY (DENSITY)	2.07(Air =1)
SOLUBILITY	Readily soluble in Hydrocarbonic solvents

PHYSICAL STATE as Propane

MELTING POINT/FREEZING POINT	-187°C
BOILING POINT	-42°C
(INITIAL AND RANGE)	
SPECIFIC GRAVITY (DENSITY)	1.55(15.6 °C/760mmHg/Air =1)

10. STABILITY AND REACTIVITY

STABILITY	Stable under normal handling.
POSSIBLY HAZARDOUS REACTION	Reacts to strong oxidizers, then may cause a fire hazard.
CONDITION TO AVOID	Heating.
INCOMPATIBLE MATERIALS	Strong oxidizer.
HAZARDOUS DECOMPOSITION	Incineration may produce poisonous gasses (Carbon monoxide, Sulphuric compound, etc.) upon condition.

11. TOXICOLOGICAL INFORMATION**HEALTH HAZARDS**

ACUTE TOXICITY	No data as product
SKIN CORROSION/IRRITATION	No data as product

Information on GHS Hazard Communication is in accordance with Japanese Law

12. ECOLOGICAL INFORMATION**ENVIRONMENTAL HAZARDS**

HAZARDS TO THE AQUATIC ENVIRONMENT	No data as product
ECOTOXICITY	No data

Information on GHS Hazard Communication is in accordance with Japanese Law

Safety Data Sheet

Issued Date: November 12, 2008

Revised Date: November 21, 2008

13. DISPOSAL CONSIDERATIONS**METHOD OF DISPOSAL**

To dispose product, solicit waste disposal management experts.
Prohibited that to dispose the waste or waste liquid containing the product in the river, etc., to reclaim, to dump the product as it is.

CONTAMINATED CONTAINERS AND PACKAGING

Handle in used container and cloth same as above.

14. TRANSPORT INFORMATION**INTERNATIONAL REGULATION****SEA TRANSPORTATION**

Follows IMO regulation

UN number

1950

Proper shipping name

Aerosols

UN Classification

2.1

AIR TRANSPORTATION

Follows ICAO/IATA regulation

UN number

1950

Proper shipping name

Aerosols

UN Classification

2.1

JAPAN DOMESTIC REGULATION**LAND TRANSPORTATION**

In accordance with Japanese Law

SEA TRANSPORTATION

In accordance with Japanese Law

UN number

1950

Proper shipping name

Aerosols

UN Classification

2.1

AIR TRANSPORTATION

In accordance with Japanese Law

UN number

1950

Proper shipping name

Aerosols

UN Classification

2.1

EMERGENCY ACCIDENTAL MEASURE

Yellow card number

126

15. REGULATORY INFORMATION

Handle in accordance with applicable laws and regulations.

16. OTHER INFORMATION

Portions of the above evaluation of dangerous and harmful effects may be insufficient, please perform adequate investigation.

The content in this report is based on information which was available as of the Effective date.

But Three Bond Co., Ltd. and its affiliates are not responsible for guaranteeing the above data and evaluations.

The above data assumes usage under normal working conditions.

In case of special handling is required, please handle with suitable safety measures according to the application and usage.

The content in this report may change due to new evaluation and tests, etc.

In case there are differences in the translation, the Japanese language version takes precedence.