

Safety Data Sheet

Kolliccoat® Protect

Revision date : 2025/09/11

Version: 7.0

Page: 1/10

(30235579/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

Kolliccoat® Protect

Recommended use of the chemical and restriction on use

Recommended use*: pharmaceutical excipient

Unsuitable for use: Not intended for sale to or use by the general public.

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Synonyms:

Coprocessed blend of Polyvinyl alcohol-polyethylene glycol graft
copolymer and Polyvinyl alcohol

2. Hazards Identification

According to Regulation 2024 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Combustible Dust

Combustible Dust (1)

Combustible Dust

Label elements

Signal Word:

Safety Data Sheet

Kolliccoat® Protect

Revision date: 2025/09/11

Version: 7.0

Page: 2/10

(30235579/SDS_GEN_US/EN)

Warning

Hazard Statement:

May form combustible dust concentration in air.

Hazards not otherwise classified

The product is under certain conditions capable of dust explosion.

3. Composition / Information on Ingredients

According to Regulation 2024 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Under the referenced regulation, this product does not contain any components classified for health hazards above the relevant cut off value.

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air.

If on skin:

Wash thoroughly with soap and water

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

If swallowed:

Rinse mouth and then drink 200-300 ml of water.

Most important symptoms and effects, both acute and delayed

Symptoms: No data available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:

Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Extinguishing media

Safety Data Sheet

Kolliccoat® Protect

Revision date: 2025/09/11

Version: 7.0

Page: 3/10

(30235579/SDS_GEN_US/EN)

Suitable extinguishing media:
water spray, carbon dioxide, foam, dry powder

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon oxides, harmful vapours

The substances/groups of substances mentioned can be released in case of fire.

Dust explosion hazard.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Dusty conditions may ignite explosively in the presence of an ignition source causing flash fire.

6. Accidental release measures

Further accidental release measures:

Avoid dispersal of dust in the air (e.g. by clearing dusty surfaces with compressed air). Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Information regarding personal protective measures, see section 8.

Avoid dust formation.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Contain with dust binding material and dispose of.

For large amounts: Sweep/shovel up.

Dispose of absorbed material in accordance with regulations. Avoid raising dust.

Nonsparking tools should be used.

7. Handling and Storage

Precautions for safe handling

Avoid dust formation. Provide exhaust ventilation if dust is formed.

Protection against fire and explosion:

Avoid dust formation. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate

Safety Data Sheet

Kollicoat® Protect

Revision date: 2025/09/11

Version: 7.0

Page: 4/10

(30235579/SDS_GEN_US/EN)

precautions, such as electrical grounding and bonding, or inert atmospheres. Refer to NFPA 660 (2025) Standard for Combustible Dust and Particulate Solids. NFPA 660 is a combination of Standards NFPA 61 (Agriculture and Food), NFPA 484 (Metals), NFPA 652 (Fundamentals of Combustible Dusts), NFPA 654 (Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids), NFPA 65 (Sulfur), and NFPA 664 (Woodworking/Processing). Consult NFPA 660 standard for relevant commodity-specific and general safety information.

Conditions for safe storage, including any incompatibilities

No applicable information available.

Further information on storage conditions: Keep container tightly closed and dry.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Acetic acid	ACGIH, US:	STEL value 15 ppm ;
	ACGIH, US:	TWA value 10 ppm ;
	OSHA Z1:	PEL 10 ppm 25 mg/m3 ;
	NIO ID, US:	IDLH 50 ppm ; IDLH values based on the 1994 Revised Criteria
	NIO ID, US:	LEL 4.0 % ;

Advice on system design:

Ensure adequate ventilation. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.

Personal protective equipment

Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Wear a NIOSH-certified (or equivalent) particulate respirator.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Safety glasses with side-shields.

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is recommended. Wear protective clothing as necessary to minimize contact. Avoid inhalation of dust. No eating, drinking, smoking or tobacco use at the place of work. Hands and/or face should be washed before breaks and at the end of the shift. Store work clothing separately.

Safety Data Sheet

Kollicoat® Protect

Revision date: 2025/09/11

Version: 7.0

Page: 5/10

(30235579/SDS_GEN_US/EN)

9. Physical and Chemical Properties

Physical state:	solid	
Form:	powder	
Odour:	almost odourless	
Colour:	yellowish to white	
pH value:	5.0 - 8.0	
Melting point:	> 200 °C	
	The statements are based on the properties of the individual components.	
Freezing point:	No data available.	
Boiling point:	not relevant	
Sublimation point:	No applicable information available.	
Flash point:	not applicable, the product is a solid	
Flammability:	not highly flammable	(UN Test N.1 (ready combustible solids))
Lower explosion limit:	For solids not relevant for classification and labelling.	
Upper explosion limit:	For solids not relevant for classification and labelling.	
SADT:	Not a substance liable to self-decomposition according to UN transport regulations, class 4.1.	
Vapour pressure:	negligible	
Density:	No information is available for the absolute density. Instead the bulk density was determined as a more relevant value.	
Bulk density:	200 kg/m ³	
Relative vapour density:	not relevant	
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures	
Thermal decomposition:	>= 125 °C (DSC (DIN 51007))	
Viscosity, dynamic:	not applicable, the product is a solid	
Viscosity, kinematic:	No data available.	
Solubility in water:	> 200 g/l (25 °C) soluble	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molecular weight:	No data available.	
Evaporation rate:	The product is a non-volatile solid.	

Particle characteristics

Particle size distribution: typically > 50 µm

(D50, Volumetric Distribution, ISO 13320-1)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

No corrosive effect on metal.

Safety Data Sheet

Kolliccoat® Protect

Revision date: 2025/09/11

Version: 7.0

Page: 6/10

(30235579/SDS_GEN_US/EN)

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

Minimum ignition energy:

The product is capable of dust explosion.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

Dust explosion hazard.

Conditions to avoid

Avoid dust formation. Avoid electro-static discharge. Avoid all sources of ignition: heat, sparks, open flame.

Incompatible materials

strong oxidizing agents

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

$\geq 125\text{ }^{\circ}\text{C}$ (DSC (DIN 51007))

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion.

Oral

Information on: Polyvinylalcohol-polyethylene glycol graft copolymer

Type of value: LD50

Species: rat

Value: $> 2,000\text{ mg/kg}$ (OECD Guideline 423)

Inhalation

No data available.

Safety Data Sheet

Kollicoat® Protect

Revision date: 2025/09/11

Version: 7.0

Page: 7/10

(30235579/SDS_GEN_US/EN)

Dermal

No data available.

Assessment other acute effects

No applicable information available.

Irritation / corrosion

Assessment of irritating effects: Not irritating to eyes and skin.

Sensitization

Assessment of sensitization: Based on the ingredients, there is no suspicion of a skin-sensitizing potential.

Aspiration Hazard

not applicable

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: No data available.

Experimental/calculated data: No data available.

Genetic toxicity

Assessment of mutagenicity: Based on the ingredients, there is no suspicion of a mutagenic effect.

Carcinogenicity

Assessment of carcinogenicity: No data available.

Reproductive toxicity

Assessment of reproduction toxicity: Based on the ingredients, there is no suspicion of a toxic effect on reproduction.

Reproduction

Experimental/calculated data: No data available.

Teratogenicity

Assessment of teratogenicity: No data available.

Other Information

The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

Assessment of terrestrial toxicity

No data available.

Persistence and degradability

Safety Data Sheet

Kollicoat® Protect

Revision date: 2025/09/11

Version: 7.0

Page: 8/10

(30235579/SDS_GEN_US/EN)

Assessment biodegradation and elimination (H2O)

Not readily biodegradable (by OECD criteria). Poorly biodegradable.

Bioaccumulative potential

Bioaccumulation potential

No data available.

Mobility in soil

Assessment transport between environmental compartments

No data available.

Additional information

Other ecotoxicological advice:

The product has not been tested. The statement has been derived from the properties of the individual components.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations.

Observe national and local legal requirements.

Container disposal:

Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

USDOT

Hazard class: 4.2

Packing group: III

ID number: UN 3088

Hazard label: 4.2

Proper shipping name: SELF-HEATING SOLID, ORGANIC, N.O.S. (contains POLYVINYL ALCOHOL-POLYETHYLENE GLYCOL GRAFT COPOLYMER)

Sea transport

IMDG

Hazard class: 4.2

Packing group: III

ID number: UN 3088

Hazard label: 4.2

Marine pollutant: NO

Proper shipping name: SELF-HEATING SOLID, ORGANIC, N.O.S. (contains POLYVINYL ALCOHOL-POLYETHYLENE GLYCOL GRAFT COPOLYMER)

Air transport

IATA/ICAO

Hazard class: 4.2

Safety Data Sheet

Kolliccoat® Protect

Revision date: 2025/09/11

Version: 7.0

Page: 9/10

(30235579/SDS_GEN_US/EN)

Packing group: III
ID number: UN 3088
Hazard label: 4.2
Proper shipping name: SELF-HEATING SOLID, ORGANIC, N.O.S. (contains POLYVINYL ALCOHOL-POLYETHYLENE GLYCOL GRAFT COPOLYMER)

Further information

Not dangerous goods of class 4.2 in packages up to 3000 litres capacity.

15. Regulatory Information

Federal Regulations

Registration status:

Pharma TSCA, US released / exempt

Chemical TSCA, US blocked / not listed

Chemical TSCA, US

Contains non-registered, non-listed substance.

Individual registration may be required.

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

CERCLA RQ

5000 LBS

CAS Number

107-21-1; 64-19-7; 108-05-4

Chemical name

ethylene glycol; Acetic acid; vinyl acetate

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including Vinyl acetate, which is known to the State of California to cause cancer, and ETHYLENE GLYCOL (INGESTED), which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 0 Fire: 1 Reactivity: 0 Special:

HMIS III rating

Health: 0 Flammability: 1 Physical hazard: 0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2025/09/11

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our

Safety Data Sheet

Kolliccoat® Protect

Revision date: 2025/09/11

Version: 7.0

Page: 10/10

(30235579/SDS_GEN_US/EN)

commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Kolliccoat® Protect is a registered trademark of BASF Corporation or BASF SE
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. Any other intended applications should be discussed with the manufacturer. Corresponding occupational protection measurements must be followed.

Date / Revised: 2025/09/11

Date / Previous version: 2023/08/04

Version: 7.0

Previous version: 6.0

END OF DATA SHEET