

Jacobi, Gauss Seidel y Gauss Seidel (SOR)

- 1) We ask the user for a matrix. We call the matrix A. The matrix must be a square matrix.
- 2) We ask for a vector b and we make sure that it is the same length as matrix A.
- 3) Now ask the user for an initial value approximation which we will call x0, a tolerance (tol) and we make sure it is not negative, we also ask for a maximum number of iterations(Nmax), which also has to be nonnegative, l (it will be 1 if you want to execute Jacobi, or 2 if you want to execute Gauss Seidel) y w if you want to use the method of relaxation.
- 4) We make sure that A does not have any 0's in the diagonal, and that the $\det(A) \neq 0$.
- 5) Now make 3 new matrices, named D, L and U. All must be the same size as A and must have the following parameters:
 - a) D must be a matrix that has the same main diagonal elements that matrix A has and the rest of the elements must be 0.
 - b) L will have the same elements that are below the diagonal in A but with the opposite sign. The diagonal in L will be the same as A, and all other elements will be 0.
 - c) U will have the same elements in A that are above the diagonal with opposite signs, and will have the same elements in the diagonal as A and the rest of the elements will be 0.
- 6) Now we begin to execute the method.
 - a) If l is equal to 1, execute Jacobi method,
 - (i) $T = D^{-1} * (L+U)$
 - (ii) $C = D^{-1} * b$
 - b) If l is equal to 2 execute the Gauss Seidel Method:
 - (i) $T = (D-L)^{-1} * U$
 - (ii) $C = (D-L)^{-1} * b$
 - c) All other cases execute SOR
 - (i) $T = (D-w * L)^{-1} * ((1-w) * (D+w * U))$
 - (ii) $C = (w * (D-w * L))^{-1} * b$
- 7) Now we find and make the spectral radius as the absolute value of the largest proper values making sure they are less than 1.

- 8) Now we make a counter for the iterations beginning with 0, a variable for the error which begins with 1, and a variable for the old X , we will call X_{ant} , and we will start it off as $X_{ant}=x_0$ our initial approximation
- 9) Now we make a cycle, while the $\text{Error} > \text{the tolerance}$, $\text{iterations}(\text{counter}) < N_{\text{max}}$, Do:
- a) $X_{act} = X_{ant} * T + C$
 - b) $\text{Error} = \text{norm of } X_{ant} - X_{act}$
 - c) $X_{ant} = X_{act}$
 - d) $\text{Counter}++$