A trace has been found.

Honest Process
Attacker
{1}new skS_2
!
~M = vk(skS_2)
!
Beginning of process Server
{31}event serverBegin(skS_2)
~M_1 = vk(skS_2)
!
Beginning of process Server
{31}event serverBegin(skS_2)
~M_2 = vk(skS_2)
!
Beginning of process Server
{31}event serverBegin(skS_2)
~M_3 = vk(skS_2)
!
~M_4 = vk(skS_2)
!
Beginning of process Server
{31}event serverBegin(skS_2)
~M_5 = vk(skS_2)
!
Beginning of process Server
{31}event serverBegin(skS_2)
{3}new skC_11
{3}new skC_10
{3}new skC_9
{3}new skC_8
{3}new skC_7
~M_6 = vk(skC_7)
!
Beginning of process Client
{7}event clientBegin(skC_7)
Beginning of process Client
{7}event clientBegin(skC_7)
Beginning of process Client
{7}event clientBegin(skC_7)
Beginning of process Client
{7}event clientBegin(skC_7)
Beginning of process Client
{7}event clientBegin(skC_7)
Beginning of process Client
{7}event clientBegin(skC_7)
~M_7 = vk(skC_8)
!
Beginning of process Client
{7}event clientBegin(skC_8)
~M_8 = vk(skC_9)
!
Beginning of process Client
{7}event clientBegin(skC_9)
~M_9 = vk(skC_10)
!
Beginning of process Client
{7}event clientBegin(skC_10)
~M_10 = vk(skC_11)
!
Beginning of process Client
{7}event clientBegin(skC_11)
vk(skC_11)
vk(skC_10)
{10}new b_2
vk(skC_9)
{10}new b_3
vk(skC_8)
{10}new b_4
vk(skC_7)
{10}new b_5
vk(skC_7)
{10}new b_6
vk(skC_7)
{10}new b_7
vk(skC_7)
{10}new b_8
vk(skC_7)
{10}new b_9
vk(skS_2)
{10}new b_10
{34}new a_28
~M_11 = exp(g,a_28)
vk(skC_7)
vk(skS_2)
{10}new b_11
{34}new a_29
~M_12 = exp(g,a_29)
~M_12 = exp(g,a_29)
~M_13 = exp(g,b_10)
~M_13 = exp(g,b_10)
(~M_14,~M_15) = (vk(skS_2),sign(sessionId(
g,a_29),exp(g,b_10)),skS_2))
(~M,~M_15) = (vk(skS_2),sign(sessionId(exp(g,a_29),
exp(g,b_10)),skS_2))
{18}event clientKeyExchanged(skC_7,vk(skS_2))
~M_16 = encrypt(vk(skC_7),exp(exp(g,a_29),b_10))
~M_16 = encrypt(vk(skC_7),exp(exp(g,a_29)
{43}new n_4
~M_17 = encrypt(n_4,exp(exp(g,b_10),a_
~M_17 = encrypt(n_4,exp(exp(g,a_29),b_10))
~M_18 = encrypt(sign((sessionId(exp(g,a_29),exp(
g,b_10)),n_4),skC_7),exp(exp(g,a_29),b_10))
~M_18 = encrypt(sign((sessionId(exp(g,a_29
g,b_10)),n_4),skC_7),exp(exp(g,a_29),b_1
{48}event serverAccept(skS_2,vk(skC_7))
~M_19 = encrypt(accept,exp(exp(g,b_10),a_
~M_19 = encrypt(accept,exp(exp(g,a_29),b_10))
~M_20 = encrypt(message,exp(exp(g,a_29),b_10))
{26}event clientEnd(skC_7,vk(skS_2))
~M_20 = encrypt(message,exp(exp(g,a_29),b
{52}event serverEnd(skS_2,vk(skC_7))