


LOC I-BVI	APP CRS	Rwy Ldg	4501
109.3	101°	TDZE	1238
		Apt Elev	1253

LOC RWY 10

BEAVER COUNTY (BVI)

DME or RADAR REQUIRED	MISSED APPROACH: Climb to 2000 then climbing left turn to 3000 direct EWC VOR/DME and hold.
▼ ▲ Rwy 10 helicopter visibility reduction below ¾ SM NA. When local alimeter setting not received, use Pittsburgh Intl alimeter setting and increase all MDAs 60 feet and visibility S-10 Cats C and D ¼ SM. Circling Rwy 28 NA at night.	

ATIS 118.35	PITTSBURGH APP CON 338.2	BEAVER COUNTY TOWER ★ 120.3 (CTAF) 0	GND CON 121.8
----------------	-----------------------------	---	------------------



One Minute Holding Pattern		JOTMI EWC 20.8 RADAR	NAMTH OM	2000	3000	EWC
6000 ← 281° 3000 ← 101°		101° → 3000	2.94° TCH 42	↑	↶	☐
		6.5 NM	5.6 NM			
CATEGORY	A	B	C	D	MIRL Rwy 10-28 0 REIL Rwys 10 and 28 0	
S-10	1640-1	402 (400-1)	1640-1½	402 (400-1½)	FAF to MAP 5.6 NM	
CIRCLING	1720-1	467 (500-1)	1720-1½ 467 (500-1½)	1820-2 567 (600-2)	Knots	60 90 120 150 180
					Min:Sec	5:36 3:44 2:48 2:14 1:52

NE-4, 03 SEP 2026 to 01 OCT 2026

NE-4, 03 SEP 2026 to 01 OCT 2026