

LOC/DME I-DDO

110.5

Chan 42

APP CRS

005°

Rwy Ldg

10000

TDZE

88

Apt Elev

96

ILS RWY 35L (CAT II & III)

ORLANDO INTL (MCO)

RADAR required for procedure entry. DME or RADAR required.

Bright lights on highway midway between Rwy 35L and Rwy 35R may be mistaken for runway lights. Simultaneous approach authorized. When using alternate missed approach, simultaneous approach NA.

ALSF-2

MISSED APPROACH: Climb to 3000 on heading 005° and ORL VORTAC R-049 to OVIDO INT/ORL 13 DME and hold.

D-ATIS 121.25	ORLANDO APP CON 124.8 307.0	ORLANDO TOWER 118.45 253.5 (17L/35R, 17R/35L) 124.3 253.5 (18L/36R, 18R/36L)	GND CON 126.4 (E) 121.8 (W)
------------------	--------------------------------	--	-----------------------------------

Enroute chart showing the Orlando area. Key features include:

- ORLANDO** 112.2 ORL 35L Chan 59
- LOCALIZER 110.5** I-DDO Chan 42
- ORLANDO EXEC** (VORTAC)
- MLB R-329** (049°)
- OVIDO ORL 13** (229°)
- 115.85 MLB** Chan 105(Y)
- ALTERNATE MISSED APCH FIX** (113.7 OCF Chan 84, 112.6 OMN Chan 73, 193°)
- ZOKUM INT OMN 31.8** (013°)
- R-114** (114°)
- R-193** (193°)

Terminal area chart showing the ILS approach for RWY 35L. Key features include:

- MSA ORL 25 NM** (3000)
- SPURR I-DDO 6.4** RADAR
- FITEM I-DDO 10.8** RADAR
- (IF) FOBUK I-DDO 14** RADAR
- (IAF) NOGGI I-DDO 16.5** RADAR
- 1600** (005° (4.4))
- 3000** (005° (3.2))
- 4000** (005° (2.5) 185°)
- 166±**
- 1600**

ELEV 96

D

TDZE 88

18L

18R

36L

36R

35L

35R

TWR

HIRL all Rwys

REIL Rwy 36L

TDZ/CL Rwys 17L/R, 18R, 35L/R and 36R

3000

hdg 005°

ORL R-049

OVIDO

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 72).

NOGGI I-DDO 16.5

FOBUK I-DDO 14

FITEM I-DDO 10.8

SPURR I-DDO 6.4

5000

4000

3000

1600

GS 3.00°

TCH 57

4.6 NM

4.4 NM

3.2 NM

2.5 NM

CATEGORY	A	B	C	D
S-ILS 35L	CAT II RA 106/12	100	DA 188	
S-ILS 35L	CAT III	RVR 06		

CATEGORY II & III ILS - SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED

ORLANDO, FLORIDA

Amdt 8A 29DEC22

ORLANDO INTL (MCO)

28°26'N-81°19'W

ILS RWY 35L (CAT II & III)