

WAAS CH 42909 W36A	APP CRS 359°	Rwy Ldg TDZE Apt Elev	5000 54 55
--	------------------------	-----------------------------	---------------------------------------


RNAV (GPS) RWY 36

PICAYUNE MUNI (MJD)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Stennis Intl altimeter setting. DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. Procedure NA when R-4403 A, B, C, or E is active. When local altimeter setting not received, use Stennis Intl altimeter setting: increase LPV DA to 338 and all Cats visibility ½ mile; increase LNAV/VNAV DA to 374 and all Cats visibility ½ mile; increase all MDA 40 feet and LNAV Cats C and D visibility ½ mile, and Circling Cat C visibility ¼ mile.

MISSED APPROACH:
Climb to 1800 direct CIQYI and hold.

AWOS-3PT 119.075	GULFPORT APP CON ★ 124.6 354.1	UNICOM 122.8 (CTAF) 0
----------------------------	--	---------------------------------



1800

CIQYI

*LNAV only.

CATEGORY	A	B	C	D
LPV DA	304-7⁄8 250 (300-7⁄8)			
LNAV/VNAV DA	340-1 286 (300-1)			
LNAV MDA	420-1 366 (400-1)			
CIRCLING	480-1 425 (500-1)	580-1 525 (600-1)	700-1¾ 645 (700-1¾)	960-3 905 (1000-3)

ELEV 55

TDZE 54

81

5000 X 75

36

359°

MIRL Rwy 18-36 0