

LOC I-SKC

109.5

APP CRS

103°

Rwy Ldg

5849

TDZE

901

Apt Elev

912

ILS or LOC RWY 10

WAUKESHA COUNTY (U/S)

RADAR required for procedure entry.

▼

▲

For inop ALS, increase S-LOC 10 visibility to 1½ SM. When local altimeter setting not received, use MWC altimeter setting and increase S-ILS 10 DA to 1149 feet; increase all MDAs 60 feet and S-LOC 10 visibility Cats C and D ½ SM, and Circling visibility Cats C and D ¼ SM.

MALSR

MISSED APPROACH: Climb to 1500 then climbing left turn to 2800 direct BAE VOR/DME and hold, continue climb-in-hold to 2800.

ATIS 118.875	MILWAUKEE APP CON 125.35 307.0	WAUKESHA TOWER ★ 123.7 (CTAF) 0	GND CON 121.6	UNICOM 122.95
-----------------	-----------------------------------	------------------------------------	------------------	------------------

The main navigation diagram illustrates the approach and arrival procedures for Waukesha County (U/S) ILS or LOC RWY 10. Key features include:

- Communication:** BADGER 116.4 BAE (Chan 111), LOCALIZER 109.5 I-SKC.
- Navigation Aids:** WENBU INT RADAR (IF), FEDKI INT RADAR (IAF), CORIR INT, ALTERNATE MISSED APCH FIX.
- Altitudes and Distances:** 2300 NoPT 103° (6.1), 283°, 103°, 238°, 058°, 270°, 090°, 270°.
- Obstacles:** 11675 OSH, 109.8 BJB, 1675 OSH, 1165 (Chan 111), 165°.
- MSA:** MSA BAE 25 NM, 2900.

ELEV 912

TDZE 901

Remain within 10 NM

FEDKI INT RADAR

1500

2800

BAE

2800

2300

GS 3.00° TCH 53

2300

4.2 NM

103°

10

AS

5849 X 100

81

36

3599 X 175

TWR

CATEGORY	A	B	C	D
S-ILS 10	1101-½ 200 (200-½)			
S-LOC 10	1400-½	499 (500-½)	1400-1	499 (500-1)
CIRCLING	1460-1 548 (600-1)	1500-1 588 (600-1)	1540-1¾ 628 (700-1¾)	1640-2¼ 728 (800-2¼)

HIRL Rwy 10-28 0

MIRL Rwy 18-36 0

REIL Rwy 28 0

REIL Rws 18 and 36

FAF to MAP 4.2 NM

Knots	60	90	120	150	180
Min:Sec	4:12	2:48	2:06	1:41	1:24

WAUKESHA, WISCONSIN

Amdt 3A 15MAY25

43°02'N-88°14'W

WAUKESHA COUNTY (U/S)

ILS or LOC RWY 10